

EOG RESOURCES, INC.
Osprey 10 No. 303H

Permit Information:

Well Name: Osprey 10 No. 303H

Location:

SHL: 200' FSL & 1733' FWL, Section 10, T-25-S, R-34-E, Lea Co., N.M.

BHL: 2535' FSL & 2178' FWL, Section 3, T-25-S, R-34-E, Lea Co., N.M.

Casing Program:

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
17.5"	0' - 925'	13.375"	54.5#	J-55	STC	1.125	1.25	1.60
12.25"	0' - 4,000'	9.625"	40#	J-55	LTC	1.125	1.25	1.60
12.25"	4000' - 5,150'	9.625"	40#	HCL-80	LTC	1.125	1.25	1.60
8.75"	0' - 17,817'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. ppg	Yld Ft ³ /ft	Slurry Description
925	600	13.5	1.73	Class C + 4.0% Bentonite + 0.6% CD-32 + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	300	14.8	1.34	Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate
5,150'	900	12.7	2.22	Class 'C' + 1.50% R-3 + 0.25 lb/sk Cello-Flake + 2.0% Sodium Metasilicate + 10% Salt + 0.005 lb/sk Static Free (TOC @ Surface)
	225	14.8	1.32	Tail: Class 'C' + 0.25 lb/sk Cello Flake + 0.005 lb/sk Static Free
17,817'	375	10.8	3.67	60:40:0 Class C + 15.0 pps BA-90 + 4% MPA-5 + 3.0% SMS + 5.0% A-10 + 1.0% BA-10A + 0.80% ASA-301 + 2.55% R-21 + 8.0 pps LCM-1 (TOC @ 4,650')
	400	11.8	2.38	50:50:10 Class H + 0.80% FL-52 + 0.30% ASA-301 + 0.40% SMS + 2.0% Salt + 0.30% R-21 + 3.0 pps LCM-1 + 0.25 pps Celloflake
	1300	14.2	1.28	50:50:2 Class H + 0.65% FL-52 + 0.45% CD-32 + 0.10% SMS + 2.0% Salt

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0' - 925'	Fresh - Gel	8.6-8.8	28-34	N/c
925' - 5,150'	Brine	10.0-10.2	28-34	N/c
5,150' - 9,870'	Cut Brine	8.4-9.0	28-34	N/c
9,870' - 17,817' Lateral	Cut Brine	9.0-9.5	40-42	8-10


Osprey 10 #303H
Lea County, New Mexico

Proposed Wellbore

200' FSL
1733' FWL
Section 10
T-25-S, R-34-E

API: 30-025-*****

KB: 3,357'
GL: 3,332'



Lateral: 17,817' MD, 10,332' TVD
BH Location: 2535' FSL & 2178' FWL
Section 3
T-25-S, R-34-E