

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 1301 W. Grand Avenue, Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-37472		5. Indicate Type of Lease STATE ☐ FEE ☒	
		State Oil & Gas Lease No.			
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER				7. Lease Name or Unit Agreement Name ROCKET	
2. Name of Operator PRIME OPERATING COMPANY				8. Well No. 001	
3. Address of Operator 3300 N. A, BLDG. 1-238, MIDLAND, TX 79705				9. Pool name or Wildcat CARRETT; SAN ANDRES	
4. Well Location Unit Letter <u>B</u> : <u>660</u> Feet From The <u>NORTH</u> Line and <u>2150</u> Feet From The <u>EAST</u> Line Section <u>22</u> Township <u>76S</u> Range <u>38E</u> NMPM <u>12</u> County _____					
10. Date Spudded 11/8/05		11. Date T.D. Reached 11/20/05		12. Date Compl. (Ready to Prod.) 3-30-06	
13. Elevations (DF& RKB, RT, GR, etc.) KB 3724'		14. Elev. Casinghead 3713'		15. Total Depth 5900'	
16. Plug Back T.D. 5473'		17. If Multiple Compl. How Many Zones? N/A		18. Intervals Drilled By Rotary Tools CAPSTAR RIG 20	
19. Producing Interval(s), of this completion - Top, Bottom, Name 5231' - 5473' SAN ADRES				20. Was Directional Survey Made YES	
21. Type Electric and Other Logs Run CD-CN., BHC, LATERALOG				22. Was Well Cored YES - SIDEWALL CORES	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE		WEIGHT LB./FT.		DEPTH SET	
8 5/8"		24#		2084	
5 1/2"		17#		5231	
HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED	
12 1/4"		700 SKS & 350 SKS		300 SKS 50/50 POZ	
7 7/8"		300 SKS 50/50 POZ			
24. LINER RECORD		25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE
					2 3/8"
					5319
					PACKER SET
26. Perforation record (interval, size, and number) OH 5231' - 5473'				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL 5231' - 5473' AMOUNT AND KIND MATERIAL USED 28,464 GAL GELLED WTR + 30,000#16/30 SAND	
28. PRODUCTION					
Date First Production 3-30-06		Production Method (Flowing, gas lift, pumping - Size and type pump) PUMPING 2 1/4" X 1 3/4" X 12 x 16' TBG PUMP			Well Status (Prod. or Shut-in) PRODUCING
Date of Test 4-19-06	Hours Tested 24	Choke Size 15	Prod'n For Test Period 15	Oil - Bbl 15	Gas - MCF TSTM
Flow Tubing Press. 18	Casing Pressure 18	Calculated 24-Hour Rate	Oil - Bbl. 15	Gas - MCF TSTM	Water - Bbl. 74
29. Disposition of Gas (Sold, used for fuel, vented, etc.) N/A		Test Witnessed By			
30. List Attachments LOGS, DIRETIONAL SURVEY					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature <u>Candy Lyle</u> Date 4/27/06		Printed Name <u>CANDY LYLE</u>		Title <u>ENG. ASST./PRODUCTION</u>	
E-mail Address					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 2070'	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 2190'	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 3142'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen 4030'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4956'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....5310.....to.....5410.....
 No. 2, from.....5540.....to.....5650.....
 No. 3, from.....to.....
 No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	2070	2070	RED BEDS				
2070	2190	120	ANHY, SH				
2190	3142	952	SALT, SH, & ANHY				
3142	4030	888	SALT, SH, ANHY, SED				
4030	4956	926	SND, SH, ANHY				
4956	5900	944	DOLO				