

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

HOBS OCD
RECEIVED
DEC 07 2018

WELL API NO. 30-041-00076
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No. V-2096
7. Lease Name or Unit Agreement Name Fox C State
8. Well Number 1
9. OGRID Number 025575
10. Pool name or Wildcat Allison; San Andres
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4055'GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [] Gas Well [] Other P&A []
2. Name of Operator EOG Y Resources, Inc.
3. Address of Operator 104 South Fourth Street, Artesia, NM 88210
4. Well Location Unit Letter G : 2310 feet from the North line and 2310 feet from the East line Section 36 Township 8S Range 36E NMPM Roosevelt County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []

SUBSEQUENT REPORT OF:

- REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB []
OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/29/18 - MIRU and POOH with production equipment. NU BOP. Tagged TOC at 4740'. Circulated 5-1/2" casing with 90 bbls plugging mud to surface. Pressure tested casing to 500 psi, good.
11/30/18 - Pumped a 25 sx Class "C" cement plug from 4205'-3960' calc TOC. Pumped a 25 sx Class "C" cement plug from 2400'-2135' calc TOC. Perforated at 440'. Pumped down 5-1/2" casing and up 8-5/8" casing, full returns. Pumped 125 sx Class "C" cement to surface.
12/1/18 - Pumped and topped off to surface 12 sx Class "C" cement. Cement level held at surface.
12/4/18 - Cut off wellhead and installed dry hole marker. Cut off anchors and cleaned location. WELL IS PLUGGED AND ABANDONED.

Approved for Plugging of wellbore only. Liability under bond is retained pending restoration and completion of the C-103, Specific for Subsequent Report of Well Plugging, which may be found on the OCD web page under forms. Restoration Due By 12-1-2019

Spud Date: [] Rig Release Date: []

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Specialist DATE December 4, 2018

Type or print name Tina Huerta E-mail address: tina_huerta@eogresources.com PHONE: 575-748-4168

For State Use Only APPROVED BY: Kerry Fisher TITLE Compliance Officer DATE 12-11-18