

Permit Information:

Well Name: Neptune 10 State Com No. 201H

Location:

SL: 359' FSL & 360' FWL, Section 10, T-24-S, R-33-E, Lea Co., N.M.

BHL: 100' FNL & 770' FWL, Section 3, T-24-S, R-33-E, Lea Co., N.M.

HOBBS OCD
FEB 25 2019
RECEIVED
Casing Program:

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF _{min} Collapse	DF _{min} Burst	DF _{min} Tension
17.5"	0 – 1,335'	13.375"	54.5#	J55	STC	1.125	1.25	1.60
12.25"	0-4000'	9.625"	40#	J55	LTC	1.125	1.25	1.60
12.25"	4000' – 5185'	9.625"	40#	HCL-80	LTC	1.125	1.25	1.60
8.75"	0' -,20,392'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

Cement Program:

Depth	No. Sacks	Wt. ppg	Yld Ft ³ /ft	Slurry Description
1,335'	600	13.5	1.73	Class C + 4.0% Bentonite + 0.6% CD-32 + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	300	14.8	1.34	Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate
5,185'	900	12.7	2.22	Class 'C' + 1.50% R-3 + 0.25 lb/sk Cello-Flake + 2.0% Sodium Metasilicate + 10% Salt + 0.005 lb/sk Static Free (TOC @ Surface)
	225	14.8	1.32	Tail: Class 'C' + 0.25 lb/sk Cello Flake + 0.005 lb/sk Static Free
20,392'	375	10.8	3.67	60:40:0 Class C + 15.0 pps BA-90 + 4% MPA-5 + 3.0% SMS + 5.0% A-10 + 1.0% BA-10A + 0.80% ASA-301 + 2.55% R-21 + 8.0 pps LCM-1 (TOC @ 4,685')
	400	11.8	2.38	50:50:10 Class H + 0.80% FL-52 + 0.30% ASA-301 + 0.40% SMS + 2.0% Salt + 0.30% R-21 + 3.0 pps LCM-1 + 0.25 pps Celloflake
	1300	14.2	1.28	50:50:2 Class H + 0.65% FL-52 + 0.45% CD-32 + 0.10% SMS + 2.0% Salt

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 1,335'	Fresh - Gel	8.6-8.8	28-34	N/c
1,335' – 5,185'	Brine	10.0-10.2	28-34	N/c
5,185' – 9711'	Cut Brine	8.4-9.0	28-34	N/c
9711' – 20,392' Lateral	Cut Brine	9.0-9.5	40-42	8-10


Neptune 10 State Com #201H
Lea County, New Mexico

359' FSL
360' FWL
Section 10
T-24-S, R-33-E

Proposed Wellbore

API: 30-025-*****

KB: 3,640'
GL: 3,615'



Lateral: 20,392' MD, 10,109' TVD

BH Location: 100' FNL & 770' FWL
Section 3
T-24-S, R-33-E