

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised August 1, 2011

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-025-35623
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Roy Riddel
8. Well Number: 4
9. OGRID Number 4323
10. Pool name or Wildcat Eumont; Yates-7 Rivers-Queen
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,536' GL 3,542' DF

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Chevron USA, Inc.

3. Address of Operator
6301 Deauville Blvd., Midland, TX 79706

4. Well Location
Unit Letter I: 1980 feet from the SOUTH line and 660 feet from the EAST line
Section 12 Township 21S Range 36E, NMPM, County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,536' GL 3,542' DF

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
 PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE
 OTHER:

SUBSEQUENT REPORT OF:
 REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

J.P.M.
 PNR

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 8 5/8" @ 408' TOC surface, 5 1/2" @ 4,000' TOC Surface, Perforations 3,540'-3,687'.

Chevron USA Inc completed abandonment of this well as follows:

- 02/13/2019: MIRU single rig, N/U BOP, perform bubble test on surface CSG - good.
- 02/14/2019: Set CIBP @ 3,490'. Attempted to pump fluid down casing - would not fill. Move off location.
- 02/20/2019: MIRU double rig. N/U and test BOPE.
- 02/21/2019: Tag CIBP @ 3,487'. Pressure test CSG to 500 PSI for 10 minutes - good. Spot 150 SKS Class C, 1.33 YLD 14.8 PPG, F/ 3,487' T/ 1,994'. WOC. Tag TOC @ 1,983'. Kerry Fortner(NMOCD) approved tag depth. M/P 36 BBLs MLF F/ 1,983' T/ 500'.
- 02/22/2019: Spot 50 SKS Class C, 1.33 YLD 14.8 PPG, F/ 500' T/ surface. N/D BOPE and top off well. Good cement to surface. RDMO.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

X 

3/11/19

Howie Lucas
 Well Abandonment Engineer

E-mail address: howie.lucas@chevron.com PHONE: 432-687-7216

For State Use Only

APPROVED BY: Kerry Fortner TITLE Compliance Officer A DATE 3-26-19

Conditions of Approval (if any):