

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87420
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

Revised July 18, 2013

HOBBS OCD
MAR 25 2019
RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-45272
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name YARROW 32 STATE
8. Well Number 704H
9. OGRID Number 7377
10. Pool name or Wildcat [98135]WC-025 G-09 S243310P; UPPER WC
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3672 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [X] Gas Well [] Other []
2. Name of Operator EOG RESOURCES
3. Address of Operator P O BOX 2267, MIDLAND TX 79702
4. Well Location Unit Letter O : 393 feet from the SOUTH line and 1733 feet from the EAST line
Section 32 Township 23S Range 33E NMPM County LEA
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3672 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [X] P AND A []
CASING/CEMENT JOB [X]
OTHER: DRILL CSG [X]

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/16/19 12-1/4" HOLE
03/17/19 Surface Casing @ 1,437'
Ran 9-5/8" 40# J-55 LTC
Lead Cement w/ 1,290 sx Class C (1.76 yld, 13.5 ppg), Tail w/200 sx Class C (1.36 yld, 14.8 ppg)
Test casing to 1,500 psi for 30 min - OK. Circ 606 sx cement to surface
Resume Drilling 8-3/4" hole

Spud Date: 03/16/19 Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Sr. Regulatory Administrator DATE 03/20/19

Type or print name Emily Follis E-mail address: emily_follis@eogresources.com PHONE: 432-848-9163
For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 03/29/19
Conditions of Approval (if any):