

F/A

Form 3160-3
(June 2015)

HOBBS OCD

MAY 09 2019 4pm

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: DRILL REENTER
1b. Type of Well: Oil Well Gas Well Other
1c. Type of Completion: Hydraulic Fracturing Single Zone Multiple Zone

5. Lease Serial No.
NMNM023199

6. If Indian, Allottee or Tribe Name

7. If Unit or CA Agreement, Name and No.

8. Lease Name and Well No.

CAMELLIA FED COM 26 36 21
101H (325400)

2. Name of Operator
AMEREDEV OPERATING LLC (372224)

9. API Well No.
30-025-45918

3a. Address
5707 Southwest Parkway, Building 1, Suite 275 Austin TX

3b. Phone No. (include area code)
(737)300-4700

10. Field and Pool, or Exploratory
~~JAL/WOLFCAMP WEST~~ 98234

4. Location of Well (Report location clearly and in accordance with any State requirements. *)
At surface LOT M / 283 FSL / 230 FWL / LAT 32.0222949 / LONG -103.2778497
At proposed prod. zone LOT D / 50 FNL / 200 FWL / LAT 32.05041 / LONG -103.27796

11. Sec., T. R. M. or Blk. and Survey or Area
SEC 21 / T26S / R36E / NMP

14. Distance in miles and direction from nearest town or post office*
5 miles

12. County or Parish
LEA

13. State
NM

15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)
230 feet

16. No of acres in lease
320

17. Spacing Unit dedicated to this well
320

18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.
760 feet

19. Proposed Depth
11845 feet / 21826 feet

20. BLM/BIA Bond No. in file
FED: NMB001478

21. Elevations (Show whether DF, KDB, RT, GL, etc.)
2923 feet

22. Approximate date work will start*
03/15/2019

23. Estimated duration
90 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- 1. Well plat certified by a registered surveyor.
- 2. A Drilling Plan.
- 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).
- 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- 5. Operator certification.
- 6. Such other site specific information and/or plans as may be requested by the BLM.

25. Signature
(Electronic Submission)

Name (Printed/Typed)
Christie Hanna / Ph: (737)300-4723

Date
04/27/2018

Title
Senior Engineering Technician

Approved by (Signature)
(Electronic Submission)

Name (Printed/Typed)
Cody Layton / Ph: (575)234-5959

Date
05/03/2019

Title
Assistant Field Manager Lands & Minerals

Office
CARLSBAD

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

GCP Rec 05/09/19

KE 05/09/19

APPROVED WITH CONDITIONS
Approval Date: 05/03/2019

INSTRUCTIONS

GENERAL: This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

ITEM 1: If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

ITEM 4: Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

ITEM 14: Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

ITEMS 15 AND 18: If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

ITEM 22: Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

ITEM 24: If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

PRINCIPAL PURPOSES: The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

ROUTINE USE: Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

EFFECT OF NOT PROVIDING INFORMATION: Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to an evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.

Additional Operator Remarks

Location of Well

1. SHL: LOT M / 283 FSL / 230 FWL / TWSP: 26S / RANGE: 36E / SECTION: 21 / LAT: 32.0222949 / LONG: -103.2778497 (TVD: 0 feet, MD: 0 feet)
PPP: LOT D / 50 FNL / 200 FWL / TWSP: 26S / RANGE: 36E / SECTION: 16 / LAT: 32.05041 / LONG: -103.27796 (TVD: 11969 feet, MD: 22775 feet)
BHL: LOT D / 50 FNL / 200 FWL / TWSP: 26S / RANGE: 36E / SECTION: 16 / LAT: 32.05041 / LONG: -103.27796 (TVD: 11845 feet, MD: 21826 feet)

BLM Point of Contact

Name: Priscilla Perez

Title: Legal Instruments Examiner

Phone: 5752345934

Email: pperez@blm.gov

Review and Appeal Rights

A person contesting a decision shall request a State Director review. This request must be filed within 20 working days of receipt of the Notice with the appropriate State Director (see 43 CFR 3165.3). The State Director review decision may be appealed to the Interior Board of Land Appeals, 801 North Quincy Street, Suite 300, Arlington, VA 22203 (see 43 CFR 3165.4). Contact the above listed Bureau of Land Management office for further information.

**PECOS DISTRICT
SURFACE USE
CONDITIONS OF APPROVAL**

Camellia Federal Com 26 36 21 81H:

Surface Hole Location: 283' FSL & 290' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 660' FWL, Section 16, T. 26 S., R. 36 E.

Camellia Federal Com 26 36 21 91H:

Surface Hole Location: 283' FSL & 310' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 660' FWL, Section 16, T. 26 S., R. 36 E.

Camellia Federal Com 26 36 21 101H:

Surface Hole Location: 283' FSL & 230' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 380' FWL, Section 16, T. 26 S., R. 36 E.

Camellia Federal Com 26 36 21 111H:

Surface Hole Location: 283' FSL & 250' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 380' FWL, Section 16, T. 26 S., R. 36 E.

Camellia Federal Com 26 36 21 121H:

Surface Hole Location: 283' FSL & 270' FWL, Section 21, T. 26 S., R. 36 E.
Bottom Hole Location: 200' FNL & 380' FWL, Section 16, T. 16 S., R. 36 E.

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- General Provisions**
- Permit Expiration**
- Archaeology, Paleontology, and Historical Sites**
- Noxious Weeds**
- Special Requirements**
 - Lesser Prairie-Chicken Timing Stipulations
 - Timing Limitation Exception
 - Ground-level Abandoned Well Marker
 - Hydrology

- Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads

- Road Section Diagram**
- Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
 - Electric Lines

- Interim Reclamation**
- Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period.

Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted.

Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.

Timing Limitation Exceptions:

The Carlsbad Field Office will publish an annual map of where the LPC timing and noise stipulations and conditions of approval (Limitations) will apply for the identified year (between March 1 and June 15) based on the latest survey information. The LPC Timing Area map will identify areas which are Habitat Areas (HA), Isolated Population Area (IPA), and Primary Population Area (PPA). The LPC Timing Area map will also have an area in red crosshatch. The red crosshatch area is the only area where an operator is required to submit a request for exception to the LPC Limitations. If an operator is operating outside the red crosshatch area, the LPC Limitations do not apply for that year and an exception to LPC Limitations is not required.

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

Hydrology

- The entire well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad. Topsoil shall not be used to construct the berm. No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad. The berm shall be maintained through the life of the well and after interim reclamation has been completed.
- Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.
- Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

- Tank battery locations will be lined and bermed. A 20 mil permanent liner will be installed with a 4 oz. felt backing to prevent tears or punctures. Tank battery berms must be large enough to contain 1 ½ times the content of the largest tank.
- Automatic shut off, check valves, or similar systems will be installed for tanks to minimize the effects of catastrophic line failures used in production or drilling.
- A leak detection plan will be submitted to the BLM Carlsbad Field Office for approval prior to pipeline installation. The method could incorporate gauges to detect pressure drops, siting valves and lines so they can be visually inspected periodically or installing electronic sensors to alarm when a leak is present. The leak detection plan will incorporate an automatic shut off system that will be installed for proposed pipelines to minimize the effects of an undesirable event.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out-sloping and in-sloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattle guards

An appropriately sized cattle guard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattle guards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattle guards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

STANDARD STIPULATIONS FOR SURFACE INSTALLED PIPELINES

A copy of the application (Grant, Sundry Notice, APD) and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 *et seq.* (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, *et seq.* or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, *et seq.*) on the Right-of-Way (unless the release or threatened release is wholly unrelated to activity of the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. The holder shall be liable for damage or injury to the United States to the extent provided by 43 CFR Sec. 2883.1-4. The holder shall be held to a standard of strict liability for damage or injury to the United States resulting from pipe rupture, fire, or spills caused or substantially aggravated by any of the following within the right-of-way or permit area:

- a. Activities of the holder including, but not limited to construction, operation, maintenance, and termination of the facility.
- b. Activities of other parties including, but not limited to:
 - (1) Land clearing.
 - (2) Earth-disturbing and earth-moving work.
 - (3) Blasting.
 - (4) Vandalism and sabotage.
- c. Acts of God.

The maximum limitation for such strict liability damages shall not exceed one million dollars (\$1,000,000) for any one event, and any liability in excess of such amount shall be determined by the ordinary rules of negligence of the jurisdiction in which the damage or injury occurred.

This section shall not impose strict liability for damage or injury resulting primarily from an act of war or from the negligent acts or omissions of the United States.

5. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil, salt water, or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil, salt water, or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any responsibility as provided herein.

6. All construction and maintenance activity will be confined to the authorized right-of-way width of 20 feet. If the pipeline route follows an existing road or buried pipeline right-of-way, the surface pipeline must be installed no farther than 10 feet from the edge of the road or buried pipeline right-of-way. If existing surface pipelines prevent this distance, the proposed surface pipeline must be installed immediately adjacent to the outer surface pipeline. All construction and maintenance activity will be confined to existing roads or right-of-ways.

7. No blading or clearing of any vegetation will be allowed unless approved in writing by the Authorized Officer.

8. The holder shall install the pipeline on the surface in such a manner that will minimize suspension of the pipeline across low areas in the terrain. In hummocky or dune areas, the pipeline will be "snaked" around hummocks and dunes rather than suspended across these features.

9. The pipeline shall be buried with a minimum of 24 inches under all roads, "two-tracks," and trails. Burial of the pipe will continue for 20 feet on each side of each crossing. The condition of the road, upon completion of construction, shall be returned to at least its former state with no bumps or dips remaining in the road surface.

10. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. Excluding the pipe, all above-ground structures not subject to safety requirement shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2; designated by the Rocky Mountain Five State Interagency Committee.

13. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. Signs will be maintained in a legible condition for the life of the pipeline.

14. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway.

15. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the authorized officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the authorized officer. An evaluation of the discovery will be made by the authorized officer to determine appropriate cultural or scientific values. The holder will

be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the authorized officer after consulting with the holder.

16. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, powerline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

17. Surface pipelines must be less than or equal to 4 inches and a working pressure below 125 psi.

18. Special Stipulations:

- a. **Lesser Prairie-Chicken:** Oil and gas activities will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Normal vehicle use on existing roads will not be restricted.
- b. This authorization is subject to your Certificate of Participation and/or Certificate of Inclusion under the New Mexico Candidate Conservation Agreement. Because it involves surface disturbing activities covered under your Certificate, your Habitat Conservation Fund Account with the Center of Excellence for Hazardous Materials Management (CEHMM) will be debited according to Exhibit B Part 2 of the Certificate of Participation.

BURIED PIPELINE STIPULATIONS

A copy of the application (Grant, APD, or Sundry Notice) and attachments, including conditions of approval, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The Holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The Holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil or other pollutant, wherever found, shall be the responsibility of holder, regardless of fault. Upon failure of holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve holder of any responsibility as provided herein.

5. All construction and maintenance activity will be confined to the authorized right-of-way.
6. The pipeline will be buried with a minimum cover of 36 inches between the top of the pipe and ground level.
7. The maximum allowable disturbance for construction in this right-of-way will be 30 feet:
 - Blading of vegetation within the right-of-way will be allowed: maximum width of blading operations will not exceed 20 feet. The trench is included in this area. (*Blading is defined as the complete removal of brush and ground vegetation.*)
 - Clearing of brush species within the right-of-way will be allowed: maximum width of clearing operations will not exceed 30 feet. The trench and bladed area are included in this area. (*Clearing is defined as the removal of brush while leaving ground vegetation (grasses, weeds, etc.) intact. Clearing is best accomplished by holding the blade 4 to 6 inches above the ground surface.*)
 - The remaining area of the right-of-way (if any) shall only be disturbed by compressing the vegetation. (*Compressing can be caused by vehicle tires, placement of equipment, etc.*)
8. The holder shall stockpile an adequate amount of topsoil where blading is allowed. The topsoil to be stripped is approximately 6 inches in depth. The topsoil will be segregated from other spoil piles from trench construction. The topsoil will be evenly distributed over the bladed area for the preparation of seeding.
9. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.
10. Vegetation, soil, and rocks left as a result of construction or maintenance activity will be randomly scattered on this right-of-way and will not be left in rows, piles, or berms, unless otherwise approved by the Authorized Officer. The entire right-of-way shall be recontoured to match the surrounding landscape. The backfilled soil shall be compacted and a 6 inch berm will be left over the ditch line to allow for settling back to grade.
11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. The holder will reseed all disturbed areas. Seeding will be done according to the attached seeding requirements, using the following seed mix.

- | | |
|--|--|
| <input type="checkbox"/> seed mixture 1 | <input type="checkbox"/> seed mixture 3 |
| <input type="checkbox"/> seed mixture 2 | <input type="checkbox"/> seed mixture 4 |
| <input checked="" type="checkbox"/> seed mixture 2/LPC | <input type="checkbox"/> Aplomado Falcon Mixture |

13. All above-ground structures not subject to safety requirements shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2.

14. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. All signs and information thereon will be posted in a permanent, conspicuous manner, and will be maintained in a legible condition for the life of the pipeline.

15. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder before maintenance begins. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway. As determined necessary during the life of the pipeline, the Authorized Officer may ask the holder to construct temporary deterrence structures.

16. Any cultural and/or paleontological resources (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

17. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes associated roads, pipeline corridor and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

18. Escape Ramps - The operator will construct and maintain pipeline/utility trenches [that are not otherwise fenced, screened, or netted] to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps,

ladders, or other methods of avian and terrestrial wildlife escape in the trenches according to the following criteria:

- a. Any trench left open for eight (8) hours or less is not required to have escape ramps; however, before the trench is backfilled, the contractor/operator shall inspect the trench for wildlife, remove all trapped wildlife, and release them at least 100 yards from the trench.
- b. For trenches left open for eight (8) hours or more, earthen escape ramps (built at no more than a 30 degree slope and spaced no more than 500 feet apart) shall be placed in the trench.

19. Special Stipulations:

Lesser Prairie-Chicken

Oil and gas activities will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

C. ELECTRIC LINES

STANDARD STIPULATIONS FOR OVERHEAD ELECTRIC DISTRIBUTION LINES

A copy of the grant and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b.

A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. There will be no clearing or blading of the right-of-way unless otherwise agreed to in writing by the Authorized Officer.

5. Power lines shall be constructed and designed in accordance to standards outlined in "Suggested Practices for Avian Protection on Power lines: The State of the Art in 2006" Edison Electric Institute, APLIC, and the California Energy Commission 2006 . The holder shall assume the burden and expense of proving that pole designs not shown in the above publication deter raptor perching, roosting, and nesting. Such proof shall be provided by a raptor expert approved by the Authorized Officer. The BLM reserves the right to require modification or additions to all powerline structures placed on this right-of-way, should they be necessary to ensure the safety of large perching birds. Such modifications and/or additions shall be made by the holder without liability or expense to the United States.

Raptor deterrence will consist of but not limited to the following: triangle perch discouragers shall be placed on each side of the cross arms and a nonconductive perching deterrence shall be placed on all vertical poles that extend past the cross arms.

6. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

7. The BLM serial number assigned to this authorization shall be posted in a permanent, conspicuous manner where the power line crosses roads and at all serviced facilities. Numbers will be at least two inches high and will be affixed to the pole nearest the road crossing and at the facilities served.

8. Upon cancellation, relinquishment, or expiration of this grant, the holder shall comply

with those abandonment procedures as prescribed by the Authorized Officer.

9. All surface structures (poles, lines, transformers, etc.) shall be removed within 180 days of abandonment, relinquishment, or termination of use of the serviced facility or facilities or within 180 days of abandonment, relinquishment, cancellation, or expiration of this grant, whichever comes first. This will not apply where the power line extends service to an active, adjoining facility or facilities.

10. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the Authorized Officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery will be made by the Authorized Officer to determine appropriate actions to prevent the loss of significant cultural or scientific values. The holder will be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the Authorized Officer after consulting with the holder.

11. Special Stipulations:

- For reclamation remove poles, lines, transformer, etc. and dispose of properly.
- Fill in any holes from the poles removed.

Timing Limitation Stipulation/Condition of Approval for Lesser Prairie-Chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration other than 3-D operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 ft. from the source of the noise.

VIII. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

IX. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture for LPC Sand/Shinnery Sites

Holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed shall be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed shall be either certified or registered seed. The seed container shall be tagged in accordance with State law(s) and available for inspection by the Authorized Officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). Holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. Seeding shall be repeated until a satisfactory stand is established as determined by the Authorized Officer. Evaluation of growth may not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains Bristlegrass	5lbs/A
Sand Bluestem	5lbs/A
Little Bluestem	3lbs/A
Big Bluestem	6lbs/A
Plains Coreopsis	2lbs/A
Sand Dropseed	1lbs/A

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Operator Certification Data Report

05/06/2019

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Christie Hanna

Signed on: 04/04/2019

Title: Senior Engineering Technician

Street Address: 5707 Southwest Parkway, Building 1, Suite 275

City: Austin

State: TX

Zip: 78735

Phone: (737)300-4723

Email address: channa@amerev.com

Field Representative

Representative Name: Zachary Boyd

Street Address: 5707 Southwest Parkway, Building 1, Suite 275

City: Austin

State: TX

Zip: 78735

Phone: (432)385-6996

Email address: zboyd@amerev.com



APD ID: 10400029847

Submission Date: 04/27/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Well Type: OIL WELL

Well Work Type: Drill



[Show Final Text](#)

Section 1 - General

APD ID: 10400029847

Tie to previous NOS?

Submission Date: 04/27/2018

BLM Office: CARLSBAD

User: Christie Hanna

Title: Senior Engineering Technician

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM023199

Lease Acres: 320

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? NO

Permitting Agent? NO

APD Operator: AMEREDEV OPERATING LLC

Operator letter of designation:

Operator Info

Operator Organization Name: AMEREDEV OPERATING LLC

Operator Address: 5707 Southwest Parkway, Building 1, Suite 275

Zip: 78735

Operator PO Box:

Operator City: Austin

State: TX

Operator Phone: (737)300-4700

Operator Internet Address:

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: JAL

Pool Name: WOLFCAMP
WEST

Is the proposed well in an area containing other mineral resources? USEABLE WATER

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Describe other minerals:

Is the proposed well in a Helium production area? N **Use Existing Well Pad?** NO **New surface disturbance?**

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name:
CAM/AZE

Number: 1N

Well Class: HORIZONTAL

Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: INFILL

Describe sub-type:

Distance to town: 5 Miles

Distance to nearest well: 760 FT

Distance to lease line: 230 FT

Reservoir well spacing assigned acres Measurement: 320 Acres

Well plat: CAMELLIA_FED_COM_26_36_21_101H__EXH_2AB_20190314085827.pdf

CAMELLIA_FED_COM_26_36_21_101H__VICINITY_MAP_20190314085827.pdf

CAMELLIA_FED_COM_26_36_21_101H__GAS_CAPTURE_PLAN_20190314085838.pdf

CAMELLIA_FED_COM_26_36_21_101H__C_102_SIG_20190314090032.pdf

CAMELLIA_FED_COM_26_36_21_101H__BLM_LEASE_MAP_20190314090257.pdf

Well work start Date: 03/15/2019

Duration: 90 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number: 18329

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
SHL Leg #1	283	FSL	230	FWL	26S	36E	21	Lot M	32.02229 - 49	103.2778 497	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 023199	292 3	0	0

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21


Well Number: 101H

	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD
KOP Leg #1	409	FNL	78	FEL	26S	36E	29	Aliquot NENE	32.0204	- 103.2788 6	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	- 847 7	114 39	114 00
PPP Leg #1	50	FNL	200	FWL	26S	36E	16	Lot D	32.05041	- 103.2779 6	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	- 904 6	227 75	119 69
EXIT Leg #1	50	FNL	200	FWL	26S	36E	16	Lot D	32.05041	- 103.2779 6	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	- 904 6	227 75	119 69
BHL Leg #1	50	FNL	200	FWL	26S	36E	16	Lot D	32.05041	- 103.2779 6	LEA	NEW MEXI CO	NEW MEXI CO	S	STATE	- 892 2	218 26	118 45

AMEREDEV

AMEREDEV OPERATING, LLC EXHIBIT 2A

SECTION 21, TOWNSHIP 26-S, RANGE 36-E, N.M.P.M.
LEA COUNTY, NEW MEXICO






**BOTTOM HOLE LOCATION
NEW MEXICO EAST**
NAD 1983
X=868319
Y=383675
LAT.: N 32.0504103
LONG.: W 103.2779606

**LAST TAKE POINT
NEW MEXICO EAST**
NAD 1983
X=868320
Y=383625
LAT.: N 32.0502729
LONG.: W 103.2779606

**FIRST TAKE POINT
NEW MEXICO EAST**
NAD 1983
X=868426
Y=373264
LAT.: N 32.0217918
LONG.: W 103.2779459

**SURFACE LOCATION
NEW MEXICO EAST**
NAD 1983
X=868454
Y=373447
LAT.: N 32.0222949
LONG.: W 103.2778497



LEASE NAME & WELL NO.: CAMELLIA FED COM 26 36 21 101H

SECTION 21 TWP 26-S RGE 36-E SURVEY N.M.P.M.
COUNTY LEA STATE NM
DESCRIPTION 283' FSL & 230' FWL

DISTANCE & DIRECTION
FROM INT. OF NM-205 & NM-128, HEAD SOUTH ON NM-205
±8.0 MILES, THENCE WEST (RIGHT) ON PROPOSED RD. ±1.1
MILES TO A POINT ±285 FEET SOUTHWEST OF THE
LOCATION.

ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID
BASED UPON THE NEW MEXICO COORDINATE SYSTEM, EAST ZONE OF THE NORTH
AMERICAN DATUM 1983, U.S. SURVEY FEET

THIS EASEMENT/SERVITUDE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND
UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF
SURVEY, AND DATA PROVIDED BY AMEREDEV OPERATING LLC. THIS CERTIFICATION IS MADE AND
LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS
NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY.



Michael Blake Brown, P.S. No. 18329
DECEMBER 17, 2018


TOPOGRAPHIC
LOYALTY INNOVATION LEGACY

1400 EVERMAN PARKWAY, Ste. 146 - FT. WORTH, TEXAS 76140
TELEPHONE: (817) 744-7512 • FAX: (817) 744-7554
2803 NORTH BIG SPRING - MIDLAND, TEXAS 79705
TELEPHONE: (432) 882-1653 OR (800) 767-1653 • FAX: (432) 882-1743
WWW.TOPOGRAPHIC.COM

EXHIBIT 2B

AMEREDEV


AMEREDEV OPERATING, LLC
 SECTION 21, TOWNSHIP 26-S, RANGE 36-E, N.M.P.M.
 LEA COUNTY, NEW MEXICO
 DETAIL VIEW
 SCALE: 1" = 100'



CENTER OF PAD
 X=868474
 Y=373448
 LAT.: N 32.0222959
 LONG.: W 103.2777852

LEASE NAME & WELL NO.: CAMELLIA FED COM 26 36 21 101H
 101H LATITUDE N 32.0222949 101H LONGITUDE W 103.2778497

CENTER OF PAD IS 283' FSL & 250' FWL




ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID BASED UPON THE NEW MEXICO COORDINATE SYSTEM, EAST ZONE OF THE NORTH AMERICAN DATUM 1983, U.S. SURVEY FEET

THIS PROPOSED PAD SITE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY, AND DATA PROVIDED BY AMEREDEV OPERATING LLC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY.

TOPOGRAPHIC
 LOYALTY INNOVATION LEGACY
 1400 EVERMAN PARKWAY, Ste. 146 • FT. WORTH, TEXAS 76140
 TELEPHONE: (817) 744-7512 • FAX (817) 744-7554
 2803 NORTH BIG SPRING • MIDLAND, TEXAS 79705
 TELEPHONE: (432) 682-1653 OR (800) 787-1653 • FAX (432) 682-1743
 WWW.TOPOGRAPHIC.COM

ORIGINAL DOCUMENT SIZE: 8.5" X 11"

EXHIBIT 2
VICINITY MAP



AMEREDEV

AMEREDEV OPERATING, LLC


LEASE NAME & WELL NO.: CAMELLIA FED COM 26 36 21 101H

SECTION 21 TWP 26-S RGE 36-E SURVEY N.M.P.M.

COUNTY LEA STATE NM

DESCRIPTION 283' FSL & 230' FWL

DISTANCE & DIRECTION
 FROM INT. OF NM-205 & NM-128, HEAD SOUTH ON NM-205
 ±8.0 MILES, THENCE WEST (RIGHT) ON PROPOSED RD. ±1.1
 MILES TO A POINT ±285 FEET SOUTHWEST OF THE
 LOCATION.




TOPOGRAPHIC
 LOYALTY INNOVATION LEGACY
 1400 EVERMAN PARKWAY, Ste. 146 • FT. WORTH, TEXAS 76140
 TELEPHONE: (817) 744-7512 • FAX (817) 744-7554
 2903 NORTH BIG SPRING • MIDLAND, TEXAS 79705
 TELEPHONE: (432) 682-1653 OR (800) 767-1653 • FAX (432) 682-1743
 WWW.TOPOGRAPHIC.COM

THIS EASEMENT/SERVITUDE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY, AND DATA PROVIDED BY AMEREDEV OPERATING LLC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY.

ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID BASED UPON THE NEW MEXICO COORDINATE SYSTEM, EAST ZONE OF THE NORTH AMERICAN DATUM 1983, U.S. SURVEY FEET.

LOCATION & ELEVATION VERIFICATION MAP



AMEREDEV OPERATING, LLC


LEASE NAME & WELL NO.: CAMELLIA FED COM 26 36 21 101H

SECTION 21 TWP 26-S RGE 36-E SURVEY N.M.P.M.

COUNTY LEA STATE NM ELEVATION 2923'

DESCRIPTION 283' FSL & 230' FWL

LATITUDE N 32.0222949 LONGITUDE W 103.2778497



1400 EVERMAN PARKWAY, Ste. 146 • FT. WORTH, TEXAS 76140
 TELEPHONE: (817) 744-7512 • FAX (817) 744-7554
 2903 NORTH BIG SPRING • MIDLAND, TEXAS 79705
 TELEPHONE: (432) 682-1653 OR (800) 787-1653 • FAX (432) 682-1743
 WWW.TOPOGRAPHIC.COM

THIS EASEMENT/SERVITUDE LOCATION SHOWN HEREON HAS BEEN SURVEYED ON THE GROUND UNDER MY SUPERVISION AND PREPARED ACCORDING TO THE EVIDENCE FOUND AT THE TIME OF SURVEY, AND DATA PROVIDED BY AMEREDEV OPERATING LLC. THIS CERTIFICATION IS MADE AND LIMITED TO THOSE PERSONS OR ENTITIES SHOWN ON THE FACE OF THIS PLAT AND IS NON-TRANSFERABLE. THIS SURVEY IS CERTIFIED FOR THIS TRANSACTION ONLY.

ALL BEARINGS, DISTANCES, AND COORDINATE VALUES CONTAINED HEREON ARE GRID BASED UPON THE NEW MEXICO COORDINATE SYSTEM, EAST ZONE OF THE NORTH AMERICAN DATUM 1983, U.S. SURVEY FEET.



APD ID: 10400029847

Submission Date: 04/27/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Well Type: OIL WELL

Well Work Type: Drill

[Show Final Text](#)

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
1	RUSTLER ANHYDRITE	1054	1876	1876	ANHYDRITE	NONE	No
2	SALADO	-1170	2224	2224	SALT	NONE	No
3	TANSILL	-2152	3206	3206	LIMESTONE	NONE	No
4	CAPITAN REEF	-2567	3621	3621	LIMESTONE	USEABLE WATER	No
5	LAMAR	-3898	4952	4952	LIMESTONE	NONE	No
6	BELL CANYON	-4032	5086	5086	SANDSTONE	NATURAL GAS,OIL	No
7	BRUSHY CANYON	-6051	7105	7105	SANDSTONE	NATURAL GAS,OIL	No
8	BONE SPRING LIME	-7075	8129	8129	LIMESTONE	NONE	No
9	BONE SPRING 1ST	-8577	9631	9631	SANDSTONE	NATURAL GAS,OIL	No
10	BONE SPRING 2ND	-9221	10275	10275	SANDSTONE	NATURAL GAS,OIL	No
11	BONE SPRING 3RD	-9752	10806	10806	LIMESTONE	NATURAL GAS,OIL	No
12	BONE SPRING 3RD	-10468	11522	11522	SANDSTONE	NATURAL GAS,OIL	No
13	WOLFCAMP	-10701	11755	11755	SHALE	NATURAL GAS,OIL	Yes

Section 2 - Blowout Prevention

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Pressure Rating (PSI): 10M

Rating Depth: 15000

Equipment: 10M BOPE SYSTEM WILL BE USED AFTER THE SURFACE CASING IS SET. A KELLY COCK WILL BE KEPT IN THE DRILL STRING AT ALL TIMES. A FULL OPENING DRILL PIPE STABBING VALVE WITH PROPER DRILL PIPE CONNECTIONS WILL BE ON THE RIG FLOOR AT ALL TIMES.

Requesting Variance? YES

Variance request: Co-Flex Choke Line, 5M Annular Preventer

Testing Procedure: See attachment

Choke Diagram Attachment:

10M_Choke_Manifold_REV_20190314091827.pdf

BOP Diagram Attachment:

5M_Annular_Preventer_Variance_and_Well_Control_Plan_20190314091844.pdf

5M_BOP_System_20190314091844.pdf

Pressure_Control_Plan_Single_Well_MB4_3String_Big_Hole_BLM_20190314091845.pdf

4_String_MB_Ameredev_Wellhead_Drawing_net_REV_20190314091922.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	2001	0	2001	2923		2001	J-55	68	OTHER - BTC	4.59	0.65	DRY	6.72	DRY	7.86
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	10931	0	10931	2923		10931	HCL-80	40	OTHER - BTC	1.26	1.22	DRY	2.14	DRY	2.15
3	PRODUCTION	8.5	5.5	NEW	API	N	0	22775	0	11969	2923		22775	HCP-110	20	OTHER - BTC	1.72	1.85	DRY	2.74	DRY	3.04

Casing Attachments

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Casing Attachments

Casing ID: 1 **String Type:** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

13.375_54.50_J55_SEAH_20190314092112.pdf

Camellia_Fed_Com_26_36_21_101H___Wellbore_Diagram_and_CDA_20190404094442.pdf

Casing ID: 2 **String Type:** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

9.625_40_SeAH80HC_4100_Collapse_20190314092327.pdf

Camellia_Fed_Com_26_36_21_101H___Wellbore_Diagram_and_CDA_20190404094458.pdf

Casing ID: 3 **String Type:** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

5.5_20_P110HP_Eagle_SFH_20190314092446.pdf

Camellia_Fed_Com_26_36_21_101H___Wellbore_Diagram_and_CDA_20190404094525.pdf

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	1615	1031	1.76	13.5	1815.28	50	CLASS C	Bentonite, Accelerator, Kolseal, Defoamer, Celloflake
SURFACE	Tail		1615	2001	200	1.34	14.8	268	100	CLASS C	Salt
INTERMEDIATE	Lead	5002	0	4152	684	2.47	11.9	1690.63	25	Class C	Salt, Bentonite, Kolseal, Defoamer, Celloflake, Anti-Settling Expansion Additive
INTERMEDIATE	Tail		4152	5002	200	1.33	14.8	266	25	Class C	Retarder
INTERMEDIATE	Lead	5002	0	9675	1572	2.47	11.9	3882.88	25	Class H	Bentonite, Salt, Kolseal, Defoamer, Celloflake, Retarder, Anti-Settling Expansion Additive
INTERMEDIATE	Tail		9675	10931	300	1.24	14.5	371.1	25	Class H	Salt, Bentonite, Retarder, Dispersant, Fluid Loss
PRODUCTION	Lead		0	22775	4863	1.34	14.2	6516.23	25	CLASS H	Salt, Bentonite, Fluid Loss, Dispersant, Retarder, Defoamer

Section 5 - Circulating Medium

Mud System Type: Semi-Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: All necessary supplies (e.g. bentonite, cedar bark) for fluid control will be on site.

Describe the mud monitoring system utilized: An electronic pit volume totalizer (PVT) will be utilized on the circulating system to monitor pit volume, flow rate, pump pressure, and pump rate.

Circulating Medium Table

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	2001	WATER-BASED MUD	8.4	8.6							
2001	1093 1	OTHER : Diesel Brine Emulsion	8.5	9.4							
1093 1	1196 9	OIL-BASED MUD	10.5	12.5							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

A directional survey, measurement while drilling and a mudlog/geologic lithology log will all be run from surface to TD.

List of open and cased hole logs run in the well:

DS,MWD,MUDLOG

Coring operation description for the well:

No coring will be done on this well.

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 5000

Anticipated Surface Pressure: 2366.82

Anticipated Bottom Hole Temperature(F): 160

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

H2S_Plan_20180427144330.pdf

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Cam101_DR_20190314093424.pdf

Cam101_LLR_20190314093425.pdf

5M_Annular_Preventer_Variance_and_Well_Control_Plan_20190314093440.pdf

Pressure_Control_Plan_Single_Well_MB4_3String_Big_Hole_BLM_20190314093441.pdf

Other proposed operations facets description:

4_String contingency plan attached






Other proposed operations facets attachment:

CAPITAN_PROTECTION_CONTINGENCY_PLAN_20190314093455.pdf

Other Variance attachment:

R616__CoC_for_hoses_12_18_17_20190314093555.pdf

Requested_Exceptions__3_String_Revised_01312019_20190314093556.pdf



PROPRIETARY
 THIS DRAWING AND THE IDEAS AND INFORMATION INCLUDED IN THIS DRAWING ARE PROPRIETARY AND ARE NOT TO BE REPRODUCED, DISTRIBUTED OR DISCLOSED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF A DULY AUTHORIZED OFFICER OF HELMERICH & PAYNE INT'L DRILLING CO.

ISSUED FOR FABRICATION
 February-10-2014
 DRAFTSMAN _____
 ENGINEER _____

STANDARD TOLERANCES		UNLESS NOTED:	
1. FABRICATION DIMENSIONS	A-UP TO 24"	± .0125"	
	B-24" TO 36"	± .015"	
	C-36" TO 48"	± .020"	
	D-48" TO 60"	± .025"	
2. MACHINED DIMENSIONS	ALL	± .005"	
	ANGULAR	± .015"	
	LINEAR (EXRESSED AS FRACTION)	± .015"	
	LINEAR (EXRESSED TO ONE DECIMAL)	± .010"	
	LINEAR (EXRESSED TO TWO DECIMALS)	± .005"	
	LINEAR (EXRESSED TO THREE DECIMALS)	± .0025"	

HELMERICH & PAYNE INTERNATIONAL DRILLING CO.	
TITLE 3 CHOKE, 3 LEVEL, 10M CHOKE MANIFOLD G.A.	
CUSTOMER H&P	
PROJECT	
DRAWN	DATE 2/10/2014
SCALE 3/8"=1'-0"	SHEET: 1 OF 1
REV	DESCRIPTION
DATE	BY
DWG. NO. HP-D1254	

5M Annular Preventer Variance Request and Well Control Procedures

Note: A copy of the Well Control Plan must be available at multiple locations on the rig for review by rig personnel, as well as review by the BLM PET/PE, and a copy must be maintained on the rig floor.

Dual Isolation Design for 5M Annular Exception

Ameredev will utilize 13-5/8" 10M (5M Annular) BOPE System consisting of:

- 13-5/8" 5M Annular
- 13-5/8" 10M Upper Pipe Rams
 - 3-1/2" – 5-1/2" Variable Bore Ram
- 13-5/8" 10M Blind Rams
- 13-5/8" 10M Drilling Spool /w 2 - 4" 10M Outlets Double 10M Isolation Valves
- 13-5/8" 10M Lower Blind Rams
 - 3-1/2" – 5-1/2" Variable Bore Ram

All drilling components and casing associated to exposure > 5000 psi BHP requiring a 10M system will have a double isolation (secondary barrier) below the 5M Annular that would provide a barrier to flow. The mud system will always be primary barrier, it will be maintained by adjusting values based on tourly mud tests and monitoring a PVT System to maintain static wellbore conditions, displacement procedures will be followed and recorded on daily drilling reports during tripping operations. Surge and swab pressure values will be calculated and maintained and static flow check will be monitored at previous casing shoe and verified static well conditions prior to tripping out of hole and again prior to pulling last joint of drill pipe through BOPE. The below table, documents that two barriers to flow can be maintained at all times, independent of the rating of the annular preventer.

Drill Components	Size	Primary Barrier	Secondary Barrier	Third Barrier
Drillpipe	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
HWDP Drillpipe	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Drill Collars	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Production Casing	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Open Hole	13-5/8	Drilling Fluid	Blind Rams	
All Drilling Components in 10M Environment will have OD that will allow full Operational RATED WORKING PRESSURE for system design. Kill line with minimum 2" ID will be available outside substructure with 10M Check Valve for OOH Kill Operations				

Well Control Procedures

Proper well control procedures are dependent to differentiating well conditions, to cover the basic well control operations there are will be standard drilling ahead, tripping pipe, tripping BHA, running casing, and pipe out of the hole/open hole scenarios that will be defined by procedures below. Initial Shut In Pressure can be taken against the Uppermost BOPE component the 5M Annular, pressure control can be transferred from the lesser 5M Annular to the 10M Upper Pipe Rams if needed. Shut In Pressures may be equal to or less than the Rated Working Pressure but at no time will the pressure on the annular preventer exceed the Rated Working Pressure of the annular. The annular will be tested to 5,000 psi. This will be the Rated Working Pressure of the annular preventer. All scenarios will be written such as shut in will be performed by closing the 10,000 psi Upper Pipe Rams for faster Accumulator pressure recovery to allow safer reaction to controlling wellbore pressure.

Shutting In While Drilling

1. Sound alarm signaling well control event to Rig Crew
2. Space out drill string to allow FOSV installation
3. Shut down pumps
4. Shut in Upper Pipe Rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
5. Install open, full open safety valve and close valve, Close Chokes
6. Verify well is shut-in and flow has stopped
7. Notify supervisory personnel
8. Record data (SIDP, SICP, Pit Gain, and Time)
9. Hold pre-job safety meeting and discuss kill procedure

Shutting In While Tripping

1. Sound alarm signaling well control event to Rig Crew
2. Space out drill string to allow FOSV installation
3. Shut in Upper Pipe Rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
4. Install open, full open safety valve and close valve, Close Chokes
5. Verify well is shut-in and flow has stopped
6. Notify supervisory personnel
7. Record data (SIDP, SICP, Pit Gain, and Time)
8. Hold pre-job safety meeting and discuss kill procedure

Shutting In While Running Casing

1. Sound alarm signaling well control event to Rig Crew
2. Space out casing to allow circulating swedge installation
3. Shut in Upper Pipe Rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
4. Install circulating swedge, Close high pressure, low torque valves, Close Chokes
5. Verify well is shut-in and flow has stopped
6. Notify supervisory personnel
7. Record data (SIDP, SICP, Pit Gain, and Time)
8. Hold Pre-job safety meeting and discuss kill procedure

Shutting in while out of hole

1. Sound alarm signaling well control event to Rig Crew
2. Shut-in well: close blind rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
3. Close Chokes, Verify well is shut-in and monitor pressures
4. Notify supervisory personnel
5. Record data (SIDP, SICP, Pit Gain, and Time)
6. Hold Pre-job safety meeting and discuss kill procedure

Shutting in prior to pulling BHA through stack

Prior to pulling last joint of drill pipe thru the stack space out and check flow
If flowing see steps below.

1. Sound alarm signaling well control event to Rig Crew
2. Shut in upper pipe ram and open HCR against Open Chokes and Valves Open
to working pressure gauge
3. Install open, full open safety valve and close valve, Close Chokes
4. Verify well is shut-in and flow has stopped
5. Notify supervisory personnel
6. Record data (SIDP, SICP, Pit Gain, and Time)
7. Hold pre-job safety meeting and discuss kill procedure

Shutting in while BHA is in the stack and ram preventer and combo immediately available

1. Sound alarm signaling well control event to Rig Crew
2. Space out BHA with upset just beneath the compatible pipe ram
3. Shut in upper compatible pipe ram and open HCR against Open Chokes and Valves Open to working pressure gauge
4. Install open, full open safety valve and close valve, Close Chokes
5. Verify well is shut-in and flow has stopped
6. Notify supervisory personnel
7. Record data (SIDP, SICP, Pit Gain, and Time)
8. Hold pre-job safety meeting and discuss kill procedure

*FOSV will be on rig floor in open position with operating handle for each type of connection utilized and tested to 10,000 psi

Shutting in while BHA is in the stack and no ram preventer or combo immediately available

1. Sound alarm signaling well control event to Rig Crew
2. If possible pick up high enough, to pull string clear and follow "Open Hole" scenario

If not possible to pick up high enough:

3. Stab Crossover, make up one joint/stand of drill pipe, and install open, full open safety valve (Leave Open)
4. Space out drill string with upset just beneath the compatible pipe ram.
5. Shut in upper compatible pipe ram and open HCR against Open Chokes and Valves Open to working pressure gauge
6. Close FOSV, Close Chokes, Verify well is shut-in and flow has stopped
7. Notify supervisory personnel
8. Record data (SIDP, SICP, Pit Gain, and Time)
9. Hold pre-job safety meeting and discuss kill procedure


13 5/8" 5M BOP Configuration

CO-FLEX LINE TO CHOKE MANIFOLD

4" 10M VALVES &

2" KILL LINE

10M Check Valve




Pressure Control Plan

Pressure Control Equipment

- Following setting of 13-3/8" Surface Casing Ameredev will install 13-5/8 MB4 Multi Bowl Casing Head by welding on a 13-5/8 SOW x 13-5/8" 5M in combination with 13-5/8 5M x 13-5/8 10M B-Sec to Land Intm #1 and a 13-5/8 10M x 13-5/8 10M shouldered to land C-Sec to Land Intm #2 (Installation procedure witnessed and verified by a manufacturer's representative).
- Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Ameredev will install a 5M System Blowout Preventer (BOPE) with a 5M Annular Preventer and related equipment (BOPE). Full testing will be performed utilizing a full isolation test plug and limited to 5,000 psi MOP of MB4 Multi Bowl Casing Head. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 50% of approved working pressure (2,500 psi). Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Setting of 9-5/8" Intermediate will be done by landing a wellhead hanger in the 13-5/8" 5M Bowl, Cementing and setting Well Head Packing seals and testing same. (Installation procedure witnessed and verified by a manufacturer's representative) Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Full testing will be performed utilizing a full isolation test plug to 10,000 psi MOP of MB4 Multi Bowl B-Section. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 100% of approved working pressure (5,000 psi).
- Before drilling >20ft of new formation under the 9-5/8" Casing Shoe a pressure integrity test of the Casing Shoe will be performed to minimum of the MWE anticipated to control formation pressure to the next casing depth.
- Following setting of 5-1/2" Production Casing and adequate WOC time Ameredev will break 10M System Blowout Preventer (BOP) from 10M DOL-2 Casing Head, install annulus casing slips and test same (Installation procedure witnessed and verified by a manufacturer's representative) and install 11" 10M x 5-1/8" 15M Tubing Head (Installation procedure witnessed and verified by a manufacturer's representative). Ameredev will test head to 70% casing design and install Dry Hole cap with needle valve and pressure gauge to monitor well awaiting completion.

Pressure Control Plan

- Slow pump speeds will be taken daily by each crew and recorded on Daily Drilling Report after mudding up.
- A choke manifold and accumulator with floor and remote operating stations will be functional and in place after installation of BOPE, as well as full functioning mud gas separator.
- Weekly BOPE pit level drills will be conducted by each crew and recorded on Daily Drilling Report.
- BOP will be fully operated when out of hole and will be documented on the daily drilling log.
- All B.O.P.s and associated equipment will be tested in accordance with Onshore Order #2
- All B.O.P. testing will be done by an independent service company.
- The B.O.P. will be tested within 21 days of the original test if drilling takes more time than planned.
- Ameredev requests a variance to connect the B.O.P. choke outlet to the choke manifold using a co-flex hose with a 10,000 psi working pressure that has been tested to 15,000psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps. (certifications will be sent to Carlsbad BLM Office prior to install)
- Ameredev requests a variance to install a 5M Annular Preventer on the 10M System to drill the Production Hole below the 9-5/8" Intermediate Section. 5M Annular will be tested to 100% working pressure (5,000 psi). A full well control procedure will be included to isolate well bore.



Quotation

Downing Wellhead Equipment

Oklahoma City,
Oklahoma - USA

Reference Data:

16925 AMEREDEV

Proprietary and Confidential

The information contained in this drawing is the sole property of Downing Wellhead Equipment, any reproduction in part or in whole without the written permission of Downing Wellhead Equipment is prohibited.

TITLE:

AMEREDEV

DRAWN		SIZE	DWG. NO.	REV.
CHECKED		A		
APPROVED		Scale:	Weight:	Sheet:

SeAH

13-3/8" 54.50# .380 J-55

Dimensions (Nominal)

Outside Diameter	13.375	in.
Wall	0.380	in.
Inside Diameter	12.615	in.
Drift	12.459	in.
Weight, T&C	54.500	lbs/ft
Weight, PE	52.790	lbs/ft

Performance Ratings, Minimum

Collapse, PE	1130	psi
Internal Yields Pressure		
PE	2730	psi
STC	2730	PSI
BTC	2730	psi
Yield Strength, Pipe Body	853	1000 lbs
Joint Strength, STC	514	1000 lbs
Joint Strength, BTC	909	1000 lbs

Note: SeAH Steel has produced this specification sheet for general information only. SeAH does not assume liability or responsibility for any loss or injury resulting from the use of information or data contained herein. All applications for the material described are at the customer's own risk and responsibility.



Wellbore Schematic

Well: Camellia Fed Com 26-36-21 101H
SHL: Sec. 21 26S-36E 283' FSL & 230' FWL
BHL: Sec. 16 26S-36E 50' FNL & 200' FWL
 Lea, NM
Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M
Xmas Tree: 2-9/16" 10M
Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: xxxxxx
AFE No.: xxxx-xxx
API No.: xxxxxxxxxxxx
GL: 2,923'
Field: Delaware
Objective: Wolfcamp A
TVD: 11,969'
MD: 22,775'
Rig: TBD **KB:** 27'
E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876'	1,231 Sacks TOC 0' 100% Excess	8.4-8.6 ppg WBM
	13.375" 68# J-55 BTC 2,001'		
12.25"	Salado 2,224'	884 Sacks TOC 0' 50% Excess	8.5 - 9.4 ppg Diesel Brine Emulsion
	Tansill 3,206'		
	Capitan Reef 3,621'		
	Lamar 4,952'		
	DV Tool 5,002'		
	Bell Canyon 5,086'		
	Brushy Canyon 7,105'		
9.625" 40# L-80HC BTC 10,931'	Bone Spring Lime 8,129'	1,723 Sacks TOC 0' 50% Excess	8.5 - 9.4 ppg Diesel Brine Emulsion
	First Bone Spring 9,631'		
	Second Bone Spring 10,275'		
	Third Bone Spring Upper 10,806'		
	Third Bone Spring 11,522'		
8.5"	Wolfcamp A 11,755'	4,863 Sacks TOC 0' 25% Excess	10.5 - 12.5 ppg OBM
	5.5" 20# P-110CYHP BTC 22,775'		
12° Build @ 11,438' MD thru 12,363' MD Target Wolfcamp A 11969 TVD // 22775 MD			

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	11,438'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	22,775'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.14	1.26	1.22
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	3.04	2.74	1.72	1.85
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	68.55	61.68	1.64	1.85

SeAH

9.625"

40#

.395"

SEAH-80 HIGH COLLAPSE

(SEAH-80 IS A NON HEAT TREATED PRODUCT)

Dimensions (Nominal)

Outside Diameter	9.625	in.
Wall	0.395	in.
Inside Diameter	8.835	in.
Drift	8.750	in.
Weight, T&C	40.000	lbs./ft.
Weight, PE	38.970	lbs./ft.

Performance Properties

Collapse	4100	psi
Internal Yield Pressure at Minimum Yield		
PE	5750	psi
LTC	5750	psi
BTC	5750	psi
Yield Strength, Pipe Body	916	1000 lbs.
Joint Strength		
LTC	717	1000 lbs.
BTC	915	1000 lbs.

Note: SeAH Steel has produced this specification sheet for general information only. SeAH does not assume liability or responsibility for any loss or injury resulting from the use of information or data contained herein. All applications for the material described are at the customer's own risk and responsibility.

AMEREDEV

AMEREDEV LLC

Wellbore Schematic

Well: Camellia Fed Com 26-36-21 101H
 SHL: Sec. 21 26S-36E 283' FSL & 230' FWL
 BHL: Sec. 16 26S-36E 50' FNL & 200' FWL
 Lea, NM
 Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M
 Xmas Tree: 2-9/16" 10M
 Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: xxxxxx
 AFE No.: xxxx-xxx
 API No.: xxxxxxxxxxxx
 GL: 2,923'
 Field: Delaware
 Objective: Wolfcamp A
 TVD: 11,969'
 MD: 22,775'
 Rig: TBD KB: 27'
 E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876'	1,231 Sacks TOC 0' 100% Excess	8.4-8.6 ppg WBM
	13.375" 68# J-55 BTC 2,001'		
12.25"	Salado 2,224'	884 Sacks TOC 0' 50% Excess	8.5 - 9.4 ppg Diesel Brine Emulsion
	Tansill 3,206'		
	Capitan Reef 3,621'		
	Lamar 4,952'		
	DV Tool 5,002'		
	Bell Canyon 5,086'	1,723 Sacks TOC 0' 50% Excess	
	Brushy Canyon 7,105'		
	Bone Spring Lime 8,129'		
	First Bone Spring 9,631'		
	Second Bone Spring 10,275'		
Third Bone Spring Upper 10,806'	1,723 Sacks TOC 0' 50% Excess		
9.625" 40# L-80HC BTC 10,931'			
8.5"	Third Bone Spring 11,522'	4,863 Sacks TOC 0' 25% Excess	10.5 - 12.5 ppg OBM
	Wolfcamp A 11,755'		
	5.5" 20# P-110CYHP BTC 22,775' Target Wolfcamp A 11969 TVD // 22775 MD		

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	11,438'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	22,775'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.14	1.26	1.22
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	3.04	2.74	1.72	1.85
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	68.55	61.68	1.64	1.85


U. S. Steel Tubular Products
5 1/2 20.00 lb (0.361) P110 HP
USS-EAGLE SFH™

	PIPE	CONNECTION	
MECHANICAL PROPERTIES			
Minimum Yield Strength	125,000	125,000	psi
Maximum Yield Strength	140,000	140,000	psi
Minimum Tensile Strength	130,000	130,000	psi
DIMENSIONS			
Outside Diameter	5.500	5.830	in.
Wall Thickness	0.361		in.
Inside Diameter	4.778	4.693	in.
Drift - API	4.653	4.653	in.
Nominal Linear Weight, T&C	19.83		lbs/ft
Plain End Weight	19.83	19.83	lbs/ft
SECTION AREA			
Cross Sectional Area Critical Area	5.828	5.054	sq. in.
Joint Efficiency		86.25	%
PERFORMANCE			
Minimum Collapse Pressure	13,150	13,150	psi
External Pressure Leak Resistance		10,000	psi
Minimum Internal Yield Pressure	14,360	14,360	psi
Minimum Pipe Body Yield Strength	729,000		lbs
Joint Strength		631,750	lbs
Compression Rating		631,750	lbs
Reference Length		21,240	ft
Maximum Uniaxial Bend Rating		89.9	deg/100 ft
Minimum Make-Up Torque		14,000	ft-lbs
Maximum Make-Up Torque		16,900	ft-lbs
Maximum Operating Torque		25,000	ft-lbs
Make-Up Loss		5.92	in.

Notes:

- Other than proprietary collapse and connection values, performance properties have been calculated using standard equations defined by API 5C3 and do not incorporate any additional design or safety factors. Calculations assume nominal pipe OD, nominal wall thickness, and Specified Minimum Yield Strength (SMYS).
- Compressive & Tensile Connection Efficiencies are calculated by dividing the connection critical area by the pipe body area.
- Uniaxial bending rating shown is structural only, and equal to compression efficiency.
- Torques have been calculated assuming a thread compound friction factor of 1.0 and are recommended only. Field make-up torques may require adjustment based on actual field conditions (e.g. make-up speed, temperature, thread compound, etc.).
- Reference length is calculated by joint strength divided by plain end weight with 1.5 safety factor.
- Connection external pressure resistance has been verified to 10,000 psi (Application specific testing).

Legal Notice: All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability, and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.
Manual USS Product Data Sheet 2017 rev25 (April)



Wellbore Schematic

Well: Camellia Fed Com 26-36-21 101H
SHL: Sec. 21 26S-36E 283' FSL & 230' FWL
BHL: Sec. 16 26S-36E 50' FNL & 200' FWL
 Lea, NM
Wellhead: A - 13-5/8" 10M x 13-5/8" SOW
 B - 13-5/8" 10M x 13-5/8" 10M
 C - 13-5/8" 10M x 13-5/8" 10M
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M
Xmas Tree: 2-9/16" 10M
Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: xxxxxx
AFE No.: xxxx-xxx
API No.: xxxxxxxxxxxx
GL: 2,923'
Field: Delaware
Objective: Wolfcamp A
TVD: 11,969'
MD: 22,775'
Rig: TBD **KB:** 27'
E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,876'	1,231 Sacks TOC 0' 100% Excess	8.4-8.6 ppg WBM
	13.375" 68# J-55 BTC 2,001'		
12.25"	Salado 2,224'	884 Sacks TOC 0' 50% Excess	8.5 - 9.4 ppg Diesel Brine Emulsion
	Tansill 3,206'		
	Capitan Reef 3,621'		
	Lamar 4,952'		
	DV Tool 5,002'		
	Bell Canyon 5,086'		
	Brushy Canyon 7,105'		
9.625" 40# L-80HC BTC	Bone Spring Lime 8,129'	1,723 Sacks TOC 0' 50% Excess	8.5 - 9.4 ppg Diesel Brine Emulsion
	First Bone Spring 9,631'		
	Second Bone Spring 10,275'		
	Third Bone Spring Upper 10,806'		
	9.625" 40# L-80HC BTC 10,931'		
8.5"	Third Bone Spring 11,522'	4,863 Sacks TOC 0' 25% Excess	10.5 - 12.5 ppg OBM
	Wolfcamp A 11,755'		
	5.5" 20# P-110CYHP BTC 22,775' Target Wolfcamp A 11969 TVD // 22775 MD		

Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	2,001'	13.375	68	J-55	BTC
Intermediate	12.25	10,931'	9.625	40	HCL-80	BTC
Prod Segment A	8.5	11,438'	5.5	20	CYHP-110	BTC
Prod Segment B	8.5	22,775'	5.5	20	CYHP-110	BTC

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
Safety Factors				
1.56	7.86	6.72	4.59	0.65
Check Intermediate Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
2.31	2.15	2.14	1.26	1.22
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	3.04	2.74	1.72	1.85
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
1.36	68.55	61.68	1.64	1.85

H₂S Drilling Operation Plan

1. **All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:**
 - a. Characteristics of H₂S
 - b. Physical effects and hazards
 - c. Principal and operation of H₂S detectors, warning system and briefing areas
 - d. Evacuation procedure, routes and first aid
 - e. Proper use of safety equipment and life support systems
 - f. Essential personnel meeting Medical Evaluation criteria will receive additional training on the proper use of 30 minute pressure demand air packs.

2. **Briefing Area:**
 - a. Two perpendicular areas will be designated by signs and readily accessible.
 - b. Upon location entry there will be a designated area to establish all safety compliance criteria (1.) has been met.

3. **H₂S Detection and Alarm Systems:**
 - a. H₂S sensors/detectors shall be located on the drilling rig floor, in the base of the sub structure/cellar area, and on the mud pits in the shale shaker area. Additional H₂S detectors may be placed as deemed necessary. All detectors will be set to initiate visual alarm at 10 ppm and visual with audible at 14 ppm and all equipment will be calibrated every 30 days or as needed.
 - b. An audio alarm will be installed on the derrick floor and in the top doghouse.

4. **Protective Equipment for Essential Personnel:**
 - a. **Breathing Apparatus:**
 - i. Rescue Packs (SCBA) - 1 Unit shall be placed at each briefing area.
 - ii. Two (SCBA) Units will be stored in safety trailer on location.
 - iii. Work/Escapes packs - 1 Unit will be available on rig floor in doghouse for emergency evacuation for driller.
 - b. **Auxiliary Rescue Equipment:**
 - i. Stretcher
 - ii. 2 - OSHA full body harnesses
 - iii. 100 ft. 5/8" OSHA approved rope
 - iv. 1 - 20# class ABC fire extinguisher

5. **Windsock and/or Wind Streamers:**
 - a. Windsock at mud pit area should be high enough to be visible.
 - b. Windsock on the rig floor should be high enough to be visible.

6. **Communication:**
 - a. While working under mask scripting boards will be used for communication where applicable.
 - b. Hand signals will be used when script boards are not applicable.

H₂S Drilling Operation Plan

- c. Two way radios will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at Drilling Foreman's Office.

7. **Drill Stem Testing:** - No Planned DST at this time.

8. **Mud program:**
 - a. If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

9. **Metallurgy:**
 - a. All drill strings, casing, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.
 - b. Drilling Contractor supervisor will be required to be familiar with the effect H₂S has on tubular goods and other mechanical equipment provided through contractor.

H₂S Contingency Plan

Emergency Procedures

In the event of a release of H₂S, the first responder(s) must:

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H₂S monitors and air packs in order to control the release.
- Use the "buddy system" to ensure no injuries occur during the response.
- Take precautions to avoid personal injury during this operation.
- Contact Operator and/or local officials the aid in operation. See list of phone numbers attached.
- Have received training in the:
 - Detection of H₂S and
 - Measures for protection against the gas,
 - Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H ₂ S	1.189 Air=1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air=1	2 ppm	N/A	1000 ppm

Contacting Authorities

Amerdev Operating LLC personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including direction to site. The following call list of essential and potential responders has been prepared for use during a release. Amerdev Operating LLC's response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER)



Amerdev Operating LLC

H₂S Contingency Plan

Amerdev Operating LLC – Emergency Phone 737-300-4799			
Key Personnel:			
Name	Title	Office	Mobile
Floyd Hammond	Chief Operating officer	737-300-4724	512-783-6810
Zachary Boyd	Operations Superintendent	737-300-4725	432-385-6996
Blake Estrada	Construction Foreman		432-385-5831

<u>Artesia</u>			
Ambulance			911
State Police			575-746-2703
City Police			575-746-2703
Sheriff's Office			575-746-9888
Fire Department			575-746-2701
Local Emergency Planning Committee			575-746-2122
New Mexico Oil Conservation Division			575-748-1283
<u>Carlsbad</u>			
Ambulance			911
State Police			575-885-3137
City Police			575-885-2111
Sheriff's Office			575-887-7551
Fire Department			575-887-3798
Local Emergency Planning Committee			575-887-6544
US Bureau of Land Management			575-887-6544
<u>Santa Fe</u>			
New Mexico Emergency Response Commission (Santa Fe)			505-476-9600
New Mexico Emergency Response Commission (Santa Fe) 24 Hrs			505-827-9126
New Mexico State Emergency Operations Center			505-476-9635
<u>National</u>			
National Emergency Response Center (Washington, D.C.)			800-424-8802
<u>Medical</u>			
Flight for Life - 4000 24th St.; Lubbock, TX			806-743-9911
Aerocare - R3, Box 49F; Lubbock, TX			806-747-8923
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM			505-842-4433
.SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM			505-842-4949

AMEREDEV

Ameredev Operating, LLC.

CAM/AZ

CAM/AZ #1N

Camellia 101H

Wellbore #1

Plan: Design #1

Standard Planning Report

16 January, 2019

Database:	EDM5000	Local Co-ordinate Reference:	Well Camellia 101H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 2951.0usft
Project:	CAM/AZ	MD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	North Reference:	Grid
Well:	Camellia 101H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Project	CAM/AZ		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	CAM/AZ #1N				
Site Position:		Northing:	373,448.30 usft	Latitude:	32° 1' 20.266 N
From:	Lat/Long	Easting:	868,493.74 usft	Longitude:	103° 16' 39.795 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16"	Grid Convergence:	0.56 °

Well	Camellia 101H					
Well Position	+N/-S	-0.8 usft	Northing:	373,447.48 usft	Latitude:	32° 1' 20.262 N
	+E/-W	-39.9 usft	Easting:	868,453.80 usft	Longitude:	103° 16' 40.259 W
Position Uncertainty		0.0 usft	Wellhead Elevation:		Ground Level:	2,924.0 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	1/11/2019	6.63	59.90	47,691.05418696

Design	Design #1				
Audit Notes:					
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0	
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.0	0.0	0.0	359.25	

Plan Survey Tool Program	Date	1/16/2019			
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks	
1	0.0	22,774.7	Design #1 (Wellbore #1)	MWD	
				OWSG MWD - Standard	

Database:	EDM5000	Local Co-ordinate Reference:	Well Camellia 101H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 2951.0usft
Project:	CAM/AZ	MD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	North Reference:	Grid
Well:	Camellia 101H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Plan Sections

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/S (usft)	+E/W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,300.0	6.00	204.00	2,299.5	-14.3	-6.4	2.00	2.00	0.00	204.00	
6,724.8	6.00	204.00	6,700.0	-436.9	-194.5	0.00	0.00	0.00	0.00	
7,024.8	0.00	0.00	6,999.5	-451.2	-200.9	2.00	-2.00	0.00	180.00	
8,525.3	0.00	0.00	8,500.0	-451.2	-200.9	0.00	0.00	0.00	0.00	
8,825.3	6.00	204.00	8,799.5	-465.5	-207.3	2.00	2.00	0.00	204.00	
11,038.0	6.00	204.00	11,000.0	-676.8	-301.3	0.00	0.00	0.00	0.00	
11,338.0	0.00	0.00	11,299.5	-691.2	-307.7	2.00	-2.00	0.00	180.00	
11,438.6	0.00	0.00	11,400.0	-691.2	-307.7	0.00	0.00	0.00	0.00	
11,764.5	39.24	60.25	11,701.0	-637.9	-214.5	12.04	12.04	0.00	60.25	
12,362.8	90.00	359.42	11,969.0	-183.3	-28.0	12.04	8.48	-10.17	-66.63	Cam101 FTP
22,774.7	90.00	359.42	11,969.0	10,228.0	-134.3	0.00	0.00	0.00	0.00	Cam101 BHL

Database:	EDM5000	Local Co-ordinate Reference:	Well Camellia 101H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 2951.0usft
Project:	CAM/AZ	MD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	North Reference:	Grid
Well:	Camellia 101H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	2.00	204.00	2,100.0	-1.6	-0.7	-1.6	2.00	2.00	0.00
2,200.0	4.00	204.00	2,199.8	-6.4	-2.8	-6.3	2.00	2.00	0.00
2,300.0	6.00	204.00	2,299.5	-14.3	-6.4	-14.3	2.00	2.00	0.00
2,400.0	6.00	204.00	2,398.9	-23.9	-10.6	-23.7	0.00	0.00	0.00
2,500.0	6.00	204.00	2,498.4	-33.4	-14.9	-33.2	0.00	0.00	0.00
2,600.0	6.00	204.00	2,597.8	-43.0	-19.1	-42.7	0.00	0.00	0.00
2,700.0	6.00	204.00	2,697.3	-52.5	-23.4	-52.2	0.00	0.00	0.00
2,800.0	6.00	204.00	2,796.7	-62.1	-27.6	-61.7	0.00	0.00	0.00
2,900.0	6.00	204.00	2,896.2	-71.6	-31.9	-71.2	0.00	0.00	0.00
3,000.0	6.00	204.00	2,995.6	-81.2	-36.1	-80.7	0.00	0.00	0.00
3,100.0	6.00	204.00	3,095.1	-90.7	-40.4	-90.2	0.00	0.00	0.00
3,200.0	6.00	204.00	3,194.5	-100.3	-44.6	-99.7	0.00	0.00	0.00
3,300.0	6.00	204.00	3,294.0	-109.8	-48.9	-109.2	0.00	0.00	0.00
3,400.0	6.00	204.00	3,393.4	-119.4	-53.2	-118.7	0.00	0.00	0.00
3,500.0	6.00	204.00	3,492.9	-128.9	-57.4	-128.2	0.00	0.00	0.00
3,600.0	6.00	204.00	3,592.3	-138.5	-61.7	-137.7	0.00	0.00	0.00
3,700.0	6.00	204.00	3,691.8	-148.0	-65.9	-147.1	0.00	0.00	0.00
3,800.0	6.00	204.00	3,791.2	-157.6	-70.2	-156.6	0.00	0.00	0.00
3,900.0	6.00	204.00	3,890.7	-167.1	-74.4	-166.1	0.00	0.00	0.00
4,000.0	6.00	204.00	3,990.1	-176.7	-78.7	-175.6	0.00	0.00	0.00
4,100.0	6.00	204.00	4,089.6	-186.2	-82.9	-185.1	0.00	0.00	0.00
4,200.0	6.00	204.00	4,189.0	-195.8	-87.2	-194.6	0.00	0.00	0.00
4,300.0	6.00	204.00	4,288.5	-205.3	-91.4	-204.1	0.00	0.00	0.00
4,400.0	6.00	204.00	4,387.9	-214.9	-95.7	-213.6	0.00	0.00	0.00
4,500.0	6.00	204.00	4,487.4	-224.4	-99.9	-223.1	0.00	0.00	0.00
4,600.0	6.00	204.00	4,586.9	-234.0	-104.2	-232.6	0.00	0.00	0.00
4,700.0	6.00	204.00	4,686.3	-243.5	-108.4	-242.1	0.00	0.00	0.00
4,800.0	6.00	204.00	4,785.8	-253.1	-112.7	-251.6	0.00	0.00	0.00
4,900.0	6.00	204.00	4,885.2	-262.6	-116.9	-261.1	0.00	0.00	0.00
5,000.0	6.00	204.00	4,984.7	-272.2	-121.2	-270.5	0.00	0.00	0.00
5,100.0	6.00	204.00	5,084.1	-281.7	-125.4	-280.0	0.00	0.00	0.00
5,200.0	6.00	204.00	5,183.6	-291.3	-129.7	-289.5	0.00	0.00	0.00
5,300.0	6.00	204.00	5,283.0	-300.8	-133.9	-299.0	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Camellia 101H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 2951.0usft
Project:	CAM/AZ	MD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	North Reference:	Grid
Well:	Camellia 101H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Bulld Rate (°/100usft)	Turn Rate (°/100usft)
5,400.0	6.00	204.00	5,382.5	-310.4	-138.2	-308.5	0.00	0.00	0.00
5,500.0	6.00	204.00	5,481.9	-319.9	-142.4	-318.0	0.00	0.00	0.00
5,600.0	6.00	204.00	5,581.4	-329.5	-146.7	-327.5	0.00	0.00	0.00
5,700.0	6.00	204.00	5,680.8	-339.0	-150.9	-337.0	0.00	0.00	0.00
5,800.0	6.00	204.00	5,780.3	-348.6	-155.2	-346.5	0.00	0.00	0.00
5,900.0	6.00	204.00	5,879.7	-358.1	-159.4	-356.0	0.00	0.00	0.00
6,000.0	6.00	204.00	5,979.2	-367.7	-163.7	-365.5	0.00	0.00	0.00
6,100.0	6.00	204.00	6,078.6	-377.2	-167.9	-375.0	0.00	0.00	0.00
6,200.0	6.00	204.00	6,178.1	-386.8	-172.2	-384.5	0.00	0.00	0.00
6,300.0	6.00	204.00	6,277.5	-396.3	-176.4	-394.0	0.00	0.00	0.00
6,400.0	6.00	204.00	6,377.0	-405.9	-180.7	-403.4	0.00	0.00	0.00
6,500.0	6.00	204.00	6,476.4	-415.4	-184.9	-412.9	0.00	0.00	0.00
6,600.0	6.00	204.00	6,575.9	-425.0	-189.2	-422.4	0.00	0.00	0.00
6,700.0	6.00	204.00	6,675.3	-434.5	-193.5	-431.9	0.00	0.00	0.00
6,724.8	6.00	204.00	6,700.0	-436.9	-194.5	-434.3	0.00	0.00	0.00
6,800.0	4.50	204.00	6,774.9	-443.2	-197.3	-440.5	2.00	-2.00	0.00
6,900.0	2.50	204.00	6,874.7	-448.7	-199.8	-446.1	2.00	-2.00	0.00
7,000.0	0.50	204.00	6,974.7	-451.1	-200.8	-448.4	2.00	-2.00	0.00
7,024.8	0.00	0.00	6,999.5	-451.2	-200.9	-448.5	2.00	-2.00	0.00
7,100.0	0.00	0.00	7,074.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
7,200.0	0.00	0.00	7,174.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
7,300.0	0.00	0.00	7,274.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
7,400.0	0.00	0.00	7,374.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
7,500.0	0.00	0.00	7,474.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
7,600.0	0.00	0.00	7,574.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
7,700.0	0.00	0.00	7,674.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
7,800.0	0.00	0.00	7,774.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
7,900.0	0.00	0.00	7,874.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
8,000.0	0.00	0.00	7,974.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
8,100.0	0.00	0.00	8,074.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
8,200.0	0.00	0.00	8,174.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
8,300.0	0.00	0.00	8,274.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
8,400.0	0.00	0.00	8,374.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
8,500.0	0.00	0.00	8,474.7	-451.2	-200.9	-448.5	0.00	0.00	0.00
8,525.3	0.00	0.00	8,500.0	-451.2	-200.9	-448.5	0.00	0.00	0.00
8,600.0	1.49	204.00	8,574.7	-452.1	-201.3	-449.4	2.00	2.00	0.00
8,700.0	3.49	204.00	8,674.6	-456.1	-203.1	-453.4	2.00	2.00	0.00
8,800.0	5.49	204.00	8,774.2	-463.2	-206.2	-460.5	2.00	2.00	0.00
8,825.3	6.00	204.00	8,799.5	-465.5	-207.3	-462.8	2.00	2.00	0.00
8,900.0	6.00	204.00	8,873.7	-472.7	-210.4	-469.9	0.00	0.00	0.00
9,000.0	6.00	204.00	8,973.2	-482.2	-214.7	-479.4	0.00	0.00	0.00
9,100.0	6.00	204.00	9,072.6	-491.8	-218.9	-488.9	0.00	0.00	0.00
9,200.0	6.00	204.00	9,172.1	-501.3	-223.2	-498.3	0.00	0.00	0.00
9,300.0	6.00	204.00	9,271.5	-510.9	-227.5	-507.8	0.00	0.00	0.00
9,400.0	6.00	204.00	9,371.0	-520.4	-231.7	-517.3	0.00	0.00	0.00
9,500.0	6.00	204.00	9,470.4	-530.0	-236.0	-526.8	0.00	0.00	0.00
9,600.0	6.00	204.00	9,569.9	-539.5	-240.2	-536.3	0.00	0.00	0.00
9,700.0	6.00	204.00	9,669.3	-549.1	-244.5	-545.8	0.00	0.00	0.00
9,800.0	6.00	204.00	9,768.8	-558.6	-248.7	-555.3	0.00	0.00	0.00
9,900.0	6.00	204.00	9,868.2	-568.2	-253.0	-564.8	0.00	0.00	0.00
10,000.0	6.00	204.00	9,967.7	-577.7	-257.2	-574.3	0.00	0.00	0.00
10,100.0	6.00	204.00	10,067.1	-587.3	-261.5	-583.8	0.00	0.00	0.00
10,200.0	6.00	204.00	10,166.6	-596.8	-265.7	-593.3	0.00	0.00	0.00
10,300.0	6.00	204.00	10,266.0	-606.4	-270.0	-602.8	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Camellia 101H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 2951.0usft
Project:	CAM/AZ	MD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	North Reference:	Grid
Well:	Camellia 101H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,400.0	6.00	204.00	10,365.5	-615.9	-274.2	-612.3	0.00	0.00	0.00
10,500.0	6.00	204.00	10,464.9	-625.5	-278.5	-621.7	0.00	0.00	0.00
10,600.0	6.00	204.00	10,564.4	-635.0	-282.7	-631.2	0.00	0.00	0.00
10,700.0	6.00	204.00	10,663.8	-644.6	-287.0	-640.7	0.00	0.00	0.00
10,740.0	6.00	204.00	10,703.6	-648.4	-288.7	-644.5	0.00	0.00	0.00
Sec 28									
10,800.0	6.00	204.00	10,763.3	-654.1	-291.2	-650.2	0.00	0.00	0.00
10,900.0	6.00	204.00	10,862.8	-663.7	-295.5	-659.7	0.00	0.00	0.00
11,000.0	6.00	204.00	10,962.2	-673.2	-299.7	-669.2	0.00	0.00	0.00
11,038.0	6.00	204.00	11,000.0	-676.8	-301.3	-672.8	0.00	0.00	0.00
11,100.0	4.76	204.00	11,061.7	-682.1	-303.7	-678.1	2.00	-2.00	0.00
11,200.0	2.76	204.00	11,161.5	-688.1	-306.4	-684.0	2.00	-2.00	0.00
11,300.0	0.76	204.00	11,261.4	-690.9	-307.6	-686.8	2.00	-2.00	0.00
11,338.0	0.00	0.00	11,299.5	-691.2	-307.7	-687.1	2.00	-2.00	0.00
11,400.0	0.00	0.00	11,361.4	-691.2	-307.7	-687.1	0.00	0.00	0.00
11,438.6	0.00	0.00	11,400.0	-691.2	-307.7	-687.1	0.00	0.00	0.00
11,500.0	7.40	60.25	11,461.3	-689.2	-304.3	-685.1	12.04	12.04	0.00
11,600.0	19.44	60.25	11,558.4	-677.7	-284.2	-673.9	12.04	12.04	0.00
11,700.0	31.48	60.25	11,648.5	-656.4	-246.9	-653.1	12.04	12.04	0.00
11,764.5	39.24	60.25	11,701.0	-637.9	-214.5	-635.0	12.04	12.04	0.00
11,800.0	41.10	54.28	11,728.2	-625.5	-195.3	-622.9	12.04	5.22	-16.83
11,900.0	47.72	39.85	11,799.8	-577.8	-144.7	-575.8	12.04	6.62	-14.42
12,000.0	55.78	28.43	11,861.7	-512.8	-101.2	-511.4	12.04	8.06	-11.42
12,100.0	64.71	19.11	11,911.4	-433.4	-66.6	-432.5	12.04	8.93	-9.32
12,144.1	68.83	15.45	11,928.8	-394.7	-54.5	-393.9	12.04	9.33	-8.29
Sec 21									
12,200.0	74.15	11.10	11,946.5	-343.1	-42.4	-342.5	12.04	9.52	-7.78
12,300.0	83.85	3.82	11,965.6	-246.0	-29.8	-245.6	12.04	9.70	-7.28
12,362.8	90.00	359.42	11,969.0	-183.3	-28.0	-182.9	12.04	9.79	-7.02
Cam101 FTP									
12,400.0	90.00	359.42	11,969.0	-146.1	-28.4	-145.8	0.00	0.00	0.00
12,500.0	90.00	359.42	11,969.0	-46.1	-29.4	-45.8	0.00	0.00	0.00
12,600.0	90.00	359.42	11,969.0	53.9	-30.4	54.2	0.00	0.00	0.00
12,700.0	90.00	359.42	11,969.0	153.8	-31.5	154.2	0.00	0.00	0.00
12,800.0	90.00	359.42	11,969.0	253.8	-32.5	254.2	0.00	0.00	0.00
12,900.0	90.00	359.42	11,969.0	353.8	-33.5	354.2	0.00	0.00	0.00
13,000.0	90.00	359.42	11,969.0	453.8	-34.5	454.2	0.00	0.00	0.00
13,100.0	90.00	359.42	11,969.0	553.8	-35.6	554.2	0.00	0.00	0.00
13,200.0	90.00	359.42	11,969.0	653.8	-36.6	654.2	0.00	0.00	0.00
13,300.0	90.00	359.42	11,969.0	753.8	-37.6	754.2	0.00	0.00	0.00
13,400.0	90.00	359.42	11,969.0	853.8	-38.6	854.2	0.00	0.00	0.00
13,500.0	90.00	359.42	11,969.0	953.8	-39.6	954.2	0.00	0.00	0.00
13,600.0	90.00	359.42	11,969.0	1,053.8	-40.7	1,054.2	0.00	0.00	0.00
13,700.0	90.00	359.42	11,969.0	1,153.8	-41.7	1,154.2	0.00	0.00	0.00
13,800.0	90.00	359.42	11,969.0	1,253.8	-42.7	1,254.2	0.00	0.00	0.00
13,900.0	90.00	359.42	11,969.0	1,353.8	-43.7	1,354.2	0.00	0.00	0.00
14,000.0	90.00	359.42	11,969.0	1,453.8	-44.7	1,454.2	0.00	0.00	0.00
14,100.0	90.00	359.42	11,969.0	1,553.8	-45.8	1,554.2	0.00	0.00	0.00
14,200.0	90.00	359.42	11,969.0	1,653.8	-46.8	1,654.2	0.00	0.00	0.00
14,300.0	90.00	359.42	11,969.0	1,753.8	-47.8	1,754.2	0.00	0.00	0.00
14,400.0	90.00	359.42	11,969.0	1,853.8	-48.8	1,854.2	0.00	0.00	0.00
14,500.0	90.00	359.42	11,969.0	1,953.8	-49.8	1,954.2	0.00	0.00	0.00
14,600.0	90.00	359.42	11,969.0	2,053.7	-50.9	2,054.2	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Camellia 101H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 2951.0usft
Project:	CAM/AZ	MD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	North Reference:	Grid
Well:	Camellia 101H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
14,700.0	90.00	359.42	11,969.0	2,153.7	-51.9	2,154.2	0.00	0.00	0.00
14,800.0	90.00	359.42	11,969.0	2,253.7	-52.9	2,254.2	0.00	0.00	0.00
14,900.0	90.00	359.42	11,969.0	2,353.7	-53.9	2,354.2	0.00	0.00	0.00
15,000.0	90.00	359.42	11,969.0	2,453.7	-55.0	2,454.2	0.00	0.00	0.00
15,100.0	90.00	359.42	11,969.0	2,553.7	-56.0	2,554.2	0.00	0.00	0.00
15,200.0	90.00	359.42	11,969.0	2,653.7	-57.0	2,654.2	0.00	0.00	0.00
15,300.0	90.00	359.42	11,969.0	2,753.7	-58.0	2,754.2	0.00	0.00	0.00
15,400.0	90.00	359.42	11,969.0	2,853.7	-59.0	2,854.2	0.00	0.00	0.00
15,500.0	90.00	359.42	11,969.0	2,953.7	-60.1	2,954.2	0.00	0.00	0.00
15,600.0	90.00	359.42	11,969.0	3,053.7	-61.1	3,054.2	0.00	0.00	0.00
15,700.0	90.00	359.42	11,969.0	3,153.7	-62.1	3,154.2	0.00	0.00	0.00
15,800.0	90.00	359.42	11,969.0	3,253.7	-63.1	3,254.2	0.00	0.00	0.00
15,900.0	90.00	359.42	11,969.0	3,353.7	-64.1	3,354.2	0.00	0.00	0.00
16,000.0	90.00	359.42	11,969.0	3,453.7	-65.2	3,454.2	0.00	0.00	0.00
16,100.0	90.00	359.42	11,969.0	3,553.7	-66.2	3,554.2	0.00	0.00	0.00
16,200.0	90.00	359.42	11,969.0	3,653.7	-67.2	3,654.2	0.00	0.00	0.00
16,300.0	90.00	359.42	11,969.0	3,753.7	-68.2	3,754.2	0.00	0.00	0.00
16,400.0	90.00	359.42	11,969.0	3,853.7	-69.2	3,854.2	0.00	0.00	0.00
16,500.0	90.00	359.42	11,969.0	3,953.6	-70.3	3,954.2	0.00	0.00	0.00
16,600.0	90.00	359.42	11,969.0	4,053.6	-71.3	4,054.2	0.00	0.00	0.00
16,700.0	90.00	359.42	11,969.0	4,153.6	-72.3	4,154.2	0.00	0.00	0.00
16,800.0	90.00	359.42	11,969.0	4,253.6	-73.3	4,254.2	0.00	0.00	0.00
16,900.0	90.00	359.42	11,969.0	4,353.6	-74.3	4,354.2	0.00	0.00	0.00
17,000.0	90.00	359.42	11,969.0	4,453.6	-75.4	4,454.2	0.00	0.00	0.00
17,100.0	90.00	359.42	11,969.0	4,553.6	-76.4	4,554.2	0.00	0.00	0.00
17,200.0	90.00	359.42	11,969.0	4,653.6	-77.4	4,654.2	0.00	0.00	0.00
17,300.0	90.00	359.42	11,969.0	4,753.6	-78.4	4,754.2	0.00	0.00	0.00
17,400.0	90.00	359.42	11,969.0	4,853.6	-79.5	4,854.2	0.00	0.00	0.00
17,500.0	90.00	359.42	11,969.0	4,953.6	-80.5	4,954.2	0.00	0.00	0.00
17,544.4	90.00	359.42	11,969.0	4,998.0	-80.9	4,998.7	0.00	0.00	0.00
Sec 16									
17,600.0	90.00	359.42	11,969.0	5,053.6	-81.5	5,054.2	0.00	0.00	0.00
17,700.0	90.00	359.42	11,969.0	5,153.6	-82.5	5,154.2	0.00	0.00	0.00
17,800.0	90.00	359.42	11,969.0	5,253.6	-83.5	5,254.2	0.00	0.00	0.00
17,900.0	90.00	359.42	11,969.0	5,353.6	-84.6	5,354.2	0.00	0.00	0.00
18,000.0	90.00	359.42	11,969.0	5,453.6	-85.6	5,454.2	0.00	0.00	0.00
18,100.0	90.00	359.42	11,969.0	5,553.6	-86.6	5,554.2	0.00	0.00	0.00
18,200.0	90.00	359.42	11,969.0	5,653.6	-87.6	5,654.2	0.00	0.00	0.00
18,300.0	90.00	359.42	11,969.0	5,753.6	-88.6	5,754.2	0.00	0.00	0.00
18,400.0	90.00	359.42	11,969.0	5,853.5	-89.7	5,854.2	0.00	0.00	0.00
18,500.0	90.00	359.42	11,969.0	5,953.5	-90.7	5,954.2	0.00	0.00	0.00
18,600.0	90.00	359.42	11,969.0	6,053.5	-91.7	6,054.2	0.00	0.00	0.00
18,700.0	90.00	359.42	11,969.0	6,153.5	-92.7	6,154.2	0.00	0.00	0.00
18,800.0	90.00	359.42	11,969.0	6,253.5	-93.7	6,254.2	0.00	0.00	0.00
18,900.0	90.00	359.42	11,969.0	6,353.5	-94.8	6,354.2	0.00	0.00	0.00
19,000.0	90.00	359.42	11,969.0	6,453.5	-95.8	6,454.2	0.00	0.00	0.00
19,100.0	90.00	359.42	11,969.0	6,553.5	-96.8	6,554.2	0.00	0.00	0.00
19,200.0	90.00	359.42	11,969.0	6,653.5	-97.8	6,654.2	0.00	0.00	0.00
19,300.0	90.00	359.42	11,969.0	6,753.5	-98.9	6,754.2	0.00	0.00	0.00
19,400.0	90.00	359.42	11,969.0	6,853.5	-99.9	6,854.2	0.00	0.00	0.00
19,500.0	90.00	359.42	11,969.0	6,953.5	-100.9	6,954.2	0.00	0.00	0.00
19,600.0	90.00	359.42	11,969.0	7,053.5	-101.9	7,054.2	0.00	0.00	0.00
19,700.0	90.00	359.42	11,969.0	7,153.5	-102.9	7,154.2	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Camellia 101H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 2951.0usft
Project:	CAM/AZ	MD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	North Reference:	Grid
Well:	Camellia 101H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
19,800.0	90.00	359.42	11,969.0	7,253.5	-104.0	7,254.2	0.00	0.00	0.00
19,900.0	90.00	359.42	11,969.0	7,353.5	-105.0	7,354.2	0.00	0.00	0.00
20,000.0	90.00	359.42	11,969.0	7,453.5	-106.0	7,454.2	0.00	0.00	0.00
20,100.0	90.00	359.42	11,969.0	7,553.5	-107.0	7,554.2	0.00	0.00	0.00
20,200.0	90.00	359.42	11,969.0	7,653.5	-108.0	7,654.2	0.00	0.00	0.00
20,300.0	90.00	359.42	11,969.0	7,753.5	-109.1	7,754.2	0.00	0.00	0.00
20,400.0	90.00	359.42	11,969.0	7,853.4	-110.1	7,854.2	0.00	0.00	0.00
20,500.0	90.00	359.42	11,969.0	7,953.4	-111.1	7,954.2	0.00	0.00	0.00
20,600.0	90.00	359.42	11,969.0	8,053.4	-112.1	8,054.2	0.00	0.00	0.00
20,700.0	90.00	359.42	11,969.0	8,153.4	-113.1	8,154.2	0.00	0.00	0.00
20,800.0	90.00	359.42	11,969.0	8,253.4	-114.2	8,254.2	0.00	0.00	0.00
20,900.0	90.00	359.42	11,969.0	8,353.4	-115.2	8,354.2	0.00	0.00	0.00
21,000.0	90.00	359.42	11,969.0	8,453.4	-116.2	8,454.2	0.00	0.00	0.00
21,100.0	90.00	359.42	11,969.0	8,553.4	-117.2	8,554.2	0.00	0.00	0.00
21,200.0	90.00	359.42	11,969.0	8,653.4	-118.2	8,654.2	0.00	0.00	0.00
21,300.0	90.00	359.42	11,969.0	8,753.4	-119.3	8,754.2	0.00	0.00	0.00
21,400.0	90.00	359.42	11,969.0	8,853.4	-120.3	8,854.2	0.00	0.00	0.00
21,500.0	90.00	359.42	11,969.0	8,953.4	-121.3	8,954.2	0.00	0.00	0.00
21,600.0	90.00	359.42	11,969.0	9,053.4	-122.3	9,054.2	0.00	0.00	0.00
21,700.0	90.00	359.42	11,969.0	9,153.4	-123.4	9,154.2	0.00	0.00	0.00
21,800.0	90.00	359.42	11,969.0	9,253.4	-124.4	9,254.2	0.00	0.00	0.00
21,900.0	90.00	359.42	11,969.0	9,353.4	-125.4	9,354.2	0.00	0.00	0.00
22,000.0	90.00	359.42	11,969.0	9,453.4	-126.4	9,454.2	0.00	0.00	0.00
22,100.0	90.00	359.42	11,969.0	9,553.4	-127.4	9,554.2	0.00	0.00	0.00
22,200.0	90.00	359.42	11,969.0	9,653.4	-128.5	9,654.2	0.00	0.00	0.00
22,300.0	90.00	359.42	11,969.0	9,753.3	-129.5	9,754.2	0.00	0.00	0.00
22,400.0	90.00	359.42	11,969.0	9,853.3	-130.5	9,854.2	0.00	0.00	0.00
22,500.0	90.00	359.42	11,969.0	9,953.3	-131.5	9,954.2	0.00	0.00	0.00
22,600.0	90.00	359.42	11,969.0	10,053.3	-132.5	10,054.2	0.00	0.00	0.00
22,700.0	90.00	359.42	11,969.0	10,153.3	-133.6	10,154.2	0.00	0.00	0.00
Cam101 LTP									
22,774.7	90.00	359.42	11,969.0	10,228.0	-134.3	10,228.9	0.00	0.00	0.00
Cam101 BHL									

Database:	EDM5000	Local Co-ordinate Reference:	Well Camellia 101H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 2951.0usft
Project:	CAM/AZ	MD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	North Reference:	Grid
Well:	Camellia 101H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Design Targets

Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
Sec 28	0.00	0.00	10,236.0	-5,569.3	-174.8	367,878.13	868,279.00	32° 0' 25.171 N	103° 16' 42.920 W
- plan misses target center by 4944.5usft at 10740.0usft MD (10703.6 TVD, -648.4 N, -288.7 E)									
- Polygon									
Point 1			10,236.0	0.0	0.0	367,878.13	868,279.00		
Point 2			10,236.0	5,283.8	-52.1	373,161.93	868,226.90		
Point 3			10,236.0	5,342.2	5,232.0	373,220.33	873,511.00		
Point 4			10,236.0	60.2	5,286.0	367,938.33	873,565.00		
Sec 21	0.00	0.00	11,767.0	-285.5	-226.9	373,161.95	868,226.87	32° 1' 17.458 N	103° 16' 42.927 W
- plan misses target center by 260.4usft at 12129.1usft MD (11923.2 TVD, -408.1 N, -58.4 E)									
- Polygon									
Point 1			11,767.0	0.0	0.0	373,161.95	868,226.87		
Point 2			11,767.0	5,281.5	-54.5	378,443.45	868,172.37		
Point 3			11,767.0	5,336.0	5,230.6	378,497.95	873,457.47		
Point 4			11,767.0	58.4	5,284.2	373,220.35	873,511.07		
Sec 16	0.00	0.00	11,767.0	4,996.0	-281.4	378,443.47	868,172.36	32° 2' 9.723 N	103° 16' 42.961 W
- plan misses target center by 284.6usft at 17544.4usft MD (11969.0 TVD, 4998.0 N, -80.9 E)									
- Polygon									
Point 1			11,767.0	0.0	0.0	378,443.47	868,172.36		
Point 2			11,767.0	5,280.0	-53.4	383,723.47	868,118.96		
Point 3			11,767.0	5,332.5	5,230.8	383,775.97	873,403.16		
Point 4			11,767.0	54.4	5,285.1	378,497.87	873,457.46		
Cam101 LTP	0.00	0.00	11,969.0	10,178.0	-133.8	383,625.46	868,319.96	32° 3' 0.982 N	103° 16' 40.658 W
- plan misses target center by 24.7usft at 22700.0usft MD (11969.0 TVD, 10153.3 N, -133.6 E)									
- Point									
Cam101 FTP	0.00	0.00	11,969.0	-183.3	-28.0	373,264.16	868,425.77	32° 1' 18.450 N	103° 16' 40.605 W
- plan hits target center									
- Point									
Cam101 BHL	0.00	0.00	11,969.0	10,228.0	-134.3	383,675.45	868,319.47	32° 3' 1.477 N	103° 16' 40.658 W
- plan hits target center									
- Point									

AMEREDEV

Ameredev Operating, LLC.

CAM/AZ

CAM/AZ #1N

Camellia 101H

Wellbore #1

Plan: Design #1

Lease Penetration Section Line Footages

16 January, 2019

Company:	Ameredev Operating, LLC.	Local Co-ordinate Reference:	Well Camellia 101H
Project:	CAM/AZ	TVD Reference:	KB @ 2951.0usft
Site:	CAM/AZ #1N	MD Reference:	KB @ 2951.0usft
Well:	Camellia 101H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Design #1	Database:	EDM5000

Project	CAM/AZ		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	CAM/AZ #1N				
Site Position:		Northing:	373,448.30 usft	Latitude:	32° 1' 20.266 N
From:	Lat/Long	Easting:	868,493.74 usft	Longitude:	103° 16' 39.795 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.56 °

Well	Camellia 101H					
Well Position	+N/-S	0.0 usft	Northing:	373,447.48 usft	Latitude:	32° 1' 20.262 N
	+E/-W	0.0 usft	Easting:	868,453.80 usft	Longitude:	103° 16' 40.259 W
Position Uncertainty		0.0 usft	Wellhead Elevation:	usft	Ground Level:	2,924.0 usft

Wellbore	Wellbore #1					
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength	
			(°)	(°)	(nT)	
	IGRF2015	1/11/2019	6.63	59.90	47,691.05418696	

Design	Design #1				
Audit Notes:					
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0	
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction	
	(usft)	(usft)	(usft)	(°)	
	0.0	0.0	0.0	359.25	

Survey Tool Program	Date	1/16/2019			
From	To	Survey (Wellbore)	Tool Name	Description	
(usft)	(usft)				
0.0	22,774.7	Design #1 (Wellbore #1)	MWD	OWSG MWD - Standard	

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
0.0	0.00	0.00	0.0	282.2	230.1	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	282.2	230.1	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	282.2	230.1	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	282.2	230.1	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	282.2	230.1	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	282.2	230.1	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	282.2	230.1	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	282.2	230.1	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	282.2	230.1	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	282.2	230.1	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	282.2	230.1	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	282.2	230.1	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	282.2	230.1	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	282.2	230.1	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	282.2	230.1	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	282.2	230.1	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	282.2	230.1	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	282.2	230.1	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	282.2	230.1	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	282.2	230.1	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	282.2	230.1	0.0	0.00	0.00	0.00
2,100.0	2.00	204.00	2,100.0	280.6	229.3	-1.6	2.00	2.00	0.00
2,200.0	4.00	204.00	2,199.8	275.8	227.2	-6.3	2.00	2.00	0.00
2,300.0	6.00	204.00	2,299.5	267.8	223.7	-14.3	2.00	2.00	0.00
2,400.0	6.00	204.00	2,398.9	258.3	219.4	-23.7	0.00	0.00	0.00
2,500.0	6.00	204.00	2,498.4	248.7	215.2	-33.2	0.00	0.00	0.00
2,600.0	6.00	204.00	2,597.8	239.2	210.9	-42.7	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
2,700.0	6.00	204.00	2,697.3	229.6	206.7	-52.2	0.00	0.00	0.00
2,800.0	6.00	204.00	2,796.7	220.1	202.4	-61.7	0.00	0.00	0.00
2,900.0	6.00	204.00	2,896.2	210.5	198.2	-71.2	0.00	0.00	0.00
3,000.0	6.00	204.00	2,995.6	201.0	193.9	-80.7	0.00	0.00	0.00
3,100.0	6.00	204.00	3,095.1	191.4	189.7	-90.2	0.00	0.00	0.00
3,200.0	6.00	204.00	3,194.5	181.9	185.4	-99.7	0.00	0.00	0.00
3,300.0	6.00	204.00	3,294.0	172.3	181.2	-109.2	0.00	0.00	0.00
3,400.0	6.00	204.00	3,393.4	162.8	176.9	-118.7	0.00	0.00	0.00
3,500.0	6.00	204.00	3,492.9	153.2	172.7	-128.2	0.00	0.00	0.00
3,600.0	6.00	204.00	3,592.3	143.7	168.4	-137.7	0.00	0.00	0.00
3,700.0	6.00	204.00	3,691.8	134.1	164.1	-147.1	0.00	0.00	0.00
3,800.0	6.00	204.00	3,791.2	124.6	159.9	-156.6	0.00	0.00	0.00
3,900.0	6.00	204.00	3,890.7	115.0	155.6	-166.1	0.00	0.00	0.00
4,000.0	6.00	204.00	3,990.1	105.5	151.4	-175.6	0.00	0.00	0.00
4,100.0	6.00	204.00	4,089.6	96.0	147.1	-185.1	0.00	0.00	0.00
4,200.0	6.00	204.00	4,189.0	86.4	142.9	-194.6	0.00	0.00	0.00
4,300.0	6.00	204.00	4,288.5	76.9	138.6	-204.1	0.00	0.00	0.00
4,400.0	6.00	204.00	4,387.9	67.3	134.4	-213.6	0.00	0.00	0.00
4,500.0	6.00	204.00	4,487.4	57.8	130.1	-223.1	0.00	0.00	0.00
4,600.0	6.00	204.00	4,586.9	48.2	125.9	-232.6	0.00	0.00	0.00
4,700.0	6.00	204.00	4,686.3	38.7	121.6	-242.1	0.00	0.00	0.00
4,800.0	6.00	204.00	4,785.8	29.1	117.4	-251.6	0.00	0.00	0.00
4,900.0	6.00	204.00	4,885.2	19.6	113.1	-261.1	0.00	0.00	0.00
5,000.0	6.00	204.00	4,984.7	10.0	108.9	-270.5	0.00	0.00	0.00
5,100.0	6.00	204.00	5,084.1	0.5	104.6	-280.0	0.00	0.00	0.00
5,200.0	6.00	204.00	5,183.6	-9.1	100.4	-289.5	0.00	0.00	0.00
5,300.0	6.00	204.00	5,283.0	-18.6	96.1	-299.0	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
5,400.0	6.00	204.00	5,382.5	-28.2	91.9	-308.5	0.00	0.00	0.00
5,500.0	6.00	204.00	5,481.9	-37.7	87.6	-318.0	0.00	0.00	0.00
5,600.0	6.00	204.00	5,581.4	-47.3	83.4	-327.5	0.00	0.00	0.00
5,700.0	6.00	204.00	5,680.8	-56.8	79.1	-337.0	0.00	0.00	0.00
5,800.0	6.00	204.00	5,780.3	-66.4	74.9	-346.5	0.00	0.00	0.00
5,900.0	6.00	204.00	5,879.7	-75.9	70.6	-356.0	0.00	0.00	0.00
6,000.0	6.00	204.00	5,979.2	-85.5	66.4	-365.5	0.00	0.00	0.00
6,100.0	6.00	204.00	6,078.6	-95.0	62.1	-375.0	0.00	0.00	0.00
6,200.0	6.00	204.00	6,178.1	-104.6	57.9	-384.5	0.00	0.00	0.00
6,300.0	6.00	204.00	6,277.5	-114.1	53.6	-394.0	0.00	0.00	0.00
6,400.0	6.00	204.00	6,377.0	-123.7	49.4	-403.4	0.00	0.00	0.00
6,500.0	6.00	204.00	6,476.4	-133.2	45.1	-412.9	0.00	0.00	0.00
6,600.0	6.00	204.00	6,575.9	-142.8	40.9	-422.4	0.00	0.00	0.00
6,700.0	6.00	204.00	6,675.3	-152.3	36.6	-431.9	0.00	0.00	0.00
6,724.8	6.00	204.00	6,700.0	-154.7	35.5	-434.3	0.00	0.00	0.00
6,800.0	4.50	204.00	6,774.9	-161.0	32.8	-440.5	2.00	-2.00	0.00
6,900.0	2.50	204.00	6,874.7	-166.5	30.3	-446.1	2.00	-2.00	0.00
7,000.0	0.50	204.00	6,974.7	-168.9	29.2	-448.4	2.00	-2.00	0.00
7,024.8	0.00	0.00	6,999.5	-169.0	29.2	-448.5	2.00	-2.00	0.00
7,100.0	0.00	0.00	7,074.7	-169.0	29.2	-448.5	0.00	0.00	0.00
7,200.0	0.00	0.00	7,174.7	-169.0	29.2	-448.5	0.00	0.00	0.00
7,300.0	0.00	0.00	7,274.7	-169.0	29.2	-448.5	0.00	0.00	0.00
7,400.0	0.00	0.00	7,374.7	-169.0	29.2	-448.5	0.00	0.00	0.00
7,500.0	0.00	0.00	7,474.7	-169.0	29.2	-448.5	0.00	0.00	0.00
7,600.0	0.00	0.00	7,574.7	-169.0	29.2	-448.5	0.00	0.00	0.00
7,700.0	0.00	0.00	7,674.7	-169.0	29.2	-448.5	0.00	0.00	0.00
7,800.0	0.00	0.00	7,774.7	-169.0	29.2	-448.5	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
7,900.0	0.00	0.00	7,874.7	-169.0	29.2	-448.5	0.00	0.00	0.00
8,000.0	0.00	0.00	7,974.7	-169.0	29.2	-448.5	0.00	0.00	0.00
8,100.0	0.00	0.00	8,074.7	-169.0	29.2	-448.5	0.00	0.00	0.00
8,200.0	0.00	0.00	8,174.7	-169.0	29.2	-448.5	0.00	0.00	0.00
8,300.0	0.00	0.00	8,274.7	-169.0	29.2	-448.5	0.00	0.00	0.00
8,400.0	0.00	0.00	8,374.7	-169.0	29.2	-448.5	0.00	0.00	0.00
8,500.0	0.00	0.00	8,474.7	-169.0	29.2	-448.5	0.00	0.00	0.00
8,525.3	0.00	0.00	8,500.0	-169.0	29.2	-448.5	0.00	0.00	0.00
8,600.0	1.49	204.00	8,574.7	-169.9	28.8	-449.4	2.00	2.00	0.00
8,700.0	3.49	204.00	8,674.6	-173.9	27.0	-453.4	2.00	2.00	0.00
8,800.0	5.49	204.00	8,774.2	-181.0	23.8	-460.5	2.00	2.00	0.00
8,825.3	6.00	204.00	8,799.5	-183.4	22.8	-462.8	2.00	2.00	0.00
8,900.0	6.00	204.00	8,873.7	-190.5	19.6	-469.9	0.00	0.00	0.00
9,000.0	6.00	204.00	8,973.2	-200.0	15.4	-479.4	0.00	0.00	0.00
9,100.0	6.00	204.00	9,072.6	-209.6	11.1	-488.9	0.00	0.00	0.00
9,200.0	6.00	204.00	9,172.1	-219.1	6.9	-498.3	0.00	0.00	0.00
9,300.0	6.00	204.00	9,271.5	-228.7	2.6	-507.8	0.00	0.00	0.00
9,400.0	6.00	204.00	9,371.0	-238.2	-1.7	-517.3	0.00	0.00	0.00
9,500.0	6.00	204.00	9,470.4	-247.8	-5.9	-526.8	0.00	0.00	0.00
9,600.0	6.00	204.00	9,569.9	-257.3	-10.2	-536.3	0.00	0.00	0.00
9,700.0	6.00	204.00	9,669.3	-266.9	-14.4	-545.8	0.00	0.00	0.00
9,800.0	6.00	204.00	9,768.8	-276.4	-18.7	-555.3	0.00	0.00	0.00
9,900.0	6.00	204.00	9,868.2	-286.0	-22.9	-564.8	0.00	0.00	0.00
10,000.0	6.00	204.00	9,967.7	-295.5	-27.2	-574.3	0.00	0.00	0.00
10,100.0	6.00	204.00	10,067.1	-305.1	-31.4	-583.8	0.00	0.00	0.00
10,200.0	6.00	204.00	10,166.6	-314.6	-35.7	-593.3	0.00	0.00	0.00
10,300.0	6.00	204.00	10,266.0	-324.2	-39.9	-602.8	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
10,400.0	6.00	204.00	10,365.5	-333.7	-44.2	-612.3	0.00	0.00	0.00
10,500.0	6.00	204.00	10,464.9	-343.3	-48.4	-621.7	0.00	0.00	0.00
10,600.0	6.00	204.00	10,564.4	-352.8	-52.7	-631.2	0.00	0.00	0.00
10,700.0	6.00	204.00	10,663.8	-362.4	-56.9	-640.7	0.00	0.00	0.00
10,740.0	6.00	204.00	10,703.6	-366.2	-58.6	-644.5	0.00	0.00	0.00
Sec 28									
10,800.0	6.00	204.00	10,763.3	-371.9	-61.2	-650.2	0.00	0.00	0.00
10,900.0	6.00	204.00	10,862.8	-381.5	-65.4	-659.7	0.00	0.00	0.00
11,000.0	6.00	204.00	10,962.2	-391.0	-69.7	-669.2	0.00	0.00	0.00
11,038.0	6.00	204.00	11,000.0	-394.7	-71.3	-672.8	0.00	0.00	0.00
11,100.0	4.76	204.00	11,061.7	-400.0	-73.7	-678.1	2.00	-2.00	0.00
11,200.0	2.76	204.00	11,161.5	-406.0	-76.3	-684.0	2.00	-2.00	0.00
11,300.0	0.76	204.00	11,261.4	-408.8	-77.6	-686.8	2.00	-2.00	0.00
11,338.0	0.00	0.00	11,299.5	-409.0	-77.7	-687.1	2.00	-2.00	0.00
11,400.0	0.00	0.00	11,361.4	-409.0	-77.7	-687.1	0.00	0.00	0.00
11,438.6	0.00	0.00	11,400.0	-409.0	-77.7	-687.1	0.00	0.00	0.00
11,500.0	7.40	60.25	11,461.3	-407.0	-74.2	-685.1	12.04	12.04	0.00
11,600.0	19.44	60.25	11,558.4	-395.5	-54.1	-673.9	12.04	12.04	0.00
11,700.0	31.48	60.25	11,648.5	-374.2	-16.9	-653.1	12.04	12.04	0.00
11,764.5	39.24	60.25	11,701.0	-355.7	15.5	-635.0	12.04	12.04	0.00
11,800.0	41.10	54.28	11,728.2	-343.3	34.7	-622.9	12.04	5.22	-16.83
11,900.0	47.72	39.85	11,799.8	-295.6	85.3	-575.8	12.04	6.62	-14.42
12,000.0	55.78	28.43	11,861.7	-230.6	128.9	-511.4	12.04	8.06	-11.42
12,100.0	64.71	19.11	11,911.4	-151.2	163.5	-432.5	12.04	8.93	-9.32
12,144.1	68.83	15.45	11,928.8	-112.5	175.5	-393.9	12.04	9.33	-8.29
Sec 21									
12,200.0	74.15	11.10	11,946.5	-61.0	187.6	-342.5	12.04	9.52	-7.78

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
12,300.0	83.85	3.82	11,965.6	36.2	200.3	-245.6	12.04	9.70	-7.28
12,362.8	90.00	359.42	11,969.0	98.9	202.0	-182.9	12.04	9.79	-7.02
Cam101 FTP									
12,400.0	90.00	359.42	11,969.0	136.0	201.6	-145.8	0.00	0.00	0.00
12,500.0	90.00	359.42	11,969.0	236.0	200.6	-45.8	0.00	0.00	0.00
12,600.0	90.00	359.42	11,969.0	336.0	199.6	54.2	0.00	0.00	0.00
12,700.0	90.00	359.42	11,969.0	436.0	198.6	154.2	0.00	0.00	0.00
12,800.0	90.00	359.42	11,969.0	536.0	197.6	254.2	0.00	0.00	0.00
12,900.0	90.00	359.42	11,969.0	636.0	196.5	354.2	0.00	0.00	0.00
13,000.0	90.00	359.42	11,969.0	736.0	195.5	454.2	0.00	0.00	0.00
13,100.0	90.00	359.42	11,969.0	836.0	194.5	554.2	0.00	0.00	0.00
13,200.0	90.00	359.42	11,969.0	936.0	193.5	654.2	0.00	0.00	0.00
13,300.0	90.00	359.42	11,969.0	1,036.0	192.5	754.2	0.00	0.00	0.00
13,400.0	90.00	359.42	11,969.0	1,136.0	191.4	854.2	0.00	0.00	0.00
13,500.0	90.00	359.42	11,969.0	1,236.0	190.4	954.2	0.00	0.00	0.00
13,600.0	90.00	359.42	11,969.0	1,336.0	189.4	1,054.2	0.00	0.00	0.00
13,700.0	90.00	359.42	11,969.0	1,436.0	188.4	1,154.2	0.00	0.00	0.00
13,800.0	90.00	359.42	11,969.0	1,536.0	187.4	1,254.2	0.00	0.00	0.00
13,900.0	90.00	359.42	11,969.0	1,636.0	186.3	1,354.2	0.00	0.00	0.00
14,000.0	90.00	359.42	11,969.0	1,736.0	185.3	1,454.2	0.00	0.00	0.00
14,100.0	90.00	359.42	11,969.0	1,835.9	184.3	1,554.2	0.00	0.00	0.00
14,200.0	90.00	359.42	11,969.0	1,935.9	183.3	1,654.2	0.00	0.00	0.00
14,300.0	90.00	359.42	11,969.0	2,035.9	182.2	1,754.2	0.00	0.00	0.00
14,400.0	90.00	359.42	11,969.0	2,135.9	181.2	1,854.2	0.00	0.00	0.00
14,500.0	90.00	359.42	11,969.0	2,235.9	180.2	1,954.2	0.00	0.00	0.00
14,600.0	90.00	359.42	11,969.0	2,335.9	179.2	2,054.2	0.00	0.00	0.00
14,700.0	90.00	359.42	11,969.0	2,435.9	178.2	2,154.2	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
14,800.0	90.00	359.42	11,969.0	2,535.9	177.1	2,254.2	0.00	0.00	0.00
14,900.0	90.00	359.42	11,969.0	2,635.9	176.1	2,354.2	0.00	0.00	0.00
15,000.0	90.00	359.42	11,969.0	2,735.9	175.1	2,454.2	0.00	0.00	0.00
15,100.0	90.00	359.42	11,969.0	2,835.9	174.1	2,554.2	0.00	0.00	0.00
15,200.0	90.00	359.42	11,969.0	2,935.9	173.1	2,654.2	0.00	0.00	0.00
15,300.0	90.00	359.42	11,969.0	3,035.9	172.0	2,754.2	0.00	0.00	0.00
15,400.0	90.00	359.42	11,969.0	3,135.9	171.0	2,854.2	0.00	0.00	0.00
15,500.0	90.00	359.42	11,969.0	3,235.9	170.0	2,954.2	0.00	0.00	0.00
15,600.0	90.00	359.42	11,969.0	3,335.9	169.0	3,054.2	0.00	0.00	0.00
15,700.0	90.00	359.42	11,969.0	3,435.9	168.0	3,154.2	0.00	0.00	0.00
15,800.0	90.00	359.42	11,969.0	3,535.9	166.9	3,254.2	0.00	0.00	0.00
15,900.0	90.00	359.42	11,969.0	3,635.9	165.9	3,354.2	0.00	0.00	0.00
16,000.0	90.00	359.42	11,969.0	3,735.8	164.9	3,454.2	0.00	0.00	0.00
16,100.0	90.00	359.42	11,969.0	3,835.8	163.9	3,554.2	0.00	0.00	0.00
16,200.0	90.00	359.42	11,969.0	3,935.8	162.9	3,654.2	0.00	0.00	0.00
16,300.0	90.00	359.42	11,969.0	4,035.8	161.8	3,754.2	0.00	0.00	0.00
16,400.0	90.00	359.42	11,969.0	4,135.8	160.8	3,854.2	0.00	0.00	0.00
16,500.0	90.00	359.42	11,969.0	4,235.8	159.8	3,954.2	0.00	0.00	0.00
16,600.0	90.00	359.42	11,969.0	4,335.8	158.8	4,054.2	0.00	0.00	0.00
16,700.0	90.00	359.42	11,969.0	4,435.8	157.7	4,154.2	0.00	0.00	0.00
16,800.0	90.00	359.42	11,969.0	4,535.8	156.7	4,254.2	0.00	0.00	0.00
16,900.0	90.00	359.42	11,969.0	4,635.8	155.7	4,354.2	0.00	0.00	0.00
17,000.0	90.00	359.42	11,969.0	4,735.8	154.7	4,454.2	0.00	0.00	0.00
17,100.0	90.00	359.42	11,969.0	4,835.8	153.7	4,554.2	0.00	0.00	0.00
17,200.0	90.00	359.42	11,969.0	4,935.8	152.6	4,654.2	0.00	0.00	0.00
17,300.0	90.00	359.42	11,969.0	5,035.8	151.6	4,754.2	0.00	0.00	0.00
17,400.0	90.00	359.42	11,969.0	5,135.8	150.6	4,854.2	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
17,500.0	90.00	359.42	11,969.0	5,235.8	149.6	4,954.2	0.00	0.00	0.00
17,544.4	90.00	359.42	11,969.0	5,280.2	149.1	4,998.7	0.00	0.00	0.00
Sec 16									
17,600.0	90.00	359.42	11,969.0	5,335.8	148.6	5,054.2	0.00	0.00	0.00
17,700.0	90.00	359.42	11,969.0	5,435.8	147.5	5,154.2	0.00	0.00	0.00
17,800.0	90.00	359.42	11,969.0	5,535.8	146.5	5,254.2	0.00	0.00	0.00
17,900.0	90.00	359.42	11,969.0	5,635.7	145.5	5,354.2	0.00	0.00	0.00
18,000.0	90.00	359.42	11,969.0	5,735.7	144.5	5,454.2	0.00	0.00	0.00
18,100.0	90.00	359.42	11,969.0	5,835.7	143.5	5,554.2	0.00	0.00	0.00
18,200.0	90.00	359.42	11,969.0	5,935.7	142.4	5,654.2	0.00	0.00	0.00
18,300.0	90.00	359.42	11,969.0	6,035.7	141.4	5,754.2	0.00	0.00	0.00
18,400.0	90.00	359.42	11,969.0	6,135.7	140.4	5,854.2	0.00	0.00	0.00
18,500.0	90.00	359.42	11,969.0	6,235.7	139.4	5,954.2	0.00	0.00	0.00
18,600.0	90.00	359.42	11,969.0	6,335.7	138.3	6,054.2	0.00	0.00	0.00
18,700.0	90.00	359.42	11,969.0	6,435.7	137.3	6,154.2	0.00	0.00	0.00
18,800.0	90.00	359.42	11,969.0	6,535.7	136.3	6,254.2	0.00	0.00	0.00
18,900.0	90.00	359.42	11,969.0	6,635.7	135.3	6,354.2	0.00	0.00	0.00
19,000.0	90.00	359.42	11,969.0	6,735.7	134.3	6,454.2	0.00	0.00	0.00
19,100.0	90.00	359.42	11,969.0	6,835.7	133.2	6,554.2	0.00	0.00	0.00
19,200.0	90.00	359.42	11,969.0	6,935.7	132.2	6,654.2	0.00	0.00	0.00
19,300.0	90.00	359.42	11,969.0	7,035.7	131.2	6,754.2	0.00	0.00	0.00
19,400.0	90.00	359.42	11,969.0	7,135.7	130.2	6,854.2	0.00	0.00	0.00
19,500.0	90.00	359.42	11,969.0	7,235.7	129.2	6,954.2	0.00	0.00	0.00
19,600.0	90.00	359.42	11,969.0	7,335.7	128.1	7,054.2	0.00	0.00	0.00
19,700.0	90.00	359.42	11,969.0	7,435.7	127.1	7,154.2	0.00	0.00	0.00
19,800.0	90.00	359.42	11,969.0	7,535.6	126.1	7,254.2	0.00	0.00	0.00
19,900.0	90.00	359.42	11,969.0	7,635.6	125.1	7,354.2	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
20,000.0	90.00	359.42	11,969.0	7,735.6	124.1	7,454.2	0.00	0.00	0.00
20,100.0	90.00	359.42	11,969.0	7,835.6	123.0	7,554.2	0.00	0.00	0.00
20,200.0	90.00	359.42	11,969.0	7,935.6	122.0	7,654.2	0.00	0.00	0.00
20,300.0	90.00	359.42	11,969.0	8,035.6	121.0	7,754.2	0.00	0.00	0.00
20,400.0	90.00	359.42	11,969.0	8,135.6	120.0	7,854.2	0.00	0.00	0.00
20,500.0	90.00	359.42	11,969.0	8,235.6	119.0	7,954.2	0.00	0.00	0.00
20,600.0	90.00	359.42	11,969.0	8,335.6	117.9	8,054.2	0.00	0.00	0.00
20,700.0	90.00	359.42	11,969.0	8,435.6	116.9	8,154.2	0.00	0.00	0.00
20,800.0	90.00	359.42	11,969.0	8,535.6	115.9	8,254.2	0.00	0.00	0.00
20,900.0	90.00	359.42	11,969.0	8,635.6	114.9	8,354.2	0.00	0.00	0.00
21,000.0	90.00	359.42	11,969.0	8,735.6	113.8	8,454.2	0.00	0.00	0.00
21,100.0	90.00	359.42	11,969.0	8,835.6	112.8	8,554.2	0.00	0.00	0.00
21,200.0	90.00	359.42	11,969.0	8,935.6	111.8	8,654.2	0.00	0.00	0.00
21,300.0	90.00	359.42	11,969.0	9,035.6	110.8	8,754.2	0.00	0.00	0.00
21,400.0	90.00	359.42	11,969.0	9,135.6	109.8	8,854.2	0.00	0.00	0.00
21,500.0	90.00	359.42	11,969.0	9,235.6	108.7	8,954.2	0.00	0.00	0.00
21,600.0	90.00	359.42	11,969.0	9,335.6	107.7	9,054.2	0.00	0.00	0.00
21,700.0	90.00	359.42	11,969.0	9,435.6	106.7	9,154.2	0.00	0.00	0.00
21,800.0	90.00	359.42	11,969.0	9,535.5	105.7	9,254.2	0.00	0.00	0.00
21,900.0	90.00	359.42	11,969.0	9,635.5	104.7	9,354.2	0.00	0.00	0.00
22,000.0	90.00	359.42	11,969.0	9,735.5	103.6	9,454.2	0.00	0.00	0.00
22,100.0	90.00	359.42	11,969.0	9,835.5	102.6	9,554.2	0.00	0.00	0.00
22,200.0	90.00	359.42	11,969.0	9,935.5	101.6	9,654.2	0.00	0.00	0.00
22,300.0	90.00	359.42	11,969.0	10,035.5	100.6	9,754.2	0.00	0.00	0.00
22,400.0	90.00	359.42	11,969.0	10,135.5	99.6	9,854.2	0.00	0.00	0.00
22,500.0	90.00	359.42	11,969.0	10,235.5	98.5	9,954.2	0.00	0.00	0.00
22,600.0	90.00	359.42	11,969.0	10,335.5	97.5	10,054.2	0.00	0.00	0.00

Company: Ameredev Operating, LLC.
Project: CAM/AZ
Site: CAM/AZ #1N
Well: Camellia 101H
Wellbore: Wellbore #1
Design: Design #1

Local Co-ordinate Reference: Well Camellia 101H
TVD Reference: KB @ 2951.0usft
MD Reference: KB @ 2951.0usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	V. Sec (usft)	DLeg (°/100usft)	Build (°/100usft)	Turn (°/100usft)
22,700.0	90.00	359.42	11,969.0	10,435.5	96.5	10,154.2	0.00	0.00	0.00
Cam101 LTP									
22,774.7	90.00	359.42	11,969.0	10,510.1	95.7	10,228.9	0.00	0.00	0.00
Cam101 BHL									

5M Annular Preventer Variance Request and Well Control Procedures

Note: A copy of the Well Control Plan must be available at multiple locations on the rig for review by rig personnel, as well as review by the BLM PET/PE, and a copy must be maintained on the rig floor.

Dual Isolation Design for 5M Annular Exception

Ameredev will utilize 13-5/8" 10M (5M Annular) BOPE System consisting of:

- 13-5/8" 5M Annular
- 13-5/8" 10M Upper Pipe Rams
 - 3-1/2" – 5-1/2" Variable Bore Ram
- 13-5/8" 10M Blind Rams
- 13-5/8" 10M Drilling Spool /w 2 - 4" 10M Outlets Double 10M Isolation Valves
- 13-5/8" 10M Lower Blind Rams
 - 3-1/2" – 5-1/2" Variable Bore Ram

All drilling components and casing associated to exposure > 5000 psi BHP requiring a 10M system will have a double isolation (secondary barrier) below the 5M Annular that would provide a barrier to flow. The mud system will always be primary barrier, it will be maintained by adjusting values based on tourly mud tests and monitoring a PVT System to maintain static wellbore conditions, displacement procedures will be followed and recorded on daily drilling reports during tripping operations. Surge and swab pressure values will be calculated and maintained and static flow check will be monitored at previous casing shoe and verified static well conditions prior to tripping out of hole and again prior to pulling last joint of drill pipe through BOPE. The below table, documents that two barriers to flow can be maintained at all times, independent of the rating of the annular preventer.

Drill Components	Size	Primary Barrier	Secondary Barrier	Third Barrier
Drillpipe	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
HWDP Drillpipe	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Drill Collars	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Production Casing	3-1/2"-5-1/2"	Drilling Fluid	Upper Pipe Rams	Lower Pipe Rams
Open Hole	13-5/8	Drilling Fluid	Blind Rams	
All Drilling Components in 10M Environment will have OD that will allow full Operational RATED WORKING PRESSURE for system design. Kill line with minimum 2" ID will be available outside substructure with 10M Check Valve for OOH Kill Operations				

Well Control Procedures

Proper well control procedures are dependent to differentiating well conditions, to cover the basic well control operations there are will be standard drilling ahead, tripping pipe, tripping BHA, running casing, and pipe out of the hole/open hole scenarios that will be defined by procedures below. Initial Shut In Pressure can be taken against the Uppermost BOPE component the 5M Annular, pressure control can be transferred from the lesser 5M Annular to the 10M Upper Pipe Rams if needed. Shut In Pressures may be equal to or less than the Rated Working Pressure but at no time will the pressure on the annular preventer exceed the Rated Working Pressure of the annular. The annular will be tested to 5,000 psi. This will be the Rated Working Pressure of the annular preventer. All scenarios will be written such as shut in will be performed by closing the 10,000 psi Upper Pipe Rams for faster Accumulator pressure recovery to allow safer reaction to controlling wellbore pressure.

Shutting In While Drilling

1. Sound alarm signaling well control event to Rig Crew
2. Space out drill string to allow FOSV installation
3. Shut down pumps
4. Shut in Upper Pipe Rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
5. Install open, full open safety valve and close valve, Close Chokes
6. Verify well is shut-in and flow has stopped
7. Notify supervisory personnel
8. Record data (SIDP, SICP, Pit Gain, and Time)
9. Hold pre-job safety meeting and discuss kill procedure

Shutting In While Tripping

1. Sound alarm signaling well control event to Rig Crew
2. Space out drill string to allow FOSV installation
3. Shut in Upper Pipe Rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
4. Install open, full open safety valve and close valve, Close Chokes
5. Verify well is shut-in and flow has stopped
6. Notify supervisory personnel
7. Record data (SIDP, SICP, Pit Gain, and Time)
8. Hold pre-job safety meeting and discuss kill procedure

Shutting In While Running Casing

1. Sound alarm signaling well control event to Rig Crew
2. Space out casing to allow circulating swedge installation
3. Shut in Upper Pipe Rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
4. Install circulating swedge, Close high pressure, low torque valves, Close Chokes
5. Verify well is shut-in and flow has stopped
6. Notify supervisory personnel
7. Record data (SIDP, SICP, Pit Gain, and Time)
8. Hold Pre-job safety meeting and discuss kill procedure

Shutting in while out of hole

1. Sound alarm signaling well control event to Rig Crew
2. Shut-in well: close blind rams and open HCR against Open Chokes and Valves
Open to working pressure gauge
3. Close Chokes, Verify well is shut-in and monitor pressures
4. Notify supervisory personnel
5. Record data (SIDP, SICP, Pit Gain, and Time)
6. Hold Pre-job safety meeting and discuss kill procedure

Shutting in prior to pulling BHA through stack

Prior to pulling last joint of drill pipe thru the stack space out and check flow
If flowing see steps below.

1. Sound alarm signaling well control event to Rig Crew
2. Shut in upper pipe ram and open HCR against Open Chokes and Valves Open
to working pressure gauge
3. Install open, full open safety valve and close valve, Close Chokes
4. Verify well is shut-in and flow has stopped
5. Notify supervisory personnel
6. Record data (SIDP, SICP, Pit Gain, and Time)
7. Hold pre-job safety meeting and discuss kill procedure

Shutting in while BHA is in the stack and ram preventer and combo immediately available

1. Sound alarm signaling well control event to Rig Crew
2. Space out BHA with upset just beneath the compatible pipe ram
3. Shut in upper compatible pipe ram and open HCR against Open Chokes and Valves Open to working pressure gauge
4. Install open, full open safety valve and close valve, Close Chokes
5. Verify well is shut-in and flow has stopped
6. Notify supervisory personnel
7. Record data (SIDP, SICP, Pit Gain, and Time)
8. Hold pre-job safety meeting and discuss kill procedure

*FOSV will be on rig floor in open position with operating handle for each type of connection utilized and tested to 10,000 psi

Shutting in while BHA is in the stack and no ram preventer or combo immediately available

1. Sound alarm signaling well control event to Rig Crew
2. If possible pick up high enough, to pull string clear and follow "Open Hole" scenario

If not possible to pick up high enough:

3. Stab Crossover, make up one joint/stand of drill pipe, and install open, full open safety valve (Leave Open)
4. Space out drill string with upset just beneath the compatible pipe ram.
5. Shut in upper compatible pipe ram and open HCR against Open Chokes and Valves Open to working pressure gauge
6. Close FOSV, Close Chokes, Verify well is shut-in and flow has stopped
7. Notify supervisory personnel
8. Record data (SIDP, SICP, Pit Gain, and Time)
9. Hold pre-job safety meeting and discuss kill procedure

Pressure Control Plan

Pressure Control Equipment

- Following setting of 13-3/8" Surface Casing Ameredev will install 13-5/8 MB4 Multi Bowl Casing Head by welding on a 13-5/8 SOW x 13-5/8" 5M in combination with 13-5/8 5M x 13-5/8 10M B-Sec to Land Intm #1 and a 13-5/8 10M x 13-5/8 10M shouldered to land C-Sec to Land Intm #2 (Installation procedure witnessed and verified by a manufacturer's representative).
- Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Ameredev will install a 5M System Blowout Preventer (BOPE) with a 5M Annular Preventer and related equipment (BOPE). Full testing will be performed utilizing a full isolation test plug and limited to 5,000 psi MOP of MB4 Multi Bowl Casing Head. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 50% of approved working pressure (2,500 psi). Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Setting of 9-5/8" Intermediate will be done by landing a wellhead hanger in the 13-5/8" 5M Bowl, Cementing and setting Well Head Packing seals and testing same. (Installation procedure witnessed and verified by a manufacturer's representative) Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Full testing will be performed utilizing a full isolation test plug to 10,000 psi MOP of MB4 Multi Bowl B-Section. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 100% of approved working pressure (5,000 psi).
- Before drilling >20ft of new formation under the 9-5/8" Casing Shoe a pressure integrity test of the Casing Shoe will be performed to minimum of the MWE anticipated to control formation pressure to the next casing depth.
- Following setting of 5-1/2" Production Casing and adequate WOC time Ameredev will break 10M System Blowout Preventer (BOP) from 10M DOL-2 Casing Head, install annulus casing slips and test same (Installation procedure witnessed and verified by a manufacturer's representative) and install 11" 10M x 5-1/8" 15M Tubing Head (Installation procedure witnessed and verified by a manufacturer's representative). Ameredev will test head to 70% casing design and install Dry Hole cap with needle valve and pressure gauge to monitor well awaiting completion.

Pressure Control Plan

- Slow pump speeds will be taken daily by each crew and recorded on Daily Drilling Report after mudding up.
- A choke manifold and accumulator with floor and remote operating stations will be functional and in place after installation of BOPE, as well as full functioning mud gas separator.
- Weekly BOPE pit level drills will be conducted by each crew and recorded on Daily Drilling Report.
- BOP will be fully operated when out of hole and will be documented on the daily drilling log.
- All B.O.P.s and associated equipment will be tested in accordance with Onshore Order #2
- All B.O.P. testing will be done by an independent service company.
- The B.O.P. will be tested within 21 days of the original test if drilling takes more time than planned.
- Ameredev requests a variance to connect the B.O.P. choke outlet to the choke manifold using a co-flex hose with a 10,000 psi working pressure that has been tested to 15,000psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps. (certifications will be sent to Carlsbad BLM Office prior to install)
- Ameredev requests a variance to install a 5M Annular Preventer on the 10M System to drill the Production Hole below the 9-5/8" Intermediate Section. 5M Annular will be tested to 100% working pressure (5,000 psi). A full well control procedure will be included to isolate well bore.

Ameredev Drilling Plan: 3 String with 4 String Contingency

- Contingency Plan If Losses Exceed 50% in Intermediate Interval
 - We will utilize a MB4 wellhead that will enable us to convert a 3 string design to a 4 string design. (Schematic Attached)
 - We will displace well with FW and drill or condition to run 9-5/8" Casing at the Lamar Limestone, we will utilize DV Tool w/ ACP @ the Tansill to Isolate Capitan Reef and cement to surface.
 - Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.

- 7.625 Casing will be Additional 4th String
 - Drill remaining hole section to 10,670'
 - Run 7.625 29.7# HCL80 FJM Casing



4-String Contingency Wellbore Schematic

Well: (Well Name)	Co. Well ID: xxxxxx
SHL: (SHL)	AFE No.: xxxx-xxx
BHL: (BHL)	API No.: xxxxxxxxxxxx
Lea, NM	GL: (Elevation)'
Wellhead: A - 13-5/8" 10M x 13-5/8" SOW	Field: Delaware
B - 13-5/8" 10M x 13-5/8" 10M	Objective: Wolfcamp B
C - 13-5/8" 10M x 13-5/8" 10M	TVD: (TVD)'
Tubing Spool - 5-1/8" 15M x 13-3/8" 10M	MD: (MD)'
Xmas Tree: 2-9/16" 10M	Rig: TBD KB 27'
Tubing: 2-7/8" L-80 6.5# 8rd EUE	E-Mail: Wellsite2@amerdev.com


Hole Size	Formation Tops	Logs	Cement	Mud Weight
17.5"	Rustler 125' below Rustler 13.375" 54.5# J-55 BTC	TOC 0'	100% Excess	8.4-8.6 ppg WBM
12.25"	Salado At Tansill DV Tool with ACP Tansill Capitan Reef Lamar 50' below Lamar 9.625" 40# L-80HC BTC	TOC 0'	50% Excess	8.3-10.2 Fresh Water
8.75"	Bell Canyon Brushy Canyon Bone Spring Lime First Bone Spring Second Bone Spring Third Bone Spring Upper 125' below TBSG Upper 7.625" 29.7# L-80HC FJM	TOC 0'	25% Excess	8.5-9.4 Diesel Brine Emulsion
6.75" 12" Build @ KOP	Third Bone Spring Wolfcamp Wolfcamp B (If Applicable) 5.5" 20# P-110CYHP TMK UP SF TORQ (MD) Target Wolfcamp B TVD // MD	TOC 0'	25% Excess	10.5-14 ppg OBM

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Contingency Casing Design and Safety Factor Check

Casing Specifications						
Segment	Hole ID	Depth	OD	Weight	Grade	Coupling
Surface	17.5	1,888'	13.375	54.5	J-55	BTC
Int #1	12.25	5,013'	9.625	40	HCL-80	BTC
Int #2	8.75	11,147'	7.625	29.7	HCL-80	FJM
Prod Segment A	6.75	11,147'	5.5	20	CYHP-110	TMK UPSF
Prod Segment B	6.75	22,496'	5.5	20	CYHP-110	TMK UPSF

Check Surface Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.38	853	909	1,130	2,730
Safety Factors				
1.56	8.29	8.83	1.15	0.91
Check Int #1 Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
10.625	916	1042	4230	5750
Safety Factors				
0.81	4.57	5.20	1.41	0.95
Check Int #2 Casing				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
Safety Factors				
0.56	2.84	1.96	1.10	1.24
Check Prod Casing, Segment A				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
0.49	3.11	2.79	1.77	1.89
Check Prod Casing, Segment B				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
Safety Factors				
0.49	63.53	57.16	1.68	1.89



Quotation

Downing Wellhead Equipment

Oklahoma City,
Oklahoma - USA

Reference Data:

16925 AMEREDEV

Proprietary and Confidential

The information contained in this drawing is the sole property of Downing Wellhead Equipment, any reproduction in part or in whole without the written permission of Downing Wellhead Equipment is prohibited.

TITLE:

AMEREDEV

DRAWN		SIZE	DWG. NO.	REV.
CHECKED		A		
APPROVED		Scale:	Weight:	Sheet:

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 1 Lead	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">17.5</td> <td align="center">13.375</td> <td align="center">1888</td> <td style="background-color: black;"></td> <td align="center">1.76</td> <td align="center">13.5</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	17.5	13.375	1888		1.76	13.5	
	Hole Size	Casing Size	Depth	Sacks	Yield	Density													
	17.5	13.375	1888		1.76	13.5													
	Bbl/Sk	0.31372549																	
	bbls	419.402246																	
	Stage Tool Depth	N/A																	
	Top MD of Segment	0																	
	Bottom MD of Segment	1502																	
	Cement Type	C																	
	Additives	Bentonite, Accelerator, Kolseal, Defoamer, Celloflake																	
	Quantity (sks)	1,337																	
	Yield (cu ft/sk)	1.76																	
	Density (lbs/gal)	13.5																	
	Volume (cu ft)	2,352.85																	
	Percent Excess	100%	Target %	100%															
	Column Height	3,389.88																	
	Target TOC																		
		0																	
	Calc TOC	-1888	bbl	25% Excess	100%														
	calc vol	0.12372195	233.587041	291.9838012	467.174082														
	Stage 1 Tail	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">17.5</td> <td align="center">13.375</td> <td align="center">1888</td> <td style="background-color: black;"></td> <td align="center">1.34</td> <td align="center">14.8</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	17.5	13.375	1888		1.34	14.8
		Hole Size	Casing Size	Depth	Sacks	Yield	Density												
		17.5	13.375	1888		1.34	14.8												
		Bbl/Sk	0.23885918																
bbls		47.77183601																	
Top MD of Segment		1502																	
Bottom MD of Segment		1888																	
Cement Type		C																	
Additives																			
Quantity (sks)		200																	
Yield (cu ft/sk)		1.34																	
Density (lbs/gal)		14.8																	
Volume (cu ft)		268																	
Percent Excess		100%																	
Column Height		386.1225606																	

SURFACE CEMENT

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 2 Lead	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">12.25</td> <td align="center">9.625</td> <td align="center">3262</td> <td></td> <td align="center">3.5</td> <td align="center">9</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	12.25	9.625	3262		3.5	9	
	Hole Size	Casing Size	Depth	Sacks	Yield	Density													
	12.25	9.625	3262		3.5	9													
	Bbl/Sk				0.623885918														
	bbls				225.5254458														
	Stage Tool Depth				N/A														
	Top MD of Segment				0														
	Bottom MD of Segment				2412														
	Cement Type				C														
	Additives				Bentonite,Salt,Kolseal,Defoamer,Celloclake														
	Quantity (sks)				361														
	Yield (cu ft/sk)				3.5														
	Density (lbs/gal)				9														
	Volume (cu ft)				1,265.20														
	Percent Excess				50%	Target %	50%												
	Column Height				4,042.99														
	Target TOC				0														
	Calc TOC				-1631	bbl	25% Excess												
	calc vol				0.055781888	181.960517	227.4506463												
					272.9407756	50%													
	Stage 2 Tail	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">12.25</td> <td align="center">9.625</td> <td align="center">3262</td> <td></td> <td align="center">1.33</td> <td align="center">14.8</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	12.25	9.625	3262		1.33	14.8
		Hole Size	Casing Size	Depth	Sacks	Yield	Density												
		12.25	9.625	3262		1.33	14.8												
Bbl/Sk				0.237076649															
bbls				47.41532977															
Top MD of Segment				2412															
Bottom MD of Segment				3262															
Cement Type				C															
Additives																			
Quantity (sks)				200															
Yield (cu ft/sk)				1.33															
Density (lbs/gal)				14.8															
Volume (cu ft)				266															
Percent Excess				25%															
Column Height				850.013004															

INTERMEDIATE 1 CEMENT - STAGE 2

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 1 Lead	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">8.75</td> <td align="center">7.625</td> <td align="center">10670</td> <td></td> <td align="center">2.47</td> <td align="center">9</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	8.75	7.625	10670		2.47	9
	Hole Size	Casing Size	Depth	Sacks	Yield	Density												
	8.75	7.625	10670		2.47	9												
	Bbl/Sk					0.440285205												
	bbbs					168.6309595												
	Stage Tool Depth					N/A												
	Top MD of Segment					0												
	Bottom MD of Segment					6755												
	Cement Type					H												
	Additives					Bentonite,Retarder,Kolseal,Defoamer,Celloflake, Anti-Settling												
	Expansion Additive																	
	Quantity (sks)					383												
	Yield (cu ft/sk)					2.47												
	Density (lbs/gal)					9												
	Volume (cu ft)					946.02												
	Percent Excess					25%												
	Column Height					9,422.97												
	Target TOC					0												
	Calc TOC					-2667.5												
	calc vol					0.01789574												
						bbl												
						25% Excess												
						25%												
						238.6844354												
						238.6844354												
					Target %													
					25%													
Stage 1 Tail	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">8.75</td> <td align="center">7.625</td> <td align="center">10670</td> <td></td> <td align="center">1.31</td> <td align="center">14.2</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	8.75	7.625	10670		1.31	14.2
	Hole Size	Casing Size	Depth	Sacks	Yield	Density												
	8.75	7.625	10670		1.31	14.2												
	Bbl/Sk					0.233511586												
	bbbs					70.05347594												
	Top MD of Segment					6755												
	Bottom MD of Segment					10670												
	Cement Type					H												
	Additives					Salt,Bentonite,Retarder,Dispersant,Fluid Loss												
	Quantity (sks)					300												
	Yield (cu ft/sk)					1.31												
	Density (lbs/gal)					14.2												
	Volume (cu ft)					393												
	Percent Excess					25%												
	Column Height					3914.533571												

INTERMEDIATE 2 CEMENT

****EXAMPLE ONLY - NOT FOR CONSTRUCTION****

Stage 1 Lead	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">6.75</td> <td align="center">5.5</td> <td align="center">22496</td> <td></td> <td align="center">1.34</td> <td align="center">14.2</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	6.75	5.5	22496		1.34	14.2	
	Hole Size	Casing Size	Depth	Sacks	Yield	Density													
	6.75	5.5	22496		1.34	14.2													
	Bbl/Sk				0.23885918														
	bbbls				418.2897805														
	Stage Tool Depth				N/A														
	Top MD of Segment				0														
	Bottom MD of Segment				22496														
	Cement Type				H														
	Additives				Salt, Bentonite, Fluid Loss, Dispersant, Retarder, Defoamer														
	Quantity (sks)				1,751														
	Yield (cu ft/sk)				1.34														
	Density (lbs/gal)				14.2														
	Volume (cu ft)				2,346.61														
	Percent Excess				25%	Target %	25%												
	Column Height				28,120.00														
	<p align="center">Target TOC</p>				0														
	Calc TOC				-5624	bbl	25% Excess												
	calc vol				0.01487517	334.6318244	418.2897805												
	Stage 1 Tail	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Hole Size</th> <th>Casing Size</th> <th>Depth</th> <th>Sacks</th> <th>Yield</th> <th>Density</th> </tr> <tr> <td align="center">6.75</td> <td align="center">5.5</td> <td align="center">22496</td> <td align="center">0</td> <td align="center">0</td> <td align="center">0</td> </tr> </table>						Hole Size	Casing Size	Depth	Sacks	Yield	Density	6.75	5.5	22496	0	0	0
		Hole Size	Casing Size	Depth	Sacks	Yield	Density												
6.75		5.5	22496	0	0	0													
Bbl/Sk				0															
bbbls				0															
Top MD of Segment				22496															
Bottom MD of Segment				22496															
Cement Type				H															
Additives																			
Quantity (sks)				0															
Yield (cu ft/sk)				0															
Density (lbs/gal)				0															
Volume (cu ft)				0															
Percent Excess																			
Column Height				0															

PRODUCTION CEMENT

HALLIBURTON

Permian Basin, Ft Stockton

Lab Results- Lead

Job Information

Request/Slurry	2488456/2	Rig Name		Date	18/DEC/2018
Submitted By	Dillon Briers	Job Type	Intermediate Casing	Bulk Plant	
Customer	Ameredev	Location	Lea	Well	

Well Information

Casing/Liner Size	7.625 in	Depth MD	5013 ft	BHST	165°F
Hole Size	8.75 in	Depth TVD	5013 ft	BHCT	130°F

Cement Information - Lead Design

Conc	UOM	Cement/Additive	Cement Properties		
100	% BWOC	NeoCem	Slurry Density	9	lbm/gal
14.68	gal/sack	Heated Fresh Water	Slurry Yield	3.5	ft3/sack
			Water Requirement	14.68	gal/sack

Pilot Test Results Request ID 2488456/1

API Rheology, Request Test ID:35665340

Temp (degF)	300	200	100	60	30	6	3	Cond Time (min)
-------------	-----	-----	-----	----	----	---	---	-----------------

80 (up)	82	67	49	42	39	36	28	0
80 (down)	82	59	35	26	18	10	9	0
80 (avg.)	82	63	42	34	29	23	19	0

PV (cP) & YP (lbs/100ft²): 61.73 22.32 (Least-squares method)

PV (cP) & YP (lbs/100ft²): 60 22 (Traditional method (300 & 100 rpm based))

Generalized Herschel-Bulkley 4: YP(lbf/100ft²)=20.33 MuInf(cP)=52.39 m=0.81 n=0.81

API Rheology, Request Test ID:35665341

Temp (degF)	300	200	100	60	30	6	3	Cond Time (min)	Cond Temp (degF)
-------------	-----	-----	-----	----	----	---	---	-----------------	------------------

134 (up)	63	47	29	21	15	7	6	30	134
134 (down)	63	46	29	21	14	7	4	30	134
134 (avg.)	63	47	29	21	15	7	5	30	134

PV (cP) & YP (lbs/100ft²): 57.12 7.98 (Least-squares method)

PV (cP) & YP (lbs/100ft²): 51 12 (Traditional method (300 & 100 rpm based))

Generalized Herschel-Bulkley 4: YP(lbf/100ft²)=2.26 MuInf(cP)=30.64 m=0.41 n=0.41

API Fluid Loss, Request Test ID:35665342

Test Temp (degF)	Test Pressure (psi)	Test Time (min)	Meas. Vol.	Calculated FL (<30 min)	Conditioning time (min)	Conditioning Temp (degF)
134	1000	9.12	52	189	30	134

This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.

Free Fluid API 10B-2, Request Test ID:35665343

Con. Temp (degF)	Cond. Time (min)	Static T. (F)	Static time (min)	Incl. (deg)	% Fluid
134	30	80	120	0	0

Pilot Test Results Request ID 2504116/5**Thickening Time - ON-OFF-ON, Request Test ID:35852392**

Test Temp (degF)	Pressure (psi)	Reached in (min)	70 Bc (hh:mm)	Start Bc
126	5800	40	6:18	16

UCA Comp. Strength, Request Test ID:35852394

End Temp (degF)	Pressure (psi)	50 psi (hh:mm)	500 psi (hh:mm)	12 hr CS (psi)	24 hr CS (psi)	48 hr CS (psi)
159	4000	8:55	12:23	456	749	681


This report is the property of Halliburton Energy Services and neither it nor any part thereof, nor a copy thereof, is to be published or disclosed without first securing the expressed written approval of Halliburton. It may however be used in the course of regular business operations by any person or concern receiving such report from Halliburton. This report is for information purposes only and the content is limited to the sample described. Halliburton makes no warranties, expressed or implied, as to the accuracy of the contents or results. Any user of this report agrees Halliburton shall not be liable for any loss or damage regardless of cause, including any act or omission of Halliburton, resulting from the use hereof.



U. S. Steel Tubular Products

6/6/2017 8:18:53 PM

7.625" 29.70lbs/ft (0.375" Wall) HCL80 USS-LIBERTY FJM®



MECHANICAL PROPERTIES	Pipe	USS-LIBERTY FJM®	
Minimum Yield Strength	110,000	--	psi
Maximum Yield Strength	140,000	--	psi
Minimum Tensile Strength	125,000	--	psi

DIMENSIONS	Pipe	USS-LIBERTY FJM®	
Outside Diameter	7.625	7.625	in.
Wall Thickness	0.375	--	in.
Inside Diameter	6.875	6.789	in.
Standard Drift	6.750	6.750	in.
Alternate Drift	--	--	in.
Nominal Linear Weight, T&C	29.70	--	lbs/ft
Plain End Weight	29.06	--	lbs/ft

SECTION AREA	Pipe	USS-LIBERTY FJM®	
Critical Area	8.541	5.074	sq. in.
Joint Efficiency	--	59.4	%

PERFORMANCE	Pipe	USS-LIBERTY FJM®	
Minimum Collapse Pressure	6,700	6,700	psi
Minimum Internal Yield Pressure	9,460	9,460	psi
Minimum Pipe Body Yield Strength	940,000	--	lbs
Joint Strength	--	558,000	lbs
Compression Rating	--	558,000	lbs
Reference Length	--	12,810	ft
Maximum Uniaxial Bend Rating	--	39.3	deg/100 ft

Make-Up Loss	--	3.92	in.
Minimum Make-Up Torque	--	10,800	ft-lbs
Maximum Make-Up Torque	--	15,250	ft-lbs

1. Other than proprietary collapse and connection values, performance properties have been calculated using standard equations defined by API 5C3 and do not incorporate any additional design or safety factors. Calculations assume nominal pipe OD, nominal wall thickness and Specified Minimum Yield Strength (SMYS).
2. Compressive & Tensile Connection Efficiencies are calculated by dividing the connection critical area by the pipe body area.
3. Uniaxial bending rating shown is structural only, and equal to compression efficiency.
4. USS-LIBERTY FJM™ connections are optimized for each combination of OD and wall thickness and cannot be interchanged.
5. Torques have been calculated assuming a thread compound friction factor of 1.0 and are recommended only. Field make-up torques may require adjustment based on actual field conditions (e.g. make-up speed, temperature, thread compound, etc.).
6. Reference length is calculated by joint strength divided by nominal plain end weight with 1.5 safety factor.
7. Connection external pressure leak resistance has been verified to 100% API pipe body collapse pressure following the guidelines of API 5C5 Cat III.

Legal Notice

USS-LIBERTY FJM® is a trademark of U. S. Steel Corporation. All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U.S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products
10343 Sam Houston Park Dr., #120
Houston, TX 77064

1-877-893-9461
connections@uss.com
www.usstubular.com



U. S. Steel Tubular Products

5 1/2 20.00 lb (0.361) P110 HP

USS-EAGLE SFH™

	PIPE	CONNECTION	
MECHANICAL PROPERTIES			
Minimum Yield Strength	125,000	125,000	psi
Maximum Yield Strength	140,000	140,000	psi
Minimum Tensile Strength	130,000	130,000	psi
DIMENSIONS			
Outside Diameter	5.500	5.830	in.
Wall Thickness	0.361		in.
Inside Diameter	4.778	4.693	in.
Drift - API	4.653	4.653	in.
Nominal Linear Weight, T&C	19.83		lbs/ft
Plain End Weight	19.83	19.83	lbs/ft
SECTION AREA			
Cross Sectional Area Critical Area	5.828	5.054	sq. in.
Joint Efficiency		86.25	%
PERFORMANCE			
Minimum Collapse Pressure	13,150	13,150	psi
External Pressure Leak Resistance		10,000	psi
Minimum Internal Yield Pressure	14,360	14,360	psi
Minimum Pipe Body Yield Strength	729,000		lbs
Joint Strength		631,750	lbs
Compression Rating		631,750	lbs
Reference Length		21,240	ft
Maximum Uniaxial Bend Rating		89.9	deg/100 ft
Minimum Make-Up Torque		14,000	ft-lbs
Maximum Make-Up Torque		16,900	ft-lbs
Maximum Operating Torque		25,000	ft-lbs
Make-Up Loss		5.92	in.

Notes:

- Other than proprietary collapse and connection values, performance properties have been calculated using standard equations defined by API 5C3 and do not incorporate any additional design or safety factors. Calculations assume nominal pipe OD, nominal wall thickness, and Specified Minimum Yield Strength (SMYS).
- Compressive & Tensile Connection Efficiencies are calculated by dividing the connection critical area by the pipe body area.
- Uniaxial bending rating shown is structural only, and equal to compression efficiency.
- Torques have been calculated assuming a thread compound friction factor of 1.0 and are recommended only. Field make-up torques may require adjustment based on actual field conditions (e.g. make-up speed, temperature, thread compound, etc.).
- Reference length is calculated by joint strength divided by plain end weight with 1.5 safety factor.
- Connection external pressure resistance has been verified to 10,000 psi (Application specific testing).

Legal Notice: All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability, and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.
Manuel USS Product Data Sheet 2017 rev25 (April)

QUALITY CONTROL	No.: QC-DB- 651 / 2013
	Page : 1 / 44
Hose No.: 66551, 66552, 66553, 66554	Revision : 0
	Date: 14. November 2013.
	Prepared by : <i>Sebastian Sander</i>
	Appr. by: <i>[Signature]</i>

CHOKER AND KILL HOSES

id.: 3" 69 MPa x 35 ft (10,67 m)

DATA BOOK

Purchaser: H&P STOCK

Purchaser Order No.:

ContiTech Rubber Order No.: 537587

ContiTech Oil & Marine Corp. Order No.:
4500370505

NOT DESIGNED FOR WELL TESTING

CONTENT

	<u>Page</u>
1. API QMS Certificate (No.: 0760)	3.
2. American Petroleum Institute Certificate of Authority To Use the Official API Monogram (No.: 16C-0004)	4.
3. Quality Control Inspection and Test Certificates (No.: 1905, 1906, 1907, 1908)	5-8.
4. Hose Data Sheet	9.
5. Metal Parts	
5.1. Raw Material Quality Certificates (No.: TR070687, EUR-265844, 86989/13-0)	10-13.
5.2. Hardness Test Reports (No.: 561/13, 562/13)	14-15.
5.3. Ultrasonic Test Reports (No.: 513/13, 514/13, 515/13)	16-18.
5.4. NDT Examiner Certificate (Name: Tóth Ákos József)	19-20.
5.5. Welding Procedure Specification (No.: 140-71)	21-24.
5.6. Welding Procedure Qualification Record (No.: BUD 0700002/1)	25-26.
5.7. Welder's Approval Test Certificate (No.: RK1825997.R1)	27-28.
5.8. Welding Log Sheet (No.: 2013/2898)	29.
5.9. Visual Examination Record (No.: 813/13)	30.
5.10. NDT Examiner Certificate (Name: Kis Gábor Balázs)	31-32.
5.11. Radiographic Test Certificates (No.: 2431/13, 2430/13)	33-34.
5.12. NDT Examiner Certificate (Name: Ménesi István)	35-36.
5.13. MP Examination Record (No.: 1222/13)	37.
5.14. NDT Examiner Certificate (Name: Oravecz Gábor)	38-39.
6. Steel Cord	
6.1. Inspection Certificate (No.: 4046181212)	40.
7. Outside Stripwound Tube	
7.1. Inspection Certificate (No.: 63892/2012)	41.
8. Certificate of Calibration (Manometer Serial No.: 1518086)	42-44.

ContiTech Rubber
Industrial Kft.
Quality Control Dept.
(1)



Certificate of Registration

APIQR® REGISTRATION NUMBER

0760

This certifies that the quality management system of

CONTITECH RUBBER INDUSTRIAL LTD.

Budapesti ut 10

Szeged

Hungary

has been assessed by the American Petroleum Institute Quality Registrar (APIQR®) and found it to be in conformance with the following standard:

ISO 9001:2008

The scope of this registration and the approved quality management system applies to the
Design and Manufacture of High Pressure Hoses

APIQR® approves the organization's justification for excluding:

No Exclusions Identified as Applicable

Effective Date: October 15, 2013
Expiration Date: October 15, 2016
Registered Since: October 15, 2007

W. Don Whitaker
Manager of Operations, APIQR

Accredited by Member of
the International
Accreditation Forum
Multilateral Recognition
Arrangement for Quality
Management Systems



This certificate is valid for the period specified herein. The registered organization must continually meet all requirements of APIQR's Registration Program and the requirements of the Registration Agreement. Registration is maintained and renewed through annual full system audits. Further clarifications regarding the scope of this certificate and the applicability of ISO 9001 standard requirements may be obtained by contacting the registered organization. This certificate has been issued from APIQR offices located at 1120 L Street, N.W., Washington, D.C. 20037-4070, U.S.A., it is the property of APIQR, and must be returned upon request. To verify the authenticity of this certificate, go to www.api.org/comproductlist.





**American
Petroleum
Institute**



2011 1-1

Certificate of Authority to use the Official API Monogram

License Number: **16C-0004**

ORIGINAL

The American Petroleum Institute hereby grants to

**CONTITECH RUBBER INDUSTRIAL LTD.
Budapesti ut 10
Szeged
Hungary**

the right to use the Official API Monogram[®] on manufactured products under the conditions in the official publications of the American Petroleum Institute entitled **API Spec Q1[®]** and **API Spec 16C** and in accordance with the provisions of the License Agreement.

In all cases where the Official API Monogram is applied, the API Monogram should be used in conjunction with this certificate number: **16C-0004**

The American Petroleum Institute reserves the right to revoke this authorization to use the Official API Monogram for any reason satisfactory to the Board of Directors of the American Petroleum Institute.

The scope of this license includes the following product: **Flexible Choke and Kill Lines**

QMS Exclusions: **No Exclusions Identified as Applicable**

Effective Date: **OCTOBER 15, 2013**

Expiration Date: **OCTOBER 15, 2016**

To verify the authenticity of this license, go to www.api.org/compositefile.

American Petroleum Institute


Director of Global Industry Services

CONTITECH RUBBER
Industrial Kft.

No: QC-DB- 651 /2013
Page: 4 / 44

Yam
 ContTech Rubber
 Industrial Kft.
 Quality Control Dept.

RD	+19.65	OC	20:20
BL	+19.47	BAR	20:20
RD	+19.68	OC	20:10
BL	+19.67	OC	20:10
BL	+19.49	BAR	20:10
RD	+19.57	OC	20:00
RD	+20.09	OC	20:00
BL	+19.51	BAR	20:00
RD	+20.01	OC	19:50
RD	+20.17	OC	19:50
BL	+19.53	BAR	19:50
RD	+20.00	OC	19:40
RD	+20.26	OC	19:40
BL	+19.55	BAR	19:40
RD	+19.50	OC	19:30
RD	+20.17	OC	19:30
BL	+19.59	BAR	19:30
RD	+20.00	OC	19:20
BL	+19.64	BAR	19:20
12.11.2013. 19:10			
66511.66551 19:10			
0 10 20 30 40 50 60 70 80 90 100			
10			
38896			

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE				CERT. N°: 1907	
PURCHASER: ContiTech Oil & Marine Corp.			P.O. N°: 4500370505		
CONTITECH RUBBER order N°: 537587		HOSE TYPE: 3" ID		Choke and Kill Hose	
HOSE SERIAL N°: 66553		NOMINAL / ACTUAL LENGTH: 10,67 m / 10,745 m			
W.P. 68,9 MPa	10000 psi	T.P. 103,4 MPa	15000 psi	Duration: 60	min.
<p>Pressure test with water at ambient temperature</p> <p style="text-align: center;">See attachment. (1 page)</p> <p>↑ 10 mm = 10 Min. → 10 mm = 25 MPa</p>					
COUPLINGS Type		Serial N°		Quality	
3" coupling with		8089 8087		AISI 4130	
4 1/16" 10K API Flange end				AISI 4130	
NOT DESIGNED FOR WELL TESTING				API Spec 16 C	
				Temperature rate:"B"	
All metal parts are flawless					
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.					
STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.					
COUNTRY OF ORIGIN HUNGARY/EU					
Date:		Inspector		Quality Control	
13. November 2013.					

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE				CERT. N°: 1908			
PURCHASER: ContiTech Oil & Marine Corp.			P.O. N°: 4500370505				
CONTITECH RUBBER order N°: 537587		HOSE TYPE: 3" ID		Choke and Kill Hose			
HOSE SERIAL N°: 66554		NOMINAL / ACTUAL LENGTH: 10,67 m / 10,71 m					
W.P. 68,9 MPa	10000 psi	T.P. 103,4 MPa	15000 psi	Duration: 60	min.		
<p>Pressure test with water at ambient temperature</p> <p style="text-align: center;">See attachment. (1 page)</p> <p>↑ 10 mm = 10 Min. → 10 mm = 25 MPa</p>							
COUPLINGS Type		Serial N°		Quality		Heat N°	
3" coupling with		8090 8086		AISI 4130		23171 24613	
4 1/16" 10K API Flange end				AISI 4130		034939	
NOT DESIGNED FOR WELL TESTING				API Spec 16 C			
				Temperature rate:"B"			
All metal parts are flawless							
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER INSPECTED AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.							
STATEMENT OF CONFORMITY: We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.							
COUNTRY OF ORIGIN HUNGARY/EU							
Date: 13. November 2013.		Inspector		Quality Control ContiTech Rubber Industrial Kft. Quality Control Dept. 			



Hose Data Sheet

CRI Order No.	537587
Customer	ContiTech Oil & Marine Corp.
Customer Order No	4500370505
Item No.	1
Hose Type	Flexible Hose
Standard	API SPEC 16 C
Inside dia in inches	3
Length	35 ft
Type of coupling one end	FLANGE 4.1/16" 10KPSI API SPEC 6A TYPE 6BX FLANGE C/W BX155STANDARD RING GROOVE
Type of coupling other end	FLANGE 4.1/16" 10KPSI API SPEC 6A TYPE 6BX FLANGE C/W BX155 STANDARD RING GROOVE
H2S service NACE MR0175	Yes
Working Pressure	10 000 psi
Design Pressure	10 000 psi
Test Pressure	15 000 psi
Safety Factor	2,25
Marking	USUAL PHOENIX
Cover	NOT FIRE RESISTANT
Outside protection	St.steel outer wrap
Internal stripwound tube	No
Lining	OIL RESISTANT
Safety clamp	No
Lifting collar	No
Element C	No
Safety chain	No
Safety wire rope	No
Max.design temperature [°C]	100
Min.design temperature [°C]	-20
Min. Bend Radius operating [m]	0,90
Min. Bend Radius storage [m]	0,90
Electrical continuity	The Hose is electrically continuous
Type of packing	WOODEN CRATE ISPM-15

Body

Customer: ContiTech Rubber Industrial Kft
 Order Number: 32258500
 Part Number: 4205160045
 Our Ref: SO64201
 Date: 11th February 2013
 Certificate Number: TR070687 (Rev. 18/06/2013)
 Approved Signatories: R M Greaves A Cocking J Jarvis A Pears S Selman

8083 - 8088



3451 - 3466

42 0516 0045

DESCRIPTION **CERTIFICATE OF CONFORMITY** **Heat Treatment**

AISI4130 BLACK ROLLED BAR, HEAT TREATED & TESTED TO 197-238 BHN, 655MPA MIN TENSILE, 517MPA MIN YIELD, 18% MIN ELONGATION, CHARPY IMPACT TESTING 27J MIN @ -30C (OR COLDER) LATERAL EXPANSION 0.38 MIN. ROLLING REDUCTION 3:1 MIN, NI 1% MAX & CE 0.82 MAX. TESTS MAY BE TAKEN FROM A 4" SQR QTC AS PER API 6APSL 3 QTC SIZE. MECHANICAL TEST SPECIMEN TO ASTM A370 NACE MR0175/ISO15156 APPLIES

HARDENED FROM 860°C FOR 5:30 HOURS (WATER QUENCH) TEMPERED AT 670°C FOR 10 HOURS (AIR COOL) WATER TEMPERATURE BEFORE QUENCH, 28°C. AFTER, 35°C. TEMP. MEASUREMENT, FURNACE ATMOSPHERE THERMOCOUPLE COMPONENT HARDNESS E10 - 211 HBW10/3000 TEST COUPON - 4" SQ X 8" LONG, TESTED AT 1/4 T LOCATION REDUCTION RATIO - 6,2 REDUCTION RATIO & HT APPLY TO BOTH JOB & TEST PIECE FURNACE CALIBRATION: API8A 20th ed. annex M C/E = 0.683

APPROX 20 TONNES 210 MM DIA
 CERTS TO EN10204 3.1

CAST 24613

C	Si	Mn	S	P	Ni	Cr	Mo	Al	Cu	Sn	Nb
0.3200	0.2590	0.5680	0.0090	0.0100	0.1860	1.0580	0.2350	0.0200	0.1420	0.0070	0.0010
V	Ta	Ti	Nb+Ta	Co	N	B	W	Ca	Fe	As	Sb
0.0010		0.0010			0.0079	0.0001					
Pb	Ca	H (ppm)	CEV								
		1.20	0.69								

TEST SPECIFICATION 517 N/mm2 MIN YIELD

Temperature RT	Re	Rp 0.2	Rm	A %	Z %	Impact	Temp.	Hardness
	N/mm2	N/mm2	N/mm2	%	%			
		517.000						

TEST RESULTS

Test Number	Dir./Temp.	Re	Rp	Rm	A %	Z %	Joules	Charpy Direction
ST22561N	20.0°C		524.000	698.000	27.80	87.70	KCV 48°C 60 50 78 KCV 80°C 50 50 46	LONG
Specimen Ø 12.500mm							% Shear Surface 62.0% 52.0% 80.0%	LONG
							Lateral Expansion (mm) 0.840 0.740 1.020	LONG

For and on Behalf of TM Steels Ltd.

A Cocking

ContiTech Rubber Industrial Kft. CERTIFICATE ACCEPTABLE
 QC INSPECTOR
 DATE: 14.06.21.

TM Steels Ltd
 Foxwood Way
 Foxwood Road
 Chesterfield
 S41 9RA

Steel for the Oil and Engineering Industries
 Machining and Boring Facilities

Tel +44 (0)1246 268312
 Sales Fax +44 (0)1246 268313
 Production Fax +44 (0)1248 268841
 email sales@tmsteels.co.uk
 Co Reg No: 3523526 Vat No: GB 706 2814 57



Carbrook Street
Sheffield S9 2JN
Telephone: +44 114 244 6711
Facsimile: +44 114 244 7469



Cert No. 65203

Results quoted only refer to the items tested.

Material Specification	AISI4130		
Heat Treatment Spec	197-237BHN	Test Spec	517N/MM2MIN.YLD
Melt Practice	EFVD	Production Method	FORGED

Heat Treatment	Temp(°C)	Soak	Coolant	Charge Ref.	Init	Max(°C)	Batch	Temp recorded using	CONTACT THERMOCOUPLE				
HARDEN	860	3 HRS	WATER QUENCH	SHF-158284	20	30	0912091308	Nature of T/P	Separate				
TEMPER	650	4 HRS	TABLE COOL	SHF-158284			1012091319	Qts size	4inch SQ X 6inch LONG				
								Req. Min/Max	Achieved				
								Hardness on T/P	197	237 HBW	229	229	HBW
								Hardness on Material	197	237 HBW	218	235	HBW

Tensile -				Impacts -						
Location	Direction	Rp 0.20%	Rm	A%	Z%	Location	Direction	CVN	Lat. Exp. (mm)	% Shear
1/4T	LONGITUDINAL	517 Min	655 to 800	18 Min (4d)	0 Min	1/4T	LONGITUDINAL	27 Min Ave	0.380 Min	0
Results (N/mm2)		580	785	25 (50.0mm)	84.0 (12.56mm)	Results (Joules)	-30 Centigrade	106 104 102	1.44 1.42 1.4	40 40 40
Results						Results				

Corrosion											
Pitting Resistance				Ferrite				Microstructure			
Carbon Equivalent: .671											
Grain Size: Min 6 Max 8											
C	Si	Mn	P	S	Cr	Mo	Ni	Cu			
0.2940	0.2920	0.5370	0.0110	0.0050	1.0620	0.2280	0.1860	0.2430			

Certs to BSEN10204.2004 3.1
NACE MR-01-75
FE = BAL
REDUCTION RATIO 6.5:1

Contitech Rubber Industrial Kft.
CERTIFICATE ACCEPTABLE
David
QC INSPECTOR
DATE: 12.10.04

All furnace Calibration conforms to API6A 20th Edition ANNEX M.
Hardness load/penetration depth - HBW 10 diameter (mm)/3000 kgf test force per ASTM E10.
Third party inspection :

Names of Approved Signatories : S.Maxted G.Smith S.Sutar P.Rogers M.Brown
This report is not to be reproduced without written approval.

Signature *M...*

Body
8089-8090

Test Certificate

To:	CONTITECH RUBBER INDUSTRIAL KFT H-6728, SZEGED, BUDAPESTI UT 10. K-1562-K1575 HUNGARY	Customer Order Number	32252193 - 01	Test Number	402483
	420516 0045	Customer Order Date	27Feb12	Part Number	4205160045
		Sales Order Number	EUR-352087-1	Cast Number	23171
		Report Date	25Sep12	Cert Number	EUR-265844
		Quantity	14 Pos 17402 Kgs 210 mm Dia		
Description AISI 4130 75KSI .2% PS API QTC				Steel Type ALLOY 4130	

CONTITECH RUBBER
Industrial Kft.
No: QC-DB-651 / 2013
Page: 11 / 44

HAMOR zRt.

Flange

FORGING, MACHINING, HEAT-TREATING

8083-8090 3386
4205140284

ÉMI-TÜV
ISO9001

H-3531 Miskolc, Kiss Ernő u. 17. Phone: 36/46/401-033 Fax: 36/46/379-199

INSPECTION CERTIFICATE

ACCEPTANCE ACCORDING EN 10204-05/3.1 | Certificate No.: **86989/13-0**
 Date of issue: 2013.03.27 | Hámor No.: 98-39B5263 | Order No.: 32259784/13/2
 Customer: Contitech Rubber Industrial Kft.
 6728 Szeged Budapesti út 10
 Quality: AISI 4130/CONTI Spec.No.: API 6A PSL3 325/133 x 182
 Dimension: MSO-100597-002/A/H mm
 Final dim.: MSO-100597-002/A(4 1/16") Heat-treatment: Quenched & tempered
 Quantity: 30 pcs | Weight: 73.0 kg/pc | Total weight: 2190.00 kg

nomination of product: Forged, machined disc

Chemical analysis %

Heat No.: **034939**

Steelmaker: CELSA Hutaostrowiec POLA

Test No.	Spec. value	C	MN	SI	P	S	CR	MO	V	Ce
	Min.									
	Max.	0.45	1.80	1.00	0.025	0.025	2.75	1.500	0.300	0.82
	Result	0.28	0.56	0.20	0.006	0.003	0.99	0.170	0.003	0.62

Mechanical properties:

Test No.	Spec. value	HB	Rp0.2 MPa	Rm MPa	A5 %	KV-J -30°C
	Min.	197	517	655	18	27
	Max.	238				
L13314	Result	235				
	Result	238	525	662	19.50	35
						52
						82

ContiTech Rubber Industrial Kft.
CERTIFICATE ACCEPTABLE
 QC INSPECTOR
 DATE: 1.03.29

Test bar from product.
 Dimensional and visual control: passed
 Ultrasonic test acc. to SEP 1921-84 spec. is satisfactory C/c
 Steel making (melting) process: UHP-ASEA vacuum-treated.
 NACE MR 0175/ISO 15156+API 17K + API 6A PSL3.
 HB-E10, Mechanika: ASTM A370 acc.
 Grade Of forging: 9.81 30 pc/series.

Executive

Hámor Zrt.
 Minőség ellenőrzés
 Osztály

Expert

MU-4-10/1/96
HÁMOR zRt.
 FIALKA




MISKOLC Kiss Ernő u. 17. sz. H-3531 tel:36/46/401-033 fax:36/46/379-199 e-mail: hamor@t-online.hu

PROTOCOL NUMMER: 98-39B5263

HEAT-TREATMENT PROTOCOL		
BUYER: CONTITECH RUBBER INDUSTRIAL Kft. Szeged Budapesti út 10. sz.	Order No. of Buyer: 32259784/13/2	
	Work No. of Buyer:	
PRODUCT: forged	QUANTITY: PIECE 30	No. of drawing: MSO-100597-002/A/H
MATERIAL QUALITY: AISI 4130 CONTI API 6A PSL3	Charge No.: 34939	Test No.:
<u>HEAT-TREATMENT:</u> quenching and tempering		
Typ of furnace: electric furnace		Hardening medium: water

PROCESS OF HEAT-TREATMENT



Miskolc, Hámor ZRt. 2013-03-26.

Kandó
head of heat-treatment

Hámor zRt.
minőség ellenőrzés
osztály


Felado : 61344 gamma controll kft 19/10/13 12:54 Lap: 2

 <p>www.gamma-controll.hu 6750 Algyó, Költérület 0188/14. hrsz. Tel/Fax: +36 258 17-420 / 01344</p>	HARDNESS TEST REPORT	Report No: 561/13.
		CLIENT: JE-20 KFT. SZEGED, KÜLTÉRÜLET, 01408/22.

TEST EQUIPMENT:	TH 160-D Hardness tester
PROCEDURE:	QCP-45-R1
DESCRIPTION OF COUPLING:	coupling(s) after PWHT
DRAWING NUMBER:	MT-3121-3000
SERIAL NUMBER:	8083; 8084; 8085; 8086

BRINELL HARDNESS REQUIREMENT	SERIAL NO OF COUPLING	PART OF THE COUPLING	ACTUAL HARDNESS RESULT (HB)
Min HB 197 Max HB 238	✓ 8083	body	224
		weld	222
		flange	236
		connection face	238
	✓ 8084	body	213
		weld	208
		flange	220
		connection face	238
	✓ 8085	body	214
		weld	214
		flange	219
		connection face	222
	✓ 8086	body	232
		weld	237
		flange	238
		connection face	197

The coupling(s) conform to API Spec 6A requirements.

DATE: 2013. október 30.	PREPARED:  Ménési István	APPROVED: GAMMA-CONTROLL KFT. 6750 Algyó, Költérület 0188/14. hrsz. Addszám: 11094574-2-01 www.gamma-controll.hu Ménési István
-----------------------------------	---	--

Feladó : 61344 gamma controll kft 19/10/13 12:54 Lap: 3

 <p>www.gamma-controll.hu 6750 Algyő, Kültérület 01408/22. Irod. Tel/Fax: +36 62811-400 / 61344</p>	HARDNESS TEST REPORT	Report No: 562/13.
--	-----------------------------	--------------------

CLIENT: JE-ZO KFT. SZEGED, KÜLTÉRÜLET, 01408/22.

TEST EQUIPMENT: TH 160-D Hardness tester

PROCEDURE: QCP-45-R1


DESCRIPTION OF COUPLING: coupling(s) after PWHT

DRAWING NUMBER: MT-3121-3000

SERIAL NUMBER: 8087; 8088; 8089; 8090

BRINELL HARDNESS REQUIREMENT	SERIAL NO OF COUPLING	PART OF THE COUPLING	ACTUAL HARDNESS RESULT (HB)
Min HB 197 Max HB 238	✓ 8087	body	213
		weld	216
		flange	220
		connection face	225
	✓ 8088	body	229
		weld	212
		flange	223
		connection face	213
	✓ 8089	body	219
		weld	229
		flange	231
		connection face	238
✓ 8090	body	207	
	weld	210	
	flange	226	
	connection face	234	

The coupling(s) conform to API Spec 6A requirements.

DATE: 2013. október 30.	PREPARED:  Ménési István	APPROVED:  GAMMA-CONTRULL KFT. 6750 Algyő, Kültérület 01408/14. hrsz. Adószám: 11094074-0-06 www.gamma-controll.hu Varga Péter
-----------------------------------	---	---

 <p>GAMMA-CONTROLL Röntgen- és Ultrahangvizsgáló Kft. www.gamma-controll.hu 6750 Algyő, Kőterület 01884/14. hrsz. Tel./Fax.: +36 62/517-400 / 61344 A NAT által NAT-1-114/2010 sz.úron akkreditált vizsgálólaboratórium</p>	<p>ULTRAHANG VIZSGÁLATI JEGYZŐKÖNYV</p> <p>ULTRASONIC EXAMINATION REPORT</p>	<p>Vizsgálati szám: Report No.:</p> <p style="text-align: center;">513/13</p>
---	--	--


Vizsgálat tárgya / Object of test		Coupling (Body)	
Gyártó Manufacturer	Megrendelő Customer	JE-ZO Kft. Szeged	
Gyáriszám Serial-No.	Rendelési szám Order-No.	---	
Azonosító jel Identification	Követelmény Requirement	8083-8088 ASTM A388	
Geometriai kialakítás / Rajzszám Geometric configuration / Drawing-No.	Vizsgálati hőkezelés Test heat treatment	előtt prior	
Anyagminőség Material	Letapogatósi irányok Direction of scanning	AISI 4130 / axiális és radiális	
Adagszám Heat-No.	Vizsgálati terjedelem Exted of Test	24613 / 100%	
Vizsgálati felület állapota Surface condition	Vizsgált darabszám Testing pieces	forgácsolt machined 6 db	

Vizsgálati adatok / Examination data			
Készülék típusa Type of US-equipment	USM25	Készülék gyári száma Serial-No. Of US-equipment	7875f
Vizsgálófej(ek) Searc unit(s)	SEB-2, SEB4H	Frekvencia(k) Frequency(ies)	2 MHz 4 MHz MHz MHz
Kalibrációs blokk Calibration standard identification	ET1,ET2	Erősítés(ek) Gain	axiálisan 18 dB dB dB radiálisan 6 dB
Csatoló közeg Couplant	olaj oil	Hanggyengülés Attenuation	dB/m

Értékelés / észlelt kijelzések / Evaluation / recordable indications

Értékelés Evaluation	X	megfelelő satisfactory	nem megfelelő / not acceptable
-------------------------	----------	---------------------------	--------------------------------

Megjegyzés(ek)
Remark(s)

Hely / kelt Place / date	 Vizsgálatot végezte Tested by Tóth Ákos UT20103090307	GAMMA-CONTROLL KFT. 6750 Algyő, Kőterület 01884/14. hrsz. Adószám: 11094614-2-06 www.gamma-controll.hu Tel.: 06-30-2182640 Approved by Benkő Péter - Felelős vezetőh.
-----------------------------	--	---



Ez a jegyzőkönyv részleteiben nem másolható! / Copying details is prohibited!

 <p>GAMMA-CONTROLL www.gamma-control.hu 6750 Algyó, köberdét 01884/14. hrsz. Tel./Fax.: +36 62/517-400 / 61344 A NAT évi NAT-1-1140/2010 sz. számú elnöki határozat alapján vizsgálati szervezetként</p>	<p>ULTRAHANG VIZSGÁLATI JEGYZŐKÖNYV</p> <p>ULTRASONIC EXAMINATION REPORT</p>	<p>Vizsgálati szám: Report No.:</p> <p style="text-align: center;">514/13</p>

Vizsgálat tárgya / Object of test		Coupling (Body)	
Gyártó Manufacturer		Megrendelő Customer	JE-ZO Kft. Szeged
Gyártás szám Serial-No.		Rendelési szám Order-No.	---
Azonosító jel Identification	8089-8090	Követelmény Requirement	ASTM A388
Geometria kialakítás / Rajzszám Geometric configuration / Drawing-No.	MT-3121-3000 ø200xø70x491	Vizsgálati hőkezelés Test heat treatment	előtt prior
Anyagminőség Material	AISI 4130 /	Letapogatási irányok Direction of scanning	axiális és radiális
Adagszám Heat-No.	23171 /		
Vizsgálati felület állapota Surface condition	forgácsolt machined	Vizsgálati terjedeleme Exted of Test	100%
Vizsgált darabszám Testing pieces	2 db		
Vizsgálati adatok / Examination data			
Készülék típusa Type of US-equipment	USM25	Készülék gyári száma Serial-No. Of US-equipment	7875f
Vizsgálófeje(ek) Searc unit(s)	SEB-2, SEB4H	Frekvencia(k) Frequency(ies)	2 MHz 4 MHz MHz MHz
Kalibrációs blokk Calibration standard identification	ET1,ET2	Erősítés(ek) Gain	axiálisan 18 dB dB dB radiálisan 6 dB
Csatoló közeg Couplant	olaj oil	Hanggyengülés Attenuation	dB/m
Értékelés / észlelt kijelzések / Evaluation / recordable indications			
Értékelés Evaluation	X	megfelelő satisfactory	nem megfelelő / not acceptable
Megjegyzés(ek) Remark(s)			
Hely / kelet Place / date	<p style="text-align: center;"><i>Bankó Péter</i></p> <p style="text-align: center;">Vizsgálatot végezte Tested by</p> <p style="text-align: center;">Tóth Ákos UT20103090307</p>		<p>GAMMA - CONTROLL KFT. 6750 Algyó, köberdét 01884/14. hrsz. Adószám: 1-094614-2-06 www.gamma-control.hu Tel.: +36 62/517-400-2640</p> <p style="text-align: center;">Approved by Bankó Péter - Felelős vezetőh.</p>

Ez a jegyzőkönyv részleteiben nem másolható! / Copying details is prohibited!

 <p>GAMMA-CONTROL www.gamma-control.hu 6750 Algyő Kölcsey út 114-116 Tel./Fax.: +36 82/517-400 / 8 1994 ANKY 624 833-1-11432030 szellemi tulajdon védelme alatt</p>	<p>ULTRAHANG VIZSGÁLATI JEGYZŐKÖNYV</p> <p>ULTRASONIC EXAMINATION REPORT</p>	<p>Vizsgálattal azonosító Report No.:</p> <p>516/13</p>

Vizsgálat tárgya / Object of test		Flange	
Gyártó Manufacturer	Megrendelő Customer	JE-ZO Kft. Szeged	
Gyártási szám Serial-No.	Rendelési szám Order-No.	-	
Azonosító jel Identification	Követelmény Requirement	8083-8080 ASTM A388	
Geometriai kialakítás / Rajzszám Geometric configuration / Drawing-No.	Vizsgálati hőkezelés Test heat treatment	MT-3121-3000 ø315x45x190x94x70 előt prior	
Anyagminőség Material	Letapogatóirányok Direction of scanning	AISI 4130 / axiális és radiális	
Adagszám Heat-No.	Vizsgálati terjedeleme Extent of Test	034939 / 100%	
Vizsgálati felület állapota Surface condition	Vizsgálati darabszám Testing pieces	forgácsolt machined 8 db	
Vizsgálati adatok / Examination data			
Készülék típusa Type of US-equipment	Készülék gyári száma Serial-No. Of US-equipment	USM25 7875f	
Vizsgálófej(ek) Search unit(s)	Frekvencia(k) Frequency(ies)	SEB-2, SEB4H 2 MHz 4 MHz MHz MHz	
Kalibrációs blokk Calibration standard identification	Erősítés(ek) Gain	ET1,ET2 axiálisan radiálisan 6 dB dB dB 6 dB	
Csatoló közeg Couplant	Hanggyengülés Attenuation	olaj oil dB/m	
Ertékelés / észlelt kijelzések / Evaluation / recordable indications			
Ertékelés Evaluation	X	megfelelő satisfactory	nem megfelelő / not acceptable
Megjegyzés(ek) Remark(s)			
Hely / hely Place / date	 Vizsgálattal végezte Tested by Tóth Ákos UT20103090307		 GAMMA-CONTROL KFT. 6750 Algyő Kölcsey út 114-116 Adress: 6750 Algyő Kölcsey út 114-116 www.gamma-control.hu Tel.: +36 82/517-400 Benkő Péter - Felelős vezető

Ez a jegyzőkönyv részleteiben nem másolható! / Copying details is prohibited!



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)

(Certification Body)

RONCSOLÁSMENTES ANYAGVIZSGÁLÓ TANÚSÍTVÁNY

(Certificate of NDT personnel)

Azonosító szám: **UT20103090307**
(Identification No.)

A tanúsított neve:
(The name and forename of
the certificated individual):
Születési hely/idő:
(Place and date of birth):

Tóth Ákos József

**Hódmezőváráshely, 1987. 09.
19.**

A tanúsított személy aláírása
(The signature of the certificated individual)

Vizsgálati eljárás(ok):
(The NDT method(s)):

Ultrahangos anyagvizsgálat
(Ultrasonic testing)

Ipari terület:
(Industrial sector):

Készülékek, berendezések, létesítmények vizsgálata EM
(Pre and in-service testing of equipment, plant and structure)

Termék terület(ek):
(Product sector(s)):

(c)+Fv, (w)+Fv, (wp)+Fv, (f)+Fv

A minősítés fokozata:
(The level of certification):

UT2

A tanúsítás és kiadásának időpontja:
(The date of certification and its issue):

Budapest, 2009. 12. 07.

A tanúsítás érvényes:
(The date upon which certification expires):

2014. 12. 06.

Tanúsító Testület nevében
(On behalf of certifying body)

Az ipari és/vagy termék terület érvényesség kiterjesztve:
(The industrial and/or product sector has been expanded to):

9/2001 GM, 97/23 EC

Dátum (Date):

2009. 12. 07.

Nizsgáztató
(Examiner)

A tanúsítás érvényessége
(Renewed the validity of the certification until (MSZ EN 473 9.):)

-ig megújítva (MSZ EN 473 9.):

Dátum (Date):

Tanúsító Testület nevében
(On behalf of certification body)



A Magyar Hegesztéstechnikai és Anyagvizsgáló Egyesülés, mint a Nemzeti Akkreditáló Testület által a NAT-5-0013/2006 számon akkreditált tanúsító testület az MSZ EN 473 számú szabvány szerint eredményes vizsgálata alapján a nevezett személyt tanúsítja a fentiek szerint:

(The Hungarian Association of Welding Technology and Material Testing as an accredited by the National Accreditation Board (under No. NAT-5-0013/2006) certification body, on the basis of his/her successful examination under the standard MSZ EN 473, hereby certifies the named individual according to the above.)

* c - öntvények (castings); f - kovácsolt termékek (forgings); w - hegesztett kötések-termékek (welded products); t - csövek (tubes); wp - alakított termékek (wrought products); p - műanyag termékek (plastics products); k - kompozitok (composites products)

UT20103090307



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

Meghatározzuk a tanúsítvány tulajdonosát, hogy vizsgálatokat végezzen és azok eredményéért felelősséget vállaljon.
(MSZ EN 473 3.21)

(The holder of this certificate has been authorised to perform tests and take responsibility for the test results. (MSZ EN 473 3.21))

GAMMA - CONTROLL KFT

6722 Szeged, Gyertyános u. 12-16/A

Adószám: 11024514-2006

Munkáltató aláírása: *[Handwritten Signature]*

(Signature of the employer.)

OTP Bank: 1173400520406154

www.gamma-control.hu

Tel.: 06 30 218-2640

Dátum: 2009.12.07

(Date)



Folyamatos munkavégzés igazolása (MSZ EN 473 9.)
(Evidence of continued work activity (MSZ EN 473 9.))

Sorsz.	Munkáltató aláírása (Signature of the employer)	GAMMA-CONTROL Anyagvizsgáló és Minőségellenőrző Kft.	Dátum (Date)
1.	<i>[Handwritten Signature]</i>	GAMMA-CONTROL Anyagvizsgáló és Minőségellenőrző Kft.	2010.01.04.
2.	<i>[Handwritten Signature]</i>	GAMMA-CONTROL Anyagvizsgáló és Minőségellenőrző Kft.	2011.01.06.
3.	<i>[Handwritten Signature]</i>	GAMMA-CONTROL Anyagvizsgáló és Minőségellenőrző Kft.	2012.01.09.
4.	<i>[Handwritten Signature]</i>	GAMMA-CONTROL Anyagvizsgáló és Minőségellenőrző Kft.	2013.01.09.
5.			
6.			
7.			
8.			
9.			
10.			

Kiegészítések:


(Additional remarks:)

* A tanúsítvány a munkáltató aláírásával érvényes
(This certificate is valid with the signature of the employer.)

 PHOENIX PHOENIX RUBBER INDUSTRIAL LTD.		TECHNICAL DATA SHEET		TDS	Page
		WELDING PROCEDURE SPECIFICATION		WPS	N° 1 of 2
CLIENT		THIS SPECIFICATION IS BASED		WPS N° 140-71 REV 4	
IDENTITY CODE		ON ASME CODE SECTION IX		SUPPORTING PQR N°	
				BUD 0700002/1	
ITEM	Qty	WELDING PROCESS: GTAW-SMAW		PERFORMED BY:	
DATA FOR ACCEPTANCE		TYPES: MANUAL		WELDER'S STAMP	
JOINTS (QW-402) 			 <p>Sequences of weld see on addendum</p>		
JOINT DESIGN		BACKING: <u>YES/NO</u>		WELD SEQUENCE	
BASE METALS (QW-403)				PART „A”	PART „B”
DRW N°					
GRADE:		WNo.:1.7220		ASTM A 322-91: AISI 4130 / 34CrMo4 (MSZ EN 10083-1) *	
CARBON EQUIVALENT		max. C _e =		0.82	0.82
MECHANICAL PROPERTIES:					
TENSILE STRENGTH		N/mm ²	min.	655	655
DUCTILITY		%	min.	18	18
HARDNESS		HB	max.	238	238
IMPACT TEST -30°C		J	Average	27	27
THICKNESS:			t = 5-38 mm	OUTSIDE DIAMETER : ØD = 60-280 mm	
FILLER METALS (QW-404)					
WELD MATERIAL	DIAMETER	BRAND		STANDARD	SUPPLIER
Rod	2.4 mm	EML 5		AWS A5.18-01: ER70S-3	Böhler
Electrode	3.2; 4.0	T-PUT NiMo 100**		AWS A 5.5-96: E 10018-D2 (mod.)	Böhler
LAPSE BETWEEN OF PASSES			MIN./min		
POSITIONS (QW-405)			PREHEAT (QW-406)		
POSITIONS: 1G Rotated (horizontal)			PREHEAT TEMP.: 300-330 °C		
WELDING PROGRESSION: Weld flat at or near to the top			INTERPASS TEMP.: max. 350 °C		
POSITION OF FILLET			PREHEAT MAINTENANCE: Till the beginning of postweld heat treating		
OTHER			METHOD OF PREHEATING: Furnace		





CONTINUATION OF WPS N° 140-71 Rev.4							Page N° 2 of 2	
POSTWELD HEAT TREATMENT (QW-407)				GAS (QW-408)				
HOLDING TEMP. RANG		620 +20 / -0 C°		SHIELDING GAS		Argon for root		
HOLDING TEMP. TIME		4 HR		PERCENTAGE COMPOSITION (MIXTURE) 99.995 %				
HEATING RATE MAX.:								
COOLING RATE MAX.:		80 °C/HR		FLOW RATE		10-12 LITRES/min.		
LOCATION OF THERMOCOUPLE				GAS BACKING: Argon (for 1st and 2nd passes)				
FURNACE ATMOSPHERE		Air		FLOW RATE		7-9 Litres/min		
TYPE:				TRAILING SHIELDING GAS COMP.				
ELECTRICAL CHARACTERISTICS (QW-409)							1st pass: -	
CURRENT		DC		ELECTRODE POLARITY :			2nd-28th passes: +	
TUNGSTEN ELEKTRODE SIZE/TYPE: Ø3.2 mm thoriated tungsten								
MODE OF TRANSFER FOR GMAW								
ELECTRODE / WIRE FEED SPEED RANGE								
WELD LAYERS	PROCESS	FILLER METAL		CURRENT		VOLT RANGE	HEAT INPUT (KJ/cm)	
		CLASS	DIAMETER	TYPE POLAR.	AMP. RANGE			
1	GTAW	EML 5	2.4 mm	-	110-130	11-12	5-8.4	
2-3	SMAW	T-PUT NiMo 100	3.2 mm	+	120-140	24-26	12-19.6	
4-28	SMAW	T-PUT NiMo 100	4.0 mm	+	150-170	26-30	16.2-27.5	
TRAVEL SPEED RANGE		100-130 mm/min						
TECHNIQUE (QW-410)								
STRING OR WEAWE BEAD				ORIFACE OR GAS CUP SIZE Ø9mm				
INITIAL/INTERPASS CLEANING: Brushing, Grinding								
EQUIPMENTS FOR WELDING:								
OTHER:								
EXAMINATION - Acc. to the acceptance instruction N° MIO-FB 2 Based on ASME IX.				REMARKS - * Formerly CMo3 (MSZ 61) - ** Ni content less than 1 % - Before welding bake electrodes for 2 hours at 350 °C				
BY		DATE		TECHNICAL DATA SHEET				HOSE TECHNICAL DEPARTMENT WPS N° 140-71 Rev.4
Desig.	Bszb	14.06.	2007	WELDING PROCEDURE SPECIFICATION				
Appr.	Bszb	14.06.	2007	SUBJECT: Butt weld of hose coupling for H2S service; Strenght 75K				
Chek'd								

PHOENIX RUBBER Industrial Ltd. Hose Division	Nº:	WPS 140-71 Addendum
	Revision:	4
ADDENDUM for the approved wall thickness range 5-38 mm Based on WPS 140-71 Rev.4, PQR No.: BUD 0700002/1	Page Nº:	1/2
	Date:	2007-06-12
	Designed:	<i>Bauer</i>
	Checked:	
	Approval:	<i>[Signature]</i>

No.	Wall thickness [mm]	Weld layers	Electrode Ø [mm]
1.	5-7		1 2 3,2 3,2
2.	7-9		1 2-3 3,2 3,2
3.	9-11		1 2-3 4-5 3,2 3,2 4,0
4.	11-13		1 2-3 4-6 3,2 3,2 4,0
5.	13-15		1 2-3 4-8 3,2 3,2 4,0
6.	15-18		1 2-3 4-10 3,2 3,2 4,0
7.	18-20		1 2-3 4-11 3,2 3,2 4,0
8.	20-22,22		1 2-3 4-15 3,2 3,2 4,0
9.	22,2-26		1 2-3 4-19 3,2 3,2 4,0

Remarks: - Process for layer No1 GTAW with Ø3,2 mm thoriated tungsten electrode and Ø2,4 mm Rod EML 5;
for the others: SMAW with electrode T-PUT NiMo 100

PHOENIX RUBBER Industrial Ltd.		Nº:	WPS 140-71 Addendum
ADDENDUM		Revision:	4
for the approved wall thickness range 5-38 mm Based on WPS 140-71 Rev.4, PQR No.: BUD 0700002/1		Page Nº:	2/2

No.	Wall thickness [mm]	Weld layers	Electrode Ø [mm]
10.	26-29		1 2-3 4-19 3,2 3,2 4,0
11.	29-32		1 2-3 4-23 3,2 3,2 4,0
12.	32-35		1 2-3 4-24 3,2 3,2 4,0
13.	35-38		1 2-3 4-28 3,2 3,2 4,0

Remarks: - Process for layer No1 GTAW with Ø3,2 mm thoriated tungsten electrode and Ø2,4 mm wire EML 5;
for the others: SMAW with electrode T-PUT NiMo 100

Certificate no: BUD 0700002/1
Page 1 of 2



Welding Procedure Qualification Record (PQR) ASME IX Energy and Transportation

Company Name: Phoenix Rubber Gumilpan Kft, SZEGED

Procedure Qualification Record No. BUD 0700002/1



Date: 28 February 2007

WPS No. 140-71

Welding Process(es) GTAW/SMAW

Types (Manual, Automatic, Semi-Auto.) Manual

Joints: (QW-402)



Groove Design for Test Coupon
(For combination qualifications, the deposited weld metal thickness shall be recorded for each filler metal or process used.)

Base Metals (QW-403)

Material Spec. ASTM A 322-91, AISI 4130

Type or Grade AISI 4130

P.No. AISI 4130 to P.No. AISI 4130

Thickness of Test Coupon 19 mm

Diameter of Test Coupon 72 mm

Other:

Postweld Heat Treatment (QW-407)

Temperature 620 +20-0 °C

Time 4 hours

Other:

Gas (QW-406)

	Percent Composition		Flow Rate
	Gas	Mixture	
Shielding	Ar 99.95%		10-12 l/min
Backing	Ar 99.95%		7-9 l/min

Filler Metals (QW-404)

SFA Specification ER 70S-3

AWS Classification AS.18

Filler Metal F-No. 6

Weld Metal Analysis A-No. 1

Size of Filler Metal 2.4 mm

Other:

SMAW

E 1001B-G

AS.5

4

2

3.2, 4.0 mm

Other:

Electrical Characteristics (QW-409)

Current DC

Polarity GTAW DCEN, SMAW DCEP

Amps. Layer 1 120,

Layer 2-3 127,

Layer 4-12 136

Other:

Technique (QW-410)

Travel Speed Layer 1-11 100-130 Layer 12 not/hold

String or Weave Bead Layer 1-11 String Layer 12 Weave

Weld Metal Thickness 3 mm

Position (QW-405) 1G rotated

Weld Progression (Uphill, Downhill)

Other:

	GTAW	SMAW
Multipass or Single Pass (per side)	S	M
Single or Multiple Electrodes	S	M

Heat input Layer 1 6.0-8.5 KJ/cm

Layer 2-3 14.1-19.8 KJ/cm

Layer 4-12 18.7-28.1 KJ/cm

Preheat (QW-406)

Preheat Temp. 300-330 °C

Interpass Temp. max 350 °C

Other:

Lloyd's Register, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register Group'. The Lloyd's Register Group assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register Group entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Certificate no: BUD 0700002/1
Page 2 of 2

Specimen No.	Width mm	Thickness mm	Area mm ²	Tensile Test (QW150)		Type of Failure & Location
				Ultimate Total Load kN	Ultimate Unit Stress MPa	
39/1	18.9	15.8		657		Base material
39/2	18.9	15.7		664		Base material

Type and Figure No.	Results
180° Bend roller dia. 36 mm 2+2 pts.	Satisfactory

Specimen No.	Notch Location	Specimen Size mm	Test Temp. °C	Impact Value J	% Shear	Mils	Drop Weight Break (Y/N)
39	S	10x10x55	-30	33			
39	S	10x10x55	-30	49			
39	S	10x10x55	-30	41			
39	HAZ	10x10x55	-30	38			
39	HAZ	10x10x55	-30	97			
39	HAZ	10x10x55	-30	62			

Comments:


Result - Satisfactory: Yes No Penetration into Parent Metal: Yes No

Macro - Results
 Type of Test: Hardness test
 Deposit Analysis:
 Other: Macro - Satisfactory
 X-ray - Satisfactory
 Welder's Name: Tivadar Szabo DC-IL 378258 Clock No. (BC 15) Stamp No.
 Test Conducted By: DKG EAST Anyagvizsgalati Labor. Laboratory Test No: TMO 007-7/07 VJK 1207/2007


We certify that the statements in this record are correct and that the test welds were prepared, welded, and tested in accordance with the requirements of Section IX of the ASME Code.

Date issued: 28 February 2007

Manufacturer's Representative: Laszlo Bajusz
 Manufacturer: Phoenix Rubber Gumipari KR, SZEGED

Lloyd's Register
 Budapest Group

 Laszlo Penzes
 Surveyor to Lloyd's Register BMEA

A member of the Lloyd's Register Group



Fluid Technology

WELDER'S APPROVAL TEST CERTIFICATE - ASME CODE IX

Examiner or test body: ABS

Registration No.: RK1825997.R1

Designation ASME IX: GTAW / SMAW Pipe BW s19 1G

Welder's name: Tivadar Szabó (BC15)

Identification card No: 517278EA

Date and place of birth: 19. August 1949; SZEGED

		Weld test details	Range of approval	Photo (if required)
Welding process		GTAW/SMAW		
Filler metal	Type	Rod / Electrode		
	Designation	AWS 5.18: ER70S-3 AWS 5.5: E9018		
Parent metal group(s)		ASTM A 322-91; AISI 4130	ASTM A 322-91; AISI 4130	
Plate or pipe		Pipe	Pipe/Plate	
Welding position		1G	1G/Flat	
Outside diameter (mm)		72 mm	> 25 mm	Identification of test pieces:
Test piece thickness (mm)		19	Max to be welded	
Single/ both side welding		Single		WPS No.: 140-60 Rev.4
Gouging/ backing				
Joint type		Groove	Groove / Fillet	Testing standard: ASME IX
Shielding/ backing gas(es)		Argon (99,95%)		
Welding carried out, place: Szeged			Date: 29 April 2010 Welding Engineer: László Bajusz <i>Bajusz</i>	
Type of test	Performed and accepted	Not required		Place and date: Szeged, 18-Jun-2010 Surveyor: Péter Szabó Stamp and signature: 
Visual	Accepted (Vjk-1739/10)			
Radiography	Accepted (Vjk-1739/10)			
Ultrasonic		+		
Magnetic particle		+		
Penetrant		+		
Macro		+		
Fracture		+		
Bend		+		
Additional tests		+		
See attached page(s) for prolongation by employer every 6 months				

JE-ZO KFT. 6728 Szeged, Kőltérület 01408/22 hrsz. Adószám: 13341039-2-06 Bankszámlaszám: 12067008-00127077-00100001		WELDING LOG SHEET HEGESZTÉSI MUNKALAP		WLS N ^o . Szám: 2013 / 2898.	
CLIENT Megrendelő		CONTITECH RUBBER Industrial Kft.		PURCH. ORDER N ^o . Rendelésszám	
CONTRACT N ^o . Kötésszám		SPOOL/JOB N ^o . Üzemi m.szám		WPS N ^o . Heg.utazama	
NAME OF WEDED PARTS Heg. alkatrész megnevezése		body + Flange		DRWG N ^o . Rajzszám	
NAME/ N ^o . OF WELDER Hegesztő neve és száma		Szabó Ivador László. B.C. 15.		LOCATION/SHOP Munkavégzés helye	
DATE Dátum		QUANTITY Darabszám		SERIAL NUMBERS Sorszámok	
1. MATERIAL CONTROL Anyag megfelelőség azonosítása		SUBJECT 1 Tárgy 1	body	MATERIAL Anyag	CAST N ^o . Adagszám
		SUBJECT 2 Tárgy 2	Flange	MATERIAL Anyag	CAST N ^o . Adagszám
2. FILLER METAL Elektróda minőség és méret		WELD LAYERS Varratszám		1. 2-3. 4-11.	
		TYPE Típus		Ew. 5. NIMO. 100. NIMO. 100.	
		DIAMETER Átmérő		2.4. 3.2. 4.	
		FILLER CAST N ^o . Elektr.adagszám		800303. 1124075 1127750.	
3. ELECTRICAL CHARACTERISTICS Elektromos adatok		TYPE POLAR Polaritás		- + +	
		VOLT (V)		12. 24. 26.	
		AMPERE (A)		180. 140. 180.	
4. PRE HEAT TREATMENT OF ELECTRODES Elektróda felhasználást megelőző hőkezelés		300. °C		8. Hours	
5. APPLIED SHIELDING GAS Alkalmazott védőgáz		TYPE Típus		Percentage Composition Tisztaság	
		Argon.		99.95. %	
				Flow Rate Áramlási seb. l/min	
				8.	
6. HEAT TREATMENT (pre-weld) Előmelegítés		300. °C		7. POSITION Helyzet	
				Forgatott.	
8. SPEED OF TRAVELS Hegesztési sebesség		100 ÷ 130. mm/min		9. LAPSE BETWEEN OF PASSES Varratfelrakási szünetek	
				8. min	
10. POSTWELD HEAT TREATMENT Utóhőkezelési adatok		Time Idő		Temperature Hőmérséklet	
		240. min		620. °C	
				Furnace atmosph. Hőközeg	
				Levegő.	
				Cooling rate Hűlési sebesség	
				80. °C/H	
11. RADIOGRAPHIC TEST CERT. N ^o . Radiográfiai vizsg. biz. száma		2450/15, 2451/15			
REPAIR Javítás		YES/ Igen		X NO/ Nem	
PLACE OF DEFECT Hiba helye				TYPE OF DEFECT Hiba típusa	
METHOD OF REPAIR Javítási módszer					
VISUAL INSPECTION Szemrevételezés					
Megfelelő / Satisfactory.					
REMARKS Megjegyzés					
Fronius. Magic. Wave. 2600.					
Date, end of cooling down time Dátum, kihűlés vége		2013. 10. 26. - 13. óra		INSPECTOR Ellenőrző	
		WELDING CENTER HEGESZTŐ KÖZPONT WELDING CENTER HEGESZTŐ KÖZPONT 6728 Szeged, Tápé szélé 6. Té. 6793 Szeged, Heller köz 1. Adószám: 13341039-2-06 Bankszámlaszám: 12067008-00127077-00100001		JE-ZO KFT. 6728 Szeged, Kőltérület 01408/22 hrsz. Adószám: 13341039-2-06 Bankszámlaszám: 12067008-00127077-00100001	
				DATE Dátum	
				2013 NOV 06	

Feladó : 61344

gamma controll kft

19/10/13 12:58 Lap: 1

 <p>GAMMA-CONTROLL</p> <p>www.gamma-controll.hu 6750 Algyó, Kálvária út 14. sz. 11. sz. Tel./Fax.: +36 82/517-400 / 61344 A NEMzeti MŰSZ-1-14323/01 számú elrendelés alapján működünk.</p>	<p>SZEMREVÉTELEZÉSES VIZSGÁLATI JEGYZŐKÖNYV</p> <p>VISUAL EXAMINATION REPORT</p>	<p>Record No. Jegyzőkönyv száma:</p> <p>813/13</p>
--	--	---

Object Tárgy	Coupling welding Csatlakozó hegesztés	Serial No. Gyári szám	8083-8090
Customer Megrendel	JE-ZO Kft. Szeged	Drawing No. Rajzszám	MT-3121-3000
Job Nr. Munkaszám	002/13	Material/Dimension Anyagminőség/méret	ALSI 4130 118/77
Quantity Mennyiség	8 db	Extent of examination Vizsgálat terjedelme	100%
Requirements Követelmények	ASME code VIII/1	Heat treatment Hőkezelés	after PWHT
Written Procedure No. Vizsgálati eljárás száma	QCP-09-1	Welder Hegesztő	BC15

Visual examination / Szemrevételezéses vizsgálat

Technique Módszer	Direct visual	-
Instrument Készülék	-	-
Visual aids Segédeszközök	3x magnifying lens	-

Measurement / Mérés

Equipment Készülék	-	-
Instrument Készülék	-	-
Surface temperature A felület hőmérséklete	20 °C	Surface condition Felület állapota
		machined
		Lighting intensity Megvilágítás
		1000lx

Test results Eredmények :	SATISFACTORY
	megfelelő.....8 pc(s)/db
	not accepted
	nem megfelelő.....0 pc(s)/db

Vizsgálat helye és ideje: Place and date of test:	Vizsgálatot végezte: Tested by:	Áttekintette és jóváhagyta: Reviewed and approved by:
Gamma-Controll Kft. Algyó, 2013.10.30. (10h)	Kis Gábor VT20103130102	GAMMA-CONTROLL KFT. 6750 Algyó, Kálvária út 14. sz. 11. sz. Adaszliget 1109M6102-06 www.gamma-controll.hu Tel: +36 82 517 400



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

RONCSOLÁSMENTES ANYAGVIZSGÁLÓ TANÚSÍTVÁNY
(Certificate of NDT personnel)

A tanúsított neve:
(The name and forename of
the certified individual):
Születési hely/ideje:
(Place and date of birth):

Kis Gábor Balázs

Szeged, 1980. 02. 29.

Azonosító szám:
(Identification No.): **VT20103130102**

A tanúsított személy aláírása
(The signature of the certified individual)

Vizsgálási eljárás(ok):
(The NDT method(s)):

**Szemrevételezéses anyagvizsgáló
(Visual testing)**

Ipari terület:
(Industrial sector):

**Készülékek, berendezések, létesítmények vizsgálata EM
(Pre and in-service testing of equipment, plant and structure)**

Termék terület(ek):
(Product sector(s)):

(c), (w), (wp), (f)

A minősítés fokozata:
(The level of certification):

VT2

A tanúsítás és kiadásának időpontja:
(The date of certification and its issue):

Budapest, 2013. 02. 19.

A tanúsítás érvényes:
(The date upon which certification expires):

2018. 02. 18.

Tanúsító Testület nevében
(On behalf of certifying body)

Vizsgáló
(Examiner)

Az ipari és/vagy termék terület érvényesség kiterjesztve:
(The industrial and/or product sector has been expanded to):

Dátum (Date):

Tanúsító Testület nevében
(On behalf of certifying body)

A tanúsítás érvényessége

(Renewed the validity of the certification until (MSZ EN ISO 9712 10.))

ig megújítva (MSZ EN ISO 9712 10.):

Dátum
(Date):

Tanúsító Testület nevében
(On behalf of certifying body)

VT20103130102



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

Meghatározzuk a tanúsítvány tulajdonosát, hogy vizsgálatokat végezzon és azok eredményéért felelősséget vállaljon.
(MSZ EN ISO 9712 3.21)

(The holder of this certificate has authorized to perform tests and take responsibility for the test results. (MSZ EN ISO 9712 3.21))

GAMMA-CONTROL KFT.
6726 Szeged, Tüzök n. 8/A
Munkáltató aláírása: Adószám: 11094614-2-002
(Signature of the employer) Bank: 11335002-20000134
www.gamma-control.hu
Tel.: 06-30-20000134

Dátum: 2013.02.06.
(Date)

Egyesült munkatevékenység igazolása (MSZ EN ISO 9712 10.)
(Evidence of continued work activity (MSZ EN ISO 9712 10.))

Sorsz.:	Munkáltató aláírása (Signature of the employer)	Ph. "GAMMA-CONTROL" Anyagvizsgáló és Minőségellenőrzés Kft.	Dátum (Date)
1.			2013.02.06.
2.			
3.			
4.			
5.			
6.			
7.			
8.			
9.			
10.			

Kiegészítések:
(Additional remarks)

A tanúsítvány a munkáltató aláírásával érvényes
(This certificate is valid with the signature of the employer.)

Feladó : 61344

gamma controll kft

19/10/13 12:54 Lap: 1

 www.gamma-controll.hu 6750 Algyő, Kálvária út 14. hrsz. Tel/Fax: +36 62/817-400 / 81344 A NYIT ÉRTÉK NAT-1-14022010 számú utasítású vizsgálati beszerzésre	RADIOGRÁFIAI VIZSGÁLATI JEGYZŐKÖNYV RADIOGRAPHIC EXAMINATION REPORT	Jegyzőkönyv szám: Report No.: 2431/13 Készítés dátuma: Date of report: 2013.10.30
--	--	--

Vizsgálat tárgya: Objekt:	Coupling	Megrendelő: Client:	JE-ZO Kft. Szeged
Munkaszám: Job No.:	—	Rendelési szám: Order No.:	—
Rajpszám: Drawing No.:	MT-3121-3000	Anyagminőség: Material:	AISI 4130
Vizsgálati szabvány: Testing standard:	QCP-13-1	Vizsgálat terjedelme: Extent of testing:	100%
Átvételi követelmény: Acceptance criteria:	ASTM E94	Hőkezelés: Heat treatment condition:	After PWHT
Kód: Code:	MSZ EN ISO 6520-1	Hegesztési jele: Welder stamp:	BC15
Berendezés típusa: Type of equipment:	GAMMAMAT	Képmínőségjelző típusa: Type of IQI:	ASTM set B type
Sugárforrás: Source:	Ir192	Képmínőségjelző helye: Placement of IQI:	F
Sugárforrás mérete: Source size:	3x1,5mm	Előírt képmínőség: Required IQI:	2% (2-2T)
Aktivitás: Activity:	0,4 TBq	Film típusa: Film Type:	FOMA R5
Filmfeldolgozás módja: Film processing:	Kézi: Manual:	Automata: Automatic:	X
		Fóliafajta és vastagság: Screen type and thick:	Pb 0,027

Megnevezés Designation	Méret Size	Félyedések száma: Number of radiograph	Amplifikációs egyenértékűség: Penetration thickness:	Sugárforrás film átvilágítás: Source-to-film distance:	Film felületi sugárterhelés: Exposure from source side of object to film:	Félsűrűség: Density:	Megtárolási idő: Expos. Time:	Képlékenység: Sensitization Result: Nátrium-nátriosulfid Bead: Amperozás: M.A. Wert, expozíció: Vizsgálati időpontja: Date of test	Hibák/Defects						
									Porosítás A	Salak B	Kötés Lack of fusion C	Gyök Lack of penetration D	Repedés Crack E	Felület Surface F	
									200	300	401	402	100	500	
8083	115/77	4	19	96	19	2,4	0,5	A	10,30 10b						
8084	115/77	4	19	96	19	2,4	0,5	A	10,30 10b						
8085	115/77	4	19	96	19	2,4	0,5	A	10,30 10b						
8086	115/77	4	19	96	19	2,4	0,5	A	10,30 10b						
8087	115/77	4	19	96	19	2,4	0,5	A	10,30 10b						
8088	115/77	4	19	96	19	2,4	0,5	A	10,30 10b						

A filmszámok és varratszámok azonosak, beazonosításuk a megrendelőt terhel.
The numbers of the films and welds are identical, their identification is the task of the customer.

Vizsgálatot végezte:
Performed by: Ménesi I. - Szabó T.

Vizsgálat helye: Place of test: 6750 Algyő, Gamma-Controll Kft. Telephely	Értékelte: Evaluated by: Ménési István RT20101120107	Jóváhagyta: Approved by: GAMMA-CONTROLL KFT 6750 Algyő, Kálvária út 14. hrsz. Adószám: HQT-461-2-0 www.gamma-controll.hu Tel: +36 62 817 400 Felsővezető
--	---	---

Ez a jegyzőkönyv részleteiben nem másolható / Copying details is prohibited

Feladó : 61344 gamma controll kft 19/10/13 12:49 Lap: 1

 www.gamma-controll.hu 6750 Algód, Kálvária út 01904/14. hrsz. Tel./Fax.: +36 62/817-400 / 01284 E-mail: info@gamma-controll.hu	RADIOGRÁFIAI VIZSGÁLATI JEGYZŐKÖNYV RADIOGRAPHIC EXAMINATION REPORT	Jegyzőkönyv szám: Report No.: 2430/13 Kiállítás dátuma: Date of report: 2013.10.30
--	--	---

Vizsgálat tárgya: Object: Coupling		Megrendelő: Client: JE-ZO Kft. Szeged	
Munkaszám: Job No.: ---		Rendelési szám: Order No.: ---	
Rajpszám: Drawing No.: MT-3121-3000		Anyagminőség: Material: AISI 4130	
Vizsgálati szabvány: Testing standard: QCP-13-1		Vizsgálat terjedelme: Extent of testing: 100%	
Árvteli követelmény: Acceptance criteria: ASTM E94		Hőkezelés: Heat treatment condition: After PWHT	
Kód: Code: MSZ EN ISO 6520-1		Hegező jel: Welder stamp: BC15	
Berendezés típusa: Type of equipment: GAMMAMAT		Képmínőségjelölés típusa: Type of IQI: ASTM set B type	
Sugárforrás: Source: Ir192		Képmínőségjelölés helye: Placement of IQI: F	
Sugárforrás mérete: Source size: 3x1,5mm		Követelményezett IQI: Required IQI: 2% (2-2T)	
Aktivitás: Activity: 0,4 TBq		Film típusa: Film Type: FOMA R5	
Filmfeldolgozás módja: Film processing:		Fóliafajta és vastagság: Screen type and thick: Pb 0,027	
Kézi: Manual:		Automata: Automatic: X	

Megnevezés Designation	Méret Size	Férfélek száma Number of radiographs	Ábrázolt anyagvastagság Penetrated thickness	Sugárforrás film levdője Source-to-film distance	Fóliafajta Density	Mérőegységnyi idő Expos. time	Munkaszám Job No.	Rendelési szám Order No.	Vizsgálati időpontja Date of test	Hibák/Defects					
										Gáz Porosity	Salak Slag	Kötés Lack of fusion	Gyök Lack of penetration	Repedés Crack	Felület Surface
A	B	C	D	E	F										
8089	115/77	4	19	96	19	2,4	0,5	A	10.30.10h	200	300	401	402	100	500
8090	115/77	4	19	96	19	2,4	0,5	A	10.30.10h						
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

A filmszámok és varratszámok azonosak, beazonosításuk a megrendelőt terheli.
The numbers of the films and welds are identical, their identification is the task of the customer.

Vizsgálatot végezte:
Performed by: **Ménesi I. - Szabó T.**

Vizsgálat helye: Place of test: 6750 Algód, Gamma-Controll Kft. Telephely	Értékelte: Evaluated by:  Ménesi István RT20101120107	Jóváhagyta: Approved by: GAMMA-CONTROLL KFT 6750 Algód, Kálvária út 01904/14. hrsz. Adószám: W194614-2-46 www.gamma-controll.hu Tel: 06-90-247-2640
--	---	--



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

RONCSOLÁSMENTES ANYAGVIZSGÁLÓ TANÚSÍTVÁNY
(Certificate of NDT personnel)

Azonosító szám: **RT20101120107**
(Identification No.)

A tanúsított neve:
(The name and forename of
the certificated individual):
Születési hely/ideje:
(Place and date of birth):

Ménesi István
Szentes, 1988. 09. 06.

A tanúsított személy aláírása
(The signature of the certificated individual)

Vizsgálati eljárás(ok):
(The NDT method(s)):

Radiográfiai anyagvizsgálat
(Radiographic testing)

Ipari terület:
(Industrial sector):

Készülékek, berendezések, létesítmények vizsgálata: EM
(Pre and in-service testing of equipment, plant and structure)

Termék terület(ek):
(Product sector(s)):

(c), (w)

A minősítés fokozata:
(The level of certification):

RT2

A tanúsítás és kiadásának időpontja:
(The date of certification and its issue):

Budapest, 2012. 03. 28.

A tanúsítás érvényes:
(The date upon which certification expires):

2017. 03. 27.

Tanúsító Testület nevében
(On behalf of certifying body)

Vizsgáztató
(Examiner)

Az ipari és/vagy termék terület érvényesség kiterjesztve:
(The industrial and/or product sector has been expanded to):

Dátum (Date):

A tanúsítás érvényessége
(Renewed the validity of the certification until (MSZ EN 473 9.):)

-ig megújítva (MSZ EN 473 9.):

Dátum (Date):

Tanúsító Testület nevében
(On behalf of certification body)

A Magyar Hegesztéstechnikai és Anyagvizsgálati Egyesülés, mint „a Nemzeti Akkreditáló Testület által a NAT-5-0013/2010 számon akkreditált személytanúsító szervezet” a nevezett személyt tanúsítja az MSZ EN 473 szerint eredményes vizsgája alapján a fentiek szerint:
(The Hungarian Association of Welding Technology and Material Testing as an "accredited certification body for person in by National Accreditation Board (under No. NAT-5-013/2010", on the basis of his/her successful examination under the standard MSZ EN 473, hereby certifies the named individual according to the above.)

* c - öntvények (castings); f - kovacsolt termékek (forgings); w - hegesztett kötések-termékek (welded products); t - csövek (tubes); wp - alakított termékek (wrought products); p - műanyag termékek (plastics products); k - kompozitok (composites products).

RT20101120107



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

Meghatalmazzuk a tanúsítvány tulajdonosát, hogy vizsgálatokat végezzen és azok eredményéért felelősséget vállaljon.
(MSZ EN 473 3.21)
(The holder of this certificate has been authorized to perform tests and take responsibility for the test results. (MSZ EN 473 3.21))

GAMMA CONTROLL Kft.
6126 Szeged
Adószám: 11094614-2-06
OTP Bank: 11735005-20406154
www.gammacontroll.hu
Tel: 06-30-218-2640

Munkáltató aláírása:
(Signature of the employer):

Dátum: 2012. 04. 19.
(Date:)

Folyamatos munkavégzés igazolása (MSZ EN 473 9.) (Evidence of continued work activity (MSZ EN 473 9.))			
Sorsz.:	Munkáltató aláírása (Signature of the employer)	Ph. "GAMMA CONTROLL" Anyagvizsgáló és Munkavizsgáló Kft. "GAMMA CONTROLL" Anyagvizsgáló és Munkavizsgáló Kft.	Dátum (Date)
1.			2012. 04. 19.
2.			2012. 06. 09.
3.			
4.			
5.			
6.			
7.			
8.			
9.			
10.			

Kiegészítések:
(Additional remarks:)

ContiTech Rubber Industrial Kft. Szeged/Hungary		Examination record Vizsgálati jegyzőkönyv Liquid penetrant examination Festékdifúziós vizsgálat <input checked="" type="checkbox"/> Magnetic particle examination Mágneses repedésvizsgálat		Record No. Jegyzőkönyv száma : 1222/13
Manufacturer Gyártó	JE-ZO Kft.	Serial No. Gyári szám	8083-8090	
Customer Megrendelő	ContiTech Rubber Industrial Kft.	Drawing No. Rajzszám	MT 3121-3000	
Object Tárgy	coupling(s)	Material Anyagminőség	AISI 4130	
Quantity Mennyiség	8 pc(s)	Extent of examination Vizsgálat terjedelme	100 % outside	
Requirements Követelmények	ASTM E 709	Heat treatment Hőkezelés	yes	
Written Procedure No. Vizsgálati eljárás száma	QCP-11-1	Welder: Hegesztő:	Szabó T.	
Liquid penetrant examination /Folyadékbehatolásos vizsgálat				
Penetrant Behatóló anyag	Remover Tisztító	Developer Előhívó		
Dwell time Behatólási idő	Drying Szárítás	Developing time Előhívási idő		
Surface temperature A felület hőmérséklete	Surface condition Felület állapota	Lighting intensity Megvilágítás		
Magnetic particle examination/Mágnesezhető poros vizsgálat				
Equipment type Készülék típusa	TSW 1000	Testing material Vizsgáló anyag	MR 76F	Magnetizing current Mágnesező áram
Black light type UV-A lámpa típusa	Superlight C 10A-HE	Field strength checking Térorőmérő	Berthold disc	Field strength Térorő
Surface temperature A felület hőmérséklete	23 °C	Surface condition Felület állapota	machined	Lighting intensity Megvilágítás
Test results Eredmények :	satisfactory megfelelő.....8..... pc(s)/db			
	not accepted nem megfelelő.....-..... pc(s)/db			
Performed by NDE Level II. Vizsgálatot végezte	Signature Aláírás		Revised by Q.C. manager Ellenőrizte – MEO vezető	
Signature Aláírás	Oravecz Gábor		Signature Aláírás	
Place/Date Kelt	Szeged, 04.11.2013.		Signature Aláírás	
			Markó László	
			Place/Date Kelt	
			Szeged, 04.11.2013.	



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

RONCSOLÁSMENTES ANYAGVIZSGÁLÓ TANÚSÍTVÁNY
(Certificate of NDT personnel)

Azonosító szám: **MT20103010506Ú**
(Identification No.):

A tanúsított neve:
(The name and forename of
the certificated individual):

Oravec Gábor

Születési hely/ideje:
(Place and date of birth):

Szeged, 1958. 07. 07.

A tanúsított személy aláírása
(The signature of the certificated individual)

Vizsgálati eljárás(ok):
(The NDT method(s)):

Mágnesezhető poros anyagvizsgáló
(Magnetic particle testing)

Ipari terület:
(Industrial sector):

Fémfeldolgozás MM
(Metal manufacturing)

Termék terület(ek):
Product sector(s):

(c), (f), (w), (wp)

A minősítés szintje:
(The level of certification):

MT2

A tanúsítás és kiadásának időpontja:
(The date of certification and it's issue):


Budapest, 2012. 02. 21.

A tanúsítás érvényes:
(The date upon which certification expires):

2017. 02. 20.



Tanúsító Testület nevében
(On behalf of certifying body)



Vizsgáztató
(Examiner)

Az ipari és/vagy termék terület érvényesség kiterjesztve:
(The industrial and/or product sector has been expanded to):

Dátum (Date): _____

Tanúsító Testület nevében
(On behalf of certifying body)

A tanúsítás érvényessége
(Renewed the validity of the certification until (MSZ EN 473 9.):)

-ig megújítva (MSZ EN 473 9.):

Dátum (Date): _____

Tanúsító Testület nevében
(On behalf of certification body)

A Magyar Hegesztéstechnikai és Anyagvizsgálati Egyesülés, mint „a Nemzeti Akkreditáló Testület által a NAT-5-0013/2010 számon akkreditált személytanúsító szervezet” a nevezett személyt tanúsítja az MSZ EN 473 szerint eredményes vizsgája alapján a fentiek szerint:
(The Hungarian Association of Welding Technology and Material Testing as an “accredited certification body for person an by National Accreditation Board (under No. NAT-5-013/2010”, on the basis of his/her successful examination under the standard MSZ EN 473, hereby certifies the named individual according to the above:)

* c - öntvények (castings); f - kovácsolt termékek (forgings); w - hegesztett kötések-termékek (welded products); t - csövek (tubes); wp - alakított termékek (wrought products); p - műanyag termékek (plastics products); k - kompozitok (composites products).

MT201030105060



MAGYAR HEGESZTÉSTECHNIKAI ÉS ANYAGVIZSGÁLATI EGYESÜLÉS
(HUNGARIAN ASSOCIATION OF WELDING TECHNOLOGY AND MATERIAL TESTING)
(Certification Body)

* Meghatalmazzuk a tanúsítvány tulajdonosát, hogy vizsgálatokat végezzen és azok eredményéért felelősséget vállaljon.
(MSZ EN 473 3.21)
(The holder of this certificate has been authorised to perform tests and take responsibility for the test results. (MSZ EN 473 3.21))

Munkáltató aláírása:
(Signature of the employer.)

[Handwritten signature]

Dátum:
(Date:)

2012. 02. 21.

Folyamatos munkavégzés igazolása (MSZ EN 473 9.) (Evidence of continued work activity (MSZ EN 473 9.))			
Sorsz.:	Munkáltató aláírása (Signature of the employer)	Ph. Contitech Rubber Industrial Kft. Quality Control Dept. (1)	Dátum (Date)
1.	<i>[Handwritten signature]</i>		2013. 01. 24.
2.			
3.			
4.			
5.			
6.			
7.			
8.			
9.			
10.			

Kiegészítések:
(Additional remarks:)

* A tanúsítvány a munkáltató aláírásával érvényes
(This certificate is valid with the signature of the employer.)

505760

Bekaert Hlohovec a.s.
Mierová 2317
92028 Hlohovec / Slovakia
Tel.: 00421337363111
Fax: 00421337422742

STEELCORD
MANUFACTURER : BKHL

Page : 1 / 1

Certificate of Analysis

Delivery No. : 4046181212

Contitech Rubber Industrial Kft.
CONTITECH RUBBER IND SZEGED
Budapesti út 10
H-6728 SZEGED

Sales Order 3046059220/10
Purchase Order 32280330
Inspection lot 09000200665/000001
Batch 3500245378
Date produced 01.07.2013
Date COA 09.08.2013
Spools 32 delivered from a batch of 32 produced
Units 18 delivered from a batch of 18 produced
Delivery net Qty. 10517 KG
Material Description Zinc coated steelcord 1X24DW/3.6 NT 20/36 ZZ B650 5000 M
Lay direction ZZ
Lay length 20/36

Spec customer Contitech Rubber Industrial Kft.
Your code 14-18-07/1
Your spec REV.3 / 15.01.2002
Our Spec H207297 / 26.10.2012

Tests	Procedure	Unit	Specs		Results	
			Alm	Min. Max.	Avg. N	Min ind Max ind
Cord diameter	RA12-100	mm	3,6000	3,4200 3,7800	3,6845 6	3,6640 3,8930
Linear density	RA30-110	g/m	65,000	61,700 68,300	65,632 6	65,300 65,870
Cord breaking strength	RA30-203	N		17900,0	19337,0 6	19087,0 18584,0
Cord elongation at break	RA30-203	%		2,50	2,98 6	2,80 3,15
Zinc D1	RA40-741	g/m2		32,000	40,057 6	37,870 44,630
Zinc D2	RA40-741	g/m2		44,000	48,788 6	45,350 56,100
Residual torsions	RA30-150	Nt	0,000	-3,000 3,000	-0,250 6	-0,500 0,000

Comments :

D1: 0,54

D2: 0,73

Nominal Chemical composition of High Grade Oxysteel:

%Carbon : 0.70-0.90

%Manganese: 0.40-0.60

%Silicon: <0.230

%S: <0.011

%P: <0.012

Microstructure/Texture: Metallurgically the texture is known as a highly drawn, fine ferritic structure.

Conforme a EN.10204/ 3.1

n° : **63892/2012**

Specifica/Specification:
EN 10088-2

Destinatario/Receiver:
ACCIAI VENDER S.P.A.
VIA A. NOBEL, 3/A
43100 PARMA

Cliente/Customer: ACCIAI VENDER S.P.A.
VIA A. NOBEL, 4/A Q.RE IND.LE S.P.I.P
43100 PARMA
Acciaio/Steel: 304PS

25 mm

DDT/DEL. NOTE : 16753 DEL/OF: 24/05/2012 Ordine/order Terninox : P04249 Ord. Cliente/Customer :

Matricola Serial Number	Pos Item	Tipo Prodotto Product Type	Fin	Descrizione Description	Dimensioni(mm) Dimensions(mm)	Pezzi Pieces	Weight (Kg)	Rif. Cli. Cust. Ref.	Colata Heat	NIM
C47997 7-22882	22	COIL	2B		0.60 x 460.0	1	6040		0431359	310727
C54489 7-22887	27	NASTRI STRETTI	BA		0.78 x 284.7	1	1290		0431741	324612

OUTSIDE STRIP WOUND TUBE

IL MATERIALE SOPRA ELENCATO E' STATO DIMENSIONALMENTE E/O SUPERFICIALMENTE TRASFORMATO DA TERNINOX SENZA ALTERARNE LE CARATTERISTICHE MECCANICHE E CHIMICHE
 THE MATERIAL DESCRIBED ABOVE HAS BEEN DIMENSIONALLY AND/OR SUPERFICIALLY TRANSFORMED BY TERNINOX WITHOUT CHANGING THE MECHANICAL AND CHEMICAL FEATURES

Analisi di colata/Chemical Composition

Colata/Heat	C %	Si %	Mn %	P %	S %	Cr %	Ni %	Mo %	N %	Ti %	Cu %	Nb %	B %	Al %	Co %
0431359	0.045	0.300	1.290	0.027	0.001	18.000	9.040	0.260	0.024		0.310				
0431741	0.048	0.310	1.420	0.029	0.001	18.090	9.050	0.320	0.019		0.370				

Risultati delle prove/Test Result (1N/mm²=1 M Pa)

NIM	P T C	S T C	Caric. unit. snervamento Yield strenght		Caric. unit. Rottura Tensile strength	Allungamento a rottura Ultimate elongation (%)			Durezza Hardness	Piega a Bend To 180°	Temperatura Risc. di solub. / heat treatment of annealing for solubiliz.	Resistenza alla corrosione intergranulare secondo / Resistance to corrosion intergranulare	Grano Grain
			Rp0.2% N/mm²	Rp1% N/mm²	Rm N/mm²	Lo =2"	Lo =80	Lo =A5	HRB				
310727	T	T	245	271	607				70.5		1050	EN ISO 3651-2	
	C	T	230	261	604				66.0				
324612	T	T	235	262	688				70.5		1050	EN ISO 3651-2	
	C	T	237	267	605				72.0				

I dati chimici e fisici sopra riportati sono tratti dal certificato di qualità del nostro fornitore qualificato il cui originale è in ns. possesso e disponibile su richiesta.
 Chemical and physical data reported above are extracted from quality certificate emitted from our qualified supplier. The original document is in our posse and is available upon your request.
 Certificates che i prodotti sopra elencati sono conformi alle prescrizioni e standard. We certify that products listed above are conform to order prescriptions.

ITAL INOX
 HUNGARIA KFT.
 1104 Budapest, Lakatos út 42/A.
 Tel: 097-1650, 291-6239 Fax: 290-5067
 Addokszám: 12141537-2-43
 BAEK szá. 10000050-0000005-0-0000000

COMPLIES WITH ED 2000/53/EC

Certificato emesso automaticamente

Data/Date 24/05/2012

R. GOVONI

500/124
506320

CONTITECH RUBBER
 Industrial Kit.
 No: QC-DB- 651 /2013
 Page: 41 / 44

(1) Sampling
 T = Testa - Top
 C = Code - Bottom
 (2) Sens
 T = Trasversale - Transverse
 L = Longitudinale - Longitudinal



MKEH
Metrológiai Hatóság/Metrology Authority
Mechanikai Mérések Osztály
Section of Mechanical Measurements
BUDAPEST XII., NÉMETVÖLGYI ÚT 37-39.
1535 Budapest, Pf. 919
Telefon: 458-5800
Telefax: 458-5927


Ügyiratszám / File No.: MKEH-MH/00287-003/2013/NY
Bizonyítványszám / Certificate No.: NYO - 0008/2013
Hivatkozási szám / Reference No.: 32259470
Page 1/3 oldal
Kiadva / Issued
Budapest, 2013. 01. 28. / 28 01 2013

KALIBRÁLÁSI BIZONYÍTVÁNY
CALIBRATION CERTIFICATE

A kalibrálás tárgya: villamos kimenőjelű nyomásmérő
Object of calibration: electrical-output manometer
Gyártó / Manufacturer: AFRISO-EURO-INDEX GmbH
Típus / Type: DMU03 HD
Azonosító szám / Serial No.: 1518086
Műszaki adatok / Technical data: (0...2500) bar méréstartomány / measuring range (0...2500) bar
(4...20) mA kimenőjel tartomány / output signal range (4...20) mA

Kalibrálásra bemutatta: ContiTech Rubber Industrial Kft.
Customer: 6728 Szeged, Budapesti út 10.

A kalibrálás helye és ideje: Magyar Kereskedelmi Engedélyezési Hivatal
Place and date of calibration: Hungarian Trade Licensing Office
Metrológiai Hatóság, Mechanikai Mérések Osztály
Metrology Authority, Section of Mechanical Measurements
Budapest, 2013.01.24.

A kalibrálást végezte:
Calibrated by: 
Szaulich Dénes
metrológus / metrologist

A kalibrálásnál alkalmazott etalonok:
Standards used for the calibration:

Megnevezés: <i>Designation:</i>	Gyártó: <i>Manufacturer:</i>	Típus: <i>Type:</i>	Gyártási szám: <i>Serial No.:</i>	Bizonyítvány szám: <i>Certificate No.:</i>
túlnyomás etalon / pressure standard	Budenberg	283	20603	NYO-0001/2013
digitális multiméter / digital multimeter	Keithley	2000	0597910	ELD-0014/2012
normál ellenállás / resistance standard	ZIP	P 331	117530	ELD-0021/2012
hőmérő / temperature measuring instr.	GANZ MM	DTH1	33656	Hőm-0296/2012

A mérési eredmények a nemzeti (nemzetközi) etalonra visszavezetettek.
The measuring results are traceable to national standards.

A kalibrálás módja:

Calibration method:

A kalibrálást a KE NYO-3-2002 számú kalibrálás eljárás alapján végeztük.
The calibration was done according to the calibration procedure No.: KE NYO-3-2002.



This certificate is consistent with Calibration and Measurement Capabilities (CMCs) that are included in Appendix C of the Mutual Recognition Arrangement (MRA) drawn up by the International Committee for Weights and Measures (CIPM). Under the MRA, all participating institutes recognize the validity of each other's calibration and measurement certificates for the quantities, ranges and measurement uncertainties specified in Appendix C (for details see <http://www.bipm.org>).

A bizonyítvány az MKEH írásbeli engedélye nélkül csak teljes formájában és terjedelmében másolható!
The calibration certificate shall not be reproduced except in full, without written approval of MKEH!



MKEH
Metrológiai Hatóság/Metrology Authority
Mechanikai Mérések Osztály
Section of Mechanical Measurements

Ügyiratszám / File No.:

MKEH-MH/00287-003/2013/NY

Bizonyítványszám / Certificate No.:

NYO - 0008/2013

Page 2/3 oldal

A kalibrálás körülményei:

Calibration conditions:

környezeti hőmérséklet / Ambient temperature

21,1 °C

a kalibrált eszköz helyzete / Position of the calibrated manometer

függőleges / vertical

a kalibrált eszköz tápfeszültsége / Supply voltage of the calibrated manometer

24V DC

nyomóközeg / Pressure transfer medium

olaj / oil

Mérési eredmények a (0...2500) bar nyomástartományban:

Results of the measurements in the pressure range of (0...2500) bar:

Nyomás, névleges érték <i>Pressure, nominal value</i> bar	Áram-kimenőjel, névleges érték <i>Current-Output, nominal value</i> mA	Áram-kimenőjel, mért eltérés a helyes értéktől <i>Current-Output, measured deviation from the reference value</i> mA	Nyomás, mért eltérés a helyes értéktől <i>Pressure, measured deviation from the reference value</i> bar	Eredő mérési bizonytalanság <i>Expanded uncertainty of the measurement</i> bar
0	4,0	-0,0042	-0,7	2,6
250	5,6	-0,0002	0,0	
500	7,2	0,0029	0,5	
750	8,8	0,0050	0,8	
1000	10,4	0,0063	1,0	
1250	12,0	0,0053	0,8	
1500	13,6	0,0033	0,5	
1750	15,2	-0,0003	-0,1	
2000	16,8	-0,0052	-0,8	
2250	18,4	-0,0117	-1,8	
2500	20,0	-0,0192	-3,0	

Mérési bizonytalanság: A mérési eredmény(ek) mellett közölve.

Uncertainty of measurement: See next to the results of the measurements.

A közölt kiterjesztett mérési bizonytalanság a standard bizonytalanságnak *k* kiterjesztési tényezővel szorzott értéke (*k* = 2), amely normális (Gauss) eloszlás feltételezésével közelítőleg 95%-os fedési valószínűségnek felel meg.

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to coverage probability of approximately 95 %.

A mérési bizonytalanság tartalmazza az etalonból, a kalibrálás módszeréből, a környezeti feltételekből, a kalibrált mérőeszközből stb. eredő részbizonytalanságokat.

It contains the uncertainties of the standards, calibration method, environmental conditions, calibrated device etc.

A standard bizonytalanság meghatározása az EA-4/02 (Expression of the Uncertainty of Measurement in Calibration) kiadványnak megfelelően történt.

The standard uncertainty of measurement has been determined in accordance with the EA Publication EA 4/02 (Expression of the Uncertainty of Measurement in Calibration).



MKEH
Metrológiai Hatóság/Metrology Authority
Mechanikai Mérések Osztály
Section of Mechanical Measurements

Ügyiratszám / File No.:

MKEH-MH/00287-003/2013/NY

Bizonyítványszám / Certificate No.:

NYO - 0008/2013

Page 3/3 oldal

Bélyegzés:

Calibration mark:

A kalibrált mérőeszközön **K067662** azonosító számú kalibrálási bélyeget helyeztünk el.

We have placed a calibration stamp No.: K067662 on the calibrated instrument.

Megjegyzések:

Additional remarks:

Jelen bizonyítvány összhangban van a Nemzetközi Súly és Mértékügyi Bizottság (CIPM) Kölcsonös Elismerési Megegyezése (MRA) C függeléke által tartalmazott kalibrálási és mérési képességekkel (CMCs). Az MRA minden aláíró intézete elismeri egymás kalibrálási és mérési bizonyítványait a C függelék szerinti mennyiségfajtákra, azok értéktartományaival és mérési bizonytalanságaival (közelebbit lásd: <http://www.bipm.org>)

This certificate is consistent with Calibration and Measurement Capabilities (CMCs) that are included in Appendix C of the Mutual Recognition Arrangement (MRA) drawn up by the International Committee for Weights and Measures (CIPM). Under the MRA, all participating institutes recognize the validity of each other's calibration and measurement certificates for the quantities, ranges and measurement uncertainties specified in Appendix C (for details see <http://www.bipm.org>)

A kalibrálási bizonyítványban megadott értékek a mérőeszköznek a kalibrálás idejére és körülményeire jellemző adatai.

The measurement results show the metrological properties of the device during the time of the calibration under the environmental conditions listed above.

Az újrakalibrálás időpontját a felhasználó dönti el a mérőeszköz használatának és állapotának függvényében.

The date of the next calibration is decided by the user. It depends on the usage and the condition of the device.

A bizonyítvány kiadható / Approved by:




Kálóczi László
osztályvezető / Head of Section

Requested Exceptions

- Variance is requested to connect the BOP choke outlet to the choke manifold using a co-flex line (instead of using a 4" OD steel line) with a 10,000 psi working pressure that has been tested to 15,000 psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps.
- Variance is requested to allow Option of rig not capable of reaching TD presetting Surface, Drilling Plan will be same using Fresh Water fluid system.
- Variance is requested to wave any centralizer requirements on the 5-1/2" casing. Ameredev will utilize cement expansion additives in the cement slurry to maximize cement bond and zonal isolation.
- Variance is requested to wave any centralizer requirements on the 9-5/8" casing. Ameredev will utilize cement expansion additives in the cement slurry to maximize cement bond and zonal isolation.
- Variance is requested to allow Temporary Postponement of Operations on well to skid to adjacent well if multiple wells on drilling pad are drilled.
- Variance is requested to allow use of Multi-Bowl Well Head System.
- Variance is requested to allow adjustment of Casing Design Safety Factor on conditions that Ameredev keeps minimum of 1/3 casing capacity filled with OMW drilling fluids.
- Variance is requested to allow 5M Annular Preventer on 10M BOPE System to drill Production Interval. (Supporting Documentation Attached)



APD ID: 10400029847

Submission Date: 04/27/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Well Type: OIL WELL

Well Work Type: Drill



[Show Final Text](#)

Section 1 - Existing Roads

Will existing roads be used? YES

Existing Road Map:

CAMELLIA_FED_COM_26_36_21_101H__WELL_PAD_ACCESS_20190314093823.pdf

Existing Road Purpose: ACCESS

Row(s) Exist? NO

ROW ID(s)

ID:

Do the existing roads need to be improved? NO

Existing Road Improvement Description:

Existing Road Improvement Attachment:

Section 2 - New or Reconstructed Access Roads

Will new roads be needed? YES

New Road Map:

CAMELLIA_FED_COM_26_36_21_101H__WELL_PAD_ACCESS_20190314093850.pdf

EP_CAMELLIA_PAD_ROAD_EASEMENT_SEC_21_REV1_20190314093904.pdf

EP_CAMELLIA_PAD_ROAD_EASEMENT_SEC_28_S_20190314093904.pdf

New road type: RESOURCE

Length: 748

Feet

Width (ft.): 30

Max slope (%): 2

Max grade (%): 2

Army Corp of Engineers (ACOE) permit required? NO

ACOE Permit Number(s):

New road travel width: 20

New road access erosion control: Crowned and ditched

New road access plan or profile prepared? NO

New road access plan attachment:

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Access road engineering design? NO

Access road engineering design attachment:

Access surfacing type: OTHER

Access topsoil source: ONSITE

Access surfacing type description: Caliche

Access onsite topsoil source depth: 6

Offsite topsoil source description:

Onsite topsoil removal process: Grader

Access other construction information: NM One Call (811) will be notified before construction start.

Access miscellaneous information:

Number of access turnouts:

Access turnout map:

Drainage Control

New road drainage crossing: OTHER

Drainage Control comments: Crowned and ditched

Road Drainage Control Structures (DCS) description: None

Road Drainage Control Structures (DCS) attachment:

Access Additional Attachments

Additional Attachment(s):

Section 3 - Location of Existing Wells

Existing Wells Map? YES

Attach Well map:

CAMELLIA_FED_COM_26_36_21_101H__1_MILE_RADIUS_WELLS_20190314094006.pdf

Existing Wells description:

Section 4 - Location of Existing and/or Proposed Production Facilities

Submit or defer a Proposed Production Facilities plan? SUBMIT

Production Facilities description: A multiple well pad will be located on section 21, and will measure 400'x500'. The top 6" of soil and brush will be stockpiled north of the well pad. Should any type of production facilities be located on the well pad, they will be strategically placed to allow for maximum interim reclamation, re-contouring, and revegetation of the well location. Production from the proposed well will be transported to a new production facility named Camellia CTB, north of the well pad. The Camellia CTB will be 500'x525' and will include a separator, Heat Exchanger, VRU, VRT, meter run and a tank battery. A buried 4" poly flowline will be run approximately 34' from the Camellia Fed Com 26 36 21 101H to the Camellia CTB. A buried

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

8" poly water line will be run from the Camellia CTB to a line that will be installed taking our produced water in the area to an SWD that is operated by OWL. The new line will be approximately 662'. A power line will be run parallel to the water line and will connect into a power line that we will be installing for a well in the area. The new power line will be approximately 700'.
Production Facilities map:

CAMELLIA_FED_COM_26_36_21_101H__FACILITIES_MAP_20190314094917.pdf
BO_CAMELLIA_FED_COM_BATTERY_SITE_S_20190314095414.PDF
EP_CAMELLIA_PAD_FLOWLINE_SEC_21_20190314095415.pdf
EP_SOUTH_ELECTRIC_SEC_21_REV2_20190314095416.pdf
EP_SOUTH_WATER_SEC_21_REV2_20190314095417.pdf

Section 5 - Location and Types of Water Supply

Water Source Table

Water source use type: DUST CONTROL,
INTERMEDIATE/PRODUCTION CASING, STIMULATION, SURFACE
CASING

Water source type: GW WELL

Describe type:

Source longitude:

Source latitude:

Source datum:

Water source permit type: PRIVATE CONTRACT

Source land ownership: PRIVATE

Water source transport method: PIPELINE,TRUCKING

Source transportation land ownership: FEDERAL

Water source volume (barrels): 20000

Source volume (acre-feet): 2.577862

Source volume (gal): 840000

Water source and transportation map:

CAMELLIA_FED_COM_26_36_21_101H__WATER_MAP_20190314095517.pdf
CAMELLIA_FED_COM_26_36_21_101H__WATER_WELL_LIST_20190314095518.pdf

Water source comments: Water will be trucked or surface piped from existing water wells on private land. See attached list of available wells.

New water well? NO

New Water Well Info

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft):

Well casing type:

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Water well additional information:

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Construction Materials description: NM One Call (811) will be notified before construction start. Top 6" of soil and brush will be stockpiled south of the pad. V-door will face east. Closed loop drilling system will be used. Caliche will be hauled from existing caliche pits on private and state land.

Construction Materials source location attachment:

CAMELLIA_FED_COM_26_36_21_101H__CALICHE_MAP_20190314095556.pdf

CAMELLIA_FED_COM_26_36_21_101H__WELLSITE_DIAGRAM_20190314095556.pdf

Section 7 - Methods for Handling Waste

Waste type: DRILLING

Waste content description: Drill cuttings, mud, salts, and other chemicals

Amount of waste: 2000 barrels

Waste disposal frequency : Daily

Safe containment description: Steel tanks on pad

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: R360's State approved (NM-01-0006) disposal site at Halfway, NM

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit?

Reserve pit length (ft.) **Reserve pit width (ft.)**

Reserve pit depth (ft.) **Reserve pit volume (cu. yd.)**

Is at least 50% of the reserve pit in cut?

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Reserve pit liner

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? YES

Description of cuttings location Steel tanks on pad

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: NO

Ancillary Facilities attachment:

Comments:

Section 9 - Well Site Layout

Well Site Layout Diagram:

CAMELLIA_FED_COM_26_36_21_101H__WELLSITE_DIAGRAM_20190314095740.pdf

Comments:

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: CAM/AZE

Multiple Well Pad Number: 1N

Recontouring attachment:

CAMELLIA_FED_COM_26_36_21_101H__WELLSITE_DIAGRAM_20190314095755.pdf

Drainage/Erosion control construction: Crowned and ditched

Drainage/Erosion control reclamation: Harrowed on the contour

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Well pad proposed disturbance (acres): 4.59	Well pad interim reclamation (acres): 0.79	Well pad long term disturbance (acres): 3.8
Road proposed disturbance (acres): 0.52	Road interim reclamation (acres): 0	Road long term disturbance (acres): 0.52
Powerline proposed disturbance (acres): 0.42	Powerline interim reclamation (acres): 0	Powerline long term disturbance (acres): 0.42
Pipeline proposed disturbance (acres): 0.02	Pipeline interim reclamation (acres): 0	Pipeline long term disturbance (acres): 0.02
Other proposed disturbance (acres): 6.03	Other interim reclamation (acres): 0	Other long term disturbance (acres): 6.03
Total proposed disturbance: 11.58	Total interim reclamation: 0.79	Total long term disturbance: 10.79

Disturbance Comments:

Reconstruction method: Interim reclamation will be completed within 6 months of completing the well. Interim reclamation will consist of shrinking the pad 17% (.79 acre) by removing caliche and reclaiming 40' wide swaths on the north and east sides of the pad. This will leave 3.8 acres for producing five wells, with tractor-trailer turn around. Disturbed areas will be contoured to match pre-construction grades. Soil and brush will be evenly spread over disturbed areas and harrowed on the contour. Disturbed areas will be seeded in accordance with the surface owner's requirements.

Topsoil redistribution: Enough stockpiled topsoil will be retained to cover the remainder of the pad when the well is plugged. New road will be similarly reclaimed within 6 months of plugging. Noxious weeds will be controlled.

Soil treatment: None

Existing Vegetation at the well pad:

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road:

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline:

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances:

Existing Vegetation Community at other disturbances attachment:

Non native seed used? NO

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? NO

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? NO

Seed harvest description:

Seed harvest description attachment:

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Seed Management

Seed Table

Seed type:

Seed source:

Seed name:

Source name:

Source address:

Source phone:

Seed cultivar:

Seed use location:

PLS pounds per acre:

Proposed seeding season:

Seed Summary	
Seed Type	Pounds/Acre

Total pounds/Acre:

Seed reclamation attachment:

Operator Contact/Responsible Official Contact Info

First Name:

Last Name:

Phone:

Email:

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? NO

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Weed treatment plan description: To BLM standards

Weed treatment plan attachment:

Monitoring plan description: To BLM standards

Monitoring plan attachment:

Success standards: To BLM satisfaction

Pit closure description: No pit

Pit closure attachment:

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

Section 11 - Surface Ownership

Disturbance type: WELL PAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Disturbance type: NEW ACCESS ROAD

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

USFS Forest/Grassland:

USFS Ranger District:

Disturbance type: PIPELINE

Describe:

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Disturbance type: OTHER

Describe: Power line

Surface Owner: BUREAU OF LAND MANAGEMENT

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

Operator Name: AMEREDEV OPERATING LLC

Well Name: CAMELLIA FED COM 26 36 21

Well Number: 101H

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Section 12 - Other Information

Right of Way needed? YES

Use APD as ROW? YES

ROW Type(s): 281001 ROW - ROADS, 285003 ROW - POWER TRANS, 288100 ROW - O&G Pipeline, 288103 ROW - Salt Water Disposal Pipeline/Facility, 289001 ROW- O&G Well Pad

ROW Applications

SUPO Additional Information:


Use a previously conducted onsite? YES

Previous Onsite information: On-site inspection was held with Jeff Robertson (BLM) on 1/30/18. Ameredev made a donation with the MOU fund in lieu of an archaeology report.

Other SUPO Attachment

CAMELLIA_FED_COM_26_36_21_101H__SUPO_REV_20190313_20190314100155.pdf

CAMELLIA_FED_COM_26_36_21_101H_LETTER__OWNER_AGREEMENT_20190314100206.pdf



Surface Use Plan of Operations

Introduction

The following Surface Use Plan of Operations will be implemented by Ameredev Operating, LLC (Ameredev), after APD approval. No disturbance will be created other than those described in this surface use plan. If any additional surface disturbance becomes necessary after APD approval, the appropriate BLM approved sundry notice or right of way application will be acquired prior to such disturbance. This Surface Use Plan includes Ameredev's well pad, battery site, electrical, water and flow lines, and access roads.

Before any surface disturbance is created, stakes or flagging will be installed to mark boundaries of permitted areas of disturbance, including soil storage areas. As necessary, slope, grade, and other construction control stakes will be placed to ensure construction is in accordance with the surface use plan. All boundary markers will be maintained in place until final construction cleanup is completed. If disturbance boundary markers are displaced, they will be replaced before construction proceeds. Adjacent operators will be contacted before construction starts to mark adjacent pipelines.

Directions to proposed pad:

At the intersection of NM-18 and NM-128, head south on NM-18 approximately 1.3 miles. Turn west (right) on Whitworth Drive, and proceed approximately .4 mile. Turn south (left) on NM-205 and proceed about 2.9 miles. Continue on Jal-3/Frying Pan Road approximately 4.4 miles, head west (right) on Beckham Road about 1.4 miles, then north (right) on unnamed road, for approximately .7 mile, then east (right) on proposed road for approximately 113', to the well pad. See *Exhibit 1 – Well Pad Access* for a map of the route.





Exhibit 1 – Well Pad Access

Section 1 – Existing Roads

- A. The existing access road route to the proposed project is depicted on *Exhibit 1 – Well Pad Access*. Improvements to the driving surface will be done where necessary. No new surface disturbance will be done, unless otherwise noted in the New or Reconstructed Access Roads section of this surface use plan.
- B. The existing access road route to the proposed project does not cross lease or unit boundaries, so a BLM right-of-way grant will not be necessary for this proposed road route.
- C. The operator will improve or maintain existing roads in a condition the same as or better than before operations begin. The operator will repair pot holes, clear ditches, repair the crown, etc. All existing structures on the entire access route such as cattle guards, other range improvement projects, culverts, etc. will be properly repaired or replaced if they are damaged or have deteriorated beyond practical use.
- D. Operator will prevent and abate fugitive dust as needed, whether created by vehicular traffic, equipment operations, or wind events. BLM written approval will be acquired before application of surfactants, binding agents, or other dust suppression chemicals on roadways.

Section 2 – New or Reconstructed Access Roads

- A. A section of new access road will be needed for this proposed project. See *Exhibit 1 – Well Pad Access*, for locations.
- B. The length of new access road needed to be constructed for this proposed project is approximately 748 feet.
- C. New access road will be constructed with 6 inches of compacted caliche.
- D. The maximum driving width of the access road will be 20 feet. The maximum width of surface disturbance when constructing the access road will not exceed 30 feet. All areas outside of the driving surface will be revegetated.
- E. When the road travels on fairly level ground, the road will be crowned and ditched with a maximum 2% slope from the tip of the road crown to the edge of the driving surface. Ditches will be constructed on each side of the road. The ditches will be 3 feet wide with 3:1 slopes. See road cross section diagram below:



- F. No turnouts will be constructed on the new portions of access road.
- G. No cattle guards will be installed on the new portions of access road.
- H. Since the proposed portion of new access road does not cross lease boundaries, a right-of-way will not be required for this access road.
- I. No culverts or low water crossings will be constructed for the new portions of access road.



- J. Since the access road is on level ground, no lead-off ditches will be constructed for the new portions of access road.
- K. Any sharp turns in the in the new road will be rounded to facilitate turning by trucks.
- L. Newly constructed or reconstructed roads, on surface under the jurisdiction of the Bureau of Land Management, will be constructed as outlined in the BLM "Gold Book" and to meet the standards of the anticipated traffic flow and all anticipated weather requirements as needed. Construction will include ditching, draining, crowning and capping or sloping and dipping the roadbed as necessary to provide a well-constructed and safe road.
- M. All topsoil and fragmented rock removed in excavation will be used as directed in approved plan.

Section 3 - Location of Existing Wells

Exhibit 2 – One Mile Radius Existing Wells depicts all known wells within a one mile radius of the Camellia Fed Com 26 36 21 101H. See *Exhibit 2a - One Mile Radius Existing Wells List* for a list of wells depicted.




Exhibit 2 – One Mile Radius Existing Wells

Ameredeve Operating, LLC
 Camellia Fed Com 26 36 21 101H
 Section 21, Township 26S, Range 36E
 Lea County, New Mexico



API	WELL NAME	STATUS	TD
30025257840000	LEA 7406 JV-S 3	DRY	887
30025258290000	LEA 7406 JV-S 4	PLUGOIL	3268
30025259530000	NEW MEXICO `CV` STAT 1	PLUGOIL	3239
30025098560000	SAND HILLS UNIT 6	JNK	1257
30025098570000	SAND HILLS UNIT A 1	DHSO	3349
30025098580000	FEDERAL 1	DHSO	3940
30025258410000	PARKER QUANAH 2	JNK	284
30025258900000	LEA 7406 JV-S 5	OIL	3266
30025259090000	LEA 7406 JV-S 6	PLUGOIL	3250
30025259110000	PARKER QUANAH 2-Y	PLUGOIL	3258
30025259200000	LEA 7406 JV-S 7	PLUGOIL	3270
30025259300000	LEA 7406 JV-S 8	PLUGOIL	3270
30025259570000	LEA WD-1	DHSO	3420
30025260560000	LEA 7406-JV-S 9	DRY	3268
30025260680000	LEA 7406-JV-S 9-Y	PLUGOIL	3270
30025261310000	WILSON /21/-FEDERAL 1	OIL	3340
30025261320000	WILSON /21/ FED 2	OIL	3500
30025261330000	WILSON `21`-FEDERAL 3	OIL	3797
30025261340000	WILSON 21-FEDERAL 4	OIL	3575
30025261350000	WILSON 21-FEDERAL 5	OIL	3800
30025261360000	WILSON `21` FEDERAL 6	JNK	1682
30025261370000	WILSON /21-FED/ 7	OIL	3700
30025261380000	WILSON /21/ FED 8	OIL	3700
30025267180000	WILSON /21/ FED 6-Y	OIL	3750
30025270000000	LEA /21/ 7406 JV-S 1	OIL	3668
30025270280000	LEA /21/7406 JV-S 2	OIL	3658
30025270290000	LEA /21/7406 JV-S 3	OIL	3598
30025270300000	LEA /21/7406 JV-S 4	JNK	1060
30025270410000	LEA `21` 7406 JV-S 6	OIL	3495
30025270420000	LEA `21` 7406 JV-S 7	OIL	3525
30025270430000	LEA /21/7406 JV-S 8	OIL	3570
30025271970000	LEA `20` 7426 JV-S 2	PLUGOIL	3670
30025272070000	LEA /21/ 7406 JV-S 4-Y	OIL	3550
30025388850000	EAGLE FEATHER FEDERA 2	GAS	13179
30025401700000	GOOD CHIEF STATE 1	OIL	3873
30025269880000	QUANAH PARKER 3	ABDNLOC	
30025269890000	QUANAH PARKER 4	ABDNLOC	
30025441120000	WILDHOG BWX STATE CO 002H	TREATD	16659
30025442020000	AMEN CORNER 26 36 27 111H	PERMIT	

Ameredev Operating, LLC
 Camellia Fed Com 26 36 21 101H
 Section 21, Township 26S, Range 36E
 Lea County, New Mexico



30025441050100	AZALEA 26-36-28 STAT 121H	JNK	3561
30025444390000	MAGNOLIA 26-36-22 ST 111H	PERMIT	
30025444720000	MAGNOLIA 26-36-22 ST 101H	PERMIT	
30025445220000	WILDHOG BWX STATE CO 003H	PERMIT	
30025445270000	CAMELLIA 26 36 16 FE 101H	PERMIT	
30025441050000	AZALEA 26-36-28 STAT 121H	AT-TD	13600

Exhibit 2a – One Mile Radius Existing Wells List

Section 4 - Location of Existing and/or Proposed Production Facilities

- A. The multiple well pad will be located on section 21, and will measure 400'x500'. Should any type of production facilities be located on the well pad, they will be strategically placed to allow for maximum interim reclamation, re-contouring, and revegetation of the well location.
- B. Production from the proposed well will be transported to a new production facility named Camellia CTB, north of the well pad.
- C. A buried 4" poly flowline will be run approximately 34' from the Camellia Fed Com 26 36 21 101H to the Camellia CTB that will be directly north of the well pad. The Camellia CTB will be 500'x525' and will include a separator, Heat Exchanger, VRU, VRT, meter run and a tank battery. A buried 8" poly water line will be run from the Camellia CTB to a line that will be installed taking our produced water in the area to an SWD that is operated by OWL. This new line will be approximately 662'. A power line will be run parallel to the water line and will connect into a power line that we will be installing for a well in the area. The new power line will be approximately 913'.
- D. The new production facility will have a secondary containment structure that is constructed to hold the capacity of 1-1/2 times the largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.
- E. All permanent (lasting more than six months) above ground structures including but not limited to pump jacks, storage tanks, barrels, pipeline risers, meter housing, etc., that are not subject to safety requirements will be painted a non-reflective paint color, Shale Green, from the BLM Standard Environmental Colors chart, unless another color is required in the APD Conditions of Approval.
- F. If any plans change regarding the production facility or other infrastructure (pipeline, electrical lines, etc.), Ameredev will submit a sundry notice or right-of-way (if applicable) prior to installation or construction.





Exhibit 3 – Well Site Diagram

Section 5 - Location and Types of Water Supply

- A. This location will be drilled using a combination of water and mud systems (outlined in the Drilling Program). The water will be obtained from preexisting water wells, by running a pump directly to the drilling rig. See *Exhibit 4 - Water Wells*, for a list of available water wells. In cases where a polyline is used to transport water for drilling or completion purposes, the existing and proposed roads into location will be utilized.

Ameredev Operating, LLC
 Camellia Fed Com 26 36 21 101H
 Section 21, Township 26S, Range 36E
 Lea County, New Mexico



<u>Permit #</u>	<u>Well Name</u>	<u>Location (Lat/Lon)</u>
CP 1049 POD 2	Bennett	32°04'14.32" N, 103°12'32.30" W
CP 1378	S. Eppenour	32°05'40.62" N, 103°13' 35.26" W
CP 1285	Sec. 5	32°03'56.50" N, 103°17'37.04" W
CP 857	Capped	32°04'39.70" N, 103°16'51.13" W
C 2287	#1	32°03'59.0" N, 103°33'16.8" W
C 2286	#2	32°03'59.2" N, 103°33'15.2" W
C 2290	#3	32°04'1.0" N, 103°33' 12.6" W
C 2285	#4	32°04'3.7" N, 103°33'9.7" W
C 2288	#5	32°04'0.5" N, 103°33'8.4" W
C 2294	Garden	32°03'3.2" N, 103°32'38.1" W
C 2293	House	32°03'2.3" N, 103°32'36.8" W
J-11-S-3	Farm Well #2	32°03'08.4" N, 103°16'35.2" W
J-11-S-2	Farm Well #3	32°03'11.5" N, 103°17'02.0" W
J-11-S	Farm Well #4	32°03'24.6" N, 103°17'02.1" W
CP 1170 POD 1	CB 1	32°03'57.2" N, 103°18'45.3" W
CP 1170 POD 5		32°07'17.1" N, 103°17'48.0" W
CP 1263 POD 5	CB 2	32°03'56.27" N, 103°18'27.4" W
CP 1263 POD 3	CB 3	32°03'54.90" N, 103°18'16.74" W
CP 1351 POD 1	CB 4	32°03'57.16" N, 103°17'45.13" W
CP 1351 POD 2	CB 5	32°03'30.70" N, 103°17'45.70" W
J 26	Ryan	32°01'20.41" N, 103°15'49.46" W
J 3		32°02'41.5" N, 103°18'55.8" W

Exhibit 4 – Water Wells

Section 6 – Construction/Construction Materials

- A. Caliche will be obtained from the caliche pit located at Lat: 32° 6'28.78"N, Long: 103°16'58.77"W or the caliche pit at Lat: 32° 6'33.14"N, Long: 103°18'44.16"W or the caliche pit at Lat: 32° 3'8.30"N, Long: 103°13'57.00"W.
- B. Caliche utilized for the drilling pad will be obtained either from the locations listed above, an existing approved mineral pit, or by benching into a hill, which will allow the pad to be level with existing caliche from the cut, or extracted by "flipping" the well location. A mineral material permit will be obtained from the BLM prior to excavating any caliche on Federal Lands. Amount will vary for each pad. The procedure for "flipping" a well location is as follows:
1. An adequate amount of topsoil/root zone (usually top 6 inches of soil) will be stripped from the proposed well location and stockpiled along the side of the well location as depicted on the *Exhibit 3 - Well Site Diagram*.
 2. An area will be used within the proposed well site dimensions to excavate caliche.
 3. Subsoil will be removed and stockpiled within the surveyed well pad dimensions.
 4. Once caliche/surfacing mineral is found, the mineral material will be excavated and stock piled within the approved drilling pad dimensions.
 5. Subsoil will then be pushed back in the excavated hole and caliche will be spread accordingly across the entire well pad and road (if available).
 6. Neither caliche, nor subsoil will be stockpiled outside of the well pad dimensions. Topsoil will be stockpiled along the edge of the pad as depicted in *Exhibit 5 – Enlarged Well Site Diagram*.
 7. In the event that no caliche is found onsite, caliche will be hauled in from a BLM approved caliche pit or other established mineral pit. A BLM mineral material permit will be acquired prior to obtaining any mineral material from BLM pits or federal land.




Exhibit 5 – Enlarged Well Site Diagram

Section 7 - Methods of Handling Waste

- A. Drill cuttings, mud, salts and other chemicals will be properly disposed of into steel tanks on site and hauled to a State approved commercial disposal facility.
- B. Garbage and trash produced during drilling and completion operations will be collected in a portable metal trash container and disposed of properly at a State approved disposal facility. All trash on and around the well site will be collected for disposal.
- C. Human waste and grey water will be properly contained and disposed of properly at a State approved disposal facility.
- D. After drilling and completion operations, trash, chemicals, salts, frac sand and other waste material will be removed and disposed of properly at a State approved disposal facility.

Section 8 - Ancillary Facilities

- A. No ancillary facilities will be needed for the proposed project.

Section 9 - Well Site Layout

- A. See *Exhibit 3 - Well Site Diagram* and *Exhibit 5 – Enlarged Well Site Diagram*. The following information is presented:
1. Reasonable scale
 2. Well pad dimensions/orientation
 3. Drilling rig components/layout
 4. Proposed access road
 5. Topsoil stockpile
- B. The proposed drilling pad was staked and surveyed by a professional surveyor. The attached survey plat of the well site depicts the drilling pad layout as staked.
- C. Topsoil salvaging
1. Grass, forbs, and small woody vegetation such as mesquite will be excavated as the topsoil is removed. Large woody vegetation will be stripped and stored separately and re-spread evenly on the site following topsoil re-spreading. Topsoil depth is defined as the top layer of soil that contains 80% of the roots. In areas to be heavily disturbed, the top 6 inches of soil material will be stripped and stockpiled on the perimeter of the well location and along the perimeter of the access road to control run-on and run-off, to keep topsoil viable, and to make redistribution of topsoil more efficient during interim reclamation. Stockpiled topsoil should include vegetative material. Topsoil will be clearly segregated and stored separately from subsoils. Contaminated soil will not be stockpiled, but properly treated and handled prior to topsoil salvaging.

Section 10 - Plans for Final Surface Reclamation

Reclamation Objectives

- A. The objective of interim reclamation is to restore vegetative cover and a portion of the landform sufficient to maintain healthy, biologically active topsoil, to control erosion, and to minimize habitat and forage loss, visual impact, and weed infestation during the life of the well or facilities.
- B. The long-term objective of final reclamation is to return the land to a condition similar to what existed prior to disturbance. This includes restoration of the landform and natural vegetative community, hydrologic systems, visual resources, and wildlife habitats. To ensure that the long-term objective will be reached through human and natural processes, actions will be taken to ensure standards are met for site stability, visual quality, hydrological functioning, and vegetative productivity.
- C. The BLM will be notified at least 3 days prior to the commencement of any reclamation procedures.

- D. If circumstances allow, interim reclamation and/or final reclamation actions will be completed no later than 6 months from when the final well on location has been completed or plugged. Ameredev will gain written permission from the BLM if more time is needed.
- E. Interim reclamation will be performed on the well site after the well is drilled and completed. *Exhibit 3 – Well Site Diagram* depicts the location and dimension of the planned interim reclamation for the well site.

Interim Reclamation Procedures (if performed)

- A. Within 30 days of well completion, the well location and surrounding areas will be cleared of, and maintained free of, all materials, trash, and equipment not required for production.
- B. In areas planned for interim reclamation, all the surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads.
- C. The areas planned for interim reclamation will then be contoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 Ratio, unless the adjacent native topography is steeper. Note: Constructed slopes may be much steeper during drilling, but will be re-contoured to the above ratios during interim reclamation.
- D. Topsoil will be evenly re-spread and aggressively revegetated over the entire disturbed area not needed for all-weather operations, including cuts and fills. To seed the area, the proper BLM mixture, free of noxious weeds, will be used. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting, in order to break the soil crust and create seed germination micro-sites.
- E. Proper erosion control methods will be used on the area to control erosion, runoff, and siltation of the surrounding area.
- F. The interim reclamation will be monitored periodically to ensure that vegetation has reestablished and that erosion is controlled.

Final Reclamation Procedures (well pad, buried pipelines, etc.)

- A. Prior to final reclamation procedures, the well pad, road, and surrounding area will be cleared of material, trash, and equipment.
- B. All surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads.
- C. All disturbed areas, including roads, pipelines, pads, production facilities, and interim reclaimed areas will be re-contoured to the contour existing prior to initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to re-contouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation.
- D. After all the disturbed areas have been properly prepared, the areas will be seeded with the proper BLM seed mixture, free of noxious weeds. Final seedbed preparation will consist of

Ameredev Operating, LLC
Camellia Fed Com 26 36 21 101H
Section 21, Township 26S, Range 36E
Lea County, New Mexico



contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting, in order to break the soil crust and create seed germination micro-sites.

- E. Proper erosion control methods will be used on the area to control erosion, runoff, and siltation of the surrounding area.
- F. All unused equipment and structures including pipelines, electric line poles, tanks, etc. that serviced the well will be removed.
- G. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not re-disturbed, and that erosion is controlled.

Section 11 - Surface Ownership

- A. BLM has surface ownership for proposed project area.

Section 12 - Other Information

- A. There are no dwellings within 1 mile of this location.
- B. An on-site meeting for Ameredev's Camellia Fed Com 26 36 21 101H well was held on January 30, 2018 (NOS ID#: 10400029847).
- C. The well pad described in this document – Camellia (CAM/AZE #1N) - will contain 5 wells that produce into an existing central tank battery (CTB) located southwest of the well pad. The wells share a common pad access road, pipeline easement, and electrical corridor. The 6 flowlines from the individual wells will share a common corridor that will terminate into the CTB. The wells that share the pad are:
 - Camellia Fed Com 26 36 21 081H
 - Camellia Fed Com 26 36 21 091H
 - Camellia Fed Com 26 36 21 101H
 - Camellia Fed Com 26 36 21 111H
 - Camellia Fed Com 26 36 21 121H

Ameredev field representative:

Zac Boyd, Operations Supervisor

Cell: (432) 385-6996

Email: zboyd@ameredev.com

Ameredev office contact:

Christie Hanna, Regulatory Coordinator

Direct: (737) 300-4723

Email: channa@ameredev.com

Ameredev Operating, LLC Address: 5707 Southwest Parkway Building 1, Suite 275 Austin, Texas 78735

AMEREDEV

April 18, 2018

To whom it may concern:

Ameredev Operating, LLC is negotiating a private surface owner agreement with Brad Beckham of Beckham Ranch, Inc. (PO Box 1203, Jal, NM 88252; 575-712-4231) for a power line, flowline, saltwater disposal line, roads, central production facility, and pad for the Camellia Fed Com 26 36 21 101H well in sections 21 and 16 of T26S, R36E.

Thank you,



Christie Hanna
Senior Engineering Technician/Regulatory Coordinator



Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number:

Assigned injection well API number?

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection attachment:

Underground Injection Control (UIC) Permit?

UIC Permit attachment:

Injection well name:

Injection well API number:

Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 - Other

Would you like to utilize Other PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Other PWD discharge volume (bbl/day):

Other PWD type description:

Other PWD type attachment:

Have other regulatory requirements been met?

Other regulatory requirements attachment:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Bond Info Data Report

05/06/2019

Bond Information

Federal/Indian APD: FED

BLM Bond number: NMB001478

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment: