


**Adder 31 State #505H  
Lea County, New Mexico**

**Proposed Wellbore**

**311' FSL  
1930' FEL  
Section 31  
T-24-S, R-33-E**

**API: 30-025-\*\*\*\*\***

**KB: 3,526'  
GL: 3,501'**



**Lateral: 15,997' MD, 11,066' TVD  
BH Location: 100' FNL & 1730' FEL  
Section 31  
T-24-S, R-33-E**

**EOG RESOURCES, INC.**  
**Adder 31 State #505H**

**Permit Information:**

Well Name: Adder 31 State No. 505H

**Location:**

SHL: 311' FSL & 1930' FEL, Section 31, T-24-S, R-33-E, Lea Co., N.M.

BHL: 100' FNL & 1730' FEL, Section 31, T-24-S, R-33-E, Lea Co., N.M.

**Casing Program:**

Hole Size	Interval	Csg OD	Weight	Grade	Conn	DF <sub>min</sub> Collapse	DF <sub>min</sub> Burst	DF <sub>min</sub> Tension
17.5"	0' - 1,150'	13.375"	54.5#	J-55	STC	1.125	1.25	1.60
12.25"	0' - 4,000'	9.625"	40#	J-55	LTC	1.125	1.25	1.60
12.25"	4000' - 4,990'	9.625"	40#	HCL-80	LTC	1.125	1.25	1.60
8.75"	0' - 11,344'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60
8.5"	11,344' - 15,997'	5.5"	17#	HCP-110	LTC	1.125	1.25	1.60

**Cement Program:**

Depth	No. Sacks	Wt. ppg	Yld Ft <sup>3</sup> /ft	Slurry Description
1,150'	494	13.5	1.73	Lead: Class C + 4.0% Bentonite + 0.5% CaCl <sub>2</sub> + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	157	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate
4,990'	454	9.0	3.5	Lead: Class C + 10% NaCl + 6% Bentonite Gel + 3% MagOx (TOC @ Surface)
	344	14.4	1.20	Tail: Class C + 10% NaCl + 3% MagOx
15,997'	591	11.0	3.21	Lead: Class C + 3% CaCl <sub>2</sub> + 3% Microbond (TOC @ 4,490')
	1427	14.4	1.2	Tail: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond

**Mud Program:**

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0' - 1,150'	Fresh - Gel	8.6-8.8	28-34	N/c
1,150' - 4,990'	Brine	10.0-10.2	28-34	N/c
4,990' - 10,594'	Cut Brine	8.4-9.0	28-34	N/c
10,594' - 15,997' Lateral	Oil Base	9.0-9.5	40-42	8-10

**EOG RESOURCES, INC.**  
**Adder 31 State #505H**

## **Hydrogen Sulfide Plan Summary**

- A. All personnel shall receive proper H<sub>2</sub>S training in accordance with Onshore Order III.C.3.a.
- B. Briefing Area: two perpendicular areas will be designated by signs and readily accessible.
- C. Required Emergency Equipment:
- Well control equipment
    - a. Flare line 150' from wellhead to be ignited by flare gun.
    - b. Choke manifold with a remotely operated choke.
    - c. Mud/gas separator
  - Protective equipment for essential personnel.
    - Breathing apparatus:
      - a. Rescue Packs (SCBA) — 1 unit shall be placed at each breathing area, 2 shall be stored in the safety trailer.
      - b. Work/Escapes packs — 4 packs shall be stored on the rig floor with sufficient air hose not to restrict work activity.
      - c. Emergency Escape Packs — 4 packs shall be stored in the doghouse for emergency evacuation.
    - Auxiliary Rescue Equipment:
      - a. Stretcher
      - b. Two OSHA full body harness
      - c. 100 ft 5/8 inch OSHA approved rope
      - d. 1-20# class ABC fire extinguisher
  - H<sub>2</sub>S detection and monitoring equipment:
    - The stationary detector with three sensors will be placed in the upper dog house if equipped, set to visually alarm @ 10 ppm and audible @ 14 ppm. Calibrate a minimum of every 30 days or as needed. The sensors will be placed in the following places: Rig floor / Bell nipple / End of flow line or where well bore fluid is being discharged.
    - (Gas sample tubes will be stored in the safety trailer)
  - Visual warning systems.
    - a. One color code condition sign will be placed at the entrance to the site reflecting the possible conditions at the site.
    - b. A colored condition flag will be on display, reflecting the current condition at the site at the time.
    - c. Two wind socks will be placed in strategic locations, visible from all angles.

**EOG RESOURCES, INC.**  
**Adder 31 State #505H**

- **Mud program:**  
The mud program has been designed to minimize the volume of H<sub>2</sub>S circulated to surface. The operator will have the necessary mud products to minimize hazards while drilling in H<sub>2</sub>S bearing zones.
  
- **Metallurgy:**  
All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H<sub>2</sub>S service.
  
- **Communication:**  
Communication will be via cell phones and land lines where available.

**EOG RESOURCES, INC.**  
**Adder 31 State #505H**

**Emergency Assistance Telephone List**

<b>PUBLIC SAFETY:</b>	<b>911 or</b>
Lea County Sheriff's Department	(575) 396-3611
Rod Coffman	
Fire Department:	
Carlsbad	(575) 885-3125
Artesia	(575) 746-5050
Hospitals:	
Carlsbad	(575) 887-4121
Artesia	(575) 748-3333
Hobbs	(575) 392-1979
Dept. of Public Safety/Carlsbad	(575) 748-9718
Highway Department	(575) 885-3281
New Mexico Oil Conservation	(575) 476-3440
U.S. Dept. of Labor	(575) 887-1174
<b>EOG Resources, Inc.</b>	
EOG / Midland	Office (432) 686-3600
<b>Company Drilling Consultants:</b>	
David Dominique	Cell (985) 518-5839
Mike Vann	Cell (817) 980-5507
<b>Drilling Engineer</b>	
Steve Munsell	Office (432) 686-3609
	Cell (432) 894-1256
<b>Drilling Manager</b>	
Aj Dach	Office (432) 686-3751
	Cell (817) 480-1167
<b>Drilling Superintendent</b>	
Domingo Lopez	Office (432) 686-3702
	Cell (432) 215-9452
<b>H&amp;P Drilling</b>	
H&P Drilling	Office (432) 563-5757
H&P 651 Drilling Rig	Rig (903) 509-7131
<b>Tool Pusher:</b>	
Johnathan Craig	Cell (817) 760-6374
Brad Garrett	
<b>Safety</b>	
Brian Chandler (HSE Manager)	Office (432) 686-3695
	Cell (817) 239-0251