Form 3160-5 (June 2015)

## UNITED STATES Carlsbad Field Office DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT OCD Hobbs To the interior of the in

Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such property BBS OCD				1414114141122015	_
				6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on page 2 JUN 1 0 2019				7. If Unit or CA/Agreement, Name and/or No.	
1. Type of Well Gas Well Other			IVED	8. Well Name and No. DAUNTLESS 7 FE	D 722H
2. Name of Operator EOG RESOURCES INCORPO	@eogresources.com		9. API Well No. 30-025-45591-00-X1		
Ba. Address PO BOX 2267 MIDLAND, TX 79702  3b. Phone No. (include area code) Ph: 432-636-3600				10. Field and Pool or Exploratory Area RED HILLS	
4. Location of Well (Footage, Sec., T.			11. County or Parish, State		
Sec 7 T25S R33E SESE 250F 32.138546 N Lat, 103.604721			LEA COUNTY, NM		
12. CHECK THE AF	PROPRIATE BOX(ES)	TO INDICATE NATURE O	F NOTICE,	REPORT, OR OTH	ER DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
☐ Notice of Intent	☐ Acidize	□ Deepen	☐ Product	ion (Start/Resume)	■ Water Shut-Off
<del>-</del> ,	☐ Alter Casing	☐ Hydraulic Fracturing	☐ Reclama	ation	■ Well Integrity
Subsequent Report	□ Casing Repair	■ New Construction	☐ Recomp	•	Other Drilling Operations
☐ Final Abandonment Notice	Change Plans	☐ Plug and Abandon		arily Abandon	Drining Operations
	Convert to Injection	☐ Plug Back	g Back		<del></del>
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.  04/24/19 12/14" hole 04/24/19 1st Intermediate Casing @ 4,878' Ran_9-5/8", 40#, J-55 LTC (0' - 3,649') Ran 9-5/8", 40#, HCK-55 LTC (3,649' - 4,878') Lead Cement w/ 1,135 sx Class C(2.32 yld, 12.7 ppg), Trail w/ 285 sx Class C (1.42 yld, 14.8 ppg) Test casing to 1,500 psi for 30 min - Good Did not circ cement to surface, TOC @ 1,100' by Calc Operations approved to proceed by Steven at Carlsbad BLM office Plug #1 (12,117' - 13,051') Cement w/ 235 sx Class H (17.5 ppg, 0.95 yld).  Plug #2 (11,450' - 12,117')					
Electronic Submission #465336 verified by the BLM Well Information System For EOG RESOURCES INCORPORATED, sent to the Hobbs Committed to AFMSS for processing by PRISCILLA PEREZ on 05/14/2019 (19PP1887SE)					
Name (Printed/Typed) EMILY FC	Title SR REC	GULATORY ADMINISTRATOR			
Signature (Electronic S	<del></del>	Date 05/14/2			
	THIS SPACE FO	R FEDERAL OR STATE	OFFICE U	SE 	
Approved By	Title Accept	ted for l	Record	MAY 1 7 2019	
Conditions of approval, if any, are attached certify that the applicant holds legal or equ	not warrant or subject lease Jon	athon She	pard		
which would chaute use approxime to conduct operations diesecon.					
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United					

States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## Additional data for EC transaction #465336 that would not fit on the form

## 32. Additional remarks, continued

Cement w/ 215 sx Class H (0.95 yld, 17.5 ppg)

05/01/19 2nd Intermediate Casing @ 11,777'dau
Ran 7-5/8", 29.7#, ECP-110, BTC SC (0' - 1,223')
Ran 7-5/8", 29.7#, HCP-110, FXL (1,223' - 11,777')
Lead Cement w/ 267 sx Class C(1.04 yld, 14.0 ppg)
Test casing to 2,500 psi for 30 min - Good Did not circ cement to surface, TOC @ 3,900' by Calc resume drilling 6-3/4" hole