

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB NO. 1004-0137
Expires: January 31, 2018

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.

5. Lease Serial No.
NMLC062749B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.
NMNM138329X

SUBMIT IN TRIPLICATE - Other instructions on page 2 **HOBBS OCD**

1. Type of Well
 Oil Well Gas Well Other

2. Name of Operator
CONOCOPHILLIPS COMPANY
Contact: JEREMY LEE
E-Mail: Jeremy.L.Lee@cop.com

3a. Address
925 N ELDRIDGE PARKWAY
HOUSTON, TX 77079

3b. Phone No. (include area code)
Ph: 832-486-2510

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
Sec 19 T26S R32E 2487FNL 430FWL
32.028702 N Lat, 103.721657 W Lon

8. Well Name and No.
ZIA HILLS 19 FEDERAL COM 101H

9. API Well No.
30-025-44215-00-X1

10. Field and Pool or Exploratory Area
WOLFCAMP

11. County or Parish, State
LEA COUNTY, NM

JUL 03 2019

RECEIVED

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	Change to Original A PD
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

ConocoPhillips respectfully requests to change the approved drilling plan as reflected in the attached documents:

- Zia Hills 19 Fed Com 101H Kelly Cock
- Zia Hills 19 Fed Com 101H Choke Manifold
- Zia Hills 19 Fed Com 101H BOPE
- Zia Hills 19 Fed Com 101H Csg Design
- Zia Hills 19 Fed Com 101H Cement
- Zia Hills 19 Fed Com 101H Drill Plan

Carlsbad Field Office
OCD Hobbs

In particular the casing design is being modified due to availability of casing. As such we request approval at your earliest convenience.

14. I hereby certify that the foregoing is true and correct.
Electronic Submission #468145 verified by the BLM Well Information System
For CONOCOPHILLIPS COMPANY, sent to the Hobbs
Committed to AFMSS for processing by PRISCILLA PEREZ on 06/07/2019 (19PP2119SE)

Name (Printed/Typed) JEREMY LEE Title REGULATORY COORDINATOR

Signature (Electronic Submission) Date 06/07/2019

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved By LQNG VO Title PETROLEUM ENGINEER Date 06/13/2019

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office Hobbs

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

** BLM REVISED **

KZ

**PECOS DISTRICT
DRILLING CONDITIONS OF APPROVAL**

OPERATOR'S NAME:	Conocophilips Company
LEASE NO.:	NMLC062749B
WELL NAME & NO.:	101H-Zia Hills 19 Federal Com
SURFACE HOLE FOOTAGE:	2487'N & 430'W
BOTTOM HOLE FOOTAGE:	50'N & 0'W
LOCATION:	Section 19, T.26 S., R.32 E., NMPM
COUNTY:	Lea County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input type="radio"/> Medium	<input checked="" type="radio"/> High
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input type="radio"/> Multibowl	<input checked="" type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

All Previous COAs Still Apply

A. CASING

1. The 13-3/8 inch surface casing shall be set at approximately **1200 feet** (a minimum of **25 feet (Lea County)** into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

Option 1 (Single Stage):

- Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**

Option 2:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
 - b. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**
 - ❖ In High Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
3. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

B. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'

2.

Option 1:

- a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
- b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be **10,000 (10M)** psi. **Variance is approved to use a 5000 (5M) Annular which shall be tested to 5000 (5M) psi.**

Option 2:

1. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **10,000 (10M)** psi. **Variance is approved to use a 5000 (5M) Annular which shall be tested to 5000 (5M) psi.**
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

C. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.

- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Chaves and Roosevelt Counties
Call the Roswell Field Office, 2909 West Second St., Roswell NM 88201.
During office hours call (575) 627-0272.
After office hours call (575)

Eddy County
Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

Lea County
Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the

plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time.
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

Zia Hills 19 101H

Sec 19 T26S R32E

Lea, Co, NM

6/5/2019

SURFACE CASING DESIGN INFORMATION

Setting Depth: [REDACTED] [REDACTED]

PIPE BODY DIMENSIONAL / PERFORMANCE DATA:

SIZE (Inches)	WEIGHT (LB/FT)	GRADE	CPLG TYPE	BORE ID (Inches)	DRIFT ID (Inches)	COLLAPSE (PSI) API / CoP	BURST (PSI) API / CoP	TENSION (1k LBS) API / CoP
[REDACTED]	[REDACTED]	[REDACTED]	[REDACTED]	12.612	12.459	1,130 / 960	2,730 / 2,320	909 / 772

Surface Casing Test Pressure = 1,500 psi
Pressure Test Prior to Drill Out

CONNECTION DIMENSIONAL / PERFORMANCE DATA:

OD (Inches)	ID (Inches)	DRIFT (Inches)	CPLG TYPE	COLLAPSE (PSI) API / CoP	BURST (PSI) API / CoP	TENSION (1k LBS) API / CoP
14.375	12.612	12.459	BTC	1,130 / 960	2,730 / 2,320	909 / 772

Minimum Design / Safety Factors COP

Burst	Collapse	Tension (Body & Connection)
1.15	1.05	1.40

Actual Design / Safety Factors

Burst	Collapse	Tension (Body)	
5.22	3.23	14.27	Dry
		18.42	Bouyed

INTERMEDIATE CASING DESIGN INFORMATION

Setting Depth: [REDACTED] [REDACTED]

PIPE BODY DIMENSIONAL / PERFORMANCE DATA:

SIZE (Inches)	WEIGHT (LB/FT)	GRADE	CPLG TYPE	BORE ID (Inches)	DRIFT ID (Inches)	COLLAPSE (PSI) API / CoP	BURST (PSI) API / CoP	TENSION (1k LBS) API / CoP
[REDACTED]	[REDACTED]	[REDACTED]	[REDACTED]	8.835	8.75	3,870 / 3,685	5,750 / 5000	916 / 654

Production Casing Test Pressure = TBD

Minimum Design / Safety Factors

Burst	Collapse	Tension (Body & Connection)
1.15	1.05	1.40

Actual Design / Safety Factors

Burst	Collapse	Tension (Body)	
1.67	2.52	1.89	Dry
		2.21	Bouyed

PRODUCTION CASING DESIGN INFORMATION

Setting Depth: [REDACTED] [REDACTED]

PIPE BODY DIMENSIONAL / PERFORMANCE DATA:

SIZE (Inches)	WEIGHT (LB/FT)	GRADE	CPLG TYPE	BORE ID (Inches)	DRIFT ID (Inches)	COLLAPSE (PSI) API / CoP	BURST (PSI) API / CoP	TENSION (1k LBS) API / CoP
[REDACTED]	[REDACTED]	[REDACTED]	[REDACTED]	4.778	[REDACTED]	12,100 / 11,524	14,360 / 12,487	728 / 521

Production Casing Test Pressure = TBD

Minimum Design / Safety Factors

Burst	Collapse	Tension (Body & Connection)
1.15	1.05	1.40

Actual Design / Safety Factors

Burst	Collapse	Tension (Body)	
2.44	3.83	3.11	Dry
		3.92	Bouyed

-High Cave

Za Hls 19 101H
Sec 19 T283 R32E

Surface Casing Depth (Ft)	1,189	Production Casing O.D. (In.)	9.625
Surface Casing O.D. (In.)	13.378	Production Casing ID (In.)	8.835
Surface Casing ID (In.)	12.812	Hole O.D. (In.)	12.25
Hole O.D. (In.)	17.12	Excess (%)	70%
Excess (%)	30%	KOP	
Yield Lead (Cu. Ft./Sq)	1.73	Yield Lead (Cu. Ft./Sq)	2.7
Shoe Joint (Ft)	40	Calculated Total Lead (Cu. Ft.)	2,856
Shoe Volume (Cu. Ft)	34.7	Lead Volume (bbbls)	
Tail End of cement	400		
Calculated Total Volume (Cu. Ft.)	2,471		
Calc. Tail Volume (Cu. Ft.)	868		
Calc. Lead Volume (Cu. Ft.)	1,603		
Lead Volume (bbbls)	285.4		
Tail volume (bbbls)	154.6		
Displacement Volume (bbbls)	174.5		

Lead Cement Description:
Mix Weight 12.6 ppg
Control Set 'C'
1.0% CaCl₂
1.0% SMC
1.0% OIG-80
1/4 lb/sk Polybata
1/4 ppb FiberBlock

Tail Cement Description:
Mix Weight 14.8 ppg
0.10 Type III
0.5% CaCl₂
1/4 lb/sk Polybata
1/4 ppb FiberBlock

Intermediate Lead Cement Description:
Mix Weight 11 ppg
WBL
0.5% CFL-4
0.8% LTR
0.2% SPC-II
0.4% CDF-4P
1/4 lb/sk Polybata
1/4 ppb FiberBlock

Intermediate Tail Cement Description:
Mix Weight 13.2 ppg
Thermal 35
10% NaCl
0.8% CFR
0.7% CFL-4
0.1% LTR
0.2% SPC-II
0.4% CDF-4P
1/4 lb/sk Polybata
1/4 ppb FiberBlock

12,243'	Production Casing O.D. (In.)	9.625
8,835	Production Casing ID (In.)	8.835
12,225	Hole O.D. (In.)	12.25
30%	Excess (%)	
11,016'	KOP	
10,516'	Top Tail (Ft) - 1000' above KOP	
1.59	Yield Tail (Cu. Ft./Sq)	
90	Shoe Joint (Ft)	
38.3	Shoe Volume (Cu. Ft)	
741	Calc. Tail Volume (Cu. Ft.)	
	Tail Volume (cu. ft.)	
	Displacement Volume (bbbls)	
	Tail Volume (bbbls)	
	Displacement Volume (bbbls)	

Intermediate Tail Cement Description:
Mix Weight ppg
Thermal 35
10% NaCl
0.8% CFR
0.7% CFL-4
0.1% LTR
0.2% SPC-II
0.4% CDF-4P
1/4 lb/sk Polybata
1/4 ppb FiberBlock


1,169	Production Casing Depth (Ft)	12,243'
12,612	Production Casing O.D. (In.)	9,625
8,835	Production Casing ID (In.)	8,835
12,225	Production Casing Top Depth (Ft)	10,016'
8,835	Production Casing ID (In.)	19,303'
12,225	Production Casing O.D. (In.)	5,500
200%	Production Casing ID (In.)	4,778
	Hole O.D. (In.)	8,50
	Excess (%)	10%
	Yield Tail (Cu. Ft./Sq)	1.19
	Shoe Joint (Ft)	12
	Shoe Volume (Cu. Ft)	1.5
	Calc. Tail Volume (Cu. Ft.)	2,359
	Tail Volume (bbbls)	420,2508136
	Displacement Volume (bbbls)	

Production Liner Tail Cement Description:
Mix Weight 15.8 ppg
1:1.0 Poz-Latarg G
20% Silica Flour
8% Silica Fume
2% FWCA-1 (FWC-2)
0.3% HTR
0.5% CR-4 (MCR-4)
1% TAE-1 (SEA-1)
1% CFL-4
0.2% CFR-6
0.3% ASM-3 (AS-3)

Production Displacement

Volume to Latch down collar +4, 15 BBLS (net shoe track)			
Component	Capacity	Length	Volume
Drill Pipe	0108 bbls	0	0
Liner (Liner top to Float Collar)	0149382/0	0	0
Total			0

the IBOP valves




**Lower Kelly Cock and Upper Kelly
Cock function are performed by
Upper IBOP (inside BOP) and Lower
IBOP in Top Drive**

Open
↑
↓
Close

Upper
IBOP Crank
(Remote)

Lower IBOP
(Manual)

Choke Manifold 10M psi



NO.	DESCRIPTION	QTY.	UNIT
1	CAST IRON VALVE 1/2" x 1/2"	1	PC
2	CAST IRON VALVE 3/4" x 3/4"	1	PC
3	CAST IRON VALVE 1" x 1"	1	PC
4	STANDARD BALL BEARING 1/2" x 1/2" x 1/2"	1	PC
5	STANDARD BALL BEARING 3/4" x 3/4" x 3/4"	1	PC
6	STANDARD BALL BEARING 1" x 1" x 1"	1	PC
7	STANDARD BALL BEARING 1 1/2" x 1 1/2" x 1 1/2"	1	PC
8	STANDARD BALL BEARING 2" x 2" x 2"	1	PC
9	STANDARD BALL BEARING 2 1/2" x 2 1/2" x 2 1/2"	1	PC
10	STANDARD BALL BEARING 3" x 3" x 3"	1	PC
11	STANDARD BALL BEARING 3 1/2" x 3 1/2" x 3 1/2"	1	PC
12	STANDARD BALL BEARING 4" x 4" x 4"	1	PC
13	STANDARD BALL BEARING 4 1/2" x 4 1/2" x 4 1/2"	1	PC
14	STANDARD BALL BEARING 5" x 5" x 5"	1	PC
15	STANDARD BALL BEARING 5 1/2" x 5 1/2" x 5 1/2"	1	PC
16	STANDARD BALL BEARING 6" x 6" x 6"	1	PC
17	STANDARD BALL BEARING 6 1/2" x 6 1/2" x 6 1/2"	1	PC
18	STANDARD BALL BEARING 7" x 7" x 7"	1	PC
19	STANDARD BALL BEARING 7 1/2" x 7 1/2" x 7 1/2"	1	PC
20	STANDARD BALL BEARING 8" x 8" x 8"	1	PC
21	STANDARD BALL BEARING 8 1/2" x 8 1/2" x 8 1/2"	1	PC
22	STANDARD BALL BEARING 9" x 9" x 9"	1	PC
23	STANDARD BALL BEARING 9 1/2" x 9 1/2" x 9 1/2"	1	PC
24	STANDARD BALL BEARING 10" x 10" x 10"	1	PC
25	STANDARD BALL BEARING 10 1/2" x 10 1/2" x 10 1/2"	1	PC
26	STANDARD BALL BEARING 11" x 11" x 11"	1	PC
27	STANDARD BALL BEARING 11 1/2" x 11 1/2" x 11 1/2"	1	PC
28	STANDARD BALL BEARING 12" x 12" x 12"	1	PC
29	STANDARD BALL BEARING 12 1/2" x 12 1/2" x 12 1/2"	1	PC
30	STANDARD BALL BEARING 13" x 13" x 13"	1	PC
31	STANDARD BALL BEARING 13 1/2" x 13 1/2" x 13 1/2"	1	PC
32	STANDARD BALL BEARING 14" x 14" x 14"	1	PC
33	STANDARD BALL BEARING 14 1/2" x 14 1/2" x 14 1/2"	1	PC
34	STANDARD BALL BEARING 15" x 15" x 15"	1	PC
35	STANDARD BALL BEARING 15 1/2" x 15 1/2" x 15 1/2"	1	PC
36	STANDARD BALL BEARING 16" x 16" x 16"	1	PC
37	STANDARD BALL BEARING 16 1/2" x 16 1/2" x 16 1/2"	1	PC
38	STANDARD BALL BEARING 17" x 17" x 17"	1	PC
39	STANDARD BALL BEARING 17 1/2" x 17 1/2" x 17 1/2"	1	PC
40	STANDARD BALL BEARING 18" x 18" x 18"	1	PC
41	STANDARD BALL BEARING 18 1/2" x 18 1/2" x 18 1/2"	1	PC
42	STANDARD BALL BEARING 19" x 19" x 19"	1	PC
43	STANDARD BALL BEARING 19 1/2" x 19 1/2" x 19 1/2"	1	PC
44	STANDARD BALL BEARING 20" x 20" x 20"	1	PC
45	STANDARD BALL BEARING 20 1/2" x 20 1/2" x 20 1/2"	1	PC
46	STANDARD BALL BEARING 21" x 21" x 21"	1	PC
47	STANDARD BALL BEARING 21 1/2" x 21 1/2" x 21 1/2"	1	PC
48	STANDARD BALL BEARING 22" x 22" x 22"	1	PC
49	STANDARD BALL BEARING 22 1/2" x 22 1/2" x 22 1/2"	1	PC
50	STANDARD BALL BEARING 23" x 23" x 23"	1	PC
51	STANDARD BALL BEARING 23 1/2" x 23 1/2" x 23 1/2"	1	PC
52	STANDARD BALL BEARING 24" x 24" x 24"	1	PC
53	STANDARD BALL BEARING 24 1/2" x 24 1/2" x 24 1/2"	1	PC
54	STANDARD BALL BEARING 25" x 25" x 25"	1	PC
55	STANDARD BALL BEARING 25 1/2" x 25 1/2" x 25 1/2"	1	PC
56	STANDARD BALL BEARING 26" x 26" x 26"	1	PC
57	STANDARD BALL BEARING 26 1/2" x 26 1/2" x 26 1/2"	1	PC
58	STANDARD BALL BEARING 27" x 27" x 27"	1	PC
59	STANDARD BALL BEARING 27 1/2" x 27 1/2" x 27 1/2"	1	PC
60	STANDARD BALL BEARING 28" x 28" x 28"	1	PC
61	STANDARD BALL BEARING 28 1/2" x 28 1/2" x 28 1/2"	1	PC
62	STANDARD BALL BEARING 29" x 29" x 29"	1	PC
63	STANDARD BALL BEARING 29 1/2" x 29 1/2" x 29 1/2"	1	PC
64	STANDARD BALL BEARING 30" x 30" x 30"	1	PC
65	STANDARD BALL BEARING 30 1/2" x 30 1/2" x 30 1/2"	1	PC
66	STANDARD BALL BEARING 31" x 31" x 31"	1	PC
67	STANDARD BALL BEARING 31 1/2" x 31 1/2" x 31 1/2"	1	PC
68	STANDARD BALL BEARING 32" x 32" x 32"	1	PC
69	STANDARD BALL BEARING 32 1/2" x 32 1/2" x 32 1/2"	1	PC
70	STANDARD BALL BEARING 33" x 33" x 33"	1	PC
71	STANDARD BALL BEARING 33 1/2" x 33 1/2" x 33 1/2"	1	PC
72	STANDARD BALL BEARING 34" x 34" x 34"	1	PC
73	STANDARD BALL BEARING 34 1/2" x 34 1/2" x 34 1/2"	1	PC
74	STANDARD BALL BEARING 35" x 35" x 35"	1	PC
75	STANDARD BALL BEARING 35 1/2" x 35 1/2" x 35 1/2"	1	PC
76	STANDARD BALL BEARING 36" x 36" x 36"	1	PC
77	STANDARD BALL BEARING 36 1/2" x 36 1/2" x 36 1/2"	1	PC
78	STANDARD BALL BEARING 37" x 37" x 37"	1	PC
79	STANDARD BALL BEARING 37 1/2" x 37 1/2" x 37 1/2"	1	PC
80	STANDARD BALL BEARING 38" x 38" x 38"	1	PC
81	STANDARD BALL BEARING 38 1/2" x 38 1/2" x 38 1/2"	1	PC
82	STANDARD BALL BEARING 39" x 39" x 39"	1	PC
83	STANDARD BALL BEARING 39 1/2" x 39 1/2" x 39 1/2"	1	PC
84	STANDARD BALL BEARING 40" x 40" x 40"	1	PC
85	STANDARD BALL BEARING 40 1/2" x 40 1/2" x 40 1/2"	1	PC
86	STANDARD BALL BEARING 41" x 41" x 41"	1	PC
87	STANDARD BALL BEARING 41 1/2" x 41 1/2" x 41 1/2"	1	PC
88	STANDARD BALL BEARING 42" x 42" x 42"	1	PC
89	STANDARD BALL BEARING 42 1/2" x 42 1/2" x 42 1/2"	1	PC
90	STANDARD BALL BEARING 43" x 43" x 43"	1	PC
91	STANDARD BALL BEARING 43 1/2" x 43 1/2" x 43 1/2"	1	PC
92	STANDARD BALL BEARING 44" x 44" x 44"	1	PC
93	STANDARD BALL BEARING 44 1/2" x 44 1/2" x 44 1/2"	1	PC
94	STANDARD BALL BEARING 45" x 45" x 45"	1	PC
95	STANDARD BALL BEARING 45 1/2" x 45 1/2" x 45 1/2"	1	PC
96	STANDARD BALL BEARING 46" x 46" x 46"	1	PC
97	STANDARD BALL BEARING 46 1/2" x 46 1/2" x 46 1/2"	1	PC
98	STANDARD BALL BEARING 47" x 47" x 47"	1	PC
99	STANDARD BALL BEARING 47 1/2" x 47 1/2" x 47 1/2"	1	PC
100	STANDARD BALL BEARING 48" x 48" x 48"	1	PC
101	STANDARD BALL BEARING 48 1/2" x 48 1/2" x 48 1/2"	1	PC
102	STANDARD BALL BEARING 49" x 49" x 49"	1	PC
103	STANDARD BALL BEARING 49 1/2" x 49 1/2" x 49 1/2"	1	PC
104	STANDARD BALL BEARING 50" x 50" x 50"	1	PC
105	STANDARD BALL BEARING 50 1/2" x 50 1/2" x 50 1/2"	1	PC
106	STANDARD BALL BEARING 51" x 51" x 51"	1	PC
107	STANDARD BALL BEARING 51 1/2" x 51 1/2" x 51 1/2"	1	PC
108	STANDARD BALL BEARING 52" x 52" x 52"	1	PC
109	STANDARD BALL BEARING 52 1/2" x 52 1/2" x 52 1/2"	1	PC
110	STANDARD BALL BEARING 53" x 53" x 53"	1	PC
111	STANDARD BALL BEARING 53 1/2" x 53 1/2" x 53 1/2"	1	PC
112	STANDARD BALL BEARING 54" x 54" x 54"	1	PC
113	STANDARD BALL BEARING 54 1/2" x 54 1/2" x 54 1/2"	1	PC
114	STANDARD BALL BEARING 55" x 55" x 55"	1	PC
115	STANDARD BALL BEARING 55 1/2" x 55 1/2" x 55 1/2"	1	PC
116	STANDARD BALL BEARING 56" x 56" x 56"	1	PC
117	STANDARD BALL BEARING 56 1/2" x 56 1/2" x 56 1/2"	1	PC
118	STANDARD BALL BEARING 57" x 57" x 57"	1	PC
119	STANDARD BALL BEARING 57 1/2" x 57 1/2" x 57 1/2"	1	PC
120	STANDARD BALL BEARING 58" x 58" x 58"	1	PC
121	STANDARD BALL BEARING 58 1/2" x 58 1/2" x 58 1/2"	1	PC
122	STANDARD BALL BEARING 59" x 59" x 59"	1	PC
123	STANDARD BALL BEARING 59 1/2" x 59 1/2" x 59 1/2"	1	PC
124	STANDARD BALL BEARING 60" x 60" x 60"	1	PC
125	STANDARD BALL BEARING 60 1/2" x 60 1/2" x 60 1/2"	1	PC
126	STANDARD BALL BEARING 61" x 61" x 61"	1	PC
127	STANDARD BALL BEARING 61 1/2" x 61 1/2" x 61 1/2"	1	PC
128	STANDARD BALL BEARING 62" x 62" x 62"	1	PC
129	STANDARD BALL BEARING 62 1/2" x 62 1/2" x 62 1/2"	1	PC
130	STANDARD BALL BEARING 63" x 63" x 63"	1	PC
131	STANDARD BALL BEARING 63 1/2" x 63 1/2" x 63 1/2"	1	PC
132	STANDARD BALL BEARING 64" x 64" x 64"	1	PC
133	STANDARD BALL BEARING 64 1/2" x 64 1/2" x 64 1/2"	1	PC
134	STANDARD BALL BEARING 65" x 65" x 65"	1	PC
135	STANDARD BALL BEARING 65 1/2" x 65 1/2" x 65 1/2"	1	PC
136	STANDARD BALL BEARING 66" x 66" x 66"	1	PC
137	STANDARD BALL BEARING 66 1/2" x 66 1/2" x 66 1/2"	1	PC
138	STANDARD BALL BEARING 67" x 67" x 67"	1	PC
139	STANDARD BALL BEARING 67 1/2" x 67 1/2" x 67 1/2"	1	PC
140	STANDARD BALL BEARING 68" x 68" x 68"	1	PC
141	STANDARD BALL BEARING 68 1/2" x 68 1/2" x 68 1/2"	1	PC
142	STANDARD BALL BEARING 69" x 69" x 69"	1	PC
143	STANDARD BALL BEARING 69 1/2" x 69 1/2" x 69 1/2"	1	PC
144	STANDARD BALL BEARING 70" x 70" x 70"	1	PC
145	STANDARD BALL BEARING 70 1/2" x 70 1/2" x 70 1/2"	1	PC
146	STANDARD BALL BEARING 71" x 71" x 71"	1	PC
147	STANDARD BALL BEARING 71 1/2" x 71 1/2" x 71 1/2"	1	PC
148	STANDARD BALL BEARING 72" x 72" x 72"	1	PC
149	STANDARD BALL BEARING 72 1/2" x 72 1/2" x 72 1/2"	1	PC
150	STANDARD BALL BEARING 73" x 73" x 73"	1	PC
151	STANDARD BALL BEARING 73 1/2" x 73 1/2" x 73 1/2"	1	PC
152	STANDARD BALL BEARING 74" x 74" x 74"	1	PC
153	STANDARD BALL BEARING 74 1/2" x 74 1/2" x 74 1/2"	1	PC
154	STANDARD BALL BEARING 75" x 75" x 75"	1	PC
155	STANDARD BALL BEARING 75 1/2" x 75 1/2" x 75 1/2"	1	PC
156	STANDARD BALL BEARING 76" x 76" x 76"	1	PC
157	STANDARD BALL BEARING 76 1/2" x 76 1/2" x 76 1/2"	1	PC
158	STANDARD BALL BEARING 77" x 77" x 77"	1	PC
159	STANDARD BALL BEARING 77 1/2" x 77 1/2" x 77 1/2"	1	PC
160	STANDARD BALL BEARING 78" x 78" x 78"	1	PC
161	STANDARD BALL BEARING 78 1/2" x 78 1/2" x 78 1/2"	1	PC
162	STANDARD BALL BEARING 79" x 79" x 79"	1	PC
163	STANDARD BALL BEARING 79 1/2" x 79 1/2" x 79 1/2"	1	PC
164	STANDARD BALL BEARING 80" x 80" x 80"	1	PC
165	STANDARD BALL BEARING 80 1/2" x 80 1/2" x 80 1/2"	1	PC
166	STANDARD BALL BEARING 81" x 81" x 81"	1	PC
167	STANDARD BALL BEARING 81 1/2" x 81 1/2" x 81 1/2"	1	PC
168	STANDARD BALL BEARING 82" x 82" x 82"	1	PC
169	STANDARD BALL BEARING 82 1/2" x 82 1/2" x 82 1/2"	1	PC
170	STANDARD BALL BEARING 83" x 83" x 83"	1	PC
171	STANDARD BALL BEARING 83 1/2" x 83 1/2" x 83 1/2"	1	PC
172	STANDARD BALL BEARING 84" x 84" x 84"	1	PC
173	STANDARD BALL BEARING 84 1/2" x 84 1/2" x 84 1/2"	1	PC
174	STANDARD BALL BEARING 85" x 85" x 85"	1	PC
175	STANDARD BALL BEARING 85 1/2" x 85 1/2" x 85 1/2"	1	PC
176	STANDARD BALL BEARING 86" x 86" x 86"	1	PC
177	STANDARD BALL BEARING 86 1/2" x 86 1/2" x 86 1/2"	1	PC
178	STANDARD BALL BEARING 87" x 87" x 87"	1	PC
179	STANDARD BALL BEARING 87 1/2" x 87 1/2" x 87 1/2"	1	PC
180	STANDARD BALL BEARING 88" x 88" x 88"	1	PC
181	STANDARD BALL BEARING 88 1/2" x 88 1/2" x 88 1/2"	1	PC
182	STANDARD BALL BEARING 89" x 89" x 89"	1	PC
183	STANDARD BALL BEARING 89 1/2" x 89 1/2" x 89 1/2"	1	PC
184	STANDARD BALL BEARING 90" x 90" x 90"	1	PC
185	STANDARD BALL BEARING 90 1/2" x 90 1/2" x 90 1/2"	1	PC
186	STANDARD BALL BEARING 91" x 91" x 91"	1	PC
187	STANDARD BALL BEARING 91 1/2" x 91 1/2" x 91 1/2"	1	PC
188	STANDARD BALL BEARING 92" x 92" x 92"	1	PC
189	STANDARD BALL BEARING 92 1/2" x 92 1/2" x 92 1/2"	1	PC
190	STANDARD BALL BEARING 93" x 93" x 93"	1	PC
191	STANDARD BALL BEARING 93 1/2" x 93 1/2" x 93 1/2"	1	PC
192	STANDARD BALL BEARING 94" x 94" x 94"	1	PC
193	STANDARD BALL BEARING 94 1/2" x 94 1/2" x 94 1/2"	1	PC
194	STANDARD BALL BEARING 95" x 95" x 95"	1	PC
195	STANDARD BALL BEARING 95 1/2" x 95 1/2" x 95 1/2"	1	PC
196	STANDARD BALL BEARING 96" x 96" x 96"	1	PC
197	STANDARD BALL BEARING 96 1/2" x 96 1/2" x 96 1/2"	1	PC
198	STANDARD BALL BEARING 97" x 97" x 97"	1	PC
199	STANDARD BALL BEARING 97 1/2" x 97 1/2" x 97 1/2"	1	PC
200	STANDARD BALL BEARING 98" x 98" x 98"	1	PC
201	STANDARD BALL BEARING 98 1/2" x 98 1/2" x 98 1/2"	1	PC
202	STANDARD BALL BEARING 99" x 99" x 99"	1	PC
203	STANDARD BALL BEARING 99 1/2" x 99 1/2" x 99 1/2"	1	PC
204	STANDARD BALL BEARING 100" x 100" x 100"	1	PC
205	STANDARD BALL BEARING 100 1/2" x 100 1/2" x 100 1/2"	1	PC
206	STANDARD BALL BEARING 101" x 101" x 101"	1	PC
207	STANDARD BALL BEARING 101 1/2" x 101 1/2" x 101 1/2"	1	PC
208	STANDARD BALL BEARING 102" x 102" x 102"	1	PC
209	STANDARD BALL BEARING 102 1/2" x 102 1/2" x 102 1/2"	1	PC
210	STANDARD BALL BEARING 103" x 103" x 103"	1	PC
211	STANDARD BALL BEARING 103 1/2" x 103 1/2" x 103 1/2"	1	PC
212	STANDARD BALL BEARING 104" x 104" x 104"	1	PC
213	STANDARD BALL BEARING 104 1/2" x 104 1/2" x 104 1/2"	1	PC
214	STANDARD BALL BEARING 105" x 105" x 105"	1	PC
215	STANDARD BALL BEARING 105 1/2" x 105 1/2" x 105 1/2"	1	PC
216	STANDARD BALL BEARING 106" x 106" x 106"	1	PC
217	STANDARD BALL BEARING 106 1/2" x 106 1/2" x 106 1/2"	1	PC
218	STANDARD BALL BEARING 107" x 107" x 107"	1	PC
219	STANDARD BALL BEARING 107 1/2" x 107 1/2" x 107 1/2"	1	PC
220	STANDARD BALL BEARING 108" x 108" x 108"	1	PC
221	STANDARD BALL BEARING 108 1/2" x 108 1/2" x 108 1/2"	1	PC
222	STANDARD BALL BEARING 109" x 109" x 109"	1	PC
223	STANDARD BALL BEARING 109 1/2" x 109 1/2" x 109 1/2"	1	PC
224	STANDARD BALL BEARING 110" x 110" x 110"	1	PC
225	STANDARD BALL BEARING 110 1/2" x 110 1/2" x 110 1/2"	1	PC
226	STANDARD BALL BEARING 111" x 111" x 111"	1	PC
2			

BOPE Configuration & Specifications
13-5/8" x 10,000 psi System

Rotating Head (w/ fill up line)
 13-5/8" x 10k psi

Annular Preventer
 13-5/8" x 5k psi

Pipe Ram
 13-5/8" x 10k psi


Blind Ram
 13-5/8" x 10k psi

Kill Line 2-1/16" x 10k Chicksan
 (2) 2-1/16" x 10k Gate Valves
 Outer Check Valve

Pipe Ram
 13-5/8" x 10k psi

Spacer Spool
 13-5/8" x 10k psi

Casing Head
 13-5/8" x 10k psi



Choke Line 6" x 3" x 10k psi
 4-1/16" x 10k psi Inner Manual Valve
 4 - 1/16" x 10k psi Outer Remote HCR

2" x 5k psi Gate Valves
 Pressure Testing Lines

ConocoPhillips Wild Well Control Plan

Zia Hills 19 Federal Com 101H-104H

1. DRILLING WELL CONTROL PLAN

1.1 WELL CONTROL - CERTIFICATIONS

Required IADC/IWCF Well Control Certifications Supervisor Level:

Any personnel who supervises or operates the BOP must possess a valid current IADC training certification and photo identification. This would include the onsite drilling supervisor, tool pusher/rig manager, driller, and any personnel that will be acting in these capacities. Another example of this may be a wireline or snubbing crew rigged up on the rig to assist the rig, the operator of each system must also have a valid control certification for their level of operation.

BLM recognizes IADC training as the industry approved accredited training. Online self-certifications will not be acceptable. Enforcement actions for the lack of a valid Supervisory Level certificate shall be prompt action to correct the deficiency. **Enforcement actions include but are not limited to immediate replacement of personnel lacking certifications, drilling operations being shut down or installment of a 10M annular.**

IADC Driller Level for all Drillers and general knowledge for the Assistant Driller, Derrick Hands, Floor Hands and Motor Hands is recognized by the BLM; however, a Driller Level certification will need to be presented only if acting in a temporary Driller Level certification capacity.

Well Control-Position/Roles

IADC Well control training and certification is targeted toward each role, e.g., Supervisor Level toward those who direct, Driller Level to those who act, Introductory to those who need to know.

- **Supervisor Level**
 - Specifies and has oversight that the correct actions are carried out
 - Role is to supervise well control equipment, training, testing, and well control events
 - Directs the testing of BOP and other well control equipment
 - Regularly direct well control crew drills
 - Land based rigs – usually runs the choke during a well kill operation
 - Due to role on the rig, training and certification is targeted more toward management of well control and managing an influx out of the well

- **Driller Level**
 - Performs an action to prevent or respond to well control accident
 - Role is to monitor the well via electronic devices while drilling and detect unplanned influxes
 - Assist with the testing of BOP and other well control equipment
 - Regularly assist with well control crew drills
 - When influx is detected, responsible to close the BOP
 - Due to role on the rig, training and certification is targeted more toward monitoring and shutting the well in (closing the BOP) when an influx is detected

(Well Control-Positions/Roles Continued)

- **Derrick Hand, Assistant Driller Introductory Level**
 - Role is to assist Driller with kick detection by physically monitoring the well at the mixing pits/tanks
 - Regularly record mud weights/viscosity for analysis by the Supervisor level and mud engineer so pre-influx signs can be detected
 - Mix required kill fluids as directed by Supervisor or Driller
 - Due to role on the rig, training and certification is targeted more toward monitoring for influxes, either via mud samples or visual signs on the pits/tanks

- **Motorman, Floor Hand Introductory Level**
 - Role is to assist the Supervisor, Driller, or Derrick Hand with detecting influxes
 - Be certain all valves are aligned for proper well control as directed by Supervisor
 - Perform Supervisor or Driller assigned tasks during a well control event
 - Due to role on the rig, training and certification is targeted more toward monitoring for influxes

1.2 WELL CONTROL-COMPONENT AND PREVENTER COMPATIBILITY CHECKLIST

The table below, which covers the drilling and casing of the 10M Stack portion of the well, outlines the tubulars and the compatible preventers in use. This table, combined with the mud program, documents that two barriers to flow can be maintained at all times, independent of the rating of the annular preventer.

- **Example 8-3/4" Production hole section, 10M requirement**

Component	OD	Preventer	RWP
Drill pipe	5"	Fixed lower 5" Upper 4.5-7" VBR	10M
HWDP	5"	Fixed lower 5" Upper 4.5-7" VBR	10M
Drill collars and MWD tools	6.25-6.75"	Upper 4.5-7" VBR	10M
Mud Motor	6.75"	Upper 4.5-7" VBR	10M
Production casing	5.5"	Upper 4.5-7" VBR	10M
ALL	0-13-5/8"	Annular	5M
Open-hole	-	Blind Rams	10M

- VBR = Variable Bore Ram. Compatible range listed in chart.

1.3 WELL CONTROL-BOP TESTING

BOP Test will be completed per Onshore Oil and Gas Order #2 Well Control requirements. The 5M Annular Preventer on a required 10M BOP stack will be tested to 70 % of rated working pressure including a 10 minute low pressure test. Pressure shall be maintained at least 10 minutes.

1.4 WELL CONTROL - DRILLS

The following drills are conducted and recorded in the Daily Drilling Report and the Contractor's reporting system while engaged in drilling operations:

Type	Frequency	Objective	Comments
Shallow gas kick drill - drilling	Once per well with crew on tour	Response training to a shallow gas influx	To be done prior to drilling surface hole if shallow gas is noted
Kick drill - drilling	Once per week per crew	Response training to an influx while drilling (bit on bottom)	Only one kick drill per week per crew is required, alternating between drilling and tripping.
Kick drill - tripping	Once per week per crew	Response training to an influx while tripping (bit off bottom). Practice stabbing TIW valve	
Choke drill	Once per well with crew on tour	Practice in operating the remotely operated choke with pressure in the well	Before drilling out of the last casing set above a prospective reservoir Include the scenario of flowing well with gas on drill floor as a table top
H ₂ S drill	Prior to drilling into a potential H ₂ S zone/reservoir	Practice in use of respiratory equipment	

1.5 WELL CONTROL – MONITORING

- Drilling operations which utilize static fluid levels in the wellbore as the active barrier element, a means of accurately monitoring fill-up and displacement volumes during trips are available to the driller and operator. A recirculating trip tank is installed and equipped with a volume indicator easily read from the driller's / operator's position. This data is recorded on a calibrated chart recorder or digitally. The actual volumes are compared to the calculated volumes.
- The On-Site Supervisor ensures hole-filling and pit monitoring procedures are established and documented for every rig operation.
- The well is kept full of fluid with a known density and monitored at all times even when out of the hole.
- Flow checks are a minimum of 15 minutes.
- A flow check is made:
 - In the event of a drilling break.
 - After indications of down hole gains or losses.
 - Prior to all trips out of the hole.
 - After pulling into the casing shoe.
 - Before the BHA enters the BOP stack.
 - If trip displacement is incorrect.

Well Control-Monitoring (Continued)

- Prior to dropping a survey instrument.
- Prior to dropping a core ball.
- After a well kill operation.
- When the mud density is reduced in the well.
- Flow checks may be made at any time at the sole discretion of the driller or his designate. The Onsite Supervisor ensures that personnel are aware of this authority and the authority to close the well in immediately without further consultation.
- Record slow circulating rates (SCR) after each crew change, bit trip, and 500' of new hole drilled and after any variance greater than 0.2 ppg in MW. Slow pump rate recordings should include return flow percent, TVD, MD & pressure. SCR's will be done on all pumps at 30, 40 & 50 SPM. Pressures will be recorded at the choke panel. SCR will be recorded in the IADC daily report and MRO Wellview daily report
- Drilling blind (i.e. without returns) is permissible only in known lithology where the absence of hydrocarbons has been predetermined and written approval of the Drilling Manager.
- All open hole logs to be run with pack-off, lubricator or Drilling Manager approved alternative means.
- The Drilling Contractor has a fully working pit level totalizer / monitoring system with read out for the driller and an audible alarm set to 10 BBL gain / loss volume. Systems are selectable to enable monitoring of all pits in use. Pit volumes are monitored at all times, especially when transferring fluids. Both systems data is recorded on a calibrated chart recorder or electronically.
- The Drilling Contractor has a fully working return mud flow indicator with drillers display and an audible alarm, and is adjustable to record any variance in return volumes.

1.6 WELL CONTROL – SHUT IN

- The "hard shut in" method (i.e. against a closed choke using either an annular or ram type preventer) is the Company standard.
- The HCR(s) or failsafe valves are left closed during drilling to prevent any erosion and buildup of solids. The adjustable choke should also be left closed.
- The rig specific shut in procedure, the BOP configuration along with space-out position for the tool joints is posted in the Driller's control cabin or doghouse.
- No well kill operation commences until there is a plan agreed by the Superintendent, On-Site Supervisor and the Drilling Manager.
- During a well kill by circulation, constant bottom hole pressure is maintained throughout.
- Kill sheets are maintained by the Driller and posted in the Driller's control cabin or doghouse. The sheet is updated at a minimum every 500 feet.

2. SHUT-IN PROCEDURES:

2.1 PROCEDURE WHILE DRILLING

- Sound alarm (alert crew)
- Space out drill string – Stop rotating, pick the drill string up off bottom, and space out to ensure no tool joint is located in the BOP element selected for initial closure.
- Shut down pumps (stop pumps and observe well.)
- Shut-in Well - If flow is suspected or confirmed, close uppermost applicable BOP element. (HCR and choke will already be in the closed position.)
 - **Note:** Either the uppermost pipe ram or annular preventer can be used.
- Confirm shut-in
- Notify toolpusher/company representative
- Gather all relevant data required:
 - SIDPP and SICP
 - Hole Depth and Hole TVD
 - Pit gain
 - Time
 - Kick Volume
 - Pipe depth
 - MW in, MW out
 - SPR's (Slow Pump Rate's)
- Regroup and identify forward plan (let well stabilize, update kill sheet, inventory mud additives and mud volumes on location)
- Company Representative, Drilling Superintendent, Drilling Engineer and Drilling Manager will discuss well control kill method to be utilized. A verbal Risk Assessment and preferred kill method will be finalized. Initial Risk Assessment will be finalized within 1 hour of initial shut in.
- No well kill operation commences until there is a plan agreed by the Superintendent, On-Site Supervisor and the Drilling Contractor PIC.
- Recheck all pressures and fluid volume on accumulator unit
- If pressure has built or is anticipated during the kill to reach 2,500 psi or greater, the annular preventer CANNOT be used as per Oil Company Well Control Policy, swap to the upper BOP pipe ram.

2.2 PROCEDURE WHILE TRIPPING

- Sound alarm (alert crew)
- Stab full opening safety valve in the drill string and close.
- Space out drill string (ensure no tool joint is located in the BOP element selected for initial closure).
- Shut down pumps (stop pumps and observe well.)
- Shut-in Well - If flow is suspected or confirmed, close uppermost applicable BOP element. (HCR and choke will already be in the closed position.)
 - **Note:** Either the uppermost pipe ram or annular preventer can be used.
- Confirm shut-in
- Notify tool pusher/company representative
- Gather all relevant data required:
 - SIDPP and SICP
 - Hole Depth and Hole TVD
 - Pit gain

Procedure While Tripping (Continued)

- Time
- Kick Volume
- Pipe depth
- MW in, MW out
- SPR's (Slow Pump Rate's)
- Regroup and identify forward plan (let well stabilize, update kill sheet, inventory mud additives and mud volumes on location)
- Company Representative, Drilling Superintendent, Drilling Engineer and Drilling Manager will discuss well control kill method to be utilized. A verbal Risk Assessment and preferred kill method will be finalized. Initial Risk Assessment will be finalized within 1 hour of initial shut in.
- No well kill operation commences until there is a plan agreed by the Superintendent, On-Site Supervisor and the Drilling Contractor PIC.
- Recheck all pressures and fluid volume on accumulator unit
If pressure has built or is anticipated during the kill to reach X,XXX psi or greater, the annular preventer CANNOT be used as per Company Well Control Policy, swap to the upper BOP pipe ram.

2.3 PROCEDURE WHILE RUNNING CASING

- Sound alarm (alert crew)
- Stab crossover and full opening safety valve and close
- Space out casing (ensure no coupling is located in the BOP element selected for initial closure).
- Shut down pumps (stop pumps and observe well.)
- Shut-in Well - If flow is suspected or confirmed, close uppermost applicable BOP element. (HCR and choke will already be in the closed position.)
 - **Note:** Either the uppermost pipe ram or annular preventer can be used.
- Confirm shut-in
- Notify tool pusher/company representative
- Gather all relevant data required:
 - SIDPP and SICP
 - Hole Depth and Hole TVD
 - Pit gain
 - Time
 - Kick Volume
 - Pipe depth
 - MW in, MW out
 - SPR's (Slow Pump Rate's)
- Regroup and identify forward plan (let well stabilize, update kill sheet, inventory mud additives and mud volumes on location)
- Company Representative, Drilling Superintendent, Drilling Engineer and Drilling Manager will discuss well control kill method to be utilized. A verbal Risk Assessment and preferred kill method will be finalized. Initial Risk Assessment will be finalized within 1 hour of initial shut in.
- No well kill operation commences until there is a plan agreed by the Superintendent, On-Site Supervisor and the Drilling Contractor PIC.
- Recheck all pressures and fluid volume on accumulator unit
If pressure has built or is anticipated during the kill to reach 2,500 psi or greater, the annular preventer CANNOT be used, swap to the upper BOP pipe ram.

2.4 PROCEDURE WITH NO PIPE IN HOLE (OPEN HOLE)

- Sound alarm (alert crew)
- Shut-in with blind rams or BSR. (HCR and choke will already be in the closed position.)
- Confirm shut-in
- Notify toolpusher/company representative
- Gather all relevant data required:
 - Shut-In Pressure
 - Hole Depth and Hole TVD
 - Pit gain
 - Time
 - Kick Volume
 - MW in, MW out
 - SPR's (Slow Pump Rate's)
- Regroup and identify forward plan (let well stabilize, update kill sheet, inventory mud additives and mud volumes on location)
- Company Representative, Drilling Superintendent, Drilling Engineer and Drilling Manager will discuss well control kill method to be utilized. A verbal Risk Assessment and preferred kill method will be finalized. Initial Risk Assessment will be finalized within 1 hour of initial shut in.
- No well kill operation commences until there is a plan agreed by the Superintendent, On-Site Supervisor and the Drilling Contractor PIC.
- Recheck all pressures and fluid volume on accumulator unit.

2.5 PROCEDURE WHILE PULLING BHA THRU STACK

- PRIOR to pulling last joint of drill pipe thru the stack.
 - Perform flow check, if flowing.
 - Sound alarm (alert crew).
 - Stab full opening safety valve and close
 - Space out drill string with tool joint just beneath the upper pipe ram.
 - Shut-in using upper pipe ram. (HCR and choke will already be in the closed position).
 - Confirm shut-in.
 - Notify toolpusher/company representative
 - Read and record the following:
 - SIDPP and SICP
 - Pit gain
 - Time
 - Regroup and identify forward plan
- **With BHA in the stack and compatible ram preventer and pipe combo immediately available.**
 - Sound alarm (alert crew)
 - Stab crossover and full opening safety valve and close
 - Space out drill string with upset just beneath the compatible pipe ram.
 - Shut-in using compatible pipe ram. (HCR and choke will already be in the closed position.)
 - Confirm shut-in
 - Notify toolpusher/company representative
 - Read and record the following:
 - SIDPP and SICP
 - Pit gain

Procedures While Pulling BHA thru Stack (Continued)

- Time
- Regroup and identify forward plan

- **With BHA in the stack and NO compatible ram preventer and pipe combo immediately available.**
 - Sound alarm (alert crew)
 - If possible to pick up high enough, pull string clear of the stack and follow "Open Hole" scenario.
 - If impossible to pick up high enough to pull the string clear of the stack:
 - Stab crossover, make up one joint/stand of drill pipe, and full opening safety valve and close
 - Space out drill string with tool joint just beneath the upper pipe ram.
 - Shut-in using upper pipe ram. (HCR and choke will already be in the closed position.)
 - Confirm shut-in
 - Notify toolpusher/company representative
 - Read and record the following:
 - SIDPP and SICP
 - Pit gain
 - Time