



7821 Will Rogers Blvd.
Fort Worth, Texas 76140
817.568.1038 (office)
817.568.1499 (fax)
www.msdir.com

MS Directional Survey Data Certification

MS Directional Job Number: DDMO-180497
Survey Type: MWD
Operating Company: ConocoPhillips Company
Well Name & Number: Peridot 8 Federal 1H
Location: Lea County, NM
API Number: 30-025-44528
Tie In Depth: Surface
Surveyed Depths: 110' – 13,087' MD
Projected TD Survey: 13,151' MD
Dates Performed: 05/16/2018 – 06/02/2018

HOBBS OCD

AUG 05 2019

RECEIVED

I certify that the data is true, correct and complete and within the limitations of the tool set forth by MS Directional; that I am authorized and qualified to make this report and that I have reviewed this report and find it conforms to the principles and procedures as set forth by MS Directional.

Digitally signed by:

MWD Surveyor Name: Addison Bailey

Date: 07-16-2018

Email: abailey@msdir.com

CONFIDENTIALITY NOTICE: This document contains MS Directional's proprietary and confidential information and may not be copied, published, distributed or transmitted, in whole or in part, by any medium or in any form without MS Directional's prior written consent. The information contained in this document is not to be used by or disclosed to any individuals other than those who need to know such information and who have been given notice that such information is proprietary and confidential.

V09.04.02

Company:	ConocoPhillips Company				
Well Name:	Peridot 8 Federal 1H				
Location:	Lea County, NM				
Rig:	Trinidad #417		Magnetic Declination:	6.76	REFERENCED TO GRID NORTH
Job Number:	DDMO-180497				
API #:	30-025-44528				

Vertical Section Azimuth:	269.73	Proposed Direction:	269.73
---------------------------	--------	---------------------	--------

Survey Calculation Method:	Minimum Curvature
----------------------------	-------------------

PTB:	MD	INC	AZM	TVD	N/S	E/W	VS
	13,151	93	268.3	5466.15	-320.45	-7822.79	7824.21

#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance	Azm	DLS/ 100	BUR/ 100'
TIE IN	0	0.00	0.00	0.00	0.00	0.00			0.00		
1	110	0.10	356.30	110.00	0.10	-0.01	0.01	0.10	356.30	0.09	0.09
2	264	0.40	285.20	264.00	0.37	-0.53	0.53	0.65	304.80	0.25	0.19
3	453	0.50	287.30	452.99	0.79	-1.96	1.95	2.11	291.95	0.05	0.05
4	653	0.40	245.90	652.99	0.76	-3.43	3.42	3.51	282.56	0.17	-0.05
5	832	0.50	288.70	831.98	0.76	-4.74	4.73	4.80	279.10	0.19	0.06
6	909	0.20	154.20	908.98	0.75	-5.00	4.99	5.05	278.48	0.85	-0.39
7	972	0.70	247.60	971.98	0.50	-5.31	5.30	5.33	275.38	1.17	0.79
8	1,031	1.60	213.50	1030.97	-0.32	-6.09	6.10	6.10	266.95	1.85	1.53
9	1,094	3.10	203.30	1093.91	-2.62	-7.25	7.27	7.71	250.12	2.46	2.38
10	1,157	4.10	203.10	1156.79	-6.26	-8.81	8.84	10.81	234.61	1.59	1.59
11	1,282	5.40	185.60	1281.36	-16.22	-11.14	11.21	19.68	214.47	1.55	1.04
12	1,407	5.70	174.60	1405.78	-28.26	-11.13	11.26	30.37	201.49	0.88	0.24
13	1,533	5.10	172.50	1531.22	-40.04	-9.81	10.00	41.22	193.76	0.50	-0.48
14	1,658	4.40	168.80	1655.79	-50.25	-8.15	8.39	50.91	189.21	0.61	-0.56
15	1,784	3.70	176.70	1781.48	-59.05	-6.98	7.26	59.46	186.74	0.71	-0.56
16	1,909	3.60	177.00	1906.22	-67.00	-6.54	6.86	67.32	185.58	0.08	-0.08
17	2,034	3.80	175.30	2030.96	-75.04	-6.00	6.35	75.28	184.57	0.18	0.16
18	2,160	3.80	174.90	2156.68	-83.36	-5.28	5.68	83.53	183.63	0.02	0.00
19	2,187	3.70	176.70	2183.63	-85.13	-5.15	5.55	85.28	183.46	0.57	-0.37
20	2,357	3.40	175.20	2353.30	-95.63	-4.42	4.87	95.73	182.64	0.18	-0.18
21	2,545	2.50	162.10	2541.05	-105.08	-2.69	3.18	105.12	181.47	0.60	-0.48
22	2,733	3.30	177.90	2728.81	-114.39	-1.23	1.77	114.40	180.62	0.60	0.43
23	2,922	5.00	183.90	2917.31	-128.05	-1.59	2.19	128.06	180.71	0.93	0.90
24	3,110	4.20	186.30	3104.70	-143.06	-2.90	3.58	143.09	181.16	0.44	-0.43
25	3,298	4.00	185.00	3292.22	-156.44	-4.23	4.97	156.50	181.55	0.12	-0.11
26	3,486	5.30	178.60	3479.60	-171.65	-4.59	5.40	171.71	181.53	0.74	0.69
27	3,674	5.00	176.00	3666.84	-188.50	-3.81	4.69	188.54	181.16	0.20	-0.16
28	3,862	5.00	178.10	3854.13	-204.87	-2.96	3.93	204.89	180.83	0.10	0.00
29	4,052	4.80	182.20	4043.43	-221.08	-2.99	4.04	221.10	180.78	0.21	-0.11
30	4,241	4.70	188.50	4231.79	-236.64	-4.44	5.56	236.69	181.08	0.28	-0.05
31	4,304	3.30	190.50	4294.63	-240.98	-5.15	6.29	241.03	181.23	2.23	-2.22
32	4,430	0.90	108.60	4420.55	-244.86	-4.88	6.03	244.91	181.14	2.62	-1.90
33	4,619	1.10	90.70	4609.52	-245.36	-1.66	2.81	245.36	180.39	0.20	0.11

Company:	ConocoPhillips Company		
Well Name:	Peridot 8 Federal 1H		
Location:	Lea County, NM		
Rig:	Trinidad #417	Magnetic Declination:	6.76
Job Number:	DDMO-180497		
API #:	30-025-44528		
Vertical Section Azimuth:	269.73	Proposed Direction:	269.73
Survey Calculation Method:	Minimum Curvature		

Survey Calculation Method:											
PTB:	MD	INC	AZM	TVD	N/S	E/W	VS				
	13,151	93	268.3	5466.15	-320.45	-7822.79	7824.21				
#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance	Azm	DLS/ 100	BUR/ 100'
34	4,808	0.40	117.20	4798.51	-245.68	0.74	0.41	245.68	179.83	0.40	-0.37
35	4,840	0.80	279.60	4830.51	-245.70	0.62	0.53	245.70	179.85	3.71	1.25
36	4,987	2.20	279.00	4977.45	-245.08	-3.18	4.33	245.10	180.74	0.95	0.95
37	4,997	2.80	276.50	4987.44	-245.03	-3.61	4.76	245.05	180.84	6.10	6.00
38	5,060	8.70	275.00	5050.10	-244.44	-9.89	11.04	244.64	182.32	9.37	9.37
39	5,123	15.20	273.80	5111.70	-243.47	-22.89	24.04	244.55	185.37	10.32	10.32
40	5,186	21.80	273.50	5171.41	-242.21	-42.83	43.97	245.97	190.03	10.48	10.48
41	5,248	27.50	273.10	5227.74	-240.73	-68.63	69.77	250.32	195.91	9.20	9.19
42	5,312	33.00	272.50	5283.00	-239.17	-100.83	101.95	259.55	202.86	8.61	8.59
43	5,376	38.30	273.60	5334.99	-237.16	-138.06	139.17	274.42	210.20	8.34	8.28
44	5,439	43.20	272.70	5382.70	-234.92	-179.11	180.21	295.41	217.32	7.83	7.78
45	5,502	46.40	270.30	5427.40	-233.78	-223.47	224.57	323.41	223.71	5.74	5.08
46	5,565	51.70	267.90	5468.68	-234.57	-271.03	272.13	358.44	229.12	8.89	8.41
47	5,627	58.30	267.10	5504.22	-236.80	-321.73	322.85	399.48	233.65	10.70	10.65
48	5,690	64.30	266.90	5534.47	-239.69	-376.89	378.02	446.66	237.54	9.53	9.52
49	5,754	70.30	267.60	5559.15	-242.52	-435.84	436.98	498.77	240.91	9.43	9.38
50	5,817	76.50	267.60	5577.14	-245.04	-496.13	497.28	553.35	243.71	9.84	9.84
51	5,880	81.30	267.90	5589.27	-247.47	-557.89	559.05	610.31	246.08	7.63	7.62
52	5,943	86.20	268.10	5596.12	-249.65	-620.46	621.63	668.80	248.08	7.78	7.78
53	6,128	93.70	267.40	5596.28	-256.91	-805.18	806.38	845.17	252.30	4.07	4.05
54	6,313	91.10	268.90	5588.54	-262.88	-989.90	991.13	1024.21	255.13	1.62	-1.41
55	6,502	90.20	268.50	5586.39	-267.16	-1178.84	1180.08	1208.73	257.23	0.52	-0.48
56	6,686	92.90	268.10	5581.42	-272.62	-1362.67	1363.94	1389.68	258.69	1.48	1.47
57	6,881	93.20	269.90	5571.04	-276.02	-1557.36	1558.64	1581.63	259.95	0.93	0.15
58	7,070	91.20	271.40	5563.79	-273.87	-1746.19	1747.46	1767.54	261.09	1.32	-1.06
59	7,259	87.60	271.90	5565.76	-268.43	-1935.07	1936.32	1953.60	262.10	1.92	-1.90
60	7,445	90.10	271.60	5569.50	-262.75	-2120.93	2122.15	2137.15	262.94	1.35	1.34
61	7,627	88.70	270.10	5571.40	-260.05	-2302.89	2304.09	2317.53	263.56	1.13	-0.77
62	7,826	89.70	268.50	5574.18	-262.49	-2501.85	2503.06	2515.58	264.01	0.95	0.50
63	8,015	92.60	267.60	5570.39	-268.91	-2690.68	2691.92	2704.08	264.29	1.61	1.53
64	8,204	89.50	271.20	5566.92	-270.89	-2879.58	2880.83	2892.30	264.63	2.51	-1.64
65	8,391	92.10	271.40	5564.31	-266.65	-3066.50	3067.72	3078.07	265.03	1.39	1.39
66	8,574	90.30	270.00	5560.48	-264.41	-3249.44	3250.65	3260.18	265.35	1.25	-0.98
67	8,755	92.30	267.70	5556.37	-268.04	-3430.33	3431.56	3440.79	265.53	1.68	1.10

Company:		ConocoPhillips Company												
Well Name:		Peridot 8 Federal 1H												
Location:		Lea County, NM												
Rig:		Trinidad #417				Magnetic Declination:		6.76		REFERENCED TO GRID NORTH ▼				
Job Number:		DDMO-180497												
API #:		30-025-44528												
Vertical Section Azimuth:				269.73		Proposed Direction:		269.73						
Survey Calculation Method:				Minimum Curvature										
PTB:	MD		INC		AZM		TVD		N/S		E/W		VS	
	13,151		93		268.3		5466.15		-320.45		-7822.79		7824.21	
#	Depth Feet	Inc Degrees	Azm Degrees	TVD Feet	N/S Feet	E/W Feet	Surface Vert Sec	Closure Distance	Azm	DLS/ 100	BUR/ 100'			
68	8,940	89.40	267.20	5553.63	-276.27	-3615.11	3616.37	3625.65	265.63	1.59	-1.57			
69	9,129	90.90	267.70	5553.14	-284.68	-3803.91	3805.21	3814.55	265.72	0.84	0.79			
70	9,318	92.20	269.10	5548.02	-289.96	-3992.76	3994.08	4003.28	265.85	1.01	0.69			
71	9,507	92.20	270.00	5540.77	-291.44	-4181.62	4182.94	4191.76	266.01	0.48	0.00			
72	9,696	91.20	269.50	5535.16	-292.26	-4370.53	4371.86	4380.29	266.17	0.59	-0.53			
73	9,884	89.60	270.90	5533.85	-291.61	-4558.51	4559.83	4567.83	266.34	1.13	-0.85			
74	10,073	92.20	270.20	5530.88	-289.79	-4747.46	4748.77	4756.30	266.51	1.42	1.38			
75	10,261	93.30	271.70	5521.86	-286.68	-4935.21	4936.51	4943.53	266.68	0.99	0.59			
76	10,450	90.80	271.90	5515.10	-280.75	-5123.98	5125.25	5131.67	266.86	1.33	-1.32			
77	10,639	91.30	270.70	5511.64	-276.46	-5312.90	5314.14	5320.08	267.02	0.69	0.26			
78	10,828	92.70	268.70	5505.04	-277.45	-5501.76	5503.01	5508.76	267.11	1.29	0.74			
79	11,018	90.60	269.60	5499.57	-280.27	-5691.65	5692.91	5698.55	267.18	1.20	-1.11			
80	11,207	90.70	270.80	5497.42	-279.61	-5880.64	5881.89	5887.28	267.28	0.64	0.05			
81	11,395	92.30	270.80	5492.50	-276.98	-6068.55	6069.78	6074.86	267.39	0.85	0.85			
82	11,584	90.90	270.40	5487.23	-275.00	-6257.46	6258.68	6263.50	267.48	0.77	-0.74			
83	11,774	89.10	270.80	5487.23	-273.01	-6447.44	6448.65	6453.22	267.58	0.97	-0.95			
84	11,963	89.50	269.50	5489.54	-272.52	-6636.42	6637.63	6642.01	267.65	0.72	0.21			
85	12,152	91.80	269.30	5487.39	-274.50	-6825.38	6826.60	6830.90	267.70	1.22	1.22			
86	12,341	89.60	267.50	5485.08	-279.78	-7014.28	7015.52	7019.85	267.72	1.50	-1.16			
87	12,530	90.20	267.00	5485.41	-288.84	-7203.06	7204.34	7208.85	267.70	0.41	0.32			
88	12,720	90.40	266.70	5484.42	-299.28	-7392.77	7394.10	7398.82	267.68	0.19	0.11			
89	12,909	93.00	266.50	5478.81	-310.49	-7581.34	7582.72	7587.69	267.65	1.38	1.38			
90	13,087	93.00	268.30	5469.49	-318.55	-7758.90	7760.32	7765.44	267.65	1.01	0.00			
PTB:	13,151	93.00	268.30	5466.15	-320.45	-7822.79	7824.21	7829.35	267.65	0.00	0.00			