Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103		
<u>District I</u> – (575) 393-6161	Energy, Minerals and Natural Resources OIL CONSERVATION DIVISION 220 South St. Francis Dr. Santa Fe, NM 87505	Revised August 1, 2011 WELL API NO.		
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283	ON CONCERNATION DIVIGION	30-025-30010		
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178	JOIL CONSERVATION DIVISION	5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM \$410	Santa Fe NIM 87505	STATE FEE S		
District IV – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Fe, NM 87505 AND REPORTS ON WELLS	6. State Oil & Gas Lease No. 4 40/		
SUNDRY NOT	AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name		
(DO NOT USE THIS FORM FOR PROPE	ALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A CATION FOR PERMIT" (FORM C-101) FOR SUCH	WEST DOLLARHIDE QUEEN SAND UNIT		
1. Type of Well: Oil Well	8. Well Number 80			
2. Name of Operator		9. OGRID Number 309777		
RAM ENERGY LLC 3. Address of Operator		10. Pool name or Wildcat		
2100 S. UTICA AVE., SUITE	175, TULSA, OK 74114	DOLLARHIDE QUEEN (018810)		
4. Well Location				
Unit LetterG:	1600feet from theEAST line and1	650feet from theNORTH_line		
Section 30	Township 24S Range 38E	NMPM LEA County		
	11. Elevation (Show whether DR, RKB, RT, GR, et	c.)		
	3177' KB			
12. Check	Appropriate Box to Indicate Nature of Notice	. Report or Other Data		
		•		
NOTICE OF IT PERFORM REMEDIAL WORK □	NTENTION TO: SUI PLUG AND ABANDON ⊠ REMEDIAL WO	BSEQUENT REPORT OF: RK		
TEMPORARILY ABANDON	_	RILLING OPNS. P AND A		
PULL OR ALTER CASING		<u> </u>		
DOWNHOLE COMMINGLE				
OTHER:	☐ OTHER:			
	pleted operations. (Clearly state all pertinent details, a			
of starting any proposed w proposed completion or re	ork). SEE RULE 19.15.7.14 NMAC. For Multiple C completion.	ompletions: Attach wellsore diagram of		
		SUBJECT TO LIKE 3350'. (PERFS)		
1. NOTIFY NMOCD 24 HR		PROVA TO LTUE		
2. MIRU. ND WH, NU BOP	E. SPOT 25SX OF CLASS "C" CEMENT FROM 3625'-	3350' (DEDES)		
4. CIRCULATE 9.5 PPG MI		SSSO : (I EIG S)		
	C" CEMENT FROM 2815'-2545'. WOC&TAG. (YA	TES/B.SALT)		
	C" CEMENT FROM 1312'-1162'. WOC&TAG. (T.S			
 SPOT 55SX OF CLASS "C" CEMENT FROM 479'-SURFACE. VERIFY CEMENT TO SURFACE. (FW/SHOE/SURFACE). CUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE MARKER. TURN OVER FOR 				
RECLAMATION.				
CLOSED LOOP CONTAI	INMENT SYSTEM WILL BE USED FOR FLUIDS.			
Spud Date:	Rig Release Date:			
Spud Date:	Rig Release Date:			
	Rig Release Date:	ge and belief.		
I hereby certify that the information	above is true and complete to the best of my knowled			
I hereby certify that the information	above is true and complete to the best of my knowled	NAGERDATE08/26/19		
I hereby certify that the information SIGNATURE Type or print name MATTHEW PA	above is true and complete to the best of my knowled	NAGERDATE08/26/19 MENERGY.NET PHONE: _(918)947-6301_		

WELLBORE DIAGRAM WEST DOLLARHIDE QUEEN SAND UNIT #80

Created: 08/26/19 Well #: 80 By: LEE R. Updated: By: API 30-025-30010 Lease: WEST DOOLARHIDE QUEEN SAND UNIT Unit Ltr.: G 30 Sec. TSHP/Rng: QUEEN Field: 24S-T38E 1650' FNL & 1600' FEL Pool Code: 309777 Surf. Loc.: OGRID: Bot. Loc.: County: LEA St.: NM Directions: Status:

Surface Cas Size: Wt., Grd.: Depth: Sxs Cmt: Circulate: TOC: Hole Size:	8-5/8" 24# 429' 250 YES SURFACE 12-1/4"		
FORMATION		\	
T Call	142621	F:00000	1000000

FORMATION TOPS		
T.Salt	1262'	
B. Salt	2595'	

Intermediate Casing

C	i7	Δ.

5-1/2"

Wt., Grd.:

15.5#/17#

Depth:

3995'

Sxs Cmt:

1135

Circulate:

YES

TOC: Hole Size: SURFACE 7-7/8"

Queen: 3704'-3861'(OA)

WELLBORE DIAGRAM WEST DOLLARHIDE QUEEN SAND UNIT #80

Well #: Created: 08/26/19 Ву: LEE R. 80 Updated: Ву: API 30-025-30010 WEST DOOLARHIDE QUEEN SAND UNIT G 30 Lease: Unit Ltr.: Sec. Field: QUEEN TSHP/Rng: 24S-T38E 1650' FNL & 1600' FEL Pool Code: OGRID: 309777 Surf. Loc.: Bot. Loc.: LEA St.: NM Directions: County: Status: Surface Casing Size: 8-5/8" Wt., Grd.: 24# Depth: 429' Sxs Cmt: 250 Circulate: YES TOC: SURFACE Hole Size: 12-1/4" SPOT 55SX OF CMT FROM 479'-SURFACE. VERIFY. (FW/SHOE/SURFACE) MLF SPOT 25SX OF CMT FROM 1312'-1162'. WOC&TAG. (T.SALT) MLF FORMATION TOPS T.Salt 1262 SPOT 35SX OF CMT FROM 2815'-2545'. B. Salt 2595 MLF WOC&TAG. (YATES/B.SALT) SET CIBP@3625' AND SPOT 25SX ON TOP Intermediate Casing FROM 3625'-3350'.(PERFS) Size: 5-1/2" 15.5#/17# Queen: 3704'-3861'(OA) Wt., Grd.: Depth: 3995' Sxs Cmt: 1135 Circulate: YES

TOC:

Hole Size:

SURFACE

7-7/8"