

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-27032

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Bobbi State Waterflood Unit

8. Well Number 7

9. OGRID Number
232611

10. Pool name or Wildcat
W, Arkansas Junction SA

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-103) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
SUNDOWN ENERGY LP

3. Address of Operator
16400 DALLAS PARKWAY, STE. 100 DALLAS, TX 75248

4. Well Location

Unit Letter C : 660 feet from the North line and 1980 feet from the West line
Section 29 Township 18S Range 36E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3838.6' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: Add additional perfs ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MI RU Well service Rig
 2. POOH w/ production equipment
 3. RU WL & perf @ 5295- 5302' & 5329 - 5335'
 4. Acidize perfs w/1000 gals NeFe 15% acid
 5. RBIH w/ production equipment.
 6. Return to production.
- OPEN PERFS: 5152 - 5252' & 5496 - 5516'

R-13731

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Belinda Bradley TITLE Field Production Analyst DATE 10/17/2019

Type or print name Belinda Bradley E-mail address: bbradley@sundownenergy.com PHONE 432-943-8770

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 10/24/19

Conditions of Approval (if any):

WELL DATA SHEET

LEASE: Bobbi State Waterflood Unit

WELL: 7

FIELD: W. ARKANSAS JUNCTION - SA

LOC: 1980' FWL & 660' FNL

Fed, State, Fee: STATE

Unit: C Sec: 29 Township: 18S Range: 36E

STATUS: ACTIVE

CO: LEA

API NO: 30-025-27032

TD: 5600'

ST:

LEASE # B-2317

PBTD: 5568'

COTD:

CURRENT

Spud Date: 9/8/80

Comp. Date: 10/10/80

GL: 3838.6'

DF:

KB:

Csg Detail:

Hole Size: 12-1/4"

8-5/8" OD, 24 #/ft, grade

csg set @ 1896' w/ 850 sx.

Circ? YES TOC @ SURF By

Hole Size: 7-7/8"

4-1/2" OD, 10.5 #/ft, grade

csg set @ 5600' w/ 225 sx.

Circ? NO TOC @ 4500' By CALC

5568' PBTD

5152-58' 2 SPF SA } 10/11/1982
5242-52' 2 SPF SA }

5496-5500' 2 SPF SA
5506-5516' 2 SPF SA

5600' TD

WELL DATA SHEET

LEASE: Bobbi State Waterflood Unit

WELL: 7

FIELD: W. ARKANSAS JUNCTION - SA

LOC: 1980' FWL & 660' FNL

Fed, State, Fee: STATE

Unit: C Sec: 29 Township: 18S Range: 36E

STATUS: ACTIVE

CO: LEA

API NO: 30-025-27032

TD: 5600'

ST:

LEASE # B-2317

PBTD: 5568'

COTD:

PROPOSED

Spud Date: 9/8/80

Comp.Date: 10/10/80

GL: 3838.6'

DF:

KB:

Csg Detail:

Hole Size: 12-1/4"

8-5/8" OD 24 #/ft, grade

csg set @ 1896' w/ 850 sx.


Circ? YES TOC @ SURF By

Hole Size: 7-7/8"

4-1/2" OD 10.5 #/ft, grade

csg set @ 5600' w/ 225 sx.

Circ? NO TOC @ 4500' By CALC



5568' PBTD

5152-58' 2 SPF SA } 10/11/1982
5242-52' 2 SPF SA }

5295-5302' proposed new perfs
5329-5335'

5496-5500' 2 SPF SA
5506-5516' 2 SPF SA

5600' TD