State of New Mexico Energy Minerals and Natural Resources

Form C-144 June 1, 2004

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe office

Pit or Below-Grade Tank Registration or Closure				
Is pit or below-grade tank covered by a "general plan"? Yes 🛛 No 🗍 Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🖾				
Operator: Yates Petroleum Corporation Telephone: <u>505-748-4500</u> e-mail address: <u>mikes@ypcnm.com</u>				
Address: <u>105 South 4<sup>th</sup> Street</u> , Artesia, N.M. 88210				
Facility or well name: Chicken Little State Unit 1 API #: 30-005-27940 U/L or Qtr/Qtr M Sec 36 T 10S R 31E				
County: <u>Chaves</u> <u>Latitude: 33.39709</u> Longitude: <u>103.73609</u> NAD: 1927 🛛 1983 🗌				
Surface Owner: Federal I State Private Indian I				
Pit	Below-grade tank	6		
Type: Drilling 🛛 Production 🗌 Disposal 🗌	Volume:bbl Type of fluid:	<u> </u>		
Work over 🔲 Emergency 🗌	Construction material:	<u>a 8)                                    </u>		
Lined 🛛 Unlined 🗌	Double-walled, with leak detection? Yes Fringe exp			
Liner type: Synthetic 🛛 Thickness <u>12</u> mil Clay 🗌				
Pit Volume <u>24,000 bbi</u>	THE C	cus/		
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.) $-50^4$	Less than 50 feet 50 feet or more, but less than 100 feet			
	50 feet or more, but less than 100 feet	(10 points) OCT 2 1 2005		
	100 feet or more	( 0 points)		
Wellhead protection area: (Less than 200 feet from a private domestic water	Yes	(20 points)		
source, or less than 1000 feet from all other water sources.)	No	( 0 points) XXXX		
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet	(20 points)		
	200 feet or more, but less than 1000 feet	(10 points)		
	1000 feet or more	( 0 points) XXXX		
	Ranking Score (Total Points)	20 points		

(5) Attach soil sample results and a diagram of sample locations and excavations.

Additional Comments: Closure work plan for drilling pit. An encapsulation trench will be constructed and lined with 12 mil synthetic liner next to existing drilling pit. The drilling pit contents will be excavated and emplaced into the encapsulation trench using a mixture of three to one pit material and Class H bulk cement or CKD. The emulsion of pit material and cement will be mixed using a track hoe and water added if needed. After completion of solidifying pit material in cement and pit contents have set in place for a minimum of 24 hours, the encapsulation trench will then be capped using a 20 mil synthetic liner and backfilled to grade using a minimum of 3' of like material and clean soil. A one call and 48 hour notification to OCD will be made before pit closure action begins. Beginning pit closure date: N/A.

I hereby certify that the information above is true and complete to the best of my kno been/will be constructed or closed according to NMOCD guidelines , a genera			
Date: 09/28/2005		ENTERED	
Printed Name Title Mike Stubblefield / Regulatory Agent	Signature	The second se	
Your certification and NMOCD approval of this application/closure does not relieve endanger public health or the environment. Nor doet it refleve the operator of its res	the operator of liability should the contents sponsibility for compliance with any other f	s of the pit or tank contaminate ground water or otherwise rederal, state, or local laws and/or regulations.	- \
See ATTAINED TOY JAN	nDI, Ng = 100000000000000000000000000000000000	Sale CA.	)
Approval: Field Supervisor Printed Name/Title	nature	Date: 0CT 2 6 2005	

Water Resources

Geographic Area: New Mexico

go

# **Ground-water levels for New Mexico**

### Search Results -- 1 sites found

Search Criteria

Agency code = usgs site\_no list = • 332433103444901

Save file of selected sites to local disk for future upload

Chicken Little State Unif (

## USGS 332433103444901 10S.31E.35.121131

Chaves County, New Mexico

Latitude 33°24'33", Longitude 103°44'49" NAD27

Land-surface elevation

4.385.40 feet above sea level NGVD29

The depth of the well is 119 feet below land surface.

This well is completed in the OGALLALA FORMATION (1210GLL) local aquifer.

Water Water level. level. feet feet 17 2 Time Date Time Date Status Status below below land land surface surface 1957-06-10 53.00 1969-11-06 45.76 R 71.30 P R 1961-03-06 1971-04-02 46.20 1961-04-14 47.02 R 1976-04-20 45.83 1966-03-24 48.17R 1981-02-11 44.45 1986-02-25 44.31 1996-02-06 44.87

Questions about data <u>New Mexico NWISWeb Data Inquiries</u> Feedback on this website<u>New Mexico NWISWeb Maintainer</u> Ground water for New Mexico: Water Levels http://waterdata.usgs.gov/nm/nwis/gwlevels?

Retrieved on 2005-09-28 13:37:18 EDT Department of the Interior, U.S. Geological Survey USGS Water Resources of New Mexico Privacy Statement || Disclaimer || Accessibility || FOIA 1.12 1.12 nadww01

#### **Output formats**

Table of data Tab-separated data

Graph of data

Reselect period

Top Explanation of terms





# YATES PETROLEUM CORPORATION

**Reserve Pit Solidification Procedure** 

1. Diagram of deep burial trench(s) is provided with application for closure (form C-144)



Reserve pit 150' x 150'

#### 2. Solidification of Cuttings:

- (A) The cuttings will be mixed with a track hoe. Contents will be lifted and dropped so as to create a stirring process. This process will continue until CKD and pit contents are thoroughly bonded.
- (B) The solidification material will be Cement Kiln Dust (CKD).
- (C) CKD to pit contents ratio will be 1 yard of pit contents to 240 lbs. of CKD or 1,000 cubic yards of pit contents to 120 tons of CKD. Pit contents will be measure to determine actual volume (length x width x depth /27). CKD is weighed and delivered to the site in 40,000 lb increments.

A 1,200 cubic yard work pit is constructed inside the original reserve pit beside the encapsulation/solidification trench. One thousand cubic yards of pit contents will be placed in the work trench along with six 20 ton loads of CKD to begin the mixing process.

- (D) Fresh water may be introduced to initiate the bonding process of CKD and pit contents.
- (E) In order to assure proper mixing, all CKD is precisely weighed before delivery and pit construction is measured to a predetermined need depending on exact volume of pit contents.
- 3. A minimum of three representative samples will be taken from pit contents prior to any work. These samples will be stored in closed containers.

- 4. Each stage being mixed will be sampled prior to transferring the slurry to the deep trench as follows:
  - (A) One sample of the slurry will be taken at the beginning of the transference and stored in a <u>closed</u> container.
  - (B) One sample of the slurry will be taken at the beginning of the transference and stored in an <u>open</u> container.
  - (C) One sample of the slurry will be taken at the end of the transference and stored in a <u>closed</u> container.
  - (D) One sample of the slurry will be taken at the end of the transference and stored in an <u>open</u> container.
- 5. All samples will be stored in environmentally approved containers.
- 6. All samples and associated paperwork will be delivered to the OCD office within 3 working days of closure.