

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OCD

FEB 18 2020

RECEIVED

State of New Mexico
Energy, Minerals and Natural Resources Department

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit Original
to Appropriate
District Office

GAS CAPTURE PLAN

Original Operator: Apache Corporation OGRID No: 873 Date: 8/15/2019
 Amended Reason for Amendment: _____
Date: _____

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Ghost Rider 22-15 Fed Com 101H	30-025, 46884	Sec 15 T24S R32E	2272' FSL & 480' FEL	1,200	Flared	Flared only in emergency
Ghost Rider 22-15 Fed Com 21H		Sec 15 T24S R32E	2272' FSL & 480' FEL	1,200	Flared	Flared only in emergency
Ghost Rider 22-15 Fed Com 11H		Sec 15 T24S R32E	2272' FSL & 510' FEL	1,200	Flared	Flare only in emergency
Ghost Rider 22-15 Fed Com 31H		Sec 15 T24S R32E	2272' FSL & 480' FEL	1,200	Flared	Flared only in emergency
Ghost Rider 22-15 Fed Com 22H		Sec 15 T24S R32E	2272' FSL & 480' FEL	1,200	Flared	Flared only in emergency

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete if gas transporter system is in place. The gas produced from production facility is dedicated to **ENLINK MIDSTREAM OPERATING, LP** and will be connected to **ENLINK'S LOW** pressure gathering system located in **LEA** County, New Mexico. It will require **5,500** ft of pipeline to connect the facility to **LOW** pressure gathering system. Apache Corporation provides (periodically) to **ENLINK MIDSTREAM OPERATING, LP** a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Apache Corporation and **ENLINK MIDSTREAM OPERATING, LP** have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at **ENLINK LOBO** Processing Plant located in **Sec. 3, Blk C27, Public School Land Svy, Loving County, Texas**. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on **ENLINK MIDSTREAM OPERATING, LP's** system at that time. Based on current information, it is Apache Corporation's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
 - NGL Removal – On lease Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines