

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

HOBBS OCD
RECEIVED
MAR 05 2020

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM137469
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		6. If Indian, Allottee or Tribe Name
1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		7. If Unit or CA Agreement, Name and No.
2. Name of Operator AMEREDEV OPERATING LLC (37224)		8. Lease Name and Well No. NANDINA FED COM 25 36 31 085H (322847)
3a. Address 5707 Southwest Parkway, Building 1, Suite 275 Austin TX	3b. Phone No. (include area code) (737)300-4700	9. API Well No. 30-025-46993
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface LOT O / 230 FNL / 1970 FEL / LAT 32.078945 / LONG -103.3020339 At proposed prod. zone LOT B / 200 FNL / 1980 FEL / LAT 32.1080669 / LONG -103.3020755		10. Field and Pool, or Exploratory WC-025 G-08 S263620C / LWR BONE SI
11. Sec., T. R. M. or Blk. and Survey or Area SEC 6 / T26S / R36E / NMP		
14. Distance in miles and direction from nearest town or post office* 6.5 miles	12. County or Parish LEA	13. State NM
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 200 feet	16. No of acres in lease 600.28	17. Spacing Unit dedicated to this well 320
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 2904 feet	19. Proposed Depth 10520 feet / 20767 feet	20. BLM/BIA Bond No. in file FED: NMB001478
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3011 feet	22. Approximate date work will start* 04/25/2020	23. Estimated duration 90 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification. |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM. |

25. Signature (Electronic Submission)	Name (Printed/Typed) Christie Hanna / Ph: (737)300-4723	Date 08/29/2018
Title Senior Engineering Technician		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Christopher Walls / Ph: (575)234-2234	Date 02/27/2020
Title Petroleum Engineer		
Office CARLSBAD		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

OCF Rec 07/05/2020

KZ 07/06/2020

APPROVED WITH CONDITIONS
Approval Date: 02/27/2020

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Ameredev Operating LLC
WELL NAME & NO.:	Nandina Fed Com 25 36 31 085H
SURFACE HOLE FOOTAGE:	230'/S & 1930'/W
BOTTOM HOLE FOOTAGE:	2000'/N & 1980'/W
LOCATION:	Sec 6-26S-36E-NMP
COUNTY:	Lea County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input checked="" type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

A. CASING

1. The 13-3/8 inch surface casing shall be set at approximately 1,109' feet (a minimum of 25 feet (Lea County) into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
 - b. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office.
- ❖ In Capitan Reef Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
- ❖ **Special Capitan Reef requirements.** If lost circulation (50% or greater) occurs below the Base of the Salt, the operator shall do the following:
- Switch to fresh water mud to protect the Capitan Reef and use fresh water mud until setting the intermediate casing. The appropriate BLM office is to be notified for a PET to witness the switch to fresh water.
 - Daily drilling reports from the Base of the Salt to the setting of the intermediate casing are to be submitted to the BLM CFO engineering staff via e-mail by 0800 hours each morning. Any lost circulation encountered is to be recorded on these drilling reports. The daily drilling report should show mud volume per shift/tour. Failure to submit these reports will result in an Incidence of Non-Compliance being issued for failure to comply with the Conditions of Approval. If not already planned, the operator shall run a caliper survey for the intermediate well bore and submit to the appropriate BLM office.

3. The minimum required fill of cement behind the 7-5/8 inch alternate intermediate casing is:

- Cement should tie-back at least **50 feet** on top of Capitan Reef top. If cement does not circulate see B.1.a, c-d above.
- Fresh water should be used across the capitan interval.

4. The minimum required fill of cement behind the 5-1/2 inch production casing is:

- Cement should tie-back at least **50 feet** on top of Capitan Reef top. If cement does not circulate see B.1.a, c-d above.

B. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **10,000 (10M) psi. Variance is approved to use a 5000 (5M) Annular which shall be tested to 5000 (5M) psi.**
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

C. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not

hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Operator Certification Data Report

02/28/2020

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Christie Hanna

Signed on: 01/14/2020

Title: Senior Engineering Technician

Street Address: 5707 SOUTHWEST PKWY BLDG 1 STE 275

City: AUSTIN

State: TX

Zip: 78735

Phone: (737)300-4723

Email address: channa@ameredev.com

Field Representative

Representative Name: ZACHARY BOYD

Street Address: 5707 SOUTHWEST PARKWAY, BLDG. 1 #275

City: AUSTIN

State: TX

Zip: 78735

Phone: (580)940-5054

Email address: zboyd@ameredev.com



APD ID: 10400033015

Submission Date: 08/29/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Well Type: OIL WELL

Well Work Type: Drill

Show Final Text

Section 1 - General

APD ID: 10400033015

Tie to previous NOS? Y

Submission Date: 08/29/2018

BLM Office: CARLSBAD

User: Christie Hanna

Title: Senior Engineering Technician

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM137469

Lease Acres: 600.28

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? NO

Permitting Agent? NO

APD Operator: AMEREDEV OPERATING LLC

Operator letter of designation:

Operator Info

Operator Organization Name: AMEREDEV OPERATING LLC

Operator Address: 5707 Southwest Parkway, Building 1, Suite 275

Zip: 78735

Operator PO Box:

Operator City: Austin

State: TX

Operator Phone: (737)300-4700

Operator Internet Address:

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: WC-025 G-08
S263620C

Pool Name: LWR BONE
SPRING

Is the proposed well in an area containing other mineral resources? USEABLE WATER NATURAL GAS CO2 OIL

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Is the proposed well in an area containing other mineral resources? USEABLE WATER,NATURAL GAS,CO2,OIL

Is the proposed well in a Helium production area? N Use Existing Well Pad? NO New surface disturbance?

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name:

Number: 085H

Well Class: HORIZONTAL

NANDINA

Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: INFILL

Describe sub-type:

Distance to town: 6.5 Miles

Distance to nearest well: 2904 FT

Distance to lease line: 200 FT

Reservoir well spacing assigned acres Measurement: 320 Acres

Well plat: NANDINA_FED_COM_25_36_31_085H__BLM_LEASES_20180813083317.pdf

NANDINA_FED_COM_25_36_31_085H__GAS_CAPTURE_PLAN_20180813083330.pdf

NANDINA_FED_COM_25_36_31_085H__EXHIBIT_2A__2B_20180827071046.pdf

NANDINA_FED_COM_25_36_31_085H__VICINITY_MAP_20180827071054.pdf

NANDINA_FED_COM_25_36_31_085H__C102_SIGNED_20180829132948.pdf

Well work start Date: 04/25/2020

Duration: 90 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number: 19642

Reference Datum:

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
SHL Leg #1	230	FNL	1970	FEL	26S	36E	6	Lot 0	32.078945	-103.3020339	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137471	3011	0	0	

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
KOP Leg #1	125	FNL	1980	FEL	26S	36E	6	Aliquot NWNE	32.0792325	-103.3020319	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137471	-6936	9949	9947	
PPP Leg #1-1	1320	FSL	1980	FEL	25S	36E	31	Aliquot NWSE	32.0832054	-103.302065	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 119762	-7509	11722	10520	
PPP Leg #1-2	1320	FSL	1980	FEL	25S	36E	31	Aliquot SWSE	32.0832054	-103.302065	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137469	-7509	11722	10520	
PPP Leg #1-3	0	FNL	1971	FEL	26S	36E	6	Aliquot NWNE	32.0795772	-103.3020386	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137471	-7293	10336	10304	
PPP Leg #1-4	0	FNL	1980	FEL	25S	36E	31	Aliquot NWNE	32.0940873	-103.3020703	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137469	-7509	15681	10520	
PPP Leg #1-5	2640	FSL	1980	FEL	25S	36E	31	Aliquot NWSE	32.0868336	-103.3020667	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 119762	-7509	13042	10520	
PPP Leg #1-6	1320	FSL	1980	FEL	25S	36E	30	Aliquot SWSE	32.0977156	-103.3020722	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137469	-8639	18293	11650	
PPP Leg #1-7	0	FSL	1980	FEL	25S	36E	30	Aliquot SWSE	32.0940873	-103.3020703	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137469	-7509	15681	10520	
PPP Leg #1-8	2640	FSL	1980	FEL	25S	36E	31	Aliquot SWNE	32.0868336	-103.3020667	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137469	-7509	13042	10520	
PPP Leg #1-9	0	FSL	1971	FEL	25S	36E	31	Aliquot SWSE	32.0795772	-103.3020386	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137469	-7293	10336	10304	
PPP Leg #1-10	230	FNL	1970	FEL	26S	36E	6	Lot O	32.078945	-103.3020339	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137471	3011	0	0	
EXIT Leg #1	1320	FSL	1980	FEL	25S	36E	30	Aliquot NWSE	32.0977155	-103.302072	LEA	NEW MEXI CO	NEW MEXI CO	F	FEE	-7509	17001	10520	
BHL Leg #1	200	FNL	1980	FEL	25S	36E	30	Lot B	32.1080669	-103.3020755	LEA	NEW MEXI CO	NEW MEXI CO	F	FEE	-7509	20767	10520	

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

02/28/2020

APD ID: 10400033015

Submission Date: 08/29/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
284571	RUSTLER	1946	1068	1068	ANHYDRITE	NONE	N
284572	SALADO	438	1508	1508	SALT	NONE	N
284573	TANSILL	-1286	3234	3234	LIMESTONE	NONE	N
284574	CAPITAN REEF	-1792	3738	3738	LIMESTONE	USEABLE WATER	N
284575	LAMAR	-3088	5034	5034	LIMESTONE	NONE	N
284576	BELL CANYON	-3123	5069	5069	SANDSTONE	NATURAL GAS, OIL	N
284577	BRUSHY CANYON	-5163	7109	7109	SANDSTONE	NATURAL GAS, OIL	N
284578	BONE SPRING LIME	-6389	8335	8335	LIMESTONE	NONE	N
284579	BONE SPRING 1ST	-7765	9711	9711	SANDSTONE	NATURAL GAS, OIL	N
284580	BONE SPRING 2ND	-8323	10269	10269	SANDSTONE	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Rating Depth: 15000

Requesting Variance? YES

Testing Procedure: See attachment

Choke Diagram Attachment:

10M_Choke_Manifold_REV_20191120094653.pdf

BOP Diagram Attachment:

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

10M_Choke_Manifold_REV_20191120094653.pdf

5M_Annular_Preventer_Variance_and_Well_Control_Plan_20191120094711.pdf

5M_BOP_System_20191120094712.pdf

Pressure_Control_Plan_Single_Well_MB4_3String_Big_Hole_BLM_20191120094712.pdf

4_String_MB_Ameredev_Wellhead_Drawing_net_REV_20191120094721.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1193	0	1193	3011		1193	J-55	68	OTHER - BTC	7.69	0.67	DRY	11.28	DRY	13.18
2	INTERMEDIATE	9.875	7.625	NEW	API	N	0	10520	0	10520			10520	HCL-80	29.7	OTHER - BTC	1.3	1.84	DRY	2.09	DRY	3.01
3	PRODUCTION	6.75	5.5	NEW	API	N	0	21559	0	10520			21559	P-110	20	OTHER - BTC	1.96	2.1	DRY	3.11	DRY	3.46

Casing Attachments

Casing ID: 1 **String Type:** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

13.375_68.00_J55_BTC_20191120095050.pdf

Nandina_Fed_Com_25_36_31_085H__Wellbore_Diagram_and_CDA_20191120095101.pdf

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Casing Attachments

Casing ID: 2 String Type: INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

7.625_29.70_L80HC_BORUSAN_20191120095212.pdf

Nandina_Fed_Com_25_36_31_085H__Wellbore_Diagram_and_CDA_20191120095222.pdf

Casing ID: 3 String Type: PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

5.50_20_USS_P110_HC_BTC_API_20191120095311.pdf

Nandina_Fed_Com_25_36_31_085H__Wellbore_Diagram_and_CDA_20191120095319.pdf

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead					1.76					
SURFACE	Tail										
INTERMEDIATE	Lead					2.47					

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
INTERMEDIATE	Tail										
INTERMEDIATE	Lead					2.47					
INTERMEDIATE	Tail										
PRODUCTION	Lead					1.34					

Section 5 - Circulating Medium

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: All necessary supplies (e.g. bentonite, cedar bark) for fluid control will be on site.

Describe the mud monitoring system utilized: An electronic pit volume totalizer (PVT) will be utilized on the circulating system to monitor pit volume, flow rate, pump pressure, and pump rate.

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gal Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	1193	WATER-BASED MUD	8.4	8.6							

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
1193	1052 0	OTHER : Diesel Brine Emulsion	8.5	9.4							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

A directional survey, measurement while drilling and a mudlog/geologic lithology log will all be run from surface to TD.

List of open and cased hole logs run in the well:

DS,MWD,MUDLOG

Coring operation description for the well:

No coring will be done on this well.

Section 7 - Pressure

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

H2S_Plan_20180809142040.pdf

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Nan085_DR_20191120100005.pdf

Nan085_LLRR_20191120100005.pdf

5M_Annular_Preventer_Variance_and_Well_Control_Plan_20191120100019.pdf

Pressure_Control_Plan_Single_Well_MB4_3String_Big_Hole_BLM_20191120100020.pdf

Other proposed operations facets description:



Other proposed operations facets attachment:

CAPITAN_PROTECTION_CONTINGENCY_PLAN_BS_PACKET_20190905_20191120100124.pdf

Rig_Skid_Procedure_20191120100132.pdf

Other Variance attachment:

R616__CoC_for_hoses_12_18_17_20191120100154.pdf

Requested_Exceptions__3_String_Revised_01312019_20191120100155.pdf


13 5/8" 5M BOP Configuration

CO-FLEX LINE TO CHOKE MANIFOLD

2" KILL LINE

4" 10M VALVES &

10M Check Valve




Pressure Control Plan

Pressure Control Equipment

- Following setting of 13-3/8" Surface Casing Ameredev will install 13-5/8 MB4 Multi Bowl Casing Head by welding on a 13-5/8 SOW x 13-5/8" 5M in combination with 13-5/8 5M x 13-5/8 10M B-Sec to Land Intm #1 and a 13-5/8 10M x 13-5/8 10M shouldered to land C-Sec to Land Intm #2 (Installation procedure witnessed and verified by a manufacturer's representative).
- Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Ameredev will install a 5M System Blowout Preventer (BOPE) with a 5M Annular Preventer and related equipment (BOPE). Full testing will be performed utilizing a full isolation test plug and limited to 5,000 psi MOP of MB4 Multi Bowl Casing Head. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 50% of approved working pressure (2,500 psi). Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Setting of 9-5/8" (7-5/8" as applicable) Intermediate will be done by landing a wellhead hanger in the 13-5/8" 5M Bowl, Cementing and setting Well Head Packing seals and testing same. (Installation procedure witnessed and verified by a manufacturer's representative) Casing will be tested to 1500 psi or .22 psi/ft whichever is greater for 30 minutes with <10% leak off, but will not exceed 70% of the burst rating per Onshore Order No. 2.
- Full testing will be performed utilizing a full isolation test plug to 10,000 psi MOP of MB4 Multi Bowl B-Section. Pressure will be held for 10 min or until provisions of test are met on all valves and rams. The 5M Annular Preventer will be tested to 100% of approved working pressure (5,000 psi).
- Before drilling >20ft of new formation under the 9-5/8" (7-5/8" as applicable) Casing Shoe a pressure integrity test of the Casing Shoe will be performed to minimum of the MWE anticipated to control formation pressure to the next casing depth.
- Following setting of 5-1/2" Production Casing and adequate WOC time Ameredev will break 10M System Blowout Preventer (BOP) from 10M DOL-2 Casing Head, install annulus casing slips and test same (Installation procedure witnessed and verified by a manufacturer's representative) and install 11" 10M x 5-1/8" 15M Tubing Head (Installation procedure witnessed and verified by a manufacturer's representative). Ameredev will test head to 70% casing design and install Dry Hole cap with needle valve and pressure gauge to monitor well awaiting completion.

Pressure Control Plan

- Slow pump speeds will be taken daily by each crew and recorded on Daily Drilling Report after mudding up.
- A choke manifold and accumulator with floor and remote operating stations will be functional and in place after installation of BOPE, as well as full functioning mud gas separator.
- Weekly BOPE pit level drills will be conducted by each crew and recorded on Daily Drilling Report.
- BOP will be fully operated when out of hole and will be documented on the daily drilling log.
- All B.O.P.s and associated equipment will be tested in accordance with Onshore Order #2
- All B.O.P. testing will be done by an independent service company.
- The B.O.P. will be tested within 21 days of the original test if drilling takes more time than planned.
- Ameredev requests a variance to connect the B.O.P. choke outlet to the choke manifold using a co-flex hose with a 10,000 psi working pressure that has been tested to 15,000psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps. (certifications will be sent to Carlsbad BLM Office prior to install)
- Ameredev requests a variance to install a 5M Annular Preventer on the 10M System to drill the Production Hole below the 9-5/8" (7-5/8" as applicable) Intermediate Section. 5M Annular will be tested to 100% working pressure (5,000 psi). A full well control procedure will be included to isolate well bore.



Quotation

Downing Wellhead Equipment

Oklahoma City,
Oklahoma - USA

Reference Data:
16925 AMEREDEV

Proprietary and Confidential

The information contained in this drawing is the sole property of Downing Wellhead Equipment, any reproduction in part or in whole without the written permission of Downing Wellhead Equipment is prohibited.

TITLE:

AMEREDEV

DRAWN		SIZE	DWG. NO.	REV.
CHECKED		A		
APPROVED		Scale:	Weight:	Sheet:

H₂S Drilling Operation Plan

1. **All Company and Contract personnel admitted on location must be trained by a qualified H₂S safety instructor to the following:**
 - a. Characteristics of H₂S
 - b. Physical effects and hazards
 - c. Principal and operation of H₂S detectors, warning system and briefing areas
 - d. Evacuation procedure, routes and first aid
 - e. Proper use of safety equipment and life support systems
 - f. Essential personnel meeting Medical Evaluation criteria will receive additional training on the proper use of 30 minute pressure demand air packs.

2. **Briefing Area:**
 - a. Two perpendicular areas will be designated by signs and readily accessible.
 - b. Upon location entry there will be a designated area to establish all safety compliance criteria (1.) has been met.

3. **H₂S Detection and Alarm Systems:**
 - a. H₂S sensors/detectors shall be located on the drilling rig floor, in the base of the sub structure/cellar area, and on the mud pits in the shale shaker area. Additional H₂S detectors may be placed as deemed necessary. All detectors will be set to initiate visual alarm at 10 ppm and visual with audible at 14 ppm and all equipment will be calibrated every 30 days or as needed.
 - b. An audio alarm will be installed on the derrick floor and in the top doghouse.

4. **Protective Equipment for Essential Personnel:**
 - a. **Breathing Apparatus:**
 - i. Rescue Packs (SCBA) - 1 Unit shall be placed at each briefing area.
 - ii. Two (SCBA) Units will be stored in safety trailer on location.
 - iii. Work/Escapes packs - 1 Unit will be available on rig floor in doghouse for emergency evacuation for driller.
 - b. **Auxiliary Rescue Equipment:**
 - i. Stretcher
 - ii. 2 - OSHA full body harnesses
 - iii. 100 ft. 5/8" OSHA approved rope
 - iv. 1 - 20# class ABC fire extinguisher

5. **Windsock and/or Wind Streamers:**
 - a. Windsock at mud pit area should be high enough to be visible.
 - b. Windsock on the rig floor should be high enough to be visible.

6. **Communication:**
 - a. While working under mask scripting boards will be used for communication where applicable.
 - b. Hand signals will be used when script boards are not applicable.

H₂S Drilling Operation Plan

- c. Two way radios will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at Drilling Foreman's Office.

7. **Drill Stem Testing:** - No Planned DST at this time.

8. **Mud program:**
 - a. If H₂S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H₂S scavengers if necessary.

9. **Metallurgy:**
 - a. All drill strings, casing, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.
 - b. Drilling Contractor supervisor will be required to be familiar with the effect H₂S has on tubular goods and other mechanical equipment provided through contractor.



H₂S Contingency Plan

Emergency Procedures

In the event of a release of H₂S, the first responder(s) must:

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H₂S monitors and air packs in order to control the release.
- Use the "buddy system" to ensure no injuries occur during the response.
- Take precautions to avoid personal injury during this operation.
- Contact Operator and/or local officials the aid in operation. See list of phone numbers attached.
- Have received training in the:
 - Detection of H₂S and
 - Measures for protection against the gas,
 - Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H ₂ S	1.189 Air=1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air=1	2 ppm	N/A	1000 ppm

Contacting Authorities

Ameredev Operating LLC personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including direction to site. The following call list of essential and potential responders has been prepared for use during a release. Ameredev Operating LLC's response must be in coordination with the State of New Mexico's "Hazardous Materials Emergency Response Plan" (HMER)



H₂S Contingency Plan

Ameredev Operating LLC – Emergency Phone 737-300-4799			
Key Personnel:			
Name	Title	Office	Mobile
Floyd Hammond	Chief Operating officer	737-300-4724	512-783-6810
Zachary Boyd	Operations Superintendent	737-300-4725	432-385-6996
Blake Estrada	Construction Foreman		432-385-5831

<u>Artesia</u>			
Ambulance			911
State Police			575-746-2703
City Police			575-746-2703
Sheriff's Office			575-746-9888
Fire Department			575-746-2701
Local Emergency Planning Committee			575-746-2122
New Mexico Oil Conservation Division			575-748-1283
<u>Carlsbad</u>			
Ambulance			911
State Police			575-885-3137
City Police			575-885-2111
Sheriff's Office			575-887-7551
Fire Department			575-887-3798
Local Emergency Planning Committee			575-887-6544
US Bureau of Land Management			575-887-6544
<u>Santa Fe</u>			
New Mexico Emergency Response Commission (Santa Fe)			505-476-9600
New Mexico Emergency Response Commission (Santa Fe) 24 Hrs			505-827-9126
New Mexico State Emergency Operations Center			505-476-9635
<u>National</u>			
National Emergency Response Center (Washington, D.C.)			800-424-8802
<u>Medical</u>			
Flight for Life - 4000 24th St.; Lubbock, TX			806-743-9911
Aerocare - R3, Box 49F; Lubbock, TX			806-747-8923
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM			505-842-4433
SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM			505-842-4949

AMEREDEV

Ameredev Operating, LLC.

NAN/GB

NAN/GB #6S

Nandina 085H

Wellbore #1

Plan: Design #1

Standard Planning Report

18 June, 2019

Database:	EDM5000	Local Co-ordinate Reference:	Well Nandina 085H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Nandina 085H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Project	NAN/GB		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	NAN/GB #6S				
Site Position:		Northing:	393,984.60 usft	Latitude:	32° 4' 44.202 N
From:	Lat/Long	Easting:	860,801.36 usft	Longitude:	103° 18' 6.857 W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.55 °

Well	Nandina 085H					
Well Position	+N/-S	-0.4 usft	Northing:	393,984.22 usft	Latitude:	32° 4' 44.202 N
	+E/-W	-40.0 usft	Easting:	860,761.37 usft	Longitude:	103° 18' 7.322 W
Position Uncertainty		0.0 usft	Wellhead Elevation:		Ground Level:	3,011.0 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	12/5/2018	6.66	59.95	47,731.97742500

Design	Design #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	359.38

Plan Survey Tool Program	Date	6/18/2019		
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks
1	0.0	21,559.2 Design #1 (Wellbore #1)	MWD OWSG MWD - Standard	

Database:	EDM5000	Local Co-ordinate Reference:	Well Nandina 085H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Nandina 085H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,300.0	6.00	156.00	2,299.5	-14.3	6.4	2.00	2.00	0.00	156.00	
6,724.8	6.00	156.00	6,700.0	-436.9	194.5	0.00	0.00	0.00	0.00	
7,024.8	0.00	0.00	6,999.5	-451.2	200.9	2.00	-2.00	0.00	180.00	
10,065.3	0.00	0.00	10,040.0	-451.2	200.9	0.00	0.00	0.00	0.00	
10,812.5	89.66	346.29	10,517.5	9.9	88.4	12.00	12.00	0.00	346.29	
11,185.2	89.66	346.29	10,519.7	371.9	0.1	0.00	0.00	0.00	0.00	
11,294.7	90.00	359.43	10,520.0	480.4	-13.5	12.00	0.31	12.00	88.54	Nan085 FTP2
21,559.2	90.00	359.43	10,520.0	10,744.4	-115.7	0.00	0.00	0.00	0.00	Nan085 BHL

Database:	EDM5000	Local Co-ordinate Reference:	Well Nandina 085H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Nandina 085H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/S (usft)	+E/W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	2.00	156.00	2,100.0	-1.6	0.7	-1.6	2.00	2.00	0.00
2,200.0	4.00	156.00	2,199.8	-6.4	2.8	-6.4	2.00	2.00	0.00
2,300.0	6.00	156.00	2,299.5	-14.3	6.4	-14.4	2.00	2.00	0.00
2,400.0	6.00	156.00	2,398.9	-23.9	10.6	-24.0	0.00	0.00	0.00
2,500.0	6.00	156.00	2,498.4	-33.4	14.9	-33.6	0.00	0.00	0.00
2,600.0	6.00	156.00	2,597.8	-43.0	19.1	-43.2	0.00	0.00	0.00
2,700.0	6.00	156.00	2,697.3	-52.5	23.4	-52.8	0.00	0.00	0.00
2,800.0	6.00	156.00	2,796.7	-62.1	27.6	-62.4	0.00	0.00	0.00
2,900.0	6.00	156.00	2,896.2	-71.6	31.9	-72.0	0.00	0.00	0.00
3,000.0	6.00	156.00	2,995.6	-81.2	36.1	-81.6	0.00	0.00	0.00
3,100.0	6.00	156.00	3,095.1	-90.7	40.4	-91.2	0.00	0.00	0.00
3,200.0	6.00	156.00	3,194.5	-100.3	44.6	-100.8	0.00	0.00	0.00
3,300.0	6.00	156.00	3,294.0	-109.8	48.9	-110.3	0.00	0.00	0.00
3,400.0	6.00	156.00	3,393.4	-119.4	53.2	-119.9	0.00	0.00	0.00
3,500.0	6.00	156.00	3,492.9	-128.9	57.4	-129.5	0.00	0.00	0.00
3,600.0	6.00	156.00	3,592.3	-138.5	61.7	-139.1	0.00	0.00	0.00
3,700.0	6.00	156.00	3,691.8	-148.0	65.9	-148.7	0.00	0.00	0.00
3,800.0	6.00	156.00	3,791.2	-157.6	70.2	-158.3	0.00	0.00	0.00
3,900.0	6.00	156.00	3,890.7	-167.1	74.4	-167.9	0.00	0.00	0.00
4,000.0	6.00	156.00	3,990.1	-176.7	78.7	-177.5	0.00	0.00	0.00
4,100.0	6.00	156.00	4,089.6	-186.2	82.9	-187.1	0.00	0.00	0.00
4,200.0	6.00	156.00	4,189.0	-195.8	87.2	-196.7	0.00	0.00	0.00
4,300.0	6.00	156.00	4,288.5	-205.3	91.4	-206.3	0.00	0.00	0.00
4,400.0	6.00	156.00	4,387.9	-214.9	95.7	-215.9	0.00	0.00	0.00
4,500.0	6.00	156.00	4,487.4	-224.4	99.9	-225.5	0.00	0.00	0.00
4,600.0	6.00	156.00	4,586.9	-234.0	104.2	-235.1	0.00	0.00	0.00
4,700.0	6.00	156.00	4,686.3	-243.5	108.4	-244.7	0.00	0.00	0.00
4,800.0	6.00	156.00	4,785.8	-253.1	112.7	-254.3	0.00	0.00	0.00
4,900.0	6.00	156.00	4,885.2	-262.6	116.9	-263.9	0.00	0.00	0.00
5,000.0	6.00	156.00	4,984.7	-272.2	121.2	-273.5	0.00	0.00	0.00
5,100.0	6.00	156.00	5,084.1	-281.7	125.4	-283.0	0.00	0.00	0.00
5,200.0	6.00	156.00	5,183.6	-291.3	129.7	-292.6	0.00	0.00	0.00
5,300.0	6.00	156.00	5,283.0	-300.8	133.9	-302.2	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Nandina 085H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Nandina 085H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,400.0	6.00	156.00	5,382.5	-310.4	138.2	-311.8	0.00	0.00	0.00
5,500.0	6.00	156.00	5,481.9	-319.9	142.4	-321.4	0.00	0.00	0.00
5,600.0	6.00	156.00	5,581.4	-329.5	146.7	-331.0	0.00	0.00	0.00
5,700.0	6.00	156.00	5,680.8	-339.0	150.9	-340.6	0.00	0.00	0.00
5,800.0	6.00	156.00	5,780.3	-348.6	155.2	-350.2	0.00	0.00	0.00
5,900.0	6.00	156.00	5,879.7	-358.1	159.4	-359.8	0.00	0.00	0.00
6,000.0	6.00	156.00	5,979.2	-367.7	163.7	-369.4	0.00	0.00	0.00
6,100.0	6.00	156.00	6,078.6	-377.2	167.9	-379.0	0.00	0.00	0.00
6,200.0	6.00	156.00	6,178.1	-386.8	172.2	-388.6	0.00	0.00	0.00
6,300.0	6.00	156.00	6,277.5	-396.3	176.4	-398.2	0.00	0.00	0.00
6,400.0	6.00	156.00	6,377.0	-405.9	180.7	-407.8	0.00	0.00	0.00
6,500.0	6.00	156.00	6,476.4	-415.4	184.9	-417.4	0.00	0.00	0.00
6,600.0	6.00	156.00	6,575.9	-425.0	189.2	-427.0	0.00	0.00	0.00
6,700.0	6.00	156.00	6,675.3	-434.5	193.5	-436.6	0.00	0.00	0.00
6,724.8	6.00	156.00	6,700.0	-436.9	194.5	-438.9	0.00	0.00	0.00
6,800.0	4.50	156.00	6,774.9	-443.2	197.3	-445.2	2.00	-2.00	0.00
6,900.0	2.50	156.00	6,874.7	-448.7	199.8	-450.8	2.00	-2.00	0.00
7,000.0	0.50	156.00	6,974.7	-451.1	200.8	-453.2	2.00	-2.00	0.00
7,024.8	0.00	0.00	6,999.5	-451.2	200.9	-453.3	2.00	-2.00	0.00
7,100.0	0.00	0.00	7,074.7	-451.2	200.9	-453.3	0.00	0.00	0.00
7,200.0	0.00	0.00	7,174.7	-451.2	200.9	-453.3	0.00	0.00	0.00
7,300.0	0.00	0.00	7,274.7	-451.2	200.9	-453.3	0.00	0.00	0.00
7,400.0	0.00	0.00	7,374.7	-451.2	200.9	-453.3	0.00	0.00	0.00
7,500.0	0.00	0.00	7,474.7	-451.2	200.9	-453.3	0.00	0.00	0.00
7,600.0	0.00	0.00	7,574.7	-451.2	200.9	-453.3	0.00	0.00	0.00
7,700.0	0.00	0.00	7,674.7	-451.2	200.9	-453.3	0.00	0.00	0.00
7,800.0	0.00	0.00	7,774.7	-451.2	200.9	-453.3	0.00	0.00	0.00
7,900.0	0.00	0.00	7,874.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,000.0	0.00	0.00	7,974.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,100.0	0.00	0.00	8,074.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,200.0	0.00	0.00	8,174.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,300.0	0.00	0.00	8,274.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,400.0	0.00	0.00	8,374.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,500.0	0.00	0.00	8,474.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,600.0	0.00	0.00	8,574.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,700.0	0.00	0.00	8,674.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,800.0	0.00	0.00	8,774.7	-451.2	200.9	-453.3	0.00	0.00	0.00
8,900.0	0.00	0.00	8,874.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,000.0	0.00	0.00	8,974.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,100.0	0.00	0.00	9,074.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,200.0	0.00	0.00	9,174.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,300.0	0.00	0.00	9,274.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,400.0	0.00	0.00	9,374.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,500.0	0.00	0.00	9,474.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,600.0	0.00	0.00	9,574.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,700.0	0.00	0.00	9,674.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,800.0	0.00	0.00	9,774.7	-451.2	200.9	-453.3	0.00	0.00	0.00
9,900.0	0.00	0.00	9,874.7	-451.2	200.9	-453.3	0.00	0.00	0.00
10,000.0	0.00	0.00	9,974.7	-451.2	200.9	-453.3	0.00	0.00	0.00
10,065.3	0.00	0.00	10,040.0	-451.2	200.9	-453.3	0.00	0.00	0.00
Nan085 KOP									
10,100.0	4.16	346.29	10,074.6	-450.0	200.6	-452.1	12.00	12.00	0.00
10,200.0	16.16	346.29	10,172.9	-432.9	196.4	-435.0	12.00	12.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Nandina 085H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Nandina 085H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Buird Rate (°/100usft)	Turn Rate (°/100usft)
10,300.0	28.16	346.29	10,265.3	-396.3	187.5	-398.3	12.00	12.00	0.00
10,400.0	40.16	346.29	10,347.9	-341.8	174.2	-343.7	12.00	12.00	0.00
10,500.0	52.16	346.29	10,417.1	-271.9	157.1	-273.6	12.00	12.00	0.00
10,600.0	64.16	346.29	10,469.7	-189.5	137.1	-191.0	12.00	12.00	0.00
10,700.0	76.16	346.29	10,503.6	-98.3	114.8	-99.5	12.00	12.00	0.00
10,800.0	88.16	346.29	10,517.2	-2.2	91.4	-3.2	12.00	12.00	0.00
10,812.5	89.66	346.29	10,517.5	9.9	88.4	8.9	12.00	12.00	0.00
10,900.0	89.66	346.29	10,518.0	94.9	67.7	94.2	0.00	0.00	0.00
11,000.0	89.66	346.29	10,518.6	192.1	44.0	191.6	0.00	0.00	0.00
11,039.4	89.66	346.29	10,518.8	230.3	34.6	229.9	0.00	0.00	0.00
Nan085 into NMNM137469									
11,100.0	89.66	346.29	10,519.2	289.2	20.3	289.0	0.00	0.00	0.00
11,147.5	89.66	346.29	10,519.4	335.4	9.0	335.2	0.00	0.00	0.00
Nan085 FTP									
11,185.2	89.66	346.29	10,519.7	371.9	0.1	371.9	0.00	0.00	0.00
11,200.0	89.70	348.07	10,519.8	386.4	-3.2	386.4	12.00	0.31	12.00
11,294.7	90.00	359.43	10,520.0	480.4	-13.5	480.5	12.00	0.31	12.00
Nan085 FTP2									
11,300.0	90.00	359.43	10,520.0	485.7	-13.6	485.8	0.00	0.00	0.00
11,400.0	90.00	359.43	10,520.0	585.7	-14.5	585.8	0.00	0.00	0.00
11,500.0	90.00	359.43	10,520.0	685.7	-15.5	685.8	0.00	0.00	0.00
11,600.0	90.00	359.43	10,520.0	785.7	-16.5	785.8	0.00	0.00	0.00
11,700.0	90.00	359.43	10,520.0	885.7	-17.5	885.8	0.00	0.00	0.00
11,800.0	90.00	359.43	10,520.0	985.7	-18.5	985.8	0.00	0.00	0.00
11,900.0	90.00	359.43	10,520.0	1,085.7	-19.5	1,085.8	0.00	0.00	0.00
12,000.0	90.00	359.43	10,520.0	1,185.7	-20.5	1,185.8	0.00	0.00	0.00
12,100.0	90.00	359.43	10,520.0	1,285.7	-21.5	1,285.8	0.00	0.00	0.00
12,200.0	90.00	359.43	10,520.0	1,385.6	-22.5	1,385.8	0.00	0.00	0.00
12,300.0	90.00	359.43	10,520.0	1,485.6	-23.5	1,485.8	0.00	0.00	0.00
12,364.7	90.00	359.43	10,520.0	1,550.3	-24.2	1,550.5	0.00	0.00	0.00
Nan085 into NMNM119762									
12,400.0	90.00	359.43	10,520.0	1,585.6	-24.5	1,585.8	0.00	0.00	0.00
12,500.0	90.00	359.43	10,520.0	1,685.6	-25.5	1,685.8	0.00	0.00	0.00
12,600.0	90.00	359.43	10,520.0	1,785.6	-26.5	1,785.8	0.00	0.00	0.00
12,700.0	90.00	359.43	10,520.0	1,885.6	-27.5	1,885.8	0.00	0.00	0.00
12,800.0	90.00	359.43	10,520.0	1,985.6	-28.5	1,985.8	0.00	0.00	0.00
12,900.0	90.00	359.43	10,520.0	2,085.6	-29.5	2,085.8	0.00	0.00	0.00
13,000.0	90.00	359.43	10,520.0	2,185.6	-30.5	2,185.8	0.00	0.00	0.00
13,100.0	90.00	359.43	10,520.0	2,285.6	-31.5	2,285.8	0.00	0.00	0.00
13,200.0	90.00	359.43	10,520.0	2,385.6	-32.5	2,385.8	0.00	0.00	0.00
13,300.0	90.00	359.43	10,520.0	2,485.6	-33.5	2,485.8	0.00	0.00	0.00
13,400.0	90.00	359.43	10,520.0	2,585.6	-34.5	2,585.8	0.00	0.00	0.00
13,500.0	90.00	359.43	10,520.0	2,685.6	-35.5	2,685.8	0.00	0.00	0.00
13,600.0	90.00	359.43	10,520.0	2,785.6	-36.5	2,785.8	0.00	0.00	0.00
13,700.0	90.00	359.43	10,520.0	2,885.6	-37.5	2,885.8	0.00	0.00	0.00
13,800.0	90.00	359.43	10,520.0	2,985.6	-38.4	2,985.8	0.00	0.00	0.00
13,900.0	90.00	359.43	10,520.0	3,085.6	-39.4	3,085.8	0.00	0.00	0.00
14,000.0	90.00	359.43	10,520.0	3,185.6	-40.4	3,185.8	0.00	0.00	0.00
14,100.0	90.00	359.43	10,520.0	3,285.6	-41.4	3,285.8	0.00	0.00	0.00
14,200.0	90.00	359.43	10,520.0	3,385.5	-42.4	3,385.8	0.00	0.00	0.00
14,300.0	90.00	359.43	10,520.0	3,485.5	-43.4	3,485.8	0.00	0.00	0.00
14,400.0	90.00	359.43	10,520.0	3,585.5	-44.4	3,585.8	0.00	0.00	0.00
14,500.0	90.00	359.43	10,520.0	3,685.5	-45.4	3,685.8	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Nandina 085H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Nandina 085H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
14,600.0	90.00	359.43	10,520.0	3,785.5	-46.4	3,785.8	0.00	0.00	0.00
14,700.0	90.00	359.43	10,520.0	3,885.5	-47.4	3,885.8	0.00	0.00	0.00
14,800.0	90.00	359.43	10,520.0	3,985.5	-48.4	3,985.8	0.00	0.00	0.00
14,900.0	90.00	359.43	10,520.0	4,085.5	-49.4	4,085.8	0.00	0.00	0.00
15,000.0	90.00	359.43	10,520.0	4,185.5	-50.4	4,185.8	0.00	0.00	0.00
15,100.0	90.00	359.43	10,520.0	4,285.5	-51.4	4,285.8	0.00	0.00	0.00
15,200.0	90.00	359.43	10,520.0	4,385.5	-52.4	4,385.8	0.00	0.00	0.00
15,300.0	90.00	359.43	10,520.0	4,485.5	-53.4	4,485.8	0.00	0.00	0.00
15,400.0	90.00	359.43	10,520.0	4,585.5	-54.4	4,585.8	0.00	0.00	0.00
15,500.0	90.00	359.43	10,520.0	4,685.5	-55.4	4,685.8	0.00	0.00	0.00
15,600.0	90.00	359.43	10,520.0	4,785.5	-56.4	4,785.8	0.00	0.00	0.00
15,700.0	90.00	359.43	10,520.0	4,885.5	-57.4	4,885.8	0.00	0.00	0.00
15,800.0	90.00	359.43	10,520.0	4,985.5	-58.4	4,985.8	0.00	0.00	0.00
15,900.0	90.00	359.43	10,520.0	5,085.5	-59.4	5,085.8	0.00	0.00	0.00
16,000.0	90.00	359.43	10,520.0	5,185.5	-60.4	5,185.8	0.00	0.00	0.00
16,100.0	90.00	359.43	10,520.0	5,285.5	-61.3	5,285.8	0.00	0.00	0.00
16,200.0	90.00	359.43	10,520.0	5,385.4	-62.3	5,385.8	0.00	0.00	0.00
16,300.0	90.00	359.43	10,520.0	5,485.4	-63.3	5,485.8	0.00	0.00	0.00
16,400.0	90.00	359.43	10,520.0	5,585.4	-64.3	5,585.8	0.00	0.00	0.00
16,500.0	90.00	359.43	10,520.0	5,685.4	-65.3	5,685.8	0.00	0.00	0.00
16,600.0	90.00	359.43	10,520.0	5,785.4	-66.3	5,785.8	0.00	0.00	0.00
16,700.0	90.00	359.43	10,520.0	5,885.4	-67.3	5,885.8	0.00	0.00	0.00
16,800.0	90.00	359.43	10,520.0	5,985.4	-68.3	5,985.8	0.00	0.00	0.00
16,900.0	90.00	359.43	10,520.0	6,085.4	-69.3	6,085.8	0.00	0.00	0.00
17,000.0	90.00	359.43	10,520.0	6,185.4	-70.3	6,185.8	0.00	0.00	0.00
17,100.0	90.00	359.43	10,520.0	6,285.4	-71.3	6,285.8	0.00	0.00	0.00
17,200.0	90.00	359.43	10,520.0	6,385.4	-72.3	6,385.8	0.00	0.00	0.00
17,300.0	90.00	359.43	10,520.0	6,485.4	-73.3	6,485.8	0.00	0.00	0.00
17,400.0	90.00	359.43	10,520.0	6,585.4	-74.3	6,585.8	0.00	0.00	0.00
17,500.0	90.00	359.43	10,520.0	6,685.4	-75.3	6,685.8	0.00	0.00	0.00
17,600.0	90.00	359.43	10,520.0	6,785.4	-76.3	6,785.8	0.00	0.00	0.00
17,700.0	90.00	359.43	10,520.0	6,885.4	-77.3	6,885.8	0.00	0.00	0.00
17,800.0	90.00	359.43	10,520.0	6,985.4	-78.3	6,985.8	0.00	0.00	0.00
17,900.0	90.00	359.43	10,520.0	7,085.4	-79.3	7,085.8	0.00	0.00	0.00
18,000.0	90.00	359.43	10,520.0	7,185.4	-80.3	7,185.8	0.00	0.00	0.00
18,100.0	90.00	359.43	10,520.0	7,285.4	-81.3	7,285.8	0.00	0.00	0.00
18,200.0	90.00	359.43	10,520.0	7,385.4	-82.3	7,385.8	0.00	0.00	0.00
18,300.0	90.00	359.43	10,520.0	7,485.3	-83.3	7,485.8	0.00	0.00	0.00
18,400.0	90.00	359.43	10,520.0	7,585.3	-84.2	7,585.8	0.00	0.00	0.00
18,500.0	90.00	359.43	10,520.0	7,685.3	-85.2	7,685.8	0.00	0.00	0.00
18,600.0	90.00	359.43	10,520.0	7,785.3	-86.2	7,785.8	0.00	0.00	0.00
18,700.0	90.00	359.43	10,520.0	7,885.3	-87.2	7,885.8	0.00	0.00	0.00
18,800.0	90.00	359.43	10,520.0	7,985.3	-88.2	7,985.8	0.00	0.00	0.00
18,900.0	90.00	359.43	10,520.0	8,085.3	-89.2	8,085.8	0.00	0.00	0.00
19,000.0	90.00	359.43	10,520.0	8,185.3	-90.2	8,185.8	0.00	0.00	0.00
19,100.0	90.00	359.43	10,520.0	8,285.3	-91.2	8,285.8	0.00	0.00	0.00
19,200.0	90.00	359.43	10,520.0	8,385.3	-92.2	8,385.8	0.00	0.00	0.00
19,300.0	90.00	359.43	10,520.0	8,485.3	-93.2	8,485.8	0.00	0.00	0.00
19,400.0	90.00	359.43	10,520.0	8,585.3	-94.2	8,585.8	0.00	0.00	0.00
19,500.0	90.00	359.43	10,520.0	8,685.3	-95.2	8,685.8	0.00	0.00	0.00
19,600.0	90.00	359.43	10,520.0	8,785.3	-96.2	8,785.8	0.00	0.00	0.00
19,700.0	90.00	359.43	10,520.0	8,885.3	-97.2	8,885.8	0.00	0.00	0.00
19,800.0	90.00	359.43	10,520.0	8,985.3	-98.2	8,985.8	0.00	0.00	0.00
19,900.0	90.00	359.43	10,520.0	9,085.3	-99.2	9,085.8	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Nandina 085H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Nandina 085H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
20,000.0	90.00	359.43	10,520.0	9,185.3	-100.2	9,185.8	0.00	0.00	0.00	
20,100.0	90.00	359.43	10,520.0	9,285.3	-101.2	9,285.8	0.00	0.00	0.00	
20,200.0	90.00	359.43	10,520.0	9,385.3	-102.2	9,385.8	0.00	0.00	0.00	
20,300.0	90.00	359.43	10,520.0	9,485.2	-103.2	9,485.8	0.00	0.00	0.00	
20,400.0	90.00	359.43	10,520.0	9,585.2	-104.2	9,585.8	0.00	0.00	0.00	
20,500.0	90.00	359.43	10,520.0	9,685.2	-105.2	9,685.8	0.00	0.00	0.00	
20,600.0	90.00	359.43	10,520.0	9,785.2	-106.2	9,785.8	0.00	0.00	0.00	
20,700.0	90.00	359.43	10,520.0	9,885.2	-107.2	9,885.8	0.00	0.00	0.00	
20,800.0	90.00	359.43	10,520.0	9,985.2	-108.1	9,985.8	0.00	0.00	0.00	
20,900.0	90.00	359.43	10,520.0	10,085.2	-109.1	10,085.8	0.00	0.00	0.00	
21,000.0	90.00	359.43	10,520.0	10,185.2	-110.1	10,185.8	0.00	0.00	0.00	
21,100.0	90.00	359.43	10,520.0	10,285.2	-111.1	10,285.8	0.00	0.00	0.00	
21,200.0	90.00	359.43	10,520.0	10,385.2	-112.1	10,385.8	0.00	0.00	0.00	
21,300.0	90.00	359.43	10,520.0	10,485.2	-113.1	10,485.8	0.00	0.00	0.00	
21,400.0	90.00	359.43	10,520.0	10,585.2	-114.1	10,585.8	0.00	0.00	0.00	
21,500.0	90.00	359.43	10,520.0	10,685.2	-115.1	10,685.8	0.00	0.00	0.00	
Nan085 LTP										
21,559.2	90.00	359.43	10,520.0	10,744.4	-115.7	10,745.0	0.00	0.00	0.00	
Nan085 BHL										

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
Nan085 FTP2 - hit/miss target - Shape - Point	0.00	0.01	10,520.0	480.4	-13.5	394,464.60	860,747.87	32° 4' 48.957 N	103° 18' 7.426 W	
Nan085 BHL - plan hits target center - Point	0.00	0.00	10,520.0	10,744.4	-115.7	404,728.62	860,645.66	32° 6' 30.525 N	103° 18' 7.473 W	
Nan085 FTP - plan misses target center by 23.2usft at 11147.5usft MD (10519.4 TVD, 335.4 N, 9.0 E) - Point	0.00	0.00	10,520.0	329.9	-13.5	394,314.09	860,747.87	32° 4' 47.467 N	103° 18' 7.442 W	
Nan085 LTP - plan misses target center by 9.2usft at 21500.0usft MD (10520.0 TVD, 10685.2 N, -115.1 E) - Point	0.00	0.00	10,520.0	10,694.4	-115.2	404,678.60	860,646.14	32° 6' 30.030 N	103° 18' 7.473 W	

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Comment	
10,065.3	10,040.0	-451.2	200.9	Nan085 KOP	
11,039.4	10,518.8	230.3	34.6	Nan085 into NMNM137469	
12,364.7	10,520.0	1,550.3	-24.2	Nan085 into NMNM119762	

AMEREDEV

Ameredev Operating, LLC.

NAN/GB

NAN/GB #6S

Nandina 085H

Wellbore #1

Plan: Design #1

Lease Penetration Section Line Foot

18 June, 2019

Company: Ameredev Operating, LLC.	Local Co-ordinate Reference: Well Nandina 085H
Project: NAN/GB	TVD Reference: KB @ 3038.0usft
Site: NAN/GB #6S	MD Reference: KB @ 3038.0usft
Well: Nandina 085H	North Reference: Grid
Wellbore: Wellbore #1	Survey Calculation Method: Minimum Curvature
Design: Design #1	Database: EDM5000

Project NAN/GB	
Map System: US State Plane 1983	System Datum: Mean Sea Level
Geo Datum: North American Datum 1983	
Map Zone: New Mexico Eastern Zone	

Site NAN/GB #6S		
Site Position:	Northing: 393,984.61 usft	Latitude: 32° 4' 44.202 N
From: Lat/Long	Easting: 860,801.36 usft	Longitude: 103° 18' 6.857 W
Position Uncertainty: 0.0 usft	Slot Radius: 13-3/16"	Grid Convergence: 0.55 °

Well Nandina 085H		
Well Position +N/-S 0.0 usft	Northing: 393,984.22 usft	Latitude: 32° 4' 44.202 N
+E/-W 0.0 usft	Easting: 860,761.37 usft	Longitude: 103° 18' 7.322 W
Position Uncertainty 0.0 usft	Wellhead Elevation: usft	Ground Level: 3,011.0 usft

Wellbore Wellbore #1					
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	12/5/2018	6.66	59.95	47,731.97742500

Design Design #1				
Audit Notes:				
Version:	Phase: PROTOTYPE	Tie On Depth: 0.0		
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	359.38

Survey Tool Program	Date 6/18/2019			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.0	21,559.2	Design #1 (Wellbore #1)	MWD	OWSG MWD - Standard

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	Latitude	Longitude
0.0	0.00	0.00	0.00	0.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W
100.0	0.00	0.00	100.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
200.0	0.00	0.00	200.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
300.0	0.00	0.00	300.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
400.0	0.00	0.00	400.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
500.0	0.00	0.00	500.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
600.0	0.00	0.00	600.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
700.0	0.00	0.00	700.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
800.0	0.00	0.00	800.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
900.0	0.00	0.00	900.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
1,000.0	0.00	0.00	1,000.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	
1,100.0	0.00	0.00	1,100.0	-230.4	-1,970.0	32° 4' 44.202 N 103° 18' 7.322 W	

Company:	Ameredev Operating, LLC.	Local Co-ordinate Reference:	Well Nandina 085H
Project:	NAN/GB	TVD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	MD Reference:	KB @ 3038.0usft
Well:	Nandina 085H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Design #1	Database:	EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	Latitude	Longitude
1,200.0	0.00	0.00	1,200.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
1,300.0	0.00	0.00	1,300.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
1,400.0	0.00	0.00	1,400.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
1,500.0	0.00	0.00	1,500.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
1,600.0	0.00	0.00	1,600.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
1,700.0	0.00	0.00	1,700.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
1,800.0	0.00	0.00	1,800.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
1,900.0	0.00	0.00	1,900.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
2,000.0	0.00	0.00	2,000.0	-230.4	-1,970.0	32° 4' 44.202 N	103° 18' 7.322 W
2,100.0	2.00	156.00	2,100.0	-232.0	-1,969.3	32° 4' 44.186 N	103° 18' 7.314 W
2,200.0	4.00	156.00	2,199.8	-236.8	-1,967.1	32° 4' 44.139 N	103° 18' 7.290 W
2,300.0	6.00	156.00	2,299.5	-244.7	-1,963.6	32° 4' 44.060 N	103° 18' 7.249 W
2,400.0	6.00	156.00	2,398.9	-254.3	-1,959.4	32° 4' 43.965 N	103° 18' 7.201 W
2,500.0	6.00	156.00	2,498.4	-263.8	-1,955.1	32° 4' 43.870 N	103° 18' 7.153 W
2,600.0	6.00	156.00	2,597.8	-273.4	-1,950.9	32° 4' 43.775 N	103° 18' 7.104 W
2,700.0	6.00	156.00	2,697.3	-282.9	-1,946.6	32° 4' 43.680 N	103° 18' 7.056 W
2,800.0	6.00	156.00	2,796.7	-292.5	-1,942.3	32° 4' 43.585 N	103° 18' 7.008 W
2,900.0	6.00	156.00	2,896.2	-302.0	-1,938.1	32° 4' 43.490 N	103° 18' 6.959 W
3,000.0	6.00	156.00	2,995.6	-311.6	-1,933.8	32° 4' 43.395 N	103° 18' 6.911 W
3,100.0	6.00	156.00	3,095.1	-321.1	-1,929.6	32° 4' 43.300 N	103° 18' 6.863 W
3,200.0	6.00	156.00	3,194.5	-330.7	-1,925.3	32° 4' 43.206 N	103° 18' 6.814 W
3,300.0	6.00	156.00	3,294.0	-340.2	-1,921.1	32° 4' 43.111 N	103° 18' 6.766 W
3,400.0	6.00	156.00	3,393.4	-349.8	-1,916.8	32° 4' 43.016 N	103° 18' 6.718 W
3,500.0	6.00	156.00	3,492.9	-359.3	-1,912.6	32° 4' 42.921 N	103° 18' 6.669 W
3,600.0	6.00	156.00	3,592.3	-368.9	-1,908.3	32° 4' 42.826 N	103° 18' 6.621 W
3,700.0	6.00	156.00	3,691.8	-378.4	-1,904.1	32° 4' 42.731 N	103° 18' 6.573 W
3,800.0	6.00	156.00	3,791.2	-388.0	-1,899.8	32° 4' 42.636 N	103° 18' 6.524 W
3,900.0	6.00	156.00	3,890.7	-397.5	-1,895.6	32° 4' 42.541 N	103° 18' 6.476 W
4,000.0	6.00	156.00	3,990.1	-407.1	-1,891.3	32° 4' 42.446 N	103° 18' 6.428 W
4,100.0	6.00	156.00	4,089.6	-416.6	-1,887.1	32° 4' 42.352 N	103° 18' 6.379 W
4,200.0	6.00	156.00	4,189.0	-426.2	-1,882.8	32° 4' 42.257 N	103° 18' 6.331 W
4,300.0	6.00	156.00	4,288.5	-435.7	-1,878.6	32° 4' 42.162 N	103° 18' 6.282 W
4,400.0	6.00	156.00	4,387.9	-445.3	-1,874.3	32° 4' 42.067 N	103° 18' 6.234 W
4,500.0	6.00	156.00	4,487.4	-454.8	-1,870.1	32° 4' 41.972 N	103° 18' 6.186 W
4,600.0	6.00	156.00	4,586.9	-464.3	-1,865.8	32° 4' 41.877 N	103° 18' 6.137 W
4,700.0	6.00	156.00	4,686.3	-473.9	-1,861.6	32° 4' 41.782 N	103° 18' 6.089 W
4,800.0	6.00	156.00	4,785.8	-483.4	-1,857.3	32° 4' 41.687 N	103° 18' 6.041 W
4,900.0	6.00	156.00	4,885.2	-493.0	-1,853.1	32° 4' 41.592 N	103° 18' 5.992 W
5,000.0	6.00	156.00	4,984.7	-502.5	-1,848.8	32° 4' 41.498 N	103° 18' 5.944 W
5,100.0	6.00	156.00	5,084.1	-512.1	-1,844.6	32° 4' 41.403 N	103° 18' 5.896 W
5,200.0	6.00	156.00	5,183.6	-521.6	-1,840.3	32° 4' 41.308 N	103° 18' 5.847 W
5,300.0	6.00	156.00	5,283.0	-531.2	-1,836.1	32° 4' 41.213 N	103° 18' 5.799 W
5,400.0	6.00	156.00	5,382.5	-540.7	-1,831.8	32° 4' 41.118 N	103° 18' 5.751 W
5,500.0	6.00	156.00	5,481.9	-550.3	-1,827.6	32° 4' 41.023 N	103° 18' 5.702 W

Company:	Ameredev Operating, LLC.	Local Co-ordinate Reference:	Well Nandina 085H
Project:	NAN/GB	TVD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	MD Reference:	KB @ 3038.0usft
Well:	Nandina 085H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Design #1	Database:	EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL-FNL (usft)	+FWL-FEL (usft)	Latitude	Longitude
5,600.0	6.00	156.00	5,581.4	-559.8	-1,823.3	32° 4' 40.928 N	103° 18' 5.654 W
5,700.0	6.00	156.00	5,680.8	-569.4	-1,819.1	32° 4' 40.833 N	103° 18' 5.606 W
5,800.0	6.00	156.00	5,780.3	-578.9	-1,814.8	32° 4' 40.738 N	103° 18' 5.557 W
5,900.0	6.00	156.00	5,879.7	-588.5	-1,810.5	32° 4' 40.644 N	103° 18' 5.509 W
6,000.0	6.00	156.00	5,979.2	-598.0	-1,806.3	32° 4' 40.549 N	103° 18' 5.461 W
6,100.0	6.00	156.00	6,078.6	-607.6	-1,802.0	32° 4' 40.454 N	103° 18' 5.412 W
6,200.0	6.00	156.00	6,178.1	-617.1	-1,797.8	32° 4' 40.359 N	103° 18' 5.364 W
6,300.0	6.00	156.00	6,277.5	-626.7	-1,793.5	32° 4' 40.264 N	103° 18' 5.316 W
6,400.0	6.00	156.00	6,377.0	-636.2	-1,789.3	32° 4' 40.169 N	103° 18' 5.267 W
6,500.0	6.00	156.00	6,476.4	-645.8	-1,785.0	32° 4' 40.074 N	103° 18' 5.219 W
6,600.0	6.00	156.00	6,575.9	-655.3	-1,780.8	32° 4' 39.979 N	103° 18' 5.171 W
6,700.0	6.00	156.00	6,675.3	-664.9	-1,776.5	32° 4' 39.884 N	103° 18' 5.122 W
6,724.8	6.00	156.00	6,700.0	-667.2	-1,775.5	32° 4' 39.861 N	103° 18' 5.110 W
6,800.0	4.50	156.00	6,774.9	-673.5	-1,772.7	32° 4' 39.798 N	103° 18' 5.078 W
6,900.0	2.50	156.00	6,874.7	-679.1	-1,770.2	32° 4' 39.743 N	103° 18' 5.050 W
7,000.0	0.50	156.00	6,974.7	-681.5	-1,769.1	32° 4' 39.719 N	103° 18' 5.038 W
7,024.8	0.00	0.00	6,999.5	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,100.0	0.00	0.00	7,074.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,200.0	0.00	0.00	7,174.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,300.0	0.00	0.00	7,274.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,400.0	0.00	0.00	7,374.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,500.0	0.00	0.00	7,474.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,600.0	0.00	0.00	7,574.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,700.0	0.00	0.00	7,674.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,800.0	0.00	0.00	7,774.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
7,900.0	0.00	0.00	7,874.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,000.0	0.00	0.00	7,974.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,100.0	0.00	0.00	8,074.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,200.0	0.00	0.00	8,174.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,300.0	0.00	0.00	8,274.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,400.0	0.00	0.00	8,374.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,500.0	0.00	0.00	8,474.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,600.0	0.00	0.00	8,574.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,700.0	0.00	0.00	8,674.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,800.0	0.00	0.00	8,774.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
8,900.0	0.00	0.00	8,874.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,000.0	0.00	0.00	8,974.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,100.0	0.00	0.00	9,074.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,200.0	0.00	0.00	9,174.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,300.0	0.00	0.00	9,274.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,400.0	0.00	0.00	9,374.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,500.0	0.00	0.00	9,474.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,600.0	0.00	0.00	9,574.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,700.0	0.00	0.00	9,674.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W

Company:	Ameredev Operating, LLC.	Local Co-ordinate Reference:	Well Nandina 085H
Project:	NAN/GB	TVD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	MD Reference:	KB @ 3038.0usft
Well:	Nandina 085H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Design #1	Database:	EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	Latitude	Longitude
9,800.0	0.00	0.00	9,774.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
9,900.0	0.00	0.00	9,874.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
10,000.0	0.00	0.00	9,974.7	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
10,065.3	0.00	0.00	10,040.0	-681.6	-1,769.1	32° 4' 39.718 N	103° 18' 5.038 W
Nan085 KOP							
10,100.0	4.16	346.29	10,074.6	-680.4	-1,769.4	32° 4' 39.731 N	103° 18' 5.041 W
10,200.0	16.16	346.29	10,172.9	-663.3	-1,773.6	32° 4' 39.900 N	103° 18' 5.088 W
10,300.0	28.16	346.29	10,265.3	-626.7	-1,782.5	32° 4' 40.263 N	103° 18' 5.187 W
10,400.0	40.16	346.29	10,347.9	-572.2	-1,795.8	32° 4' 40.803 N	103° 18' 5.335 W
10,500.0	52.16	346.29	10,417.1	-502.3	-1,812.8	32° 4' 41.497 N	103° 18' 5.526 W
10,600.0	64.16	346.29	10,469.7	-419.9	-1,832.9	32° 4' 42.314 N	103° 18' 5.750 W
10,700.0	76.16	346.29	10,503.6	-328.7	-1,855.2	32° 4' 43.218 N	103° 18' 5.999 W
10,800.0	88.16	346.29	10,517.2	-232.6	-1,878.6	32° 4' 44.171 N	103° 18' 6.261 W
10,812.5	89.66	346.29	10,517.5	-220.5	-1,881.6	32° 4' 44.291 N	103° 18' 6.294 W
10,900.0	89.66	346.29	10,518.0	-135.5	-1,902.3	32° 4' 45.135 N	103° 18' 6.525 W
11,000.0	89.66	346.29	10,518.6	-38.3	-1,926.0	32° 4' 46.098 N	103° 18' 6.790 W
11,039.4	89.66	346.29	10,518.8	0.0	-1,935.4	32° 4' 46.478 N	103° 18' 6.894 W
Nan085 into NMNM137469							
11,100.0	89.66	346.29	10,519.2	58.8	-1,949.7	32° 4' 47.062 N	103° 18' 7.054 W
11,147.5	89.66	346.29	10,519.4	105.0	-1,961.0	32° 4' 47.519 N	103° 18' 7.180 W
Nan085 FTP							
11,185.2	89.66	346.29	10,519.7	141.6	-1,969.9	32° 4' 47.882 N	103° 18' 7.280 W
11,200.0	89.70	348.07	10,519.8	156.0	-1,973.2	32° 4' 48.026 N	103° 18' 7.316 W
11,294.7	90.00	359.43	10,520.0	250.0	-1,983.5	32° 4' 48.957 N	103° 18' 7.426 W
Nan085 FTP2							
11,300.0	90.00	359.43	10,520.0	255.3	-1,983.5	32° 4' 49.009 N	103° 18' 7.426 W
11,400.0	90.00	359.43	10,520.0	355.3	-1,984.5	32° 4' 49.999 N	103° 18' 7.426 W
11,500.0	90.00	359.43	10,520.0	455.3	-1,985.5	32° 4' 50.988 N	103° 18' 7.427 W
11,600.0	90.00	359.43	10,520.0	555.3	-1,986.5	32° 4' 51.978 N	103° 18' 7.427 W
11,700.0	90.00	359.43	10,520.0	655.3	-1,987.5	32° 4' 52.967 N	103° 18' 7.427 W
11,800.0	90.00	359.43	10,520.0	755.3	-1,988.5	32° 4' 53.957 N	103° 18' 7.428 W
11,900.0	90.00	359.43	10,520.0	855.3	-1,989.5	32° 4' 54.946 N	103° 18' 7.428 W
12,000.0	90.00	359.43	10,520.0	955.3	-1,990.5	32° 4' 55.936 N	103° 18' 7.429 W
12,100.0	90.00	359.43	10,520.0	1,055.3	-1,991.5	32° 4' 56.925 N	103° 18' 7.429 W
12,200.0	90.00	359.43	10,520.0	1,155.3	-1,992.5	32° 4' 57.915 N	103° 18' 7.430 W
12,300.0	90.00	359.43	10,520.0	1,255.3	-1,993.5	32° 4' 58.904 N	103° 18' 7.430 W
12,364.7	90.00	359.43	10,520.0	1,320.0	-1,994.1	32° 4' 59.544 N	103° 18' 7.430 W
Nan085 into NMNM119762							
12,400.0	90.00	359.43	10,520.0	1,355.3	-1,994.5	32° 4' 59.894 N	103° 18' 7.431 W
12,500.0	90.00	359.43	10,520.0	1,455.3	-1,995.5	32° 5' 0.883 N	103° 18' 7.431 W
12,600.0	90.00	359.43	10,520.0	1,555.2	-1,996.5	32° 5' 1.873 N	103° 18' 7.432 W
12,700.0	90.00	359.43	10,520.0	1,655.2	-1,997.5	32° 5' 2.862 N	103° 18' 7.432 W
12,800.0	90.00	359.43	10,520.0	1,755.2	-1,998.5	32° 5' 3.852 N	103° 18' 7.432 W
12,900.0	90.00	359.43	10,520.0	1,855.2	-1,999.5	32° 5' 4.841 N	103° 18' 7.433 W
13,000.0	90.00	359.43	10,520.0	1,955.2	-2,000.5	32° 5' 5.831 N	103° 18' 7.433 W

Company:	Ameredev Operating, LLC.	Local Co-ordinate Reference:	Well Nandina 085H
Project:	NAN/GB	TVD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	MD Reference:	KB @ 3038.0usft
Well:	Nandina 085H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Design #1	Database:	EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	Latitude	Longitude
13,100.0	90.00	359.43	10,520.0	2,055.2	-2,001.5	32° 5' 6.820 N	103° 18' 7.434 W
13,200.0	90.00	359.43	10,520.0	2,155.2	-2,002.5	32° 5' 7.810 N	103° 18' 7.434 W
13,300.0	90.00	359.43	10,520.0	2,255.2	-2,003.5	32° 5' 8.799 N	103° 18' 7.435 W
13,400.0	90.00	359.43	10,520.0	2,355.2	-2,004.5	32° 5' 9.789 N	103° 18' 7.435 W
13,500.0	90.00	359.43	10,520.0	2,455.2	-2,005.4	32° 5' 10.778 N	103° 18' 7.436 W
13,600.0	90.00	359.43	10,520.0	2,555.2	-2,006.4	32° 5' 11.768 N	103° 18' 7.436 W
13,700.0	90.00	359.43	10,520.0	2,655.2	-2,007.4	32° 5' 12.757 N	103° 18' 7.437 W
13,800.0	90.00	359.43	10,520.0	2,755.2	-2,008.4	32° 5' 13.747 N	103° 18' 7.437 W
13,900.0	90.00	359.43	10,520.0	2,855.2	-2,009.4	32° 5' 14.736 N	103° 18' 7.438 W
14,000.0	90.00	359.43	10,520.0	2,955.2	-2,010.4	32° 5' 15.726 N	103° 18' 7.438 W
14,100.0	90.00	359.43	10,520.0	3,055.2	-2,011.4	32° 5' 16.715 N	103° 18' 7.438 W
14,200.0	90.00	359.43	10,520.0	3,155.2	-2,012.4	32° 5' 17.705 N	103° 18' 7.439 W
14,300.0	90.00	359.43	10,520.0	3,255.2	-2,013.4	32° 5' 18.694 N	103° 18' 7.439 W
14,400.0	90.00	359.43	10,520.0	3,355.2	-2,014.4	32° 5' 19.684 N	103° 18' 7.440 W
14,500.0	90.00	359.43	10,520.0	3,455.2	-2,015.4	32° 5' 20.673 N	103° 18' 7.440 W
14,600.0	90.00	359.43	10,520.0	3,555.1	-2,016.4	32° 5' 21.663 N	103° 18' 7.441 W
14,700.0	90.00	359.43	10,520.0	3,655.1	-2,017.4	32° 5' 22.652 N	103° 18' 7.441 W
14,800.0	90.00	359.43	10,520.0	3,755.1	-2,018.4	32° 5' 23.642 N	103° 18' 7.442 W
14,900.0	90.00	359.43	10,520.0	3,855.1	-2,019.4	32° 5' 24.632 N	103° 18' 7.442 W
15,000.0	90.00	359.43	10,520.0	3,955.1	-2,020.4	32° 5' 25.621 N	103° 18' 7.443 W
15,100.0	90.00	359.43	10,520.0	4,055.1	-2,021.4	32° 5' 26.611 N	103° 18' 7.443 W
15,200.0	90.00	359.43	10,520.0	4,155.1	-2,022.4	32° 5' 27.600 N	103° 18' 7.444 W
15,300.0	90.00	359.43	10,520.0	4,255.1	-2,023.4	32° 5' 28.590 N	103° 18' 7.444 W
15,400.0	90.00	359.43	10,520.0	4,355.1	-2,024.4	32° 5' 29.579 N	103° 18' 7.444 W
15,500.0	90.00	359.43	10,520.0	4,455.1	-2,025.4	32° 5' 30.569 N	103° 18' 7.445 W
15,600.0	90.00	359.43	10,520.0	4,555.1	-2,026.4	32° 5' 31.558 N	103° 18' 7.445 W
15,700.0	90.00	359.43	10,520.0	4,655.1	-2,027.4	32° 5' 32.548 N	103° 18' 7.446 W
15,800.0	90.00	359.43	10,520.0	4,755.1	-2,028.3	32° 5' 33.537 N	103° 18' 7.446 W
15,900.0	90.00	359.43	10,520.0	4,855.1	-2,029.3	32° 5' 34.527 N	103° 18' 7.447 W
16,000.0	90.00	359.43	10,520.0	4,955.1	-2,030.3	32° 5' 35.516 N	103° 18' 7.447 W
16,100.0	90.00	359.43	10,520.0	5,055.1	-2,031.3	32° 5' 36.506 N	103° 18' 7.448 W
16,200.0	90.00	359.43	10,520.0	5,155.1	-2,032.3	32° 5' 37.495 N	103° 18' 7.448 W
16,300.0	90.00	359.43	10,520.0	5,255.1	-2,033.3	32° 5' 38.485 N	103° 18' 7.449 W
16,400.0	90.00	359.43	10,520.0	5,355.1	-2,034.3	32° 5' 39.474 N	103° 18' 7.449 W
16,500.0	90.00	359.43	10,520.0	5,455.1	-2,035.3	32° 5' 40.464 N	103° 18' 7.449 W
16,600.0	90.00	359.43	10,520.0	5,555.0	-2,036.3	32° 5' 41.453 N	103° 18' 7.450 W
16,700.0	90.00	359.43	10,520.0	5,655.0	-2,037.3	32° 5' 42.443 N	103° 18' 7.450 W
16,800.0	90.00	359.43	10,520.0	5,755.0	-2,038.3	32° 5' 43.432 N	103° 18' 7.451 W
16,900.0	90.00	359.43	10,520.0	5,855.0	-2,039.3	32° 5' 44.422 N	103° 18' 7.451 W
17,000.0	90.00	359.43	10,520.0	5,955.0	-2,040.3	32° 5' 45.411 N	103° 18' 7.452 W
17,100.0	90.00	359.43	10,520.0	6,055.0	-2,041.3	32° 5' 46.401 N	103° 18' 7.452 W
17,200.0	90.00	359.43	10,520.0	6,155.0	-2,042.3	32° 5' 47.390 N	103° 18' 7.453 W
17,300.0	90.00	359.43	10,520.0	6,255.0	-2,043.3	32° 5' 48.380 N	103° 18' 7.453 W
17,400.0	90.00	359.43	10,520.0	6,355.0	-2,044.3	32° 5' 49.369 N	103° 18' 7.454 W
17,500.0	90.00	359.43	10,520.0	6,455.0	-2,045.3	32° 5' 50.359 N	103° 18' 7.454 W

Company:	Ameredev Operating, LLC.	Local Co-ordinate Reference:	Well Nandina 085H
Project:	NAN/GB	TVD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	MD Reference:	KB @ 3038.0usft
Well:	Nandina 085H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Design #1	Database:	EDM5000

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	Latitude	Longitude
17,600.0	90.00	359.43	10,520.0	6,555.0	-2,046.3	32° 5' 51.348 N	103° 18' 7.455 W
17,700.0	90.00	359.43	10,520.0	6,655.0	-2,047.3	32° 5' 52.338 N	103° 18' 7.455 W
17,800.0	90.00	359.43	10,520.0	6,755.0	-2,048.3	32° 5' 53.327 N	103° 18' 7.455 W
17,900.0	90.00	359.43	10,520.0	6,855.0	-2,049.3	32° 5' 54.317 N	103° 18' 7.456 W
18,000.0	90.00	359.43	10,520.0	6,955.0	-2,050.3	32° 5' 55.306 N	103° 18' 7.456 W
18,100.0	90.00	359.43	10,520.0	7,055.0	-2,051.3	32° 5' 56.296 N	103° 18' 7.457 W
18,200.0	90.00	359.43	10,520.0	7,155.0	-2,052.2	32° 5' 57.285 N	103° 18' 7.457 W
18,300.0	90.00	359.43	10,520.0	7,255.0	-2,053.2	32° 5' 58.275 N	103° 18' 7.458 W
18,400.0	90.00	359.43	10,520.0	7,355.0	-2,054.2	32° 5' 59.264 N	103° 18' 7.458 W
18,500.0	90.00	359.43	10,520.0	7,455.0	-2,055.2	32° 6' 0.254 N	103° 18' 7.459 W
18,600.0	90.00	359.43	10,520.0	7,554.9	-2,056.2	32° 6' 1.243 N	103° 18' 7.459 W
18,700.0	90.00	359.43	10,520.0	7,654.9	-2,057.2	32° 6' 2.233 N	103° 18' 7.460 W
18,800.0	90.00	359.43	10,520.0	7,754.9	-2,058.2	32° 6' 3.222 N	103° 18' 7.460 W
18,900.0	90.00	359.43	10,520.0	7,854.9	-2,059.2	32° 6' 4.212 N	103° 18' 7.460 W
19,000.0	90.00	359.43	10,520.0	7,954.9	-2,060.2	32° 6' 5.201 N	103° 18' 7.461 W
19,100.0	90.00	359.43	10,520.0	8,054.9	-2,061.2	32° 6' 6.191 N	103° 18' 7.461 W
19,200.0	90.00	359.43	10,520.0	8,154.9	-2,062.2	32° 6' 7.180 N	103° 18' 7.462 W
19,300.0	90.00	359.43	10,520.0	8,254.9	-2,063.2	32° 6' 8.170 N	103° 18' 7.462 W
19,400.0	90.00	359.43	10,520.0	8,354.9	-2,064.2	32° 6' 9.159 N	103° 18' 7.463 W
19,500.0	90.00	359.43	10,520.0	8,454.9	-2,065.2	32° 6' 10.149 N	103° 18' 7.463 W
19,600.0	90.00	359.43	10,520.0	8,554.9	-2,066.2	32° 6' 11.139 N	103° 18' 7.464 W
19,700.0	90.00	359.43	10,520.0	8,654.9	-2,067.2	32° 6' 12.128 N	103° 18' 7.464 W
19,800.0	90.00	359.43	10,520.0	8,754.9	-2,068.2	32° 6' 13.118 N	103° 18' 7.465 W
19,900.0	90.00	359.43	10,520.0	8,854.9	-2,069.2	32° 6' 14.107 N	103° 18' 7.465 W
20,000.0	90.00	359.43	10,520.0	8,954.9	-2,070.2	32° 6' 15.097 N	103° 18' 7.465 W
20,100.0	90.00	359.43	10,520.0	9,054.9	-2,071.2	32° 6' 16.086 N	103° 18' 7.466 W
20,200.0	90.00	359.43	10,520.0	9,154.9	-2,072.2	32° 6' 17.076 N	103° 18' 7.466 W
20,300.0	90.00	359.43	10,520.0	9,254.9	-2,073.2	32° 6' 18.065 N	103° 18' 7.467 W
20,400.0	90.00	359.43	10,520.0	9,354.9	-2,074.2	32° 6' 19.055 N	103° 18' 7.467 W
20,500.0	90.00	359.43	10,520.0	9,454.9	-2,075.1	32° 6' 20.044 N	103° 18' 7.468 W
20,600.0	90.00	359.43	10,520.0	9,554.8	-2,076.1	32° 6' 21.034 N	103° 18' 7.468 W
20,700.0	90.00	359.43	10,520.0	9,654.8	-2,077.1	32° 6' 22.023 N	103° 18' 7.469 W
20,800.0	90.00	359.43	10,520.0	9,754.8	-2,078.1	32° 6' 23.013 N	103° 18' 7.469 W
20,900.0	90.00	359.43	10,520.0	9,854.8	-2,079.1	32° 6' 24.002 N	103° 18' 7.470 W
21,000.0	90.00	359.43	10,520.0	9,954.8	-2,080.1	32° 6' 24.992 N	103° 18' 7.470 W
21,100.0	90.00	359.43	10,520.0	10,054.8	-2,081.1	32° 6' 25.981 N	103° 18' 7.470 W
21,200.0	90.00	359.43	10,520.0	10,154.8	-2,082.1	32° 6' 26.971 N	103° 18' 7.471 W
21,300.0	90.00	359.43	10,520.0	10,254.8	-2,083.1	32° 6' 27.960 N	103° 18' 7.471 W
21,400.0	90.00	359.43	10,520.0	10,354.8	-2,084.1	32° 6' 28.950 N	103° 18' 7.472 W
21,500.0	90.00	359.43	10,520.0	10,454.8	-2,085.1	32° 6' 29.939 N	103° 18' 7.472 W
Nan085 LTP							
21,559.2	90.00	359.43	10,520.0	10,514.0	-2,085.7	32° 6' 30.525 N	103° 18' 7.473 W
Nan085 BHL							

Company:	Ameredev Operating, LLC.	Local Co-ordinate Reference:	Well Nandina 085H
Project:	NAN/GB	TVD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	MD Reference:	KB @ 3038.0usft
Well:	Nandina 085H	North Reference:	Grid
Wellbore:	Wellbore #1	Survey Calculation Method:	Minimum Curvature
Design:	Design #1	Database:	EDM5000

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
10,065.3	10,040.0	-451.2	200.9	Nan085 KOP
11,039.4	10,518.8	230.3	34.6	Nan085 into NMNM137469
12,364.7	10,520.0	1,550.3	-24.2	Nan085 into NMNM119762

Checked By: _____ Approved By: _____ Date: _____



APD ID: 10400033015

Submission Date: 08/29/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - General

Would you like to address long-term produced water disposal? NO

Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Lined pit Monitor description:

Lined pit Monitor attachment:

Lined pit: do you have a reclamation bond for the pit?

Is the reclamation bond a rider under the BLM bond?

Lined pit bond number:

Lined pit bond amount:

Additional bond information attachment:

Section 3 - Unlined Pits

Would you like to utilize Unlined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD disturbance (acres):

PWD surface owner:

Unlined pit PWD on or off channel:

Unlined pit PWD discharge volume (bbl/day):

Unlined pit specifications:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Unlined pit precipitated solids disposal schedule:

Unlined pit precipitated solids disposal schedule attachment:

Unlined pit reclamation description:

Unlined pit reclamation attachment:

Unlined pit Monitor description:

Unlined pit Monitor attachment:

Do you propose to put the produced water to beneficial use?

Beneficial use user confirmation:

Estimated depth of the shallowest aquifer (feet):

Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?

TDS lab results:

Geologic and hydrologic evidence:

State authorization:

Unlined Produced Water Pit Estimated percolation:

Unlined pit: do you have a reclamation bond for the pit?

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Is the reclamation bond a rider under the BLM bond?

Unlined pit bond number:

Unlined pit bond amount:

Additional bond information attachment:

Section 4 - Injection

Would you like to utilize Injection PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Injection PWD discharge volume (bbl/day):

Injection well mineral owner:

Injection well type:

Injection well number:

Injection well name:

Assigned injection well API number?

Injection well API number:

Injection well new surface disturbance (acres):

Minerals protection information:

Mineral protection attachment:

Underground Injection Control (UIC) Permit?

UIC Permit attachment:

Section 5 - Surface Discharge

Would you like to utilize Surface Discharge PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Surface discharge PWD discharge volume (bbl/day):

Surface Discharge NPDES Permit?

Surface Discharge NPDES Permit attachment:

Surface Discharge site facilities information:

Surface discharge site facilities map:

Section 6 - Other

Would you like to utilize Other PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Other PWD type description:

Other PWD type attachment:

Have other regulatory requirements been met?

Other regulatory requirements attachment:



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Bond Info Data Report

02/28/2020

APD ID: 10400033015

Submission Date: 08/29/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: NANDINA FED COM 25 36 31

Well Number: 085H

Well Type: OIL WELL

Well Work Type: Drill

[Show Final Text](#)

Bond Information

Federal/Indian APD: FED

BLM Bond number: NMB001478

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment: