

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
APPLICATION FOR PERMIT TO DRILL OR REENTER

**HOBBS OCD**  
MAY 5 2020  
**RECEIVED**

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER 1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		5. Lease Serial No. NMNM137471 6. If Indian, Allottee or Tribe Name 7. If Unit or CA Agreement, Name and No. 8. Lease Name and Well No. GOLDEN BELL FED COM 26 36 06 095H 322777 9. API Well No. 20-025-46940
2. Name of Operator AMEREDEV OPERATING LLC (372224)		10. Field and Pool, or Exploratory WC-025 G-08 S263620C+LWR BONE SI 97088
3a. Address 5707 Southwest Parkway, Building 1, Suite 275 Austin TX	3b. Phone No. (include area code) (737)300-4700	11. Sec., T. R. M. or Blk. and Survey or Area SEC 6 / T26S / R36E / NMP
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface LOT B / 230 FNL / 1990 FEL / LAT 32.0789449 / LONG -103.3020985 At proposed prod. zone LOT O / 200 FSL / 1980 FEL / LAT 32.0514412 / LONG -103.3020226		12. County or Parish LEA 13. State NM
14. Distance in miles and direction from nearest town or post office* 6.5 miles		15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 200 feet 16. No of acres in lease 360 17. Spacing Unit dedicated to this well 320
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 2920 feet		19. Proposed Depth 11650 feet / 21421 feet 20. BLM/BIA Bond No. in file FED: NMB001478
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3011 feet	22. Approximate date work will start* 08/23/2020	23. Estimated duration 90 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification.  |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM.            |

25. Signature (Electronic Submission)	Name (Printed/Typed) Julia Steger / Ph: (737)300-4733	Date 08/31/2018
Title Engineer		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Cody Layton / Ph: (575)234-5959	Date 02/26/2020
Title Assistant Field Manager Lands & Minerals Office CARLSBAD		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*OCP Rec 03/07/2020*

*Kaz 03/06/2020*

**APPROVED WITH CONDITIONS**  
Approval Date: 02/26/2020

**PECOS DISTRICT  
DRILLING CONDITIONS OF APPROVAL**

<b>OPERATOR'S NAME:</b>	AMEREDEV OPERATING LLC
<b>WELL NAME &amp; NO.:</b>	NMNM137471
<b>SURFACE HOLE FOOTAGE:</b>	GOLDEN BELL FED COM 26 36 06 095H
<b>BOTTOM HOLE FOOTAGE:</b>	230'/N & 2010'/E
<b>LOCATION:</b>	200'/S & 1980'/E
<b>COUNTY:</b>	SECTION 6, T26S, R36E, NMPM

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input type="radio"/> Multibowl	<input checked="" type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input checked="" type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

**A. HYDROGEN SULFIDE**

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

**B. CASING**

1. The 13-3/8 inch surface casing shall be set at approximately 1,415 feet (a minimum of 25 feet (Lea County) into the Rustler Anhydrite and above the salt) and cemented to the surface. Surface casing depth may change depth based off competent bedding. If salt is encountered, set casing at least 25 feet above the salt.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.

- b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the Choose an item. inch intermediate casing is:

**Option 1 (Single Stage):**

- Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**

**Option 2:**

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
  - b. Second stage above DV tool:
    - Cement to surface. If cement does not circulate, contact the appropriate BLM office. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**
- ❖ In Capitan Reef Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
  - ❖ **Special Capitan Reef requirements.** If lost circulation (50% or greater) occurs below the Base of the Salt, the operator shall do the following: **(Use this for 3 string wells in the Capitan Reef, if 4 string well ensure FW based mud used across the capitan interval)**
    - Switch to fresh water mud to protect the Capitan Reef and use fresh water mud until setting the intermediate casing. The appropriate BLM office is to be notified for a PET to witness the switch to fresh water.

- Daily drilling reports from the Base of the Salt to the setting of the intermediate casing are to be submitted to the BLM CFO engineering staff via e-mail by 0800 hours each morning. Any lost circulation encountered is to be recorded on these drilling reports. The daily drilling report should show mud volume per shift/tour. Failure to submit these reports will result in an Incidence of Non-Compliance being issued for failure to comply with the Conditions of Approval. If not already planned, the operator shall run a caliper survey for the intermediate well bore and submit to the appropriate BLM office.

3. The minimum required fill of cement behind the Choose an item. inch production casing is:

**Option 1 (Single Stage):**

- Cement should tie-back at least **50 feet** on top of Capitan Reef top. If cement does not circulate see B.1.a, c-d above.  
**Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**

**Option 2:**

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.

- b. Second stage above DV tool:

- Cement should tie-back at least **50 feet** on top of Capitan Reef top. If cement does not circulate see B.1.a, c-d above.  
**Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**

4. The minimum required fill of cement behind the Choose an item. inch production liner is:

- Cement should tie-back **100 feet** into the previous casing. Operator shall provide method of verification.

**C. PRESSURE CONTROL**

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
- 2.

**Option 1:**

- a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be Choose an item. psi.
- b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be Choose an item. psi. **Variance is approved to use a Choose an item. Annular which shall be tested to Choose an item. psi.**

**Option 2:**

1. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be Choose an item. psi. **Variance is approved to use a Choose an item. Annular which shall be tested to Choose an item. psi.**
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

**D. SPECIAL REQUIREMENT (S)**

**Communitization Agreement**

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases

subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.

- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

## **GENERAL REQUIREMENTS**

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
(575) 361-2822

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)  
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.

2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

**B. PRESSURE CONTROL**

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

- e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
  - b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
  - c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
  - d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
  - e. The results of the test shall be reported to the appropriate BLM office.
  - f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.

- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

**C. DRILLING MUD**

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

**D. WASTE MATERIAL AND FLUIDS**

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Operator Certification Data Report

02/28/2020

## Operator Certification

*I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.*

**NAME:** Christie Hanna

**Signed on:** 08/09/2018

**Title:** Senior Engineering Technician

**Street Address:** 5707 SOUTHWEST PKWY BLDG 1 STE 275

**City:** AUSTIN

**State:** TX

**Zip:** 78735

**Phone:** (737)300-4723

**Email address:** channa@amerdev.com

## Field Representative

**Representative Name:** ZACHARY BOYD

**Street Address:** 5707 SOUTHWEST PARKWAY, BLDG. 1 #275

**City:** AUSTIN

**State:** TX

**Zip:** 78735

**Phone:** (580)940-5054

**Email address:** zboyd@amerdev.com



APD ID: 10400032962

Submission Date: 08/31/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: GOLDEN BELL FED COM 26 36 06

Well Number: 095H

Well Type: OIL WELL

Well Work Type: Drill



Show Final Text

**Section 1 - General**

APD ID: 10400032962

Tie to previous NOS? Y

Submission Date: 08/31/2018

BLM Office: CARLSBAD

User: Christie Hanna

Title: Senior Engineering Technician

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM137471

Lease Acres: 360

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? NO

Permitting Agent? NO

APD Operator: AMEREDEV OPERATING LLC

Operator letter of designation:

**Operator Info**

Operator Organization Name: AMEREDEV OPERATING LLC

Operator Address: 5707 Southwest Parkway, Building 1, Suite 275

Zip: 78735

Operator PO Box:

Operator City: Austin

State: TX

Operator Phone: (737)300-4700

Operator Internet Address:

**Section 2 - Well Information**

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: GOLDEN BELL FED COM 26 36 06

Well Number: 095H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: WC-025 G-08  
S263620C

Pool Name: LWR BONE  
SPRING

Is the proposed well in an area containing other mineral resources? USEABLE WATER NATURAL GAS CO2 OIL

**Operator Name:** AMEREDEV OPERATING LLC

**Well Name:** GOLDEN BELL FED COM 26 36 06

**Well Number:** 095H

**Is the proposed well in an area containing other mineral resources?** USEABLE WATER,NATURAL GAS,CO2,OIL

**Is the proposed well in a Helium production area?** N    **Use Existing Well Pad?** NO    **New surface disturbance?**

**Type of Well Pad:** MULTIPLE WELL

**Multiple Well Pad Name:**

**Number:** 095H

**Well Class:** HORIZONTAL

GOLDEN BELL

**Number of Legs:** 1

**Well Work Type:** Drill

**Well Type:** OIL WELL

**Describe Well Type:**

**Well sub-Type:** INFILL

**Describe sub-type:**

**Distance to town:** 6.5 Miles

**Distance to nearest well:** 2920 FT

**Distance to lease line:** 200 FT

**Reservoir well spacing assigned acres Measurement:** 320 Acres

**Well plat:** GOLDEN\_BELL\_FED\_COM\_26\_36\_06\_095H\_\_C102\_SIGNED\_20180809124911.pdf

GOLDEN\_BELL\_FED\_COM\_26\_36\_06\_095H\_\_BLM\_LEASES\_20180809124929.pdf

GOLDEN\_BELL\_FED\_COM\_26\_36\_06\_095H\_\_GAS\_CAPTURE\_PLAN\_20180809125037.pdf

GOLDEN\_BELL\_FED\_COM\_26\_36\_06\_095H\_\_EXHIBIT\_2A\_\_2B\_20180827080101.pdf

GOLDEN\_BELL\_FED\_COM\_26\_36\_06\_095H\_\_VICINITY\_MAP\_20180831095327.pdf

**Well work start Date:** 08/23/2020

**Duration:** 90 DAYS

### Section 3 - Well Location Table

**Survey Type:** RECTANGULAR

**Describe Survey Type:**

**Datum:** NAD83

**Vertical Datum:** NAVD88

**Survey number:** 19642

**Reference Datum:**

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
SHL Leg #1	230	FNL	199 0	FEL	26S	36E	6	Lot B	32.07894 49	- 103.3020 985	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 137471	301 1	0	0	

Operator Name: AMEREDEV OPERATING LLC

Well Name: GOLDEN BELL FED COM 26 36 06

Well Number: 095H

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
KOP Leg #1	354	FNL	1947	FEL	26S	36E	6	Aliquot NWNE	32.0786054	-103.3019588	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 137471	-8066	11080	11077	
PPP Leg #1-1	0	FSL	1980	FEL	26S	36E	6	Aliquot SWSE	32.0650574	-103.3020469	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 137471	-8639	16337	11650	
PPP Leg #1-2	230	FNL	1990	FEL	26S	36E	6	Lot B	32.0789449	-103.3020985	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 137471	3011	0	0	
EXIT Leg #1	0	FNL	1980	FEL	26S	36E	7	Aliquot NWNE	32.0650574	-103.3020469	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 137472	-8639	16337	11650	
BHL Leg #1	200	FSL	1980	FEL	26S	36E	7	Lot O	32.0514412	-103.3020226	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 137472	-8639	21421	11650	



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Drilling Plan Data Report

02/23/2020

APD ID: 10400032962

Submission Date: 08/31/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: GOLDEN BELL FED COM 26 36 06

Well Number: 095H

Show Final Text

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - Geologic Formations

283210	RUSTLER	1948	1066	1066	ANHYDRITE	NONE	N
283211	SALADO	442	1506	1506	SALT	NONE	N
283212	TANSILL	-1286	3234	3234	LIMESTONE	NONE	N
283213	CAPITAN REEF	-1789	3737	3737	LIMESTONE	USEABLE WATER	N
283214	LAMAR	-3085	5033	5033	LIMESTONE	NONE	N
283215	BELL CANYON	-3120	5068	5068	SANDSTONE	NATURAL GAS, OIL	N
283216	BRUSHY CANYON	-5163	7111	7111	SANDSTONE	NATURAL GAS, OIL	N
283228	BONE SPRING LIME	-6388	8336	8336	LIMESTONE	NONE	N
283243	BONE SPRING 1ST	-7764	9712	9712	SANDSTONE	NATURAL GAS, OIL	N
283250	BONE SPRING 2ND	-8323	10271	10271	SANDSTONE	NATURAL GAS, OIL	N
283267	BONE SPRING 3RD	-8910	10858	10858	LIMESTONE	NATURAL GAS, OIL	N
283280	BONE SPRING 3RD	-9508	11456	11456	SANDSTONE	NATURAL GAS, OIL	Y

## Section 2 - Blowout Prevention

Rating Depth: 15000

Requesting Variance? YES

Testina Procedure: See attachment

Operator Name: AMEREDEV OPERATING LLC

Well Name: GOLDEN BELL FED COM 26 36 06

Well Number: 095H

**Choke Diagram Attachment:**

10M\_Choke\_Manifold\_REV\_20191119152613.pdf

**BOP Diagram Attachment:**

5M\_Annular\_Preventer\_Variance\_and\_Well\_Control\_Plan\_20191119152628.pdf

5M\_BOP\_System\_20191119152629.pdf

Pressure\_Control\_Plan\_Single\_Well\_MB4\_3String\_Big\_Hole\_BLM\_20191119152629.pdf

4\_String\_MB\_Ameredev\_Wellhead\_Drawing\_net\_REV\_20191119152640.pdf

**Section 3 - Casing**

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1191	0	1191	3011		1191	J-55	68	OTHER - BTC	7.71	0.61	DRY	11.3	DRY	13.21
2	INTERMEDIATE	9.875	7.625	NEW	API	N	0	11650	0	11650			11650	HCL-80	29.7	OTHER - BTC	1.18	1.66	DRY	1.89	DRY	2.72
3	PRODUCTION	6.75	5.5	NEW	API	N	0	22246	0	11650			22246	P-110	20	OTHER - BTC	1.76	1.9	DRY	2.81	DRY	3.12

**Casing Attachments**

Casing ID: 1 String Type: SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

13.375\_68.00\_\_J55\_BTC\_20191119152935.pdf

Golden\_Bell\_Fed\_Com\_26\_36\_06\_095H\_\_Wellbore\_Diagram\_and\_CDA\_20191119152949.pdf

**Operator Name:** AMEREDEV OPERATING LLC

**Well Name:** GOLDEN BELL FED COM 26 36 06

**Well Number:** 095H

**Casing Attachments**

**Casing ID:** 2      **String Type:** INTERMEDIATE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

7.625\_29.70\_L80HC\_BORUSAN\_20191119153153.pdf

Golden\_Bell\_Fed\_Com\_26\_36\_06\_095H\_\_Wellbore\_Diagram\_and\_CDA\_20191119153206.pdf

**Casing ID:** 3      **String Type:** PRODUCTION

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

5.50\_20\_USS\_P110\_HC\_BTC\_API\_20191119153318.pdf

Golden\_Bell\_Fed\_Com\_26\_36\_06\_095H\_\_Wellbore\_Diagram\_and\_CDA\_20191119153331.pdf

**Section 4 - Cement**

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
	Lead					1.76					
	Tail										
	Lead					2.47					

Operator Name: AMEREDEV OPERATING LLC

Well Name: GOLDEN BELL FED COM 26 36 06

Well Number: 095H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
	Tail										
	Lead					2.47					
	Tail										
	Lead					1.34					

### Section 5 - Circulating Medium

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: All necessary supplies (e.g. bentonite, cedar bark) for fluid control will be on site.

Describe the mud monitoring system utilized: An electronic pit volume totalizer (PVT) will be utilized on the circulating system to monitor pit volume, flow rate, pump pressure, and pump rate.

### Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	1191	WATER-BASED MUD	8.4	8.6							

**Operator Name:** AMEREDEV OPERATING LLC

**Well Name:** GOLDEN BELL FED COM 26 36 06

**Well Number:** 095H

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
1191	1165 0	OTHER : Diesel Brine Emulsion	8.5	9.4							

### Section 6 - Test, Logging, Coring

**List of production tests including testing procedures, equipment and safety measures:**

A directional survey, measurement while drilling and a mudlog/geologic lithology log will all be run from surface to TD.

**List of open and cased hole logs run in the well:**

DS,MWD,MUDLOG

**Coring operation description for the well:**

No coring will be done on this well.

### Section 7 - Pressure

**Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO**

**Describe:**

**Contingency Plans geohazards description:**

**Contingency Plans geohazards attachment:**

**Hydrogen Sulfide drilling operations plan required? YES**

**Hydrogen sulfide drilling operations plan:**

H2S\_Plan\_20180809142040.pdf

**Operator Name:** AMEREDEV OPERATING LLC

**Well Name:** GOLDEN BELL FED COM 26 36 06

**Well Number:** 095H

**Section 8 - Other Information**

**Proposed horizontal/directional/multi-lateral plan submission:**

GB095\_DR\_20191119154035.pdf

GB095\_LLR\_20191119154036.pdf

5M\_Annular\_Preventer\_Variance\_and\_Well\_Control\_Plan\_20191119154049.pdf

Pressure\_Control\_Plan\_Single\_Well\_MB4\_3String\_Big\_Hole\_BLM\_20191119154049.pdf

**Other proposed operations facets description:**



**Other proposed operations facets attachment:**

CAPITAN\_PROTECTION\_CONTINGENCY\_PLAN\_BS\_PACKET\_20190905\_20191119154106.pdf

Rig\_Skid\_Procedure\_20191119154116.pdf

**Other Variance attachment:**

R616\_\_CoC\_for\_hoses\_12\_18\_17\_20191119154137.pdf

Requested\_Exceptions\_\_3\_String\_Revised\_01312019\_20191119154138.pdf



# Wellbore Schematic

**Well:** Golden Bell Fed Com 26-36-06 095H  
**SHL:** Sec. 06 26S-36E 230' FNL & 1990' FEL  
**BHL:** Sec. 06 26S-36E 50' FSL & 1980' FEL  
 Lea, NM  
**Wellhead:** A - 13-5/8" 10M x 13-5/8" SOW  
 B - 13-5/8" 10M x 13-5/8" 10M  
 C - 13-5/8" 10M x 13-5/8" 10M  
 Tubing Spool - 5-1/8" 15M x 13-3/8" 10M  
**Xmas Tree:** 2-9/16" 10M  
**Tubing:** 2-7/8" L-80 6.5# 8rd EUE

**Co. Well ID:** xxxxxx  
**AFE No.:** xxxx-xxx  
**API No.:** xxxxxxxxxxxx  
**GL:** 3,011'  
**Field:** Delaware  
**Objective:** Third Bone Spring  
**TVD:** 11,650'  
**MD:** 22,246'  
**Rig:** TBD **KB:** 27'  
**E-Mail:** [Wellsite2@ameredevelop.com](mailto:Wellsite2@ameredevelop.com)

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,066'	752 Sacks TOC 0' 50% Excess	8.4-8.6 ppg WBM
	<b>13.375" 68# J-55 BTC 1,191'</b>		
9.875"	Salado 1,506'	444 Sacks TOC 0' 25% Excess	8.5 - 9.4 ppg Diesel Brine Emulsion
	<b>DV Tool 3,234'</b>		
	Tansill 3,234'		
	Capitan Reef 3,737'		
	Lamar 5,033'		
	Bell Canyon 5,068'		
	Brushy Canyon 7,111'		
	Bone Spring Lime 8,336'		
	First Bone Spring 9,712'		
	Second Bone Spring 10,271'		
	Third Bone Spring Upper 10,858'		
Third Bone Spring 11,456'			
<b>7.625" 29.7# L-80HC BTC 11,650'</b>	1,406 Sacks TOC 0' 25% Excess		
<b>5.5" 20# P-110 USS RYS SF 22,246'</b>			
	<b>Target Third Bone Spring 11650 TVD // 22246 MD</b>	1,732 Sacks TOC 0' 25% Excess	
6.75"			

## Casing Design and Safety Factor Check

<b>Casing Specifications</b>						
<b>Segment</b>	<b>Hole ID</b>	<b>Depth</b>	<b>OD</b>	<b>Weight</b>	<b>Grade</b>	<b>Coupling</b>
Surface	17.5	1,191'	13.375	68	J-55	BTC
Intermediate	9.875	11,650'	7.625	29.7	HCL-80	BTC
Prod Segment A	6.75	11,190'	5.5	20	P-110	BTC
Prod Segment B	6.75	22,246'	5.5	20	P-110	BTC

<b>Check Surface Casing</b>				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
14.375	1,069	915	4,100	3,450
<b>Safety Factors</b>				
1.56	13.21	11.30	7.71	0.61
<b>Check Intermediate Casing</b>				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
7.625	940	558	6700	9460
<b>Safety Factors</b>				
1.13	2.72	1.89	1.18	1.66
<b>Check Prod Casing, Segment A</b>				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
<b>Safety Factors</b>				
0.49	3.12	2.81	1.76	1.90
<b>Check Prod Casing, Segment B</b>				
OD Cplg	Body	Joint	Collapse	Burst
<i>inches</i>	<i>1000 lbs</i>	<i>1000 lbs</i>	<i>psi</i>	<i>psi</i>
5.777	728	655	12780	14360
<b>Safety Factors</b>				
0.49	79.13	71.20	1.69	1.90

**U.S. Steel Tubular Products**  
**Product Information**  
**5.5 in. 20 lb/ft (0.361 in. wall) P-110 HC Casing**  
**STAR SEAL - CDC™**

Grade(s)	P-110 HC			
<b>MECHANICAL PROPERTIES</b>				
	Yield Strength			
	Minimum	110	ksi	
	Maximum	140	ksi	
	Tensile Strength			
	Minimum	125	ksi	
<b>PIPE PROPERTIES</b>				
<b>Dimensions, Nominal</b>	Pipe Outside Diameter	5.500	in.	
	Wall	0.361	in.	
	Pipe Inside Diameter	4.778	in.	
	Pipe Drift			
	API	4.653	in.	
	Special (If Applicable)	N/A	in.	
	Weight, T&C	20.00	lbs/ft	
	Weight, Plain End	19.83	lbs/ft	
	Pipe Cross Sectional Area	5.828	sq. in.	
	<b>Performance Properties</b>	Minimum Pipe Body Yield Strength	641	1,000 lbs
		Minimum Collapse Pressure	12,200	psi
Minimum Internal Yield Pressure		12,640	psi	
<b>CONNECTION PROPERTIES</b>				
<b>Dimensions, Nominal</b>	Connection Outside Diameter	6.050	in.	
	Connection Inside Diameter	4.778	in.	
	Connection Drift			
	API	4.653	in.	
	Special (If Applicable)	N/A	in.	
	Makeup Loss	4.63	in.	
	Critical Area	5.828	in.	
	Joint Efficiency	100	%	
<b>Performance Properties</b>	Joint Strength	667	1,000 lbs	
	Compression Rating	400	1,000 lbs	
	API Collapse Pressure Rating	12,200	psi	
	API Internal Pressure Resistance	12,360	psi	
	Maximum Uniaxial Bend Rating	57.2	deg/100 ft	
<b>Recommended Torque Values</b>	Minimum Shoulder Torque	5,000	ft-lbs	
	Maximum Shoulder Torque	7,500	ft-lbs	
	Connection Yield Torque	16,100	ft-lbs	

\* STAR SEAL - CDC (Casing Drilling Connection) is a Modified API Buttress threaded and coupled connection designed for field proven in drilling with casing applications. Star Seal is a registered trademark of U. S. Steel Corporation. All material contained in this publication is for general information only. This material should not therefore, be used or relied upon for any specific application without independent competent professional examination and verification of its accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.



**U.S. Steel Tubular Products, Inc.**  
**600 Grant Street**  
**Pittsburgh, PA 15219**

## H<sub>2</sub>S Drilling Operation Plan

1. **All Company and Contract personnel admitted on location must be trained by a qualified H<sub>2</sub>S safety instructor to the following:**
  - a. Characteristics of H<sub>2</sub>S
  - b. Physical effects and hazards
  - c. Principal and operation of H<sub>2</sub>S detectors, warning system and briefing areas
  - d. Evacuation procedure, routes and first aid
  - e. Proper use of safety equipment and life support systems
  - f. Essential personnel meeting Medical Evaluation criteria will receive additional training on the proper use of 30 minute pressure demand air packs.
  
2. **Briefing Area:**
  - a. Two perpendicular areas will be designated by signs and readily accessible.
  - b. Upon location entry there will be a designated area to establish all safety compliance criteria (1.) has been met.
  
3. **H<sub>2</sub>S Detection and Alarm Systems:**
  - a. H<sub>2</sub>S sensors/detectors shall be located on the drilling rig floor, in the base of the sub structure/cellar area, and on the mud pits in the shale shaker area. Additional H<sub>2</sub>S detectors may be placed as deemed necessary. All detectors will be set to initiate visual alarm at 10 ppm and visual with audible at 14 ppm and all equipment will be calibrated every 30 days or as needed.
  - b. An audio alarm will be installed on the derrick floor and in the top doghouse.
  
4. **Protective Equipment for Essential Personnel:**
  - a. **Breathing Apparatus:**
    - i. Rescue Packs (SCBA) - 1 Unit shall be placed at each briefing area.
    - ii. Two (SCBA) Units will be stored in safety trailer on location.
    - iii. Work/Escapes packs - 1 Unit will be available on rig floor in doghouse for emergency evacuation for driller.
  - b. **Auxiliary Rescue Equipment:**
    - i. Stretcher
    - ii. 2 - OSHA full body harnesses
    - iii. 100 ft. 5/8" OSHA approved rope
    - iv. 1 - 20# class ABC fire extinguisher
  
5. **Windsock and/or Wind Streamers:**
  - a. Windsock at mud pit area should be high enough to be visible.
  - b. Windsock on the rig floor should be high enough to be visible.
  
6. **Communication:**
  - a. While working under mask scripting boards will be used for communication where applicable.
  - b. Hand signals will be used when script boards are not applicable.

## H<sub>2</sub>S Drilling Operation Plan

- c. Two way radios will be used to communicate off location in case of emergency help is required. In most cases cellular telephones will be available at Drilling Foreman's Office.

7. **Drill Stem Testing:** - No Planned DST at this time.

8. **Mud program:**

- a. If H<sub>2</sub>S is encountered, mud system will be altered if necessary to maintain control of formation. A mud gas separator will be brought into service along with H<sub>2</sub>S scavengers if necessary.

9. **Metallurgy:**

- a. All drill strings, casing, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H<sub>2</sub>S service.
- b. Drilling Contractor supervisor will be required to be familiar with the effect H<sub>2</sub>S has on tubular goods and other mechanical equipment provided through contractor.



## H<sub>2</sub>S Contingency Plan

### Emergency Procedures

In the event of a release of H<sub>2</sub>S, the first responder(s) must:

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H<sub>2</sub>S monitors and air packs in order to control the release.
- Use the “buddy system” to ensure no injuries occur during the response.
- Take precautions to avoid personal injury during this operation.
- Contact Operator and/or local officials the aid in operation. See list of phone numbers attached.
- Have received training in the:
  - Detection of H<sub>2</sub>S and
  - Measures for protection against the gas,
  - Equipment used for protection and emergency response.

### Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally, the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas.

### Characteristics of H<sub>2</sub>S and SO<sub>2</sub>

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H <sub>2</sub> S	1.189 Air=1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO <sub>2</sub>	2.21 Air=1	2 ppm	N/A	1000 ppm

### Contacting Authorities

Ameredeve Operating LLC personnel must liaise with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available including direction to site. The following call list of essential and potential responders has been prepared for use during a release. Ameredeve Operating LLC’s response must be in coordination with the State of New Mexico’s “Hazardous Materials Emergency Response Plan” (HMER)



## H<sub>2</sub>S Contingency Plan

<b>Ameredev Operating LLC – Emergency Phone 737-300-4799</b>			
<b>Key Personnel:</b>			
<b>Name</b>	<b>Title</b>	<b>Office</b>	<b>Mobile</b>
Floyd Hammond	Chief Operating officer	737-300-4724	512-783-6810
Zachary Boyd	Operations Superintendent	737-300-4725	432-385-6996
Blake Estrada	Construction Foreman		432-385-5831

<b><u>Artesia</u></b>			
Ambulance			911
State Police			575-746-2703
City Police			575-746-2703
Sheriff's Office			575-746-9888
Fire Department			575-746-2701
Local Emergency Planning Committee			575-746-2122
New Mexico Oil Conservation Division			575-748-1283
<b><u>Carlsbad</u></b>			
Ambulance			911
State Police			575-885-3137
City Police			575-885-2111
Sheriff's Office			575-887-7551
Fire Department			575-887-3798
Local Emergency Planning Committee			575-887-6544
US Bureau of Land Management			575-887-6544
<b><u>Santa Fe</u></b>			
New Mexico Emergency Response Commission (Santa Fe)			505-476-9600
New Mexico Emergency Response Commission (Santa Fe) 24 Hrs			505-827-9126
New Mexico State Emergency Operations Center			505-476-9635
<b><u>National</u></b>			
National Emergency Response Center (Washington, D.C.)			800-424-8802
<b><u>Medical</u></b>			
Flight for Life - 4000 24th St.; Lubbock, TX			806-743-9911
Aerocare - R3, Box 49F; Lubbock, TX			806-747-8923
Med Flight Air Amb - 2301 Yale Blvd S.E., #D3; Albuquerque, NM			505-842-4433
.'SB Air Med Service - 2505 Clark Carr Loop S.E.; Albuquerque, NM			505-842-4949

***AMEREDEV***

**Ameredev Operating, LLC.**

**NAN/GB**

**NAN/GB #6S**

**Golden Bell 095H**

**Wellbore #1**

**Plan: Design #1**

**Standard Planning Report**

**18 June, 2019**

<b>Database:</b>	EDM5000	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Company:</b>	Ameredev Operating, LLC.	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Project:</b>	NAN/GB	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>North Reference:</b>	Grid
<b>Well:</b>	Golden Bell 095H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

<b>Project</b>	NAN/GB		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Eastern Zone		

<b>Site</b>	NAN/GB #6S				
<b>Site Position:</b>		<b>Northing:</b>	393,984.60 usft	<b>Latitude:</b>	32° 4' 44.202 N
<b>From:</b>	Lat/Long	<b>Easting:</b>	860,801.36 usft	<b>Longitude:</b>	103° 18' 6.857 W
<b>Position Uncertainty:</b>	0.0 usft	<b>Slot Radius:</b>	13-3/16 "	<b>Grid Convergence:</b>	0.55 °

<b>Well</b>	Golden Bell 095H					
<b>Well Position</b>	<b>+N/-S</b>	-0.6 usft	<b>Northing:</b>	393,983.99 usft	<b>Latitude:</b>	32° 4' 44.202 N
	<b>+E/-W</b>	-60.0 usft	<b>Easting:</b>	860,741.36 usft	<b>Longitude:</b>	103° 18' 7.555 W
<b>Position Uncertainty</b>		0.0 usft	<b>Wellhead Elevation:</b>		<b>Ground Level:</b>	3,011.0 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2015	12/5/2018	6.66	59.95	47,731.97076153

<b>Design</b>	Design #1				
<b>Audit Notes:</b>					
<b>Version:</b>	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b>	0.0	
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>	
	0.0	0.0	0.0	179.32	

<b>Plan Survey Tool Program</b>	<b>Date</b> 6/18/2019				
<b>Depth From (usft)</b>	<b>Depth To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Remarks</b>	
1	0.0	22,246.1	Design #1 (Wellbore #1)	MWD	
				OWSG MWD - Standard	

<b>Database:</b>	EDM5000	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Company:</b>	Ameredev Operating, LLC.	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Project:</b>	NAN/GB	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>North Reference:</b>	Grid
<b>Well:</b>	Golden Bell 095H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,300.0	6.00	350.00	2,299.5	15.5	-2.7	2.00	2.00	0.00	350.00	
6,724.8	6.00	350.00	6,700.0	470.9	-83.0	0.00	0.00	0.00	0.00	
7,024.8	0.00	0.00	6,999.5	486.4	-85.8	2.00	-2.00	0.00	180.00	
11,190.3	0.00	0.00	11,165.0	486.4	-85.8	0.00	0.00	0.00	0.00	
11,792.9	72.29	167.36	11,619.9	162.2	-13.0	12.00	12.00	0.00	167.36	
11,801.9	72.29	167.36	11,622.7	153.8	-11.2	0.00	0.00	0.00	0.00	
11,979.3	90.00	179.36	11,650.0	-19.4	8.5	12.00	9.98	6.77	34.95	GB095 FTP2
22,246.1	90.00	179.36	11,650.0	-10,285.6	122.7	0.00	0.00	0.00	0.00	GB095 BHL

Database:	EDM5000	Local Co-ordinate Reference:	Well Golden Bell 095H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Golden Bell 095H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	2.00	350.00	2,100.0	1.7	-0.3	-1.7	2.00	2.00	0.00
2,200.0	4.00	350.00	2,199.8	6.9	-1.2	-6.9	2.00	2.00	0.00
2,300.0	6.00	350.00	2,299.5	15.5	-2.7	-15.5	2.00	2.00	0.00
2,400.0	6.00	350.00	2,398.9	25.7	-4.5	-25.8	0.00	0.00	0.00
2,500.0	6.00	350.00	2,498.4	36.0	-6.4	-36.1	0.00	0.00	0.00
2,600.0	6.00	350.00	2,597.8	46.3	-8.2	-46.4	0.00	0.00	0.00
2,700.0	6.00	350.00	2,697.3	56.6	-10.0	-56.7	0.00	0.00	0.00
2,800.0	6.00	350.00	2,796.7	66.9	-11.8	-67.1	0.00	0.00	0.00
2,900.0	6.00	350.00	2,896.2	77.2	-13.6	-77.4	0.00	0.00	0.00
3,000.0	6.00	350.00	2,995.6	87.5	-15.4	-87.7	0.00	0.00	0.00
3,100.0	6.00	350.00	3,095.1	97.8	-17.2	-98.0	0.00	0.00	0.00
3,200.0	6.00	350.00	3,194.5	108.1	-19.1	-108.3	0.00	0.00	0.00
3,300.0	6.00	350.00	3,294.0	118.4	-20.9	-118.6	0.00	0.00	0.00
3,400.0	6.00	350.00	3,393.4	128.7	-22.7	-129.0	0.00	0.00	0.00
3,500.0	6.00	350.00	3,492.9	139.0	-24.5	-139.3	0.00	0.00	0.00
3,600.0	6.00	350.00	3,592.3	149.3	-26.3	-149.6	0.00	0.00	0.00
3,700.0	6.00	350.00	3,691.8	159.6	-28.1	-159.9	0.00	0.00	0.00
3,800.0	6.00	350.00	3,791.2	169.9	-30.0	-170.2	0.00	0.00	0.00
3,900.0	6.00	350.00	3,890.7	180.2	-31.8	-180.5	0.00	0.00	0.00
4,000.0	6.00	350.00	3,990.1	190.5	-33.6	-190.8	0.00	0.00	0.00
4,100.0	6.00	350.00	4,089.6	200.7	-35.4	-201.2	0.00	0.00	0.00
4,200.0	6.00	350.00	4,189.0	211.0	-37.2	-211.5	0.00	0.00	0.00
4,300.0	6.00	350.00	4,288.5	221.3	-39.0	-221.8	0.00	0.00	0.00
4,400.0	6.00	350.00	4,387.9	231.6	-40.8	-232.1	0.00	0.00	0.00
4,500.0	6.00	350.00	4,487.4	241.9	-42.7	-242.4	0.00	0.00	0.00
4,600.0	6.00	350.00	4,586.9	252.2	-44.5	-252.7	0.00	0.00	0.00
4,700.0	6.00	350.00	4,686.3	262.5	-46.3	-263.0	0.00	0.00	0.00
4,800.0	6.00	350.00	4,785.8	272.8	-48.1	-273.4	0.00	0.00	0.00
4,900.0	6.00	350.00	4,885.2	283.1	-49.9	-283.7	0.00	0.00	0.00
5,000.0	6.00	350.00	4,984.7	293.4	-51.7	-294.0	0.00	0.00	0.00
5,100.0	6.00	350.00	5,084.1	303.7	-53.5	-304.3	0.00	0.00	0.00
5,200.0	6.00	350.00	5,183.6	314.0	-55.4	-314.6	0.00	0.00	0.00
5,300.0	6.00	350.00	5,283.0	324.3	-57.2	-324.9	0.00	0.00	0.00

<b>Database:</b>	EDM5000	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Company:</b>	Ameredev Operating, LLC.	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Project:</b>	NAN/GB	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>North Reference:</b>	Grid
<b>Well:</b>	Golden Bell 095H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
5,400.0	6.00	350.00	5,382.5	334.6	-59.0	-335.3	0.00	0.00	0.00	
5,500.0	6.00	350.00	5,481.9	344.9	-60.8	-345.6	0.00	0.00	0.00	
5,600.0	6.00	350.00	5,581.4	355.2	-62.6	-355.9	0.00	0.00	0.00	
5,700.0	6.00	350.00	5,680.8	365.5	-64.4	-366.2	0.00	0.00	0.00	
5,800.0	6.00	350.00	5,780.3	375.7	-66.3	-376.5	0.00	0.00	0.00	
5,900.0	6.00	350.00	5,879.7	386.0	-68.1	-386.8	0.00	0.00	0.00	
6,000.0	6.00	350.00	5,979.2	396.3	-69.9	-397.1	0.00	0.00	0.00	
6,100.0	6.00	350.00	6,078.6	406.6	-71.7	-407.5	0.00	0.00	0.00	
6,200.0	6.00	350.00	6,178.1	416.9	-73.5	-417.8	0.00	0.00	0.00	
6,300.0	6.00	350.00	6,277.5	427.2	-75.3	-428.1	0.00	0.00	0.00	
6,400.0	6.00	350.00	6,377.0	437.5	-77.1	-438.4	0.00	0.00	0.00	
6,500.0	6.00	350.00	6,476.4	447.8	-79.0	-448.7	0.00	0.00	0.00	
6,600.0	6.00	350.00	6,575.9	458.1	-80.8	-459.0	0.00	0.00	0.00	
6,700.0	6.00	350.00	6,675.3	468.4	-82.6	-469.3	0.00	0.00	0.00	
6,724.8	6.00	350.00	6,700.0	470.9	-83.0	-471.9	0.00	0.00	0.00	
6,800.0	4.50	350.00	6,774.9	477.7	-84.2	-478.7	2.00	-2.00	0.00	
6,900.0	2.50	350.00	6,874.7	483.7	-85.3	-484.7	2.00	-2.00	0.00	
7,000.0	0.50	350.00	6,974.7	486.3	-85.7	-487.3	2.00	-2.00	0.00	
7,024.8	0.00	0.00	6,999.5	486.4	-85.8	-487.4	2.00	-2.00	0.00	
7,100.0	0.00	0.00	7,074.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
7,200.0	0.00	0.00	7,174.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
7,300.0	0.00	0.00	7,274.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
7,400.0	0.00	0.00	7,374.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
7,500.0	0.00	0.00	7,474.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
7,600.0	0.00	0.00	7,574.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
7,700.0	0.00	0.00	7,674.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
7,800.0	0.00	0.00	7,774.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
7,900.0	0.00	0.00	7,874.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,000.0	0.00	0.00	7,974.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,100.0	0.00	0.00	8,074.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,200.0	0.00	0.00	8,174.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,300.0	0.00	0.00	8,274.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,400.0	0.00	0.00	8,374.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,500.0	0.00	0.00	8,474.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,600.0	0.00	0.00	8,574.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,700.0	0.00	0.00	8,674.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,800.0	0.00	0.00	8,774.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
8,900.0	0.00	0.00	8,874.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,000.0	0.00	0.00	8,974.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,100.0	0.00	0.00	9,074.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,200.0	0.00	0.00	9,174.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,300.0	0.00	0.00	9,274.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,400.0	0.00	0.00	9,374.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,500.0	0.00	0.00	9,474.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,600.0	0.00	0.00	9,574.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,700.0	0.00	0.00	9,674.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,800.0	0.00	0.00	9,774.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
9,900.0	0.00	0.00	9,874.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
10,000.0	0.00	0.00	9,974.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
10,100.0	0.00	0.00	10,074.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
10,200.0	0.00	0.00	10,174.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
10,300.0	0.00	0.00	10,274.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
10,400.0	0.00	0.00	10,374.7	486.4	-85.8	-487.4	0.00	0.00	0.00	
10,500.0	0.00	0.00	10,474.7	486.4	-85.8	-487.4	0.00	0.00	0.00	

<b>Database:</b>	EDM5000	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Company:</b>	Ameredev Operating, LLC.	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Project:</b>	NAN/GB	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>North Reference:</b>	Grid
<b>Well:</b>	Golden Bell 095H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

### Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,600.0	0.00	0.00	10,574.7	486.4	-85.8	-487.4	0.00	0.00	0.00
10,700.0	0.00	0.00	10,674.7	486.4	-85.8	-487.4	0.00	0.00	0.00
10,800.0	0.00	0.00	10,774.7	486.4	-85.8	-487.4	0.00	0.00	0.00
10,900.0	0.00	0.00	10,874.7	486.4	-85.8	-487.4	0.00	0.00	0.00
11,000.0	0.00	0.00	10,974.7	486.4	-85.8	-487.4	0.00	0.00	0.00
11,100.0	0.00	0.00	11,074.7	486.4	-85.8	-487.4	0.00	0.00	0.00
11,190.3	0.00	0.00	11,165.0	486.4	-85.8	-487.4	0.00	0.00	0.00
<b>GB095 KOP (NMNM137469)</b>									
11,200.0	1.16	167.36	11,174.7	486.3	-85.7	-487.3	12.00	12.00	0.00
11,300.0	13.16	167.36	11,273.7	474.2	-83.0	-475.1	12.00	12.00	0.00
11,400.0	25.15	167.36	11,368.0	442.2	-75.9	-443.1	12.00	12.00	0.00
11,500.0	37.15	167.36	11,453.4	391.8	-64.6	-392.6	12.00	12.00	0.00
11,600.0	49.15	167.36	11,526.2	325.2	-49.6	-325.8	12.00	12.00	0.00
11,700.0	61.14	167.36	11,583.3	245.3	-31.7	-245.6	12.00	12.00	0.00
11,792.9	72.29	167.36	11,619.9	162.2	-13.0	-162.3	12.00	12.00	0.00
11,800.0	72.29	167.36	11,622.1	155.6	-11.6	-155.7	0.00	0.00	0.00
11,801.9	72.29	167.36	11,622.7	153.8	-11.2	-153.9	0.00	0.00	0.00
11,833.9	75.44	169.63	11,631.6	123.7	-5.0	-123.7	12.00	9.88	7.10
<b>GB095 FTP</b>									
11,900.0	82.03	174.13	11,644.5	59.5	4.1	-59.5	12.00	9.97	6.82
11,979.3	90.00	179.36	11,650.0	-19.4	8.5	19.5	12.00	10.04	6.59
<b>GB095 FTP2</b>									
12,000.0	90.00	179.36	11,650.0	-40.0	8.8	40.1	0.00	0.00	0.00
12,100.0	90.00	179.36	11,650.0	-140.0	9.9	140.1	0.00	0.00	0.00
12,200.0	90.00	179.36	11,650.0	-240.0	11.0	240.1	0.00	0.00	0.00
12,300.0	90.00	179.36	11,650.0	-340.0	12.1	340.1	0.00	0.00	0.00
12,400.0	90.00	179.36	11,650.0	-440.0	13.2	440.1	0.00	0.00	0.00
12,500.0	90.00	179.36	11,650.0	-540.0	14.3	540.1	0.00	0.00	0.00
12,600.0	90.00	179.36	11,650.0	-640.0	15.4	640.1	0.00	0.00	0.00
12,700.0	90.00	179.36	11,650.0	-740.0	16.6	740.1	0.00	0.00	0.00
12,800.0	90.00	179.36	11,650.0	-840.0	17.7	840.1	0.00	0.00	0.00
12,900.0	90.00	179.36	11,650.0	-940.0	18.8	940.1	0.00	0.00	0.00
13,000.0	90.00	179.36	11,650.0	-1,040.0	19.9	1,040.1	0.00	0.00	0.00
13,100.0	90.00	179.36	11,650.0	-1,140.0	21.0	1,140.1	0.00	0.00	0.00
13,200.0	90.00	179.36	11,650.0	-1,240.0	22.1	1,240.1	0.00	0.00	0.00
13,300.0	90.00	179.36	11,650.0	-1,340.0	23.2	1,340.1	0.00	0.00	0.00
13,400.0	90.00	179.36	11,650.0	-1,440.0	24.3	1,440.1	0.00	0.00	0.00
13,500.0	90.00	179.36	11,650.0	-1,540.0	25.5	1,540.1	0.00	0.00	0.00
13,600.0	90.00	179.36	11,650.0	-1,639.9	26.6	1,640.1	0.00	0.00	0.00
13,700.0	90.00	179.36	11,650.0	-1,739.9	27.7	1,740.1	0.00	0.00	0.00
13,800.0	90.00	179.36	11,650.0	-1,839.9	28.8	1,840.1	0.00	0.00	0.00
13,900.0	90.00	179.36	11,650.0	-1,939.9	29.9	1,940.1	0.00	0.00	0.00
14,000.0	90.00	179.36	11,650.0	-2,039.9	31.0	2,040.1	0.00	0.00	0.00
14,100.0	90.00	179.36	11,650.0	-2,139.9	32.1	2,140.1	0.00	0.00	0.00
14,200.0	90.00	179.36	11,650.0	-2,239.9	33.2	2,240.1	0.00	0.00	0.00
14,300.0	90.00	179.36	11,650.0	-2,339.9	34.4	2,340.1	0.00	0.00	0.00
14,400.0	90.00	179.36	11,650.0	-2,439.9	35.5	2,440.1	0.00	0.00	0.00
14,500.0	90.00	179.36	11,650.0	-2,539.9	36.6	2,540.1	0.00	0.00	0.00
14,600.0	90.00	179.36	11,650.0	-2,639.9	37.7	2,640.1	0.00	0.00	0.00
14,700.0	90.00	179.36	11,650.0	-2,739.9	38.8	2,740.1	0.00	0.00	0.00
14,800.0	90.00	179.36	11,650.0	-2,839.9	39.9	2,840.1	0.00	0.00	0.00
14,900.0	90.00	179.36	11,650.0	-2,939.9	41.0	2,940.1	0.00	0.00	0.00
15,000.0	90.00	179.36	11,650.0	-3,039.9	42.1	3,040.1	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Golden Bell 095H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Golden Bell 095H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

### Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
15,100.0	90.00	179.36	11,650.0	-3,139.9	43.3	3,140.1	0.00	0.00	0.00
15,200.0	90.00	179.36	11,650.0	-3,239.8	44.4	3,240.1	0.00	0.00	0.00
15,300.0	90.00	179.36	11,650.0	-3,339.8	45.5	3,340.1	0.00	0.00	0.00
15,400.0	90.00	179.36	11,650.0	-3,439.8	46.6	3,440.1	0.00	0.00	0.00
15,500.0	90.00	179.36	11,650.0	-3,539.8	47.7	3,540.1	0.00	0.00	0.00
15,600.0	90.00	179.36	11,650.0	-3,639.8	48.8	3,640.1	0.00	0.00	0.00
15,700.0	90.00	179.36	11,650.0	-3,739.8	49.9	3,740.1	0.00	0.00	0.00
15,800.0	90.00	179.36	11,650.0	-3,839.8	51.0	3,840.1	0.00	0.00	0.00
15,900.0	90.00	179.36	11,650.0	-3,939.8	52.2	3,940.1	0.00	0.00	0.00
16,000.0	90.00	179.36	11,650.0	-4,039.8	53.3	4,040.1	0.00	0.00	0.00
16,100.0	90.00	179.36	11,650.0	-4,139.8	54.4	4,140.1	0.00	0.00	0.00
16,200.0	90.00	179.36	11,650.0	-4,239.8	55.5	4,240.1	0.00	0.00	0.00
16,300.0	90.00	179.36	11,650.0	-4,339.8	56.6	4,340.1	0.00	0.00	0.00
16,400.0	90.00	179.36	11,650.0	-4,439.8	57.7	4,440.1	0.00	0.00	0.00
16,500.0	90.00	179.36	11,650.0	-4,539.8	58.8	4,540.1	0.00	0.00	0.00
16,600.0	90.00	179.36	11,650.0	-4,639.8	59.9	4,640.1	0.00	0.00	0.00
16,700.0	90.00	179.36	11,650.0	-4,739.8	61.0	4,740.1	0.00	0.00	0.00
16,800.0	90.00	179.36	11,650.0	-4,839.7	62.2	4,840.1	0.00	0.00	0.00
16,900.0	90.00	179.36	11,650.0	-4,939.7	63.3	4,940.1	0.00	0.00	0.00
17,000.0	90.00	179.36	11,650.0	-5,039.7	64.4	5,040.1	0.00	0.00	0.00
17,009.7	90.00	179.36	11,650.0	-5,049.4	64.5	5,049.8	0.00	0.00	0.00
<b>GB095 into NMNM137472</b>									
17,100.0	90.00	179.36	11,650.0	-5,139.7	65.5	5,140.1	0.00	0.00	0.00
17,200.0	90.00	179.36	11,650.0	-5,239.7	66.6	5,240.1	0.00	0.00	0.00
17,300.0	90.00	179.36	11,650.0	-5,339.7	67.7	5,340.1	0.00	0.00	0.00
17,400.0	90.00	179.36	11,650.0	-5,439.7	68.8	5,440.1	0.00	0.00	0.00
17,500.0	90.00	179.36	11,650.0	-5,539.7	69.9	5,540.1	0.00	0.00	0.00
17,600.0	90.00	179.36	11,650.0	-5,639.7	71.1	5,640.1	0.00	0.00	0.00
17,700.0	90.00	179.36	11,650.0	-5,739.7	72.2	5,740.1	0.00	0.00	0.00
17,800.0	90.00	179.36	11,650.0	-5,839.7	73.3	5,840.1	0.00	0.00	0.00
17,900.0	90.00	179.36	11,650.0	-5,939.7	74.4	5,940.1	0.00	0.00	0.00
18,000.0	90.00	179.36	11,650.0	-6,039.7	75.5	6,040.1	0.00	0.00	0.00
18,100.0	90.00	179.36	11,650.0	-6,139.7	76.6	6,140.1	0.00	0.00	0.00
18,200.0	90.00	179.36	11,650.0	-6,239.7	77.7	6,240.1	0.00	0.00	0.00
18,300.0	90.00	179.36	11,650.0	-6,339.7	78.8	6,340.1	0.00	0.00	0.00
18,400.0	90.00	179.36	11,650.0	-6,439.7	80.0	6,440.1	0.00	0.00	0.00
18,500.0	90.00	179.36	11,650.0	-6,539.6	81.1	6,540.1	0.00	0.00	0.00
18,600.0	90.00	179.36	11,650.0	-6,639.6	82.2	6,640.1	0.00	0.00	0.00
18,700.0	90.00	179.36	11,650.0	-6,739.6	83.3	6,740.1	0.00	0.00	0.00
18,800.0	90.00	179.36	11,650.0	-6,839.6	84.4	6,840.1	0.00	0.00	0.00
18,900.0	90.00	179.36	11,650.0	-6,939.6	85.5	6,940.1	0.00	0.00	0.00
19,000.0	90.00	179.36	11,650.0	-7,039.6	86.6	7,040.1	0.00	0.00	0.00
19,100.0	90.00	179.36	11,650.0	-7,139.6	87.7	7,140.1	0.00	0.00	0.00
19,200.0	90.00	179.36	11,650.0	-7,239.6	88.9	7,240.1	0.00	0.00	0.00
19,300.0	90.00	179.36	11,650.0	-7,339.6	90.0	7,340.1	0.00	0.00	0.00
19,400.0	90.00	179.36	11,650.0	-7,439.6	91.1	7,440.1	0.00	0.00	0.00
19,500.0	90.00	179.36	11,650.0	-7,539.6	92.2	7,540.1	0.00	0.00	0.00
19,600.0	90.00	179.36	11,650.0	-7,639.6	93.3	7,640.1	0.00	0.00	0.00
19,700.0	90.00	179.36	11,650.0	-7,739.6	94.4	7,740.1	0.00	0.00	0.00
19,800.0	90.00	179.36	11,650.0	-7,839.6	95.5	7,840.1	0.00	0.00	0.00
19,900.0	90.00	179.36	11,650.0	-7,939.6	96.6	7,940.1	0.00	0.00	0.00
20,000.0	90.00	179.36	11,650.0	-8,039.6	97.8	8,040.1	0.00	0.00	0.00
20,100.0	90.00	179.36	11,650.0	-8,139.5	98.9	8,140.1	0.00	0.00	0.00

Database:	EDM5000	Local Co-ordinate Reference:	Well Golden Bell 095H
Company:	Ameredev Operating, LLC.	TVD Reference:	KB @ 3038.0usft
Project:	NAN/GB	MD Reference:	KB @ 3038.0usft
Site:	NAN/GB #6S	North Reference:	Grid
Well:	Golden Bell 095H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

### Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
20,200.0	90.00	179.36	11,650.0	-8,239.5	100.0	8,240.1	0.00	0.00	0.00
20,300.0	90.00	179.36	11,650.0	-8,339.5	101.1	8,340.1	0.00	0.00	0.00
20,400.0	90.00	179.36	11,650.0	-8,439.5	102.2	8,440.1	0.00	0.00	0.00
20,500.0	90.00	179.36	11,650.0	-8,539.5	103.3	8,540.1	0.00	0.00	0.00
20,600.0	90.00	179.36	11,650.0	-8,639.5	104.4	8,640.1	0.00	0.00	0.00
20,700.0	90.00	179.36	11,650.0	-8,739.5	105.5	8,740.1	0.00	0.00	0.00
20,800.0	90.00	179.36	11,650.0	-8,839.5	106.7	8,840.1	0.00	0.00	0.00
20,900.0	90.00	179.36	11,650.0	-8,939.5	107.8	8,940.1	0.00	0.00	0.00
21,000.0	90.00	179.36	11,650.0	-9,039.5	108.9	9,040.1	0.00	0.00	0.00
21,100.0	90.00	179.36	11,650.0	-9,139.5	110.0	9,140.1	0.00	0.00	0.00
21,200.0	90.00	179.36	11,650.0	-9,239.5	111.1	9,240.1	0.00	0.00	0.00
21,300.0	90.00	179.36	11,650.0	-9,339.5	112.2	9,340.1	0.00	0.00	0.00
21,400.0	90.00	179.36	11,650.0	-9,439.5	113.3	9,440.1	0.00	0.00	0.00
21,500.0	90.00	179.36	11,650.0	-9,539.5	114.4	9,540.1	0.00	0.00	0.00
21,600.0	90.00	179.36	11,650.0	-9,639.5	115.5	9,640.1	0.00	0.00	0.00
21,700.0	90.00	179.36	11,650.0	-9,739.4	116.7	9,740.1	0.00	0.00	0.00
21,800.0	90.00	179.36	11,650.0	-9,839.4	117.8	9,840.1	0.00	0.00	0.00
21,900.0	90.00	179.36	11,650.0	-9,939.4	118.9	9,940.1	0.00	0.00	0.00
22,000.0	90.00	179.36	11,650.0	-10,039.4	120.0	10,040.1	0.00	0.00	0.00
22,100.0	90.00	179.36	11,650.0	-10,139.4	121.1	10,140.1	0.00	0.00	0.00
22,200.0	90.00	179.36	11,650.0	-10,239.4	122.2	10,240.1	0.00	0.00	0.00
22,246.1	90.00	179.36	11,650.0	-10,285.6	122.7	10,286.3	0.00	0.00	0.00

GB095 BHL - GB095 LTP

### Design Targets

Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
GB095 FTP - plan misses target center by 23.8usft at 11833.9usft MD (11631.6 TVD, 123.7 N, -5.0 E) - Point	0.00	0.00	11,650.0	130.1	8.5	394,114.11	860,749.91	32° 4' 45.488 N	103° 18' 7.441 W
GB095 BHL - plan misses target center by 0.6usft at 22246.2usft MD (11650.0 TVD, -10285.6 N, 122.7 E) - Point	0.00	0.00	11,650.0	-10,285.6	122.2	383,698.42	860,863.54	32° 3' 2.417 N	103° 18' 7.277 W
GB095 LTP - plan misses target center by 22.7usft at 22246.2usft MD (11650.0 TVD, -10285.6 N, 122.7 E) - Point	0.00	0.00	11,650.0	-10,308.3	122.3	383,675.69	860,863.70	32° 3' 2.192 N	103° 18' 7.278 W
GB095 FTP2 - plan hits target center - Point	0.00	0.00	11,650.0	-19.4	8.5	393,964.60	860,749.91	32° 4' 44.009 N	103° 18' 7.457 W

### Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Comment
11,190.3	11,165.0	486.4	-85.8	GB095 KOP (NMNM137469)
17,009.7	11,650.0	-5,049.4	64.5	GB095 into NMNM137472

***AMEREDDEV***

**Ameredev Operating, LLC.**

**NAN/GB**

**NAN/GB #6S**

**Golden Bell 095H**

**Wellbore #1**

**Plan: Design #1**

**Lease Penetration Section Line Foot**

**18 June, 2019**

<b>Company:</b>	Ameredev Operating, LLC.	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Project:</b>	NAN/GB	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Well:</b>	Golden Bell 095H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Wellbore #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	Design #1	<b>Database:</b>	EDM5000

<b>Project</b>	NAN/GB		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Eastern Zone		

<b>Site</b>	NAN/GB #6S				
<b>Site Position:</b>		<b>Northing:</b>	393,984.61 usft	<b>Latitude:</b>	32° 4' 44.202 N
<b>From:</b>	Lat/Long	<b>Easting:</b>	860,801.36 usft	<b>Longitude:</b>	103° 18' 6.857 W
<b>Position Uncertainty:</b>	0.0 usft	<b>Slot Radius:</b>	13-3/16"	<b>Grid Convergence:</b>	0.55 °

<b>Well</b>	Golden Bell 095H					
<b>Well Position</b>	<b>+N/-S</b>	0.0 usft	<b>Northing:</b>	393,984.00 usft	<b>Latitude:</b>	32° 4' 44.202 N
	<b>+E/-W</b>	0.0 usft	<b>Easting:</b>	860,741.36 usft	<b>Longitude:</b>	103° 18' 7.555 W
<b>Position Uncertainty</b>		0.0 usft	<b>Wellhead Elevation:</b>	usft	<b>Ground Level:</b>	3,011.0 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2015	12/5/2018	6.66	59.95	47,731.97076153

<b>Design</b>	Design #1			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b>	0.0
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.0	0.0	0.0	179.32

<b>Survey Tool Program</b>	Date 6/18/2019			
<b>From (usft)</b>	<b>To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Description</b>
0.0	22,246.2	Design #1 (Wellbore #1)	MWD	OWSG MWD - Standard

<b>Planned Survey</b>							
<b>MD (usft)</b>	<b>Inc (°)</b>	<b>Azi (azimuth) (°)</b>	<b>TVD (usft)</b>	<b>+FSL/-FNL (usft)</b>	<b>+FWL/-FEL (usft)</b>	<b>Latitude</b>	<b>Longitude</b>
0.0	0.00	0.00	0.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
100.0	0.00	0.00	100.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
200.0	0.00	0.00	200.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
300.0	0.00	0.00	300.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
400.0	0.00	0.00	400.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
500.0	0.00	0.00	500.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
600.0	0.00	0.00	600.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
700.0	0.00	0.00	700.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
800.0	0.00	0.00	800.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
900.0	0.00	0.00	900.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,000.0	0.00	0.00	1,000.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,100.0	0.00	0.00	1,100.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W

<b>Company:</b>	Ameredev Operating, LLC.	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Project:</b>	NAN/GB	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Well:</b>	Golden Bell 095H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Wellbore #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	Design #1	<b>Database:</b>	EDM5000

### Planned Survey

MD (usft)	Inc (")	Azi (azimuth) (")	TVD (usft)	+FSL/FNL (usft)	+FWL/FEL (usft)	Latitude	Longitude
1,200.0	0.00	0.00	1,200.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,300.0	0.00	0.00	1,300.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,400.0	0.00	0.00	1,400.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,500.0	0.00	0.00	1,500.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,600.0	0.00	0.00	1,600.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,700.0	0.00	0.00	1,700.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,800.0	0.00	0.00	1,800.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
1,900.0	0.00	0.00	1,900.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
2,000.0	0.00	0.00	2,000.0	-230.6	-1,990.0	32° 4' 44.202 N	103° 18' 7.555 W
2,100.0	2.00	350.00	2,100.0	-228.9	-1,990.3	32° 4' 44.219 N	103° 18' 7.558 W
2,200.0	4.00	350.00	2,199.8	-223.7	-1,991.2	32° 4' 44.270 N	103° 18' 7.568 W
2,300.0	6.00	350.00	2,299.5	-215.2	-1,992.7	32° 4' 44.355 N	103° 18' 7.585 W
2,400.0	6.00	350.00	2,398.9	-204.9	-1,994.5	32° 4' 44.457 N	103° 18' 7.605 W
2,500.0	6.00	350.00	2,498.4	-194.6	-1,996.4	32° 4' 44.559 N	103° 18' 7.624 W
2,600.0	6.00	350.00	2,597.8	-184.3	-1,998.2	32° 4' 44.661 N	103° 18' 7.644 W
2,700.0	6.00	350.00	2,697.3	-174.0	-2,000.0	32° 4' 44.763 N	103° 18' 7.664 W
2,800.0	6.00	350.00	2,796.7	-163.7	-2,001.8	32° 4' 44.865 N	103° 18' 7.684 W
2,900.0	6.00	350.00	2,896.2	-153.4	-2,003.6	32° 4' 44.967 N	103° 18' 7.704 W
3,000.0	6.00	350.00	2,995.6	-143.1	-2,005.4	32° 4' 45.069 N	103° 18' 7.724 W
3,100.0	6.00	350.00	3,095.1	-132.8	-2,007.2	32° 4' 45.171 N	103° 18' 7.744 W
3,200.0	6.00	350.00	3,194.5	-122.5	-2,009.1	32° 4' 45.273 N	103° 18' 7.764 W
3,300.0	6.00	350.00	3,294.0	-112.2	-2,010.9	32° 4' 45.375 N	103° 18' 7.784 W
3,400.0	6.00	350.00	3,393.4	-101.9	-2,012.7	32° 4' 45.477 N	103° 18' 7.804 W
3,500.0	6.00	350.00	3,492.9	-91.6	-2,014.5	32° 4' 45.579 N	103° 18' 7.824 W
3,600.0	6.00	350.00	3,592.3	-81.3	-2,016.3	32° 4' 45.681 N	103° 18' 7.844 W
3,700.0	6.00	350.00	3,691.8	-71.0	-2,018.1	32° 4' 45.783 N	103° 18' 7.864 W
3,800.0	6.00	350.00	3,791.2	-60.7	-2,019.9	32° 4' 45.885 N	103° 18' 7.884 W
3,900.0	6.00	350.00	3,890.7	-50.5	-2,021.8	32° 4' 45.987 N	103° 18' 7.904 W
4,000.0	6.00	350.00	3,990.1	-40.2	-2,023.6	32° 4' 46.089 N	103° 18' 7.924 W
4,100.0	6.00	350.00	4,089.6	-29.9	-2,025.4	32° 4' 46.191 N	103° 18' 7.944 W
4,200.0	6.00	350.00	4,189.0	-19.6	-2,027.2	32° 4' 46.293 N	103° 18' 7.964 W
4,300.0	6.00	350.00	4,288.5	-9.3	-2,029.0	32° 4' 46.395 N	103° 18' 7.984 W
4,400.0	6.00	350.00	4,387.9	1.0	-2,030.8	32° 4' 46.497 N	103° 18' 8.004 W
4,500.0	6.00	350.00	4,487.4	11.3	-2,032.7	32° 4' 46.599 N	103° 18' 8.023 W
4,600.0	6.00	350.00	4,586.9	21.6	-2,034.5	32° 4' 46.701 N	103° 18' 8.043 W
4,700.0	6.00	350.00	4,686.3	31.9	-2,036.3	32° 4' 46.803 N	103° 18' 8.063 W
4,800.0	6.00	350.00	4,785.8	42.2	-2,038.1	32° 4' 46.906 N	103° 18' 8.083 W
4,900.0	6.00	350.00	4,885.2	52.5	-2,039.9	32° 4' 47.008 N	103° 18' 8.103 W
5,000.0	6.00	350.00	4,984.7	62.8	-2,041.7	32° 4' 47.110 N	103° 18' 8.123 W
5,100.0	6.00	350.00	5,084.1	73.1	-2,043.5	32° 4' 47.212 N	103° 18' 8.143 W
5,200.0	6.00	350.00	5,183.6	83.4	-2,045.4	32° 4' 47.314 N	103° 18' 8.163 W
5,300.0	6.00	350.00	5,283.0	93.7	-2,047.2	32° 4' 47.416 N	103° 18' 8.183 W
5,400.0	6.00	350.00	5,382.5	104.0	-2,049.0	32° 4' 47.518 N	103° 18' 8.203 W
5,500.0	6.00	350.00	5,481.9	114.3	-2,050.8	32° 4' 47.620 N	103° 18' 8.223 W

<b>Company:</b>	Ameredev Operating, LLC.	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Project:</b>	NAN/GB	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Well:</b>	Golden Bell 095H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Wellbore #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	Design #1	<b>Database:</b>	EDM5000

### Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL-FNL (usft)	+FWL-FEL (usft)	Latitude	Longitude
5,600.0	6.00	350.00	5,581.4	124.5	-2,052.6	32° 4' 47.722 N	103° 18' 8.243 W
5,700.0	6.00	350.00	5,680.8	134.8	-2,054.4	32° 4' 47.824 N	103° 18' 8.263 W
5,800.0	6.00	350.00	5,780.3	145.1	-2,056.3	32° 4' 47.926 N	103° 18' 8.283 W
5,900.0	6.00	350.00	5,879.7	155.4	-2,058.1	32° 4' 48.028 N	103° 18' 8.303 W
6,000.0	6.00	350.00	5,979.2	165.7	-2,059.9	32° 4' 48.130 N	103° 18' 8.323 W
6,100.0	6.00	350.00	6,078.6	176.0	-2,061.7	32° 4' 48.232 N	103° 18' 8.343 W
6,200.0	6.00	350.00	6,178.1	186.3	-2,063.5	32° 4' 48.334 N	103° 18' 8.363 W
6,300.0	6.00	350.00	6,277.5	196.6	-2,065.3	32° 4' 48.436 N	103° 18' 8.383 W
6,400.0	6.00	350.00	6,377.0	206.9	-2,067.1	32° 4' 48.538 N	103° 18' 8.403 W
6,500.0	6.00	350.00	6,476.4	217.2	-2,069.0	32° 4' 48.640 N	103° 18' 8.422 W
6,600.0	6.00	350.00	6,575.9	227.5	-2,070.8	32° 4' 48.742 N	103° 18' 8.442 W
6,700.0	6.00	350.00	6,675.3	237.8	-2,072.6	32° 4' 48.844 N	103° 18' 8.462 W
6,724.8	6.00	350.00	6,700.0	240.3	-2,073.0	32° 4' 48.869 N	103° 18' 8.467 W
6,800.0	4.50	350.00	6,774.9	247.1	-2,074.2	32° 4' 48.936 N	103° 18' 8.480 W
6,900.0	2.50	350.00	6,874.7	253.1	-2,075.3	32° 4' 48.996 N	103° 18' 8.492 W
7,000.0	0.50	350.00	6,974.7	255.7	-2,075.7	32° 4' 49.021 N	103° 18' 8.497 W
7,024.8	0.00	0.00	6,999.5	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,100.0	0.00	0.00	7,074.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,200.0	0.00	0.00	7,174.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,300.0	0.00	0.00	7,274.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,400.0	0.00	0.00	7,374.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,500.0	0.00	0.00	7,474.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,600.0	0.00	0.00	7,574.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,700.0	0.00	0.00	7,674.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,800.0	0.00	0.00	7,774.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
7,900.0	0.00	0.00	7,874.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,000.0	0.00	0.00	7,974.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,100.0	0.00	0.00	8,074.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,200.0	0.00	0.00	8,174.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,300.0	0.00	0.00	8,274.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,400.0	0.00	0.00	8,374.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,500.0	0.00	0.00	8,474.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,600.0	0.00	0.00	8,574.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,700.0	0.00	0.00	8,674.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,800.0	0.00	0.00	8,774.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
8,900.0	0.00	0.00	8,874.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,000.0	0.00	0.00	8,974.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,100.0	0.00	0.00	9,074.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,200.0	0.00	0.00	9,174.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,300.0	0.00	0.00	9,274.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,400.0	0.00	0.00	9,374.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,500.0	0.00	0.00	9,474.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,600.0	0.00	0.00	9,574.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,700.0	0.00	0.00	9,674.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W

<b>Company:</b>	Ameredev Operating, LLC.	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Project:</b>	NAN/GB	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Well:</b>	Golden Bell 095H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Wellbore #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	Design #1	<b>Database:</b>	EDM5000

### Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL-FNL (usft)	+FWL-FEL (usft)	Latitude	Longitude
9,800.0	0.00	0.00	9,774.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
9,900.0	0.00	0.00	9,874.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,000.0	0.00	0.00	9,974.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,100.0	0.00	0.00	10,074.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,200.0	0.00	0.00	10,174.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,300.0	0.00	0.00	10,274.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,400.0	0.00	0.00	10,374.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,500.0	0.00	0.00	10,474.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,600.0	0.00	0.00	10,574.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,700.0	0.00	0.00	10,674.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,800.0	0.00	0.00	10,774.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
10,900.0	0.00	0.00	10,874.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
11,000.0	0.00	0.00	10,974.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
11,100.0	0.00	0.00	11,074.7	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
11,190.3	0.00	0.00	11,165.0	255.8	-2,075.8	32° 4' 49.023 N	103° 18' 8.497 W
<b>GB095 KOP (NMNM137469)</b>							
11,200.0	1.16	167.36	11,174.7	255.7	-2,075.7	32° 4' 49.022 N	103° 18' 8.497 W
11,300.0	13.16	167.36	11,273.7	243.6	-2,073.0	32° 4' 48.901 N	103° 18' 8.467 W
11,400.0	25.15	167.36	11,368.0	211.6	-2,065.9	32° 4' 48.584 N	103° 18' 8.387 W
11,500.0	37.15	167.36	11,453.4	161.2	-2,054.6	32° 4' 48.085 N	103° 18' 8.261 W
11,600.0	49.15	167.36	11,526.2	94.6	-2,039.6	32° 4' 47.424 N	103° 18' 8.095 W
11,700.0	61.14	167.36	11,583.3	14.7	-2,021.7	32° 4' 46.632 N	103° 18' 7.896 W
11,792.9	72.29	167.36	11,619.9	-68.4	-2,003.0	32° 4' 45.808 N	103° 18' 7.688 W
11,800.0	72.29	167.36	11,622.1	-75.1	-2,001.6	32° 4' 45.742 N	103° 18' 7.672 W
11,801.9	72.29	167.36	11,622.7	-76.9	-2,001.2	32° 4' 45.724 N	103° 18' 7.667 W
11,833.9	75.44	169.63	11,631.6	-106.9	-1,995.0	32° 4' 45.426 N	103° 18' 7.599 W
<b>GB095 FTP</b>							
11,900.0	82.03	174.13	11,644.5	-171.1	-1,985.9	32° 4' 44.790 N	103° 18' 7.501 W
11,979.3	90.00	179.36	11,650.0	-250.0	-1,981.5	32° 4' 44.009 N	103° 18' 7.457 W
<b>GB095 FTP2</b>							
12,000.0	90.00	179.36	11,650.0	-270.7	-1,981.2	32° 4' 43.805 N	103° 18' 7.457 W
12,100.0	90.00	179.36	11,650.0	-370.7	-1,980.1	32° 4' 42.815 N	103° 18' 7.455 W
12,200.0	90.00	179.36	11,650.0	-470.6	-1,979.0	32° 4' 41.826 N	103° 18' 7.453 W
12,300.0	90.00	179.36	11,650.0	-570.6	-1,977.9	32° 4' 40.836 N	103° 18' 7.452 W
12,400.0	90.00	179.36	11,650.0	-670.6	-1,976.8	32° 4' 39.847 N	103° 18' 7.450 W
12,500.0	90.00	179.36	11,650.0	-770.6	-1,975.7	32° 4' 38.857 N	103° 18' 7.448 W
12,600.0	90.00	179.36	11,650.0	-870.6	-1,974.5	32° 4' 37.867 N	103° 18' 7.446 W
12,700.0	90.00	179.36	11,650.0	-970.6	-1,973.4	32° 4' 36.878 N	103° 18' 7.444 W
12,800.0	90.00	179.36	11,650.0	-1,070.6	-1,972.3	32° 4' 35.888 N	103° 18' 7.443 W
12,900.0	90.00	179.36	11,650.0	-1,170.6	-1,971.2	32° 4' 34.899 N	103° 18' 7.441 W
13,000.0	90.00	179.36	11,650.0	-1,270.6	-1,970.1	32° 4' 33.909 N	103° 18' 7.439 W
13,100.0	90.00	179.36	11,650.0	-1,370.6	-1,969.0	32° 4' 32.920 N	103° 18' 7.437 W
13,200.0	90.00	179.36	11,650.0	-1,470.6	-1,967.9	32° 4' 31.930 N	103° 18' 7.435 W
13,300.0	90.00	179.36	11,650.0	-1,570.6	-1,966.8	32° 4' 30.941 N	103° 18' 7.433 W
13,400.0	90.00	179.36	11,650.0	-1,670.6	-1,965.7	32° 4' 29.951 N	103° 18' 7.432 W

<b>Company:</b> Ameredev Operating, LLC.	<b>Local Co-ordinate Reference:</b> Well Golden Bell 095H
<b>Project:</b> NAN/GB	<b>TVD Reference:</b> KB @ 3038.0usft
<b>Site:</b> NAN/GB #6S	<b>MD Reference:</b> KB @ 3038.0usft
<b>Well:</b> Golden Bell 095H	<b>North Reference:</b> Grid
<b>Wellbore:</b> Wellbore #1	<b>Survey Calculation Method:</b> Minimum Curvature
<b>Design:</b> Design #1	<b>Database:</b> EDM5000

### Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	Latitude	Longitude
13,500.0	90.00	179.36	11,650.0	-1,770.6	-1,964.5	32° 4' 28.962 N	103° 18' 7.430 W
13,600.0	90.00	179.36	11,650.0	-1,870.6	-1,963.4	32° 4' 27.972 N	103° 18' 7.428 W
13,700.0	90.00	179.36	11,650.0	-1,970.6	-1,962.3	32° 4' 26.983 N	103° 18' 7.426 W
13,800.0	90.00	179.36	11,650.0	-2,070.5	-1,961.2	32° 4' 25.993 N	103° 18' 7.424 W
13,900.0	90.00	179.36	11,650.0	-2,170.5	-1,960.1	32° 4' 25.004 N	103° 18' 7.423 W
14,000.0	90.00	179.36	11,650.0	-2,270.5	-1,959.0	32° 4' 24.014 N	103° 18' 7.421 W
14,100.0	90.00	179.36	11,650.0	-2,370.5	-1,957.9	32° 4' 23.025 N	103° 18' 7.419 W
14,200.0	90.00	179.36	11,650.0	-2,470.5	-1,956.8	32° 4' 22.035 N	103° 18' 7.417 W
14,300.0	90.00	179.36	11,650.0	-2,570.5	-1,955.6	32° 4' 21.046 N	103° 18' 7.415 W
14,400.0	90.00	179.36	11,650.0	-2,670.5	-1,954.5	32° 4' 20.056 N	103° 18' 7.413 W
14,500.0	90.00	179.36	11,650.0	-2,770.5	-1,953.4	32° 4' 19.067 N	103° 18' 7.412 W
14,600.0	90.00	179.36	11,650.0	-2,870.5	-1,952.3	32° 4' 18.077 N	103° 18' 7.410 W
14,700.0	90.00	179.36	11,650.0	-2,970.5	-1,951.2	32° 4' 17.088 N	103° 18' 7.408 W
14,800.0	90.00	179.36	11,650.0	-3,070.5	-1,950.1	32° 4' 16.098 N	103° 18' 7.406 W
14,900.0	90.00	179.36	11,650.0	-3,170.5	-1,949.0	32° 4' 15.109 N	103° 18' 7.404 W
15,000.0	90.00	179.36	11,650.0	-3,270.5	-1,947.9	32° 4' 14.119 N	103° 18' 7.403 W
15,100.0	90.00	179.36	11,650.0	-3,370.5	-1,946.7	32° 4' 13.130 N	103° 18' 7.401 W
15,200.0	90.00	179.36	11,650.0	-3,470.5	-1,945.6	32° 4' 12.140 N	103° 18' 7.399 W
15,300.0	90.00	179.36	11,650.0	-3,570.5	-1,944.5	32° 4' 11.151 N	103° 18' 7.397 W
15,400.0	90.00	179.36	11,650.0	-3,670.4	-1,943.4	32° 4' 10.161 N	103° 18' 7.395 W
15,500.0	90.00	179.36	11,650.0	-3,770.4	-1,942.3	32° 4' 9.172 N	103° 18' 7.393 W
15,600.0	90.00	179.36	11,650.0	-3,870.4	-1,941.2	32° 4' 8.182 N	103° 18' 7.392 W
15,700.0	90.00	179.36	11,650.0	-3,970.4	-1,940.1	32° 4' 7.193 N	103° 18' 7.390 W
15,800.0	90.00	179.36	11,650.0	-4,070.4	-1,939.0	32° 4' 6.203 N	103° 18' 7.388 W
15,900.0	90.00	179.36	11,650.0	-4,170.4	-1,937.8	32° 4' 5.214 N	103° 18' 7.386 W
16,000.0	90.00	179.36	11,650.0	-4,270.4	-1,936.7	32° 4' 4.224 N	103° 18' 7.384 W
16,100.0	90.00	179.36	11,650.0	-4,370.4	-1,935.6	32° 4' 3.235 N	103° 18' 7.383 W
16,200.0	90.00	179.36	11,650.0	-4,470.4	-1,934.5	32° 4' 2.245 N	103° 18' 7.381 W
16,300.0	90.00	179.36	11,650.0	-4,570.4	-1,933.4	32° 4' 1.255 N	103° 18' 7.379 W
16,400.0	90.00	179.36	11,650.0	-4,670.4	-1,932.3	32° 4' 0.266 N	103° 18' 7.377 W
16,500.0	90.00	179.36	11,650.0	-4,770.4	-1,931.2	32° 3' 59.276 N	103° 18' 7.375 W
16,600.0	90.00	179.36	11,650.0	-4,870.4	-1,930.1	32° 3' 58.287 N	103° 18' 7.373 W
16,700.0	90.00	179.36	11,650.0	-4,970.4	-1,928.9	32° 3' 57.297 N	103° 18' 7.372 W
16,800.0	90.00	179.36	11,650.0	-5,070.4	-1,927.8	32° 3' 56.308 N	103° 18' 7.370 W
16,900.0	90.00	179.36	11,650.0	-5,170.4	-1,926.7	32° 3' 55.318 N	103° 18' 7.368 W
17,000.0	90.00	179.36	11,650.0	-5,270.3	-1,925.6	32° 3' 54.329 N	103° 18' 7.366 W
17,009.7	90.00	179.36	11,650.0	-5,280.0	-1,925.5	32° 3' 54.233 N	103° 18' 7.366 W
<b>GB095 Into NMNM137472</b>							
17,100.0	90.00	179.36	11,650.0	-5,370.3	-1,924.5	32° 3' 53.339 N	103° 18' 7.364 W
17,200.0	90.00	179.36	11,650.0	-5,470.3	-1,923.4	32° 3' 52.350 N	103° 18' 7.363 W
17,300.0	90.00	179.36	11,650.0	-5,570.3	-1,922.3	32° 3' 51.360 N	103° 18' 7.361 W
17,400.0	90.00	179.36	11,650.0	-5,670.3	-1,921.2	32° 3' 50.371 N	103° 18' 7.359 W
17,500.0	90.00	179.36	11,650.0	-5,770.3	-1,920.0	32° 3' 49.381 N	103° 18' 7.357 W
17,600.0	90.00	179.36	11,650.0	-5,870.3	-1,918.9	32° 3' 48.392 N	103° 18' 7.355 W

<b>Company:</b>	Ameredev Operating, LLC.	<b>Local Co-ordinate Reference:</b>	Well Golden Bell 095H
<b>Project:</b>	NAN/GB	<b>TVD Reference:</b>	KB @ 3038.0usft
<b>Site:</b>	NAN/GB #6S	<b>MD Reference:</b>	KB @ 3038.0usft
<b>Well:</b>	Golden Bell 095H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Wellbore #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	Design #1	<b>Database:</b>	EDM5000

### Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	Latitude	Longitude
17,700.0	90.00	179.36	11,650.0	-5,970.3	-1,917.8	32° 3' 47.402 N	103° 18' 7.353 W
17,800.0	90.00	179.36	11,650.0	-6,070.3	-1,916.7	32° 3' 46.413 N	103° 18' 7.352 W
17,900.0	90.00	179.36	11,650.0	-6,170.3	-1,915.6	32° 3' 45.423 N	103° 18' 7.350 W
18,000.0	90.00	179.36	11,650.0	-6,270.3	-1,914.5	32° 3' 44.434 N	103° 18' 7.348 W
18,100.0	90.00	179.36	11,650.0	-6,370.3	-1,913.4	32° 3' 43.444 N	103° 18' 7.346 W
18,200.0	90.00	179.36	11,650.0	-6,470.3	-1,912.3	32° 3' 42.455 N	103° 18' 7.344 W
18,300.0	90.00	179.36	11,650.0	-6,570.3	-1,911.2	32° 3' 41.465 N	103° 18' 7.342 W
18,400.0	90.00	179.36	11,650.0	-6,670.3	-1,910.0	32° 3' 40.476 N	103° 18' 7.341 W
18,500.0	90.00	179.36	11,650.0	-6,770.3	-1,908.9	32° 3' 39.486 N	103° 18' 7.339 W
18,600.0	90.00	179.36	11,650.0	-6,870.2	-1,907.8	32° 3' 38.497 N	103° 18' 7.337 W
18,700.0	90.00	179.36	11,650.0	-6,970.2	-1,906.7	32° 3' 37.507 N	103° 18' 7.335 W
18,800.0	90.00	179.36	11,650.0	-7,070.2	-1,905.6	32° 3' 36.518 N	103° 18' 7.333 W
18,900.0	90.00	179.36	11,650.0	-7,170.2	-1,904.5	32° 3' 35.528 N	103° 18' 7.332 W
19,000.0	90.00	179.36	11,650.0	-7,270.2	-1,903.4	32° 3' 34.539 N	103° 18' 7.330 W
19,100.0	90.00	179.36	11,650.0	-7,370.2	-1,902.3	32° 3' 33.549 N	103° 18' 7.328 W
19,200.0	90.00	179.36	11,650.0	-7,470.2	-1,901.1	32° 3' 32.560 N	103° 18' 7.326 W
19,300.0	90.00	179.36	11,650.0	-7,570.2	-1,900.0	32° 3' 31.570 N	103° 18' 7.324 W
19,400.0	90.00	179.36	11,650.0	-7,670.2	-1,898.9	32° 3' 30.581 N	103° 18' 7.322 W
19,500.0	90.00	179.36	11,650.0	-7,770.2	-1,897.8	32° 3' 29.591 N	103° 18' 7.321 W
19,600.0	90.00	179.36	11,650.0	-7,870.2	-1,896.7	32° 3' 28.601 N	103° 18' 7.319 W
19,700.0	90.00	179.36	11,650.0	-7,970.2	-1,895.6	32° 3' 27.612 N	103° 18' 7.317 W
19,800.0	90.00	179.36	11,650.0	-8,070.2	-1,894.5	32° 3' 26.622 N	103° 18' 7.315 W
19,900.0	90.00	179.36	11,650.0	-8,170.2	-1,893.4	32° 3' 25.633 N	103° 18' 7.313 W
20,000.0	90.00	179.36	11,650.0	-8,270.2	-1,892.2	32° 3' 24.643 N	103° 18' 7.312 W
20,100.0	90.00	179.36	11,650.0	-8,370.2	-1,891.1	32° 3' 23.654 N	103° 18' 7.310 W
20,200.0	90.00	179.36	11,650.0	-8,470.1	-1,890.0	32° 3' 22.664 N	103° 18' 7.308 W
20,300.0	90.00	179.36	11,650.0	-8,570.1	-1,888.9	32° 3' 21.675 N	103° 18' 7.306 W
20,400.0	90.00	179.36	11,650.0	-8,670.1	-1,887.8	32° 3' 20.685 N	103° 18' 7.304 W
20,500.0	90.00	179.36	11,650.0	-8,770.1	-1,886.7	32° 3' 19.696 N	103° 18' 7.302 W
20,600.0	90.00	179.36	11,650.0	-8,870.1	-1,885.6	32° 3' 18.706 N	103° 18' 7.301 W
20,700.0	90.00	179.36	11,650.0	-8,970.1	-1,884.5	32° 3' 17.717 N	103° 18' 7.299 W
20,800.0	90.00	179.36	11,650.0	-9,070.1	-1,883.3	32° 3' 16.727 N	103° 18' 7.297 W
20,900.0	90.00	179.36	11,650.0	-9,170.1	-1,882.2	32° 3' 15.738 N	103° 18' 7.295 W
21,000.0	90.00	179.36	11,650.0	-9,270.1	-1,881.1	32° 3' 14.748 N	103° 18' 7.293 W
21,100.0	90.00	179.36	11,650.0	-9,370.1	-1,880.0	32° 3' 13.759 N	103° 18' 7.291 W
21,200.0	90.00	179.36	11,650.0	-9,470.1	-1,878.9	32° 3' 12.769 N	103° 18' 7.290 W
21,300.0	90.00	179.36	11,650.0	-9,570.1	-1,877.8	32° 3' 11.780 N	103° 18' 7.288 W
21,400.0	90.00	179.36	11,650.0	-9,670.1	-1,876.7	32° 3' 10.790 N	103° 18' 7.286 W
21,500.0	90.00	179.36	11,650.0	-9,770.1	-1,875.6	32° 3' 9.801 N	103° 18' 7.284 W
21,600.0	90.00	179.36	11,650.0	-9,870.1	-1,874.4	32° 3' 8.811 N	103° 18' 7.282 W
21,700.0	90.00	179.36	11,650.0	-9,970.1	-1,873.3	32° 3' 7.822 N	103° 18' 7.281 W
21,800.0	90.00	179.36	11,650.0	-10,070.1	-1,872.2	32° 3' 6.832 N	103° 18' 7.279 W
21,900.0	90.00	179.36	11,650.0	-10,170.0	-1,871.1	32° 3' 5.843 N	103° 18' 7.277 W
22,000.0	90.00	179.36	11,650.0	-10,270.0	-1,870.0	32° 3' 4.853 N	103° 18' 7.275 W
22,100.0	90.00	179.36	11,650.0	-10,370.0	-1,868.9	32° 3' 3.864 N	103° 18' 7.273 W

<b>Company:</b> Ameredev Operating, LLC.	<b>Local Co-ordinate Reference:</b> Well Golden Bell 095H
<b>Project:</b> NAN/GB	<b>TVD Reference:</b> KB @ 3038.0usft
<b>Site:</b> NAN/GB #6S	<b>MD Reference:</b> KB @ 3038.0usft
<b>Well:</b> Golden Bell 095H	<b>North Reference:</b> Grid
<b>Wellbore:</b> Wellbore #1	<b>Survey Calculation Method:</b> Minimum Curvature
<b>Design:</b> Design #1	<b>Database:</b> EDM5000

### Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	+FSL/-FNL (usft)	+FWL/-FEL (usft)	Latitude	Longitude
22,200.0	90.00	179.36	11,650.0	-10,470.0	-1,867.8	32° 3' 2.874 N	103° 18' 7.271 W
22,246.2	90.00	179.36	11,650.0	-10,516.2	-1,867.3	32° 3' 2.417 N	103° 18' 7.271 W

GB095 BHL - GB095 LTP

### Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
11,190.3	11,165.0	486.4	-85.8	GB095 KOP (NMNM137469)
17,009.7	11,650.0	-5,049.4	64.5	GB095 into NMNM137472

Checked By: \_\_\_\_\_ Approved By: \_\_\_\_\_ Date: \_\_\_\_\_



APD ID: 10400032962

Submission Date: 08/31/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: GOLDEN BELL FED COM 26 36 06

Well Number: 095H

Well Type: OIL WELL

Well Work Type: Drill

### Section 1 - General

Would you like to address long-term produced water disposal? NO

### Section 2 - Lined Pits

Would you like to utilize Lined Pit PWD options? NO

Produced Water Disposal (PWD) Location:

PWD surface owner:

PWD disturbance (acres):

Lined pit PWD on or off channel:

Lined pit PWD discharge volume (bbl/day):

Lined pit specifications:

Pit liner description:

Pit liner manufacturers information:

Precipitated solids disposal:

Describe precipitated solids disposal:

Precipitated solids disposal permit:

Lined pit precipitated solids disposal schedule:

Lined pit precipitated solids disposal schedule attachment:

Lined pit reclamation description:

Lined pit reclamation attachment:

Leak detection system description:

Leak detection system attachment:

**Operator Name:** AMEREDEV OPERATING LLC

**Well Name:** GOLDEN BELL FED COM 26 36 06

**Well Number:** 095H

**Lined pit Monitor description:**

**Lined pit Monitor attachment:**

**Lined pit: do you have a reclamation bond for the pit?**

**Is the reclamation bond a rider under the BLM bond?**

**Lined pit bond number:**

**Lined pit bond amount:**

**Additional bond information attachment:**

### **Section 3 - Unlined Pits**

**Would you like to utilize Unlined Pit PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD disturbance (acres):**

**PWD surface owner:**

**Unlined pit PWD on or off channel:**

**Unlined pit PWD discharge volume (bbl/day):**

**Unlined pit specifications:**

**Precipitated solids disposal:**

**Describe precipitated solids disposal:**

**Precipitated solids disposal permit:**

**Unlined pit precipitated solids disposal schedule:**

**Unlined pit precipitated solids disposal schedule attachment:**

**Unlined pit reclamation description:**

**Unlined pit reclamation attachment:**

**Unlined pit Monitor description:**

**Unlined pit Monitor attachment:**

**Do you propose to put the produced water to beneficial use?**

**Beneficial use user confirmation:**

**Estimated depth of the shallowest aquifer (feet):**

**Does the produced water have an annual average Total Dissolved Solids (TDS) concentration equal to or less than that of the existing water to be protected?**

**TDS lab results:**

**Geologic and hydrologic evidence:**

**State authorization:**

**Unlined Produced Water Pit Estimated percolation:**

**Unlined pit: do you have a reclamation bond for the pit?**

**Operator Name:** AMEREDEV OPERATING LLC

**Well Name:** GOLDEN BELL FED COM 26 36 06

**Well Number:** 095H

**Is the reclamation bond a rider under the BLM bond?**

**Unlined pit bond number:**

**Unlined pit bond amount:**

**Additional bond information attachment:**

### **Section 4 - Injection**

**Would you like to utilize Injection PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Injection PWD discharge volume (bbl/day):**

**Injection well mineral owner:**

**Injection well type:**

**Injection well number:**

**Injection well name:**

**Assigned injection well API number?**

**Injection well API number:**

**Injection well new surface disturbance (acres):**

**Minerals protection information:**

**Mineral protection attachment:**

**Underground Injection Control (UIC) Permit?**

**UIC Permit attachment:**

### **Section 5 - Surface Discharge**

**Would you like to utilize Surface Discharge PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Surface discharge PWD discharge volume (bbl/day):**

**Surface Discharge NPDES Permit?**

**Surface Discharge NPDES Permit attachment:**

**Surface Discharge site facilities information:**

**Surface discharge site facilities map:**

### **Section 6 - Other**

**Would you like to utilize Other PWD options?** NO

**Produced Water Disposal (PWD) Location:**

**PWD surface owner:**

**PWD disturbance (acres):**

**Operator Name: AMEREDEV OPERATING LLC**

**Well Name: GOLDEN BELL FED COM 26 36 06**

**Well Number: 095H**

**Other PWD type description:**

**Other PWD type attachment:**

**Have other regulatory requirements been met?**

**Other regulatory requirements attachment:**



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

## Bond Info Data Report

02/28/2020

APD ID: 10400032962

Submission Date: 08/31/2018

Operator Name: AMEREDEV OPERATING LLC

Well Name: GOLDEN BELL FED COM 26 36 06

Well Number: 095H

Well Type: OIL WELL

Well Work Type: Drill

[Show Final Text](#)

### Bond Information

Federal/Indian APD: FED

BLM Bond number: NMB001478

BIA Bond number:

Do you have a reclamation bond? NO

Is the reclamation bond a rider under the BLM bond?

Is the reclamation bond BLM or Forest Service?

BLM reclamation bond number:

Forest Service reclamation bond number:

Forest Service reclamation bond attachment:

Reclamation bond number:

Reclamation bond amount:

Reclamation bond rider amount:

Additional reclamation bond information attachment: