Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103
District I	Energy, Minerals and Natural Resources		May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II	· ·		WELL API NO. 30-025-36458
1301 W. Grand Ave., Artesia, NM 88210			5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410	District III 1000 Rio Brazos Rd., Aztec, NM 87410 1220 South St. Francis Dr.		STATE FEE
District IV 1220 S. St. Francis Dr., Santa Fe, NM	District IV Santa Fe, NM 8/505		6. State Oil & Gas Lease No.
87505			33037
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name Rawhide 29 State
1. Type of Well: Oil Well Gas Well Other			8. Well Number
2. Name of Operator			1 0. OCRID M
Samson Resources Company			9. OGRID Number 20165
3. Address of Operator			10. Pool name or Wildcat
200 N. Loraine St., Ste. 1010; Midland, TX 79701			Gramma Ridge East
4. Well Location			
Unit Letter N : 910 feet from the South line and 1980 feet from the West line			
Section 29	Township 21S	Range 35E	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc.)			
2638' GR  Pit or Below-grade Tank Application □ or Closure □			
Pit typeDepth to GroundwaterDistance from nearest fresh water well Distance from nearest surface water			
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Construction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
		CASING/CEMENT	<del>==</del>
OTHER:	MOETIFEE COMFL	OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date			
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
As a result of failed MIT on 3/22/2006:			
RU Howco Wireline and 5000 psig lubricator. RIH w/3 3/4" gauge ring to 12,450'.			
Cap w/30° of Class 'H' Cement w/positive displacement bailer (3.2 sx mixed @ 16.4 ppg). WOC 48 hours.			
RIH w/10,000 psig, 4 1/2", 13.50#, CIBP and set @ 12,440'.  Cap w/30' of Class 'H' Cement w/positive displacement bailer (3.2 sx mixed @ 16.4 ppg). WOC 48 hours.  Load hole w/4% KCl water and test casing and plug to 500 psig for 30 minutes.  Chart/record test and submit chart to Samson Midland office, attn: R. M. Burditt, for filing w/OCD.  OCD - RECEIVES ORIGINAL			
Chart/record test and submit chart to Samson Midland office, attn: R. M. Burditt, for filing w/OCD.			
OCD- RECEIVES ORIGINAL A			
CHART S			
			3212223 3212223
			1 Section 18
			(19181A18) C
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be contextured or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.			
SIGNATURE JUL	TITLE_	District Engineer	DATE5/10/06
Type or print name J. L. Farrell, II	II E-mail addr	ress:	Telephone No. (432) 683-7063
For State Use Only  OC FIELD REPRESENTATIVE II/STAFF MANAGEN  MAY 1 0 2000			
APPROVED BY: Lay	Wink TITLE		DATE MAY 1 8 2006
Conditions of Approval (if any):			