Form 3160-5 (April2004)

## UNITEDSTATES DEPARTMENT OF THE INTERIOR CD-HOBBS BUREAU OF LAND MANAGEMENT

FORMAPPROVED
OM B No. 1004-0137
Expires: March 31, 2007

Expires: March 31, 2007

5. Lease Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS			NMNM23777	
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.			7. If Unit or CA/Agreement, Name and/or No.	
Type of Well     Gas Well     Other			8. Well Name and No.	
2. NameofOperator			Linda Federal No. 3	
John H. Hendrix Corporation			9. API Well No.	
3a. Address 3b. PhoneNo. (include area code) P. O. Box 3040 Midland TX 79702-3040 (432)684-6631			30-025-25759	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			10. Field and Pool, or Exploratory Area Blinebry	
1980' FNL & 660' FWL, Sec. 23, T20S, R38E			11. County or Parish, State Lea County, NM	
12. CHECK AI	PPROPRIATE BOX(ES)TO INDICATE	NATURE OF NOTICE, I	REPORT, OR OTHER DATA	
TYPE OF SUBMISSION	ON TYPE OF ACTION			
Notice of Intent  Subsequent Report	Acidize Deepen AlterCasing FractureT Casing Repair New Con Change Plans X Plug and A	struction Recomplete	Well Integrity Other	
Final Abandonment Notice	Convert to Injection PlugBack	Water Disposa	al —	
Attach the Bond under which the following completion of the intesting has been completed. Find determined that the site is ready 3/14/06. Notified Pat Hu Nabors Well Service - Nigts. 2-3/8" tbg. & racks - 5875' - RU Providence Found (P&A mud) - Secur Comtg. called @ 7:00 PM Rescheduled - Comtg. 3/15/06 SD - WO cmtg. 3/15/06 RU Key Cmtg. 3/16/06 RU Key Cmtg. 14.8 PPG & 1.3 @ 5875' - PUH LD 58 jts plug fr. 4330 up to 4084' Continued	he work will be performed or provide the Bond Novel operations. If the operation results in a mutal Abandonment Notices shall be filed only after of final inspection.)  Itchins w/ BLM @ 9:31 AM to start DWHE, NUBOP - No tbg. in well RIH w/ ret. head on 190 jts. 2-3/8 Pump Truck & circ. 7" csg. w/ 200 ed well & SION - Prep. to cmt. @ 13/14/06 - Unable to cmt. due to 116/06.  equip.  Co Mixed & pumped 35 sx. Class yield fr. 5875 up to 5660' inside st. tbg Mixed & spotted 40 sx. Class tbg Mixed & spotted & s. tbg Mixed & s	No. on file with BLM/BIA. Req Itiple completion or recompletion: all requirements, including recla t P&A oprs - MI & RU - Unloaded & racked 2 "tbg Tagged RBP @ bbls. of Nova pre-mix 27:00 AM, 3/15/06 - Ko broken pump -	APR - 4 2006  ES BABYAK  PETROLEUM/ENGINEER  APR - 4 2006	
14. I hereby certify that the fore Name (Printed/Typed)	going is true and correct	1	1.0	
Ronnie H./Westbrook		Title Vice President	232 ALEG	
Signature De Mu	H Machous	Date 03/21/2006		
THIS SPACE FOR FEDERAL OR STATE OFFICE USE				
Approved by	attached Assessed Colored	Title	Date	
	attached. Approval of this notice does not warr I or equitable title to those rights in the subject to conduct operations thereon.			

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Structions on page 2)

Linda Federal No. 3 P&A Procedures NMNM23777

3/16/06 – Continued - Cmt. w/ 2% CaCl2 fr. 2950 up to 2710' (inside 7" csg.) – POH w/ 2-3/8" OE tbg. – WOC – RU rotary WL – RIH w/ perf. Guns – Tagged cmt. @ 2722' – Cont. to perf. 7" csg. w/ 4 JHPF @ 1600' – (4 holes) & at 60' (4 holes) – RD WL – RIH w/ 7" AD-1 pkr., SN & 43 jts. 2-3/8" tbg. – Set pkr. @ 1341' – Estab. IR thru sqz. perfs. @ 1600' – Broke circ. up 7" x 9-5/8" annulus – Cont. to mix & pump 105 sx. Class "C" cmt. w/ 2% CaCl2, down tbg., out sqz. holes & up 7" x 9-5/8" annulus – CI 9-5/8" csg. valve & sqz. 10 bbls. of cmt. away, @ 9/10 BPM @ 650 psi (max press.) Calc. TOC @ 1400' & BOC @ 1800' inside & outside 7" csg. – WOC – RIsd. pkr. & POH – LD pkr. – RIH w/ OE tbg. – Tagged cmt. inside 7" csg. @ 1417' – POH LD 46 jts. (all) tbg. RD BOP, NU tbg. flange – Cont. to mix & pump 45 sx. Class "C" Neat cmt., down 7" csg., out sqz. holes @ 60' & up 7" x 9-5/8" annulus to surf. csg. valve – Circ. 10 sx. good cmt. to pit – SI well, RD Key Cmtg. & Nabor's Well Serv. – Note: All cmtg. ops. Witnessed & approved by BLM Rep. Pat Hutchins – SDFN.

3/17/06 thru 3/20/06 - SD thru weekend.

3/20/06 Dug up cellar & achors.

3/21/06 Cut off 9-5/8" & 7" csg. heads 4' below GL – Installed dry hole marker – Back filled cellar area – Well P&A'd.