Office		f New Mexico	Form C-	
District I 1625 N. French Dr., Hobbs, NM 88240	1220 South St. Francis Dr.		WELL API NO. 30-025-29232	2004
District II 1301 W. Grand Ave., Artesia, NM 88210			5. Indicate Type of Lease	
District III 1000 Rio Brazos Rd., Aztec, NM 87410			STATE X FEE	
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	Santa I	Fe, NM 87505	6. State Oil & Gas Lease No.	
	TICES AND REPORTS O		7. Lease Name or Unit Agreement Nan State "10"	ne
(DO NOT USE THIS FORM FOR PROPODIFFERENT RESERVOIR. USE "APPL			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
PROPOSALS.) 1. Type of Well: Oil Well	Gas Weil X Other		8. Well Number 1	
2. Name of Operator Latigo Petroleum, Inc.			9. OGRID Number 227001	
3. Address of Operator 550 W. Texas, Suite 700 Midland, TX 79701			10. Pool name or Wildcat	
4. Well Location	, IX 19101		Anderson Ranch-Morrow Gas	
Unit Letter O	660 feet from the	e South line and 19	feet from the East 1	ine
Section 10		6S Range 32E	NMPM CountyLea	
	11. Elevation (Show v	whether DR, RKB, RT, GR, etc	·)	
Pit or Below-grade Tank Application	or Closure			
			stance from nearest surface water	
Pit Liner Thickness: mi		olume bbls; C		
12. Check	Appropriate Box to I	Indicate Nature of Notice	, Report or Other Data	
	NTENTION TO:		BSEQUENT REPORT OF:	_
PERFORM REMEDIAL WORK			- - , , , , , , , , , , , , , , , , , ,	
TEMPORARILY ABANDON DULL OR ALTER CASING		<u> </u>	RILLING OPNS. 🔯 PANDA 🗔	
			23101112732	
OTHER: 13 Describe proposed or com	pleted operations. (Clear	OTHER:	nd give pertinent dates, including estimate	Ldate
of starting any proposed w	ork). SEE RULE 1103.	For Multiple Completions: A	ttach wellbore diagram of proposed comp	etion
or recompletion.	t plug Taggad @ 20' F	held your hard and E/20! T/5!	7' Fell free no was	18
4/3/06-Drlg cmt F/890' - T/908' &	973' - 1001'. Broke circ	every 1000' w/kelly. Tagged	7'. Fell free, no gas. @ 6109'. No cmt plug @ 4200'. Drig cmt	1
plug F/6109' - T/6169'. Fell free, 4/4/06-Drlg cmt F/9497' - T/9938'	no gas. Broke circ every	1000' w/kelly. Tagged @ 938	30'. Drlg cmt plug F/9380' - 19497'	,Ö/
	\cdot \cdot\chi_{\chi\ti}{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi\ti}{\chi_{\chi\ti}}\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi\ti}}\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi_{\chi}\ti}}\chi_{\chi_{\chi}\chi_{\chi_{\chi}\ti}}\chi_{\chi_{\chi}\chi_{\chi\ti}\chi_{\chi_{\chi}\chi_{\chi_{\chi}\chi_{\chi_{\chi}\chi_{\chi\ti}\chi_{\chi}\chi_{\chi\tinmbr\chi\ti}\chi_{\chi\tinmbr\chi\tinmbr}\chi\tinmbr\chi\tii\tinmbr\chi\tinmbr\chi\tinmbr\	<u>ي</u> /		
4/5-4/22/06-Drlg 7 7/8" hole w/in	sert bit F/9908 - 1/12,34.	5' w/full returns.	(C)	<u>.</u>
4/23/06-Loggers TD @ 12,530'			1335 72 2625 September 1997 1997 1997 1997 1997 1997 1997 199	<u>'</u>
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i	nsert bit F/12,579' - T/12	,810' w/full returns. TD 7 7/8'	" hole @ 4:00 am 4-25-06. nable to get csg any deeper, float shoe @ 1	2,
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'.	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. \	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u	nable to get csg any deeper, float shoe @ 1	
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs Li	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. \(\) iteCrete Lead cmt (yld - 1	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s	1101c (a) 4.00 an 4-25-00.	
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs Li D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi.	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ' iteCrete Lead cmt (yld - 1 g down @ 8:00 a.m. 4-28-	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 59	
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs L/ D13 (yld - 1.39, wt - 13.0#). Plug	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ' iteCrete Lead cmt (yld - 1 g down @ 8:00 a.m. 4-28-	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 59 ferential (1725 psi). Full returns while	
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs Li D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi.	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ' iteCrete Lead cmt (yld - 1 g down @ 8:00 a.m. 4-28-	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 59 ferential (1725 psi). Full returns while	
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs Li D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi.	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ' iteCrete Lead cmt (yld - 1 g down @ 8:00 a.m. 4-28-	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 59 ferential (1725 psi). Full returns while	
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs L D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi. released @ 6:00 p.m. 4-28-06.	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. V iteCrete Lead cmt (yld - 1 down @ 8:00 a.m. 4-28- Test flange to 3500 psi.	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif Installed capping flange. Set	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 50 ferential (1725 psi). Full returns while out BOP stack. Jet & clean pits. Rig	%
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs L D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi. released @ 6:00 p.m. 4-28-06.	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ViteCrete Lead cmt (yld - 1 g down @ 8:00 a.m. 4-28- Test flange to 3500 psi.	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif Installed capping flange. Set	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 59 ferential (1725 psi). Full returns while	%
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs L D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi. released @ 6:00 p.m. 4-28-06.	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ViteCrete Lead cmt (yld - I 3 down @ 8:00 a.m. 4-28- Test flange to 3500 psi.	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif Installed capping flange. Set	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 59 ferential (1725 psi). Full returns while out BOP stack. Jet & clean pits. Rig ge and belief. I further certify that any pit or b	%
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs L D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi. released @ 6:00 p.m. 4-28-06. I hereby certify that the information grade tank has been/will be constructed of	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ViteCrete Lead cmt (yld - I 3 down @ 8:00 a.m. 4-28- Test flange to 3500 psi.	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif Installed capping flange. Set	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 59 ferential (1725 psi). Full returns while out BOP stack. Jet & clean pits. Rig ge and belief. I further certify that any pit or b or an (attached) alternative OCD-approved plan DATE 05/08/2006	velow-
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs L D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi. released @ 6:00 p.m. 4-28-06.	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ViteCrete Lead cmt (yld - I 3 down @ 8:00 a.m. 4-28- Test flange to 3500 psi.	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif Installed capping flange. Set lete to the best of my knowled D guidelines ☐, a general permit ☐ TITLE Regulatory Analyst E-mail address: lhunt@latig	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 56 ferential (1725 psi). Full returns while out BOP stack. Jet & clean pits. Rig ge and belief. I further certify that any pit or b or an (attached) alternative OCD-approved plan DATE 05/08/2006 opetro.com Telephone No. (432)684 MAY 3 1 2006	velow-
4/23/06-Loggers TD @ 12,530' 4/24-4/25/06-Drill 7 7/8" hole w/i 4/28/06-PPU & run 335 jts, 5.5", 798', FC @ 12,719'. 4/29/06-Cmt 5.5"csg w/600 sxs L D13 (yld - 1.39, wt - 13.0#). Plug cmt'g. Bumped plug to 2100 psi. released @ 6:00 p.m. 4-28-06. I hereby certify that the information grade tank has been/will be constructed of SIGNATURE Type or print name Lisa Hunt	nsert bit F/12,579' - T/12 17#, P-110, LT&C csg. ViteCrete Lead cmt (yld - I 3 down @ 8:00 a.m. 4-28- Test flange to 3500 psi.	,810' w/full returns. TD 7 7/8' Wash 32' to 12,798' by tally, u 1.99, wt - 10.5#) + tail w/350 s -06. Est TOC @ 7500' by dif Installed capping flange. Set lete to the best of my knowled D guidelines □, a general permit □	nable to get csg any deeper, float shoe @ 1 exs PVL + .3% D167, 2% D65, 2% D46, 56 ferential (1725 psi). Full returns while out BOP stack. Jet & clean pits. Rig ge and belief. I further certify that any pit or b or an (attached) alternative OCD-approved plan DATE 05/08/2006 opetro.com Telephone No. (432)684 MAY 3 1 2006	velow-