SUNDR Do not use 1			FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007 5. Lease Serial No. NMNMO634 - C 6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE- Other instructions on reverse side.			7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well Gas Well Other			8. Well Name and No.
2. Name of Operator Lewis B. Burleson, Inc.			T C Federal #1 9. AP! Well Mo.
3a Address         3b. Phone No. (include rrea code)           P.C. Box 2479 Midland, TX 79702         432/683-4747			30 - 025 - 37622 10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M. or Survey Description) 1980' FNL & 660' FWL, Sect. 19, T-20-S, R-39-E			D-K Abo 11. County or Parish, State
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
TYPE OF SUBMISSION	ISSION TYPE OF ACTION		
Notice of Intent	Acidize Deepen Alter Casing Fracture Casing Repair New Cor	Production (St Freat Reclamation Instruction Recomplete	Well Integrity
X Subsequent Report	Change Plans Plug and Convert to Injection Plug Back	Abandon Temporarily Al	
If the proposal is to deepen d Attach the Bond under which following completion of the testing has been completed. determined that the site is rea	rectionally or recomplete horizontally, give subsur the work will be performed or provide the Bond N involved operations. If the operation results in a mu Final Abandonment Notices must be filed only after	face locations and measured and tra lo. on file with BLM/BIA. Requir ultiple completion or recompletion r all requirements, including reclan	in a new interval, a Form 3160-4 must be filed once
14. I hereby certify that the for Name (Printed/Typed)	pregoing is true and correct	······	
Steven L. E	Burleson	Title Vice-Pres	ident
Signature		Date 6/2,"	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE			
	re attached. Approval of this notice does not war gal or equitable title to those rights in the subject		Date
which would entitle the applicant to conduct operations thereon. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to anymatter within its jurisdiction.			

(Instructions on page 2)

٠,

Exhibit "A"

## LEWIS B. BURLESON, INC. T C FEDERAL WELL #1

. .

- 4-6-06 DRLG. 948' REDBED 99' HR. SPUDDED 8:00 PM 4-5-06 DEV. 467' 11/4° MUD WT. 8.7 VIS 30
- 4-7-06 TD 1630' RUNNING CSG. ANHY. DEV. 980' 1 3/4°, 1457' 2° MUD WT. 9.6 VIS 31
- 4-8-06 TD 1630' TIH W/ BIT # 2 RAN 38 JTS. 85/8" 24# CSG. SET @ 1624' SCHLUMBERGER CMT. W/ 535 SKS. CLASS C , 4%GEL. , 195 SKS. CLASS C, 2% CACL. CIRC. 50 SKS TO SURFACE. PLUG DOWN 10:00 AM 4-7-06 NU BOP TEST BOP, MANIFOLD, TIW VALVES, 2000 PSI . TEST OK.
- 4-9-06 DRLG. 2952' ANHY SALT 69' HR. DEV. 2094' 2°, 2603' 3°. MUD WT. 10 VIS 29 PH 10
- 4-10-06 DRLG. 3620' ANHY DEV. 2984' 2 3/4°, 3079', 2 1/2°. MUD WT. 10 VIS 29 PH 10
- 4-11-06 DRLG. 4254' ANHY- DOLO 29' DEV. 4032'- ¼". MUD WT. 10 VIS 29 PH10
- 4-12-06 DRLG. 4930" DOLO 29' HR. DEV. 4537' 3/4° MUD WT. 10 VIS 29 PH10
- 4-13-06 DRLG. 5506' DOLOMITE 24.5' HR. DEV. 5037' MUD WT. 10 VIS 29 PH 10
- 4-14-06 DRLG. 5684' DOLOMITE 15' HR. DEV. 5510' 1° MUD WT. 10 VIS 29 PH 10 BIT #2 OUT 5510'
- 4-15-06 DRLG. 6161' DOLOMITE 18' HR. DEV. 5981' -11/2° MUD WT. 10 VIS 29 PH 10
- 4-16-06 DRLG. 6515' DOLOMITE- LIMESTONE 19' HR. MUD WT. 10 VIS 29 PH 10
- 4-17-06 DRLG. 6872' DOLOMITE 17' HR. DEV. 6483'- 11/4°. MUD WT. 10 VIS 29 PH 10

LEWIS B. BURLESON, INC. T C FED #1 PAGE 2

- 4-18-06 TOH 7120' DOLCMITE 16' HR. DEV. 6923'@ 1° MUD WT. 10 VIS 29 PH 10
- 4-19-06 WAITING FOR MECHANIC CLUTCH PROBLEM. RIH W/ MAGNET TO FISH CONE FROM BIT # 3 RECOVERED CONE.
- 4-20-06 DRLG. 7275' DOLO- ANHY. 15' HR. MUD WT. 10 VIS 29 PH 10
- 4-21-06 DRLG. 7581' DOLOMITE 9' HR. DEV. 7400'- 11/4° MUD WT. 10 VIS32 PH 10 WL 8
- 4-22-06 LOGGING 7660' DEV 7660-1° MUD WT. 10 VIS 32 PH 10 WL 8
- 4-23-06 RAN 200 JTS. 51/2" 17 # N-80 CASING. SET @ 7658' SCHLUMBERG ER CMT. W/ 615 SACKS 35/65 POZ CLASS C, AND 890 SACKS 50/50 POZ CLASS C. PLUG DOWN 1:00 AM CIRC. 50 SACKS TO PIT. SET SLIPS. ND BOP. CUT OFF CASING. RIG RELEASED 3:00AM. 4-23-06
- 5-3-06 RUPU NUWELLHEAD, BOP. RAN CBL/GR LOG. PERF 51/2" CASING 7298,7300,11,1317,21,29,41,43,45,51,57,59,69,71,82,85,7427,29,31,33,40 ,42,51,53,60,62,64,66,71,73,79,81,89,7548,58, 7560. 37 SHOTS. SDON
- 5-4-06 RIH W/ PKR. SN, 230 JTS. 23/8" TBG. SET @ 7206' WEATHERFORD ACIDIZED W/ 15,000 GALS. 15% NEFE ACID & 60 BALL SEALERS. FORM BROKE 4050 PSI. AV. 3.4 BPM @ 4900 PSI MAX 5250 PSI. BALL OUT. ISDP 3827 PSI. 15 MIN 2826 PSI. LOAD TO REC. 394 BBLS.