Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR CD-HOBBS BUREAU OF LAND MANAGEMENT

FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007

5. Lease Serial No. LC 029410B

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160 - 3 (APD) for such proposals.		6. If Indian, Allottee or I fibe Name	
SUBMIT IN TRIPLICATE- Other instructions on reverse side.			7. If Unit or CA/Agreement, Name and/or No.
1. Type of Well Gas Well Other			8920003410 8. Well Name and No.
2. Name of Operator ConocoPhillips Company			MCA Unit #161
3a. Address 3b. Phone No. (include area code)			9. API Well No. 30-025-12781
551 2 115115		58-1244	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			Maljamar GB/SA
2615' FSL & 2615' FEL, Unit Letter J, Section 30, T-17-S, R-32-E			11. County or Parish, State Lea Co., NM
12. CHECK A	PPROPRIATE BOX(ES) TO INDICAT	TE NATURE OF NOTICE, I	REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION		
Notice of Intent	Acidize Deeper Alter Casing Fracture	\`	art/Resume) Water Shut-Off Well Integrity
Subsequent Report		onstruction Recomplete	Other
Final Abandonment Notice	Convert to Injection Plug Ba	d Abandon Temporarily A	
04/14/06 SD for Good Frid 04/17/06 Held safety meet 3,429 - 3,279°. Pumped 25 cmt @ 545°. Perforated @ 04/18/06 Held safety meet Unit #201.	rig #26 & plugging equipment, dug out ce day & Easter. ing. Notified NMOCD & BLM. RIH w/ 5 sx C cmt 1,971 – 1,881'. Perforated @ 9 400'. RIH w/ packer and squeezed 110 s	tubing, tagged PBTD @ 3,429'. 35'. RIH w/ packer and squeez sx C cmt @ 400'. SI well, SDFN g. Circulated 10 sx C cmt 63' t	LES BABYAK Circulated hole WARD Fumpe 23 St CERR and 100 st Cerr @ 935; WOC and tagged
14. I hereby certify that the foreg	going is true and correct	1	No. of the state o
James F. Newman	n, P.E.	Title Engineer, Triple N Ser	rvices, Inc. 432.687.1994
Signature & -		Date 09	5/04/2006
THIS SPACE FOR FEDERAL OR STATE OFFICE USE			
Approved by	Stached. Approval of this notice CoeDHS TRAIT or equitable title to those rights in the subject I		Date Date JUN 1 5 2006
which would entitle the applicant to	conduct operations thereon.	Office	

ACTUAL PLUGGED WELLBORE SKETCH

ConocoPhillips Company -- Permian Basin Business Unit

Date: April 28, 2006

RKB@ DF @ GL@ Subarea: Maljamar MCA Unit No. 161W Lease & Well No. : Legal Description : 2615' FSL & 2615' FEL, Sec. 30, T-17-S, R-32-E State : New Mexico County: Lea Maljamar (Grayburg-San Andres)
Dec. 30, 1950 Rig Released: 10-3/4" 32# @ 29' Field: May 16. 1951 Date Spudded : Cmt'd w/10 sx 10 sx C cmt circulate 63' to surface Status: Plugged and Abandoned 04/18/06 Drilled as Simon IP No. 21 110 sx C cmt 400 - 190' Stimulation History: perf/sqz'd TAGGED 1 he May May <u>Interval</u> <u>Date</u> <u>Type</u> <u>Gais</u> Sand Press ISIP Rate 5/1/63 Well was formerly Carper Drilling Company Simon IP #21 Effective with unitization of the MCA on 5/1/63, was renumbered MCA Unit No. 161. 8-5/8" 24# @ 764' w/ 25 sx Aquagel 4/30/70 Converted from gas injection to producer 3637-3875 10/12/71 Gelled prod water 40,000 60,000 4000 1500 18.0 Top Salt @ 935' 3690-3975 12/15/81 Mod 202 acid 3.000 RS 2200 2000 2.8 100 sx C cmt 935 - 545', perf & sqz'd, TAGGED 12/19/81 Install injection wellhead converted from producer to water injection 11/24/82 Cleanout scale to TD Injection Survey - no fluid movement below 3722' 9/30/83 Repair communications 3/26/90 Run Tracer and temperature survey 8/15/91 major losses @ 3696'-3726' -- 100% No channel or packer leak indicated. 9/17/01 Pmp 70 sx cement; TOC @ 3550' 9/21/01 Set CIBP @ 3464' - would not set Set CIBP @ 1100' 3/24/01 Knock out CIBP @ 1100'; set packer @ 3470'; lay down tubing Base Salt @ 1,880* 25 sx C cmt 1,971 - 1,881' TRIPLE N
SERVICES INC. **ACTUAL PLUGGING PROCEDURE** 25 sx C cmt 3,429 - 3,279' 2) 25 sx C cmt 1,971 - 1,881' 3) 100 sx C cmt 935 - 545', perf & sqz'd TAGGED 110 sx C cmt 400 - 190', perf & sqz'd TAGGED 10 sx C cmt circulate 63' to surface Capacities 4-1/2" 9.5# csg: 10.960 ft/ft3 0.0912 ft3/ft 25 sx C cmt 3,429 - 3,279' 7" 20# csg: 4.399 ft/ft3 0.2273 ft3/ft 7-7/8" openhole: 2.957 ft/ft3 0.3382 ft3/ft Packer @ 3,470' 8-5/8" 24# csg: 2.797 ft/ft3 0.3576 ft3/ft 10-3/4" 40.5# csa: 1.815 ft/ft3 0.5508 ft3/ft 70 sx cmt, TOC @ 3,550° Formation Tops: 7" 20# @ 3,637' w/ 300 sx Salado Top Salt 9351 3690-3740 - 100 Qts Nitro - 3-1/2" shells Base Salt 1880 3740-3785 - 45 Qts Nitro - 2-1/2" Shells Yates 3785-3815 - 60 Qts Nitro - 3-1/2" Shells Seven Rivers Queen Gravburg 3915-3975 - 120 Qts Nitro - 3-1/2" Shells 6th Zone San Andres PBTD @ 3550 8th Zone TD@ 4034 9th Zone