

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-24675
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-2735
7. Lease Name or Unit Agreement Name East Vacuum GB/SA Unit Tract #2672
8. Well Number 008
9. OGRID Number 217817
10. Pool name or Wildcat Vacuum Grayburg/San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
ConocoPhillips Company ATTN: Celeste Dale

3. Address of Operator
4001 Penbrook Street Odessa, Texas 79762

4. Well Location
Unit Letter B : 990 feet from the North line and 2,310 feet from the East line
Section 26 Township 17-S Range 35-E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc)
3,914' GL

Pit or Below-grade Tank Application ☐ or Closure ☒

Pit type STEEL Depth to Groundwater _____ Distance from nearest fresh water well > 1 mile Distance from nearest surface water N/A

Pit Liner Thickness: STEEL mil Below-Grade Tank: Volume 180 bbls; Construction Material STEEL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED WELLBORE DIAGRAM

05/30/06 MIRU Triple N rig #26 & plugging equipment. Held safety meeting. Set steel pit. POOH w/ rods. NU BOP. POOH w/ production tubing.

05/31/06 Attended safety meeting. Set CIBP @ 4,413'. Circulated hole w/ mud, pumped 25 sx C cmt 4,413 - 4,263'. Pumped 25 sx C cmt 2,952 - 2,802'. Pumped 25 sx C cmt @ 1,619'. SDFN.

06/01/06 Attended safety meeting at office. Tagged cmt @ 1,400'. Pumped 25 sx C cmt 349 - 199'. ND BOP, pumped 15 sx C cmt 50' to surface. RDMO.

Cut off wellhead & anchors, installed dryhole marker.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE James F. Newman TITLE James F. Newman, P.E. (Triple N Services) DATE 06/23/06

Type or print name James F. Newman E-mail address: jim@triplenservices.com Telephone No. 432-687-1994
For State Use Only


APPROVED BY: James F. Newman TITLE OG FIELD REPRESENTATIVE II / STAFF MANAGER DATE JUN 27 2006
Conditions of Approval (if any):

PLUGGED WELLBORE SKETCH **ConocoPhillips Company -- Permian Basin Business Unit**

Date: June 1, 2006

RKB @ 3926'
 DF @ 3925'
 GL @ 3914'

Subarea : Buckeye
 Lease & Well No. : East Vacuum GB/SA Unit Tract 2672 Well No. 008
 Legal Description : 990' FNL & 2310' FEL, Sec. 26, T-17-S, R-35-E
 County : Lea State : New Mexico
 Field : Vacuum (Grayburg-San Andres)
 Date Spudded : March 2, 1974 Rig Released: March 18, 1974
 API Number : 30-025-24675
 Status: Plugged 06/01/06



15 sx C cmt 50' to surface

13-1/2" Hole

10-3/4" 30# ST&C @ 311' w/ 400 sx, circ 50 sx

25 sx C cmt 349 - 199'

25 sx C cmt 1,619 - 1,400' TAGGED
 Top of Salt @ 1,609'

Base Salt @ 2,860'

25 sx C cmt 2,952 - 2,802'

8-3/4" Hole

25 sx C cmt 4,413 - 4,263'

CIBP @ 4,413'

== 4484 - 4486 - 6 shots
 == 4514 - 4517 - 8 shots
 == 4520 - 4524 - 10 shots
 == 4532 - 4536 - 10 shots
 == 4563 - 4565 - 6 shots } Reperforated 8 shots 4 JSPF
 == 4567 - 4570 - 8 shots } Reperforated 12 shots
 == 4573 - 4577 - 10 shots } Reperforated 16 shots
 == 4583 - 4588 - 12 shots } Reperforated 20 shots

7" 24# @ 4,700' w/ 1,400 sx lead, 200 sx tail
 TOC @ Surface

PBTD: 4,671'
 TD: 4,700'

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate
4484-4588	3/25/74	Perf 4484-4588 (select fire) w/2 JSPF					
	3/25/74	Gelled SW	30,000	45,000	3500	1400	26.1
	5/3/74	Set retainer @ 4550, sqz perfs 4563-4588 w/10 sx cmt					
4484-4536	2/1/84	Shut-in					
	1/21/86	Install submersible pump and reactivate					
	11/3/89	15% NEFE HCl	3,000	40 BS	1050	800	3.0
	10/25/94	Red Acid	2,000	500# RS		440	
4563-4588	5/26/97	Drill out cement and retainer to 4680' and perforate 4583-4588, 4573-4577, 4567-4570 and 4563-4565					
	5/28/97	Attempt to acidize - perfs 4563 to 4588 communicated with perforations 4484-4536					
4484-4588	6/3/97	15% Fercheck	2,250	2500# RS	1257	594	5.0
	3/04	Shut-In					



PLUGGING PROCEDURE

- 1) set CIBP @ 4,413'
- 2) 25 sx C cmt 4,413 - 4,263'
- 3) 25 sx C cmt 2,952 - 2,802'
- 4) 25 sx C cmt 1,619 - 1,400' TAGGED
- 5) 25 sx C cmt 349 - 199'
- 6) 15 sx C cmt 50' to surface

Capacities

4-1/2" 11.6# csg:	11.468 ft/ft3	0.0872 ft3/ft
5-1/2" 17# csg:	7.661 ft/ft3	0.1305 ft3/ft
7" 20# csg:	4.399 ft/ft3	0.2273 ft3/ft
7" 24# csg:	4.567 ft/ft3	0.2189 ft3/ft
7-5/8" 26.4# csg:	3.775 ft/ft3	0.2648 ft3/ft
8-5/8" 32# csg:	2.922 ft/ft3	0.3422 ft3/ft
9-5/8" 36# csg:	2.304 ft/ft3	0.434 ft3/ft
10-3/4" 40.5# csg:	1.815 ft/ft3	0.5508 ft3/ft
7-7/8" openhole:	2.957 ft/ft3	0.3382 ft3/ft
8-3/4" openhole:	2.395 ft/ft3	0.4176 ft3/ft
11" openhole:	1.515 ft/ft4	0.6600 ft3/ft
12-1/4" openhole:	1.222 ft/ft3	0.8185 ft3/ft

Formation Tops:

Anhydrite	1662'
Yates	2901'
Queen	3783'
San Andres	4462'