NEW EXICO OIL CONSERVATION COM SSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Commission or its proper agent before the work specified will be returned to the sender on which will be given the approval, with any modifications considered advisable, rejection by the Commissioner or agent, of the plan submitted. The plan as approved should be to the plan submitted. should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	_X_		INTENTION TO SI CALLY TREAT WI		
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF OTHER	INTENTION TO P WISE ALTER CAS	ULL OR SING	
NOTICE OF INTENTION TO REPAIR WELL					
NOTICE OF INTENTION TO DEEPEN WELL		NOTICE OF	INTENTION TO P	LUG WELL	-
	Ho	obbs, New	Mexico	Jan. 10	1940
		Plac		Dat	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Gentlemen:			Care Service		
Following is a notice of intention to do certain wor. SKELLY OTL CO. E.					SE NU
Company or Operator Lease					
of Sec. 6 , T. 21 , R. 2	37	N. M. P. M.,	Hardy		Field,
Drilled to depth of 160's bottom with 150 sx cement	- Ha	alliburto	n Process.	Cement c	irculate
_	- Ha	alliburto L11 let s	n Processet 48 hrs a . will dril	Gement condon T h uil plug and	irculate rsday, 1 test
bottom with 150 sx cement back to bottom of cellar. January 11, at approximate for casing shut-off	- Ha	alliburto L11 let s	n Process.et 48 hrs a will dril	Cement c nd on T h u	irculated rsday, dest
bottom with 150 sx cement back to bottom of cellar. January 11, at approximate for casing shut-off	- Ha	alliburto L11 let s	n Processet 48 hrs a . will dril	Cement of nd on Thursday, and I plug and I of I o	irculatersday, d test
bottom with 150 sx cement back to bottom of cellar. January 11, at approximate for casing shut-off	- Ha	alliburto L11 let s	et 48 hrs a will dril	Cement of nd on Thursday, and I plug and I of I o	irculate rsday, l test
bottom with 150 sx cement back to bottom of cellar. January 11, at approximate for casing shut-off	- Ha	alliburto: ill let s 2:00 P. H	et 48 hrs a will dril	Cement of nd on Thurst plug and I	irculate rsday, l test
bottom with 150 sx cement back to bottom of cellar. January 11, at approximate for casing shut-off	- Ha	alliburto: [11 let sel:00 P. H. By Position	et 48 hrs a will dril	Cement cond on Thurst plug and I	irculatersday, l test
bottom with 150 sx cement back to bottom of cellar. January 11, at approximate for casing shut-off Approved except as follows:	- Ha	By Position	SKELLY OF	Cement of the nd on Thur I plug and I plug a	irculated rsday, l test
bottom with 150 sx cement back to bottom of cellar. January 11, at approximate for casing shut-off	- Ha	By Position Send	et 48 hrs a will dril SKELLY OF Company or or District communications of the company of the communications	Cement of the nd on Thur I plug and I plug a	irculated rsday, a test
bottom with 150 sx cement back to bottom of cellar. January 11, at approximate for casing shut-off Approved except as follows:	- Ha	By Position	SKELLY OF Company or or District decommunications of Skelly Oi	L CO. Superint en regarding well to 1 Co.	irculate rsday, l test