


## NEW-MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## Notice of Intention to Drill



HOBBS OFFICE

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

Dec. 30, 1939

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.  
Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

SKELLY OIL COMPANY E. C. Hill Well No. 4 in C/Lot 6- SE/4  
of Sec. 6 T. 21 R. 37, N. M. P. M., Hardy Field, Lea County nw/4  
Company or Operator Lease

N.

The well is 1876.5 feet XX (S.) of the North line and 1867 feet

(E.) (W) of the West line of Section 6 -

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_, Assignment No. \_\_\_\_\_

If patented land the owner is Elmer C. Hill


Address Eunice, New Mexico

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is \_\_\_\_\_

Address \_\_\_\_\_



AREA 640 ACRES  
LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Cabletools - from top to total depth... Drlg. contractor J.C. Clover,

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: \_\_\_\_\_

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing od	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
18"	16"	70#	SH	170'	Cemented	150
15"	13"	40#	SH	465'	Landed	
12 1/2"	10-3/4"	40#	SH	770'	Landed	
10 1/2"	8-5/8"	32#	SH	1220'	Landed	
8 1/2"	7"	24#	New	3525'	Cemented	250

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3610 feet.

Additional information: In cementing the 16" OD casing the cement will be circulated back into bottom of cellar. At the time the 7" OD casing is run and cemented the 13", 10-3/4" & 8-5/8" casing will be pulled. At the time of cementing the two strings of casing above sufficient time shall be given for cement to thoroughly set before drlg plug & testin

Approved except as follows:

JAN - 2 1940

Sincerely yours,

By J. T. O'Connell  
Position District Superintendent  
Send communication regarding well to  
Name Skelly Oil Co.  
Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Ray Yountrough  
Title OIL & GAS INSPECTOR