

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

Notice of Intention to Drill

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

April 20, 1940

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.
Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

SKELLY OIL COMPANY

E.C. Hill

Well No. 6 in Center of Lot 4

Company or Operator
of Sec. 6, T. 21, R. 37, N. M. P. M. Lease Hardy Field, Lea County

N.

The well is 605 feet (S.) of the North line and 603.5 feet

(E.) of the West line of Section 6-

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. , Assignment No.

If patented land the owner is Elmer C. Hill

Address Eunice, New Mexico

If government land the permittee is

Address

The lessee is Skelly Oil Company

Address Tulsa, Oklahoma

AREA 640 ACRES
LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: NEW MEXICO

CABLE tools from top to total depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
16 1/8"	16" OD	70#	SH	135'	Cemented	150
15 1/8"	13"	40#	SH	400'	Landed	
12 1/8"	10-3/4"	36#	SH	750'	Landed	
10 1/8"	8-5/8"	32#	SH	1140'	Landed	
8 1/8"	7"	20#	New	3415'	Cemented	250

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3475 feet.

Additional Information: In cementing the 16" OD casing the cement will be circulated back to bottom of cellar. The 13", 10-3/4" and 8-5/8" OD casing strings will be pulled at the time the 7" OD casing is run and cemented.

Approved APR 26 1940, 19
except as follows:

Sincerely yours,

SKELLY OIL COMPANY

Company or Operator

By

Position

District Superintendent

Send communication regarding well to

Name

Skelly Oil Company

Address

Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title Roy Garbrough OIL & GAS INSPECTOR