## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 5-27-2004

## FILE IN TRIPLICATE **OIL CONSERVATION DIVISION** WELL API NO. DISTRICT I 1220 South St. Francis Dr. 1625 N. French Dr., Hobbs, NM 88240 30-025-27001 Santa Fe, NM 87505 5. Indicate Type of Lease **DISTRICT II** STATE 1301 W. Grand Ave, Artesia, NM 88210 6. State Oil & Gas Lease No DISTRICT III 1000 Rio Brazos Rd, Aztec, NM 87410 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A North Hobbs (G/SA) Unit DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (Form C-101) for such proposals.) Section 30 8. Well No. 1. Type of Well: 442 Oil Well Gas Well Other Injector 9. OGRID No. 157984 2. Name of Operator Occidental Permian Ltd. 10. Pool name or Wildcat 3. Address of Operator Hobbs (G/SA) HCR 1 Box 90 Denver City, TX 79323 4. Well Location Feet From The Unit Letter P Feet From The 1050 1300 South East NMPM Lea County 30 Township 18-S 38-E Section 11. Elevation (Show whether DF, RKB, RT GR, etc.) 3657' KB Pit or Below-grade Tank Application or Closure Distance from nearest surface water Distance from nearest fresh water well Depth of Ground Water Below-Grade Tank: Volume \_\_\_\_\_\_ bbls; Construction Material Pit Liner Thickness Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 12. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG & ABANDONMENT CASING TEST AND CEMENT JOB **PULL OR ALTER CASING Multiple Completion** OTHER: OTHER: Plug back & Open additional pay 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Kill well & pull injection equipment. 2. Run bit & scraper to BPTD @ ±4285'. 3. Plug well back with sand & cap with cement up to 4260'. 4. Perforate well @2 JSPF with 180 degree Phase at 4220-4230' (22 holes). 5. Acidize perfs 4164'-4214' w/15% aicd. 6. Run back in hole w/injection equipment. closed according to NMOCD guidelines or an (attached) alternative OCD-approved , a general permit plan SIGNATURE TITLE DATE Administrative Associate 07/11/2006 TELEPHONE NO. 806-592-6280 TYPE OR PRINT NAME E-mail address: Mendy A. Johnson mendy\_johnson@oxy.com

For State Use Only
APPROVED BY

CONDITIONS OF APPROVAL IF AN