State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 5-27-200

Revised 5-27-2004 FILE IN TRIPLICATE OIL CONSERVATION DIVISION 1220 South St. Francis Dr. WELL API NO. DISTRICT I 1625 N. French Dr., Hobbs, NM 88240 30-025-31429 Santa Fe, NM 87505 DISTRICT II 5. Indicate Type of Lease STATE 1301 W. Grand Ave, Artesia, NM 88210 FEE 6. State Oil & Gas Lease No. DISTRICT III 1000 Rio Brazos Rd, Aztec, NM 87410 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A South Hobbs (G/SA) Unit DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (Form C-101) for such proposals.) Section 4 1. Type of Well: 8. Well No. Oil Well X Gas Well 9. OGRID No. 2. Name of Operator 157984 Occidental Permian Ltd. 3. Address of Operator 10. Pool name or Wildcat Hobbs (G/SA) HCR 1 Box 90 Denver City, TX 79323 4. Well Location Unit Letter K : 1403 Feet From The Feet From The South 1746 Section Lea County Township **NMPM** Range 38-E 11. Elevation (Show whether DF, RKB, RT GR, etc.) 3619' KB Pit or Below-grade Tank Application or Closure Pit Type ____ Depth of Ground Water __ Distance from nearest fresh water well ___ Distance from nearest surface water Pit Liner Thickness Below-Grade Tank: Volume _ bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. **PLUG & ABANDONMENT PULL OR ALTER CASING Multiple Completion** CASING TEST AND CEMENT JOB OTHER: Plug back/Open additional perfs/Stim OTHER: 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion of recompletions. 1. Pooh w/ESP equipment. 2. Clean out well to PBTD @4291'. 3. Set CICR in 7" casing @4211'. Squeeze open perfs 4214'-4264'. 4. Drill out CICR @4211'. 5. Perforate hole w/4" select fire casing guns at 4 JSPF at the following depths: 4089'-98', 4107'-13'. 6. Acid treat well w/15% HCL. 7. Scale squeeze well. 9. Run back in hole w/ESP equipment. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved plan **SIGNATURE** TITLE Administrative Associate DATE 07/18/2006 TYPE OR PRINT NAME Mendy E-mail address: Johnson mendy johnson@oxy.com TELEPHONE NO. 806-592-6280

For State Use Only

APPROVED BY

CONDITIONS OF APPROVAL IF ANY

TITLE