

**DISTRICT I**  
P.O. Box 1980, Hobbs, NM 88240

**DISTRICT II**  
P.O. Drawer DD, Artesia, NM 88210

**DISTRICT III**  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-025-07626
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name McKinley
Well No. 8
Pool name or Wildcat Bowers; Seven Rivers

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER TA'D	
Name of Operator Occidental Permian LTD	
Address of Operator 1017 W. Stanolind Rd. Hobbs, New Mexico	
Well Location Unit Letter <u>D</u> : <u>660</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>West</u> Line Section <u>5</u> Township <u>19 S</u> Range <u>38 E</u> NMPM Lea County	
Elevation (Show whether DF, RKB, RT, GR, etc.)	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐


Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 3251' 9 5/8" @ 350' Circ. 6 5/8" 3179' TOC @ 625' Perfs 3173'-3179' CIBP @ 3123'

5-1-03 Tag existing CIBP @ 3123' Circ. well w/ M.L.F. Spot 30 sks of cement @ 3123'-2926' Spot 30 sks of cement @ 2686'-2489'  
Spot 30 sks of cement @ 1624'-1427'

5-2-03 Perf @ 400' Test to 750 psi. Notify Gary Wink. Spot 75 sks of cement 464'-surface

Cut off wellhead & anchors 4'BGL. Cap well. Install dry hole marker, 4' under ground.



Approved as to plugging of the Well Bore.  
Liability under bond is retained until  
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert Gilbert TITLE SP. Engr Tech DATE 05-02-03

TYPE OR PRINT NAME Robert Gilbert TELEPHONE NC 397-8206

(This space for State Use)

APPROVED BY Gary W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE AUG 07 2003

CONDITIONS OF APPROVAL, IF ANY