

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-07688
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name South Hobbs Unit
Well No. 101
Pool name or Wildcat Hobbs (G/SA)
Well Location Unit Letter C : 990 Feet From The North Line and 2310 Feet From The West Line Section 15 Township 19-S Range 38-E NMPM Lea County
Elevation (Show whether DF, RKB, RT, GR, etc.)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER TAD
Name of Operator Occidental Permian LTD
Address of Operator 1017 W. Stanolind Rd. Hobbs, New Mexico
Well Location Unit Letter C : 990 Feet From The North Line and 2310 Feet From The West Line Section 15 Township 19-S Range 38-E NMPM Lea County
Elevation (Show whether DF, RKB, RT, GR, etc.)

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4300' PBDT 4257' 16" csg 130', 10 3/4" 1647', 8 5/8 csg 4010' CIBP @ 3912'

5-13-03 Tagged existing CIBP @ 3912' Circ. well w/ M.L.F. Spot 25 sks of cement @ 3912'-3812'. Spot 25 sks of cement @ 2695'-2595'.
Spot 55 sks of cement @ 1700'. Tagged @ 1460'
5-14-03 Spot 60 sks of cement @ 187'-surface.

Cut off wellhead and anchors 4' BGL Cap well. Install dry hole marker. Clean Location

Approved as to plugging of the Well
Liability under bond is retained
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert G. Galt TITLE SR Engr Tech DATE 6-16-03

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY

Harry W. Wink

OC FIELD REPRESENTATIVE II/STAFF MANAGER

DATE AUG 07 2003

CONDITIONS OF APPROVAL, IF ANY