

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO. 30-025-07694
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.
Lease Name or Unit Agreement Name South Hobbs (G/SA) Unit
Well No. 100
Pool name or Wildcat Hobbs (G/SA)

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER Injector TAD
Name of Operator Occidental Permian LTD
Address of Operator 1017 W. Stanolind Rd. Hobbs, New Mexico

Well Location Unit Letter C : 330 Feet From The North Line and 2310 Feet From The West Line Section 15 Township 19 S Range 38 E NMPM Lea County
Elevation (Show whether DF, RKB, RT, GR, etc.)

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER: <input type="checkbox"/>	

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ANBANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-18-03 Set CIBP @ 4050' Circulate well w/ plugging mud. Spot 25 sks of cement @ 4050'-3803'.  
Perf @ 2680' Pressured up on perfs to 1500 psi-Held ( 4-3 1/8" hollow carrier jet shots) Spot 25 sks of cement 2730' Tagged @ 2450'

7-21-03 Perf @ 1683' Pressured up to 1500 psi-Held Spot 25 sks of cement @1733' Tagged @ 1347' Perf @ 167' Pressured up to 1000 psi-Held  
Spot 25 sks of cement 240'-surface

Cut off wellhead and anchors 3'BGL. Cap well. Install dry hole marker.

Approved as to plugging of the well  
Liability under bond is retained until  
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Robert Gilbert*

TITLE

*SR Engr Tech*

DATE

*8-6-03*

TYPE OR PRINT NAME

*Robert Gilbert*

TELEPHONE NO.

*397-8206*

(This space for State Use)

APPROVED BY

*Larry W. Wink*

TITLE

*OC FIELD REPRESENTATIVE II/STAFF MANAGER*

DATE

*AUG 07 2003*

CONDITIONS OF APPROVAL, IF ANY: