

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.  
30-025-20539

Indicate Type of Lease  
STATE ☐ FEE ☒

State Oil & Gas Lease No.

Lease Name or Unit Agreement Name  
South Hobbs (G/SA) Unit

Well No.  
99

Pool name or Wildcat  
Hobbs (G/SA)

|   |  |
|---|--|
| <b>SUNDRY NOTICES AND REPORTS ON WELLS</b><br>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)       |  |
| Type of Well:<br>OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER TAD   |  |
| Name of Operator<br>Occidental Permian LTD  |  |
| Address of Operator<br>1017 W. Stanolind Rd. Hobbs, New Mexico  |  |
| Well Location<br>Unit Letter <u>D</u> : <u>350</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>West</u> Line<br>Section <u>15</u> Township <u>19 S</u> Range <u>38 E</u> NMPM <u>Lea</u> County |  |
| Elevation (Show whether DF, RKB, RT, GR, etc.)  |  |

11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☒  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-22-03 Tagged existing CIBP @ 3968' Circ. well w/ plugging mud. Spot 25 sks of cement @ 3968'-3590'

7-23-03 Perf @ 2680' Pressured up to 1500 psi-Held. Perf @ 2580' Pressured up to 1500 psi-Held Spot 35 sks of cement 2730' Tagged @ 2147'

7-24-03 Perf @ 1600' Squeezed 35 sks of cement. Tagged @ 1493'. Perf @ 480' circulated 135 sks of cement to surface.

Cut off wellhead and anchors 3'BGL. Cap well. Install dry hole marker.

Approved as to plugging of the Well Bore.  
Liability under bond is retained until  
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert Gilbert TITLE SR Engr Tech DATE 07-25-03

TYPE OR PRINT NAME Robert Gilbert TELEPHONE NO. 397-8206

(This space for State Use)

APPROVED BY Harry W. Wink OC FIELD REPRESENTATIVE II / STAFF MANAGER

CONDITIONS OF APPROVAL, IF ANY:

AUG 07 2003