


This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

Active

Byars #1 (Anadarko)
660' FNL, 660' FEL, (A) Sec 8
T 12S, R 38E, Lea Co., NM
Gladiola (Devonian) Field



Spud: 10-10-81

Completion: 1-8-82 Recompletion to Atoka 5-83.

P&A'd: 9-4-83

API # 30-025-27493

ReEntered: 3/15/06

IP P 80 BO & 18 BW. GOR 0. 1-19-82

Tbg: 31 jts 2 -7/8" 8.7# L-80 PH6(974.14')

228 jts 2 -7/8" 6.5# L-80 EUE 8rd(7,399.56')

Bottom of tbg: 8,387.48 ft

13 3/8" 48# H-40 @ 397' w/ 400 sxs.
Circ to sfc.

Pump: 5 - ESP 4" TD3000 pumps w/ 541 stages

Motors: 2 -180HP @ 1505 V - 79 amps

Cable: #2 flat Reda Lead

Date Ran: 4/13/2006

Bottom of motor: 8,566.57 ft

Intake Depth: 8,493.53 ft

8 5/8" 24# & 28# K-55 & S-80 @ 4,458' w/ 2,230 sxs.
Circ'd 105 sx to sfc.
Tie-back 5 1/2" f/ 4,532' to sfc.

TOC @ 7,750' (TS)

DVT @ 9,505'
2nd Stage Cmt'd w/ 500 sx 50/50 Poz H

Perf'd Atoka w/4 SPF @ 11,263'-275'.

Perf'd Devonian f/ 11,981' to 985'.

5 1/2" pkr/shoe 17/23# @ 11,986'. Cmt'd 1st Stg w/ 510 sx. 50/50 Poz H

TD @ 11,991' WLM 12,021' Pipe depth

Formation Tops		
Woodford	11906	-8033
Devonian	11983	-8110
Oil-water	12053	-8180

4/24/2006 JMR