District I
1625 N. French Dr., Hobbs, NM 88240
District IF
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Xio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

a.

State of New Mexico Energy Minerals and Natural Resources

> Oil Conservation Division 1220 South St. Francis Dr. Santa Fe. NM 87505

For drilling and production facilities, submit to appropriate NMOCD District Office. For downstream facilities, submit to Santa Fe office

		505			
Pit or Below-	Grade Tank Reg	istration or Clo	sure		
	e tank covered by a "ge				
Type of action: Registration of	a pit or below-grade tank	Closure of a pit or below-	-grade tank 🛛		
Deperator: COG Operating LLC Telephone: 432-685-4372 e-mail address: dkuykendall@conchoresources.com					
Address: Fasken Center Tower II, 550 W. Texas Ave., Suite 1300, Midland, TX 79701					
	L#: 30-025-37491 U/L or Qtr/Qtr:		Sec: 19 T: 20S R: 36E		
County: Lea Latitude: N 32° 33'38" Longitude: W 103° 23' 30" NAD: 1927 [] 1983 []					
Surface Owner: Federal [] State Private [] Indian []					
<u>Pit</u>	Below-grade tank				
Type: Drilling Production Disposal		Type of fluid:			
Workover Emergency		:			
	Double-walled, with	Double-walled, with leak detection? Yes [] If not, explain why not.			
Liner type: Synthetic I Thickness: 12 mil Clay					
Pit Volume: 35,000 bbl					
Depth to ground water (vertical distance from bottom of pit to season	Less than 50 feet		(20 points)		
high water elevation of ground water.) 81'	50 feet or more, but le	ess than 100 feet $X$	(10 points) 10		
	100 feet or more -		( 0 points)		
	Yes	<u></u>	(20 points)		
Wellhead protection area: (Less than 200 feet from a private domestic	No - X		(0 points) 0		
water source, or less than 1000 feet from all other water sources.)					
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)			(20 points)		
	200 feet or more, but 1		(10 points)		
	1000 feet or more - X		(0 points) 0		
	Ranking Score (Tota	l Points)	10 points		
this is a pit closure: (1) Attach a diagram of the facility showing the	nit's relationship to other equ	unment and tanks (2) Ind	licate disposal location: (check the ongite how if		
ur are burying in place) onsite 🛛 offsite 🗌 If offsite, name of facil					
nediation start date and end date. (4) Groundwater encountered: No					
		n below ground surface	it. and attach sample results.		
Attach soil sample results and a diagram of sample locations and exc					
Additional Comments: Pit Closure Plan attached					
hereby partifies that the information of the second s			State Contraction		
hereby certify that the information above is true and complete to the las been/will be constructed or closed according to NMOCD guide	elines 🛛, a general permit [	or an (attached) altern	the above-described pit or below-grade tank		
		_, (			
Date: 3/28/06	· ·	d	$\wedge  \rangle  $		
rinted Name/Title	Signature (a	a ) Jaco	dall		
our certification and NMOCD approval of this application/closure do therwise endanger public health or the environment. Nor does it relie gulations.	bes not relieve the operator of the the operator of its responsi	liability should the content bility for compliance with	ts of the pit or tank contaminate ground water or any other federal, state, or local laws and/or		
narrough 1	-				
pproval: rinted Name/Title GARY W. WINK/STAFFMGR Signature Kauf Wink Date: 8/28/06					
The value in the start of the ville start of the ville start of the st	Signature _	uju.um	$\mathcal{R}$ Date: $\mathcal{X} \subset \mathcal{O} / \mathcal{O} \mathcal{O}$		
•	· · ·		-		

## Pit Closure Plan – Drilling Pit

## Operator:COG Operating LLCWell Name:Red Raider State #2Location:Unit G, Section 19, Township 20 S, Range 36 E, Lea County, NM

The drilling pit associated with this well will be closed as per New Mexico OCD "Pit and Below-Grade Tank Guidelines" dated November 1, 2004. The visual inspection of the pit indicated that the pit liner has maintained its integrity.

- 1. Any remaining liquids will be removed from the pit.
- 2. Remaining solid wastes (i.e. buckets, cans, miscellaneous trash, debris, contaminated solids, etc.) will be removed from the pit, except for dried mud and cuttings, cement, and frac materials in drilling and reserve pits which have been approved by the OCD for encapsulation.

## 3. This well did penetrate a salt section, and 9.5 lb/gal brine or greater was used during drilling. Therefore, the pit will be closed by <u>capping</u> and <u>encapsulation</u>:

Capping and encapsulation will be accomplished by mixing earthen materials with the pit contents, as necessary to stiffen the pit contents sufficiently to provide physical stability and support for the pit cover; folding the edges of the liner over the stiffened mud and cuttings; capping with a 20 mil minimum thickness impervious, reinforced, synthetic or fabricated liner meeting ASTM standards that is designed to be resistant to the material encapsulated; the liner will overlap the underling pit by at least 3 feet on all directions; and covering the liner cap with minimum of 3 feet of clean soil that is capable of supporting native plant growth.

4. Upon closure of the pit, the surface where the pit was located will be contoured to prevent erosion and ponding of rainwater over the site.

1

80.92

Red Raidau #2