	To Appropriate District		of New Me			I	Form C-103
District I				 		May 27, 2004	
	r., Hobbs, NM 88240				WELL API NO.		
District II		OIL CONSE	RVATION	DIVISION	30-025-26493		
	ve., Artesia, NM 88210				5. Indicate Type	of Lease	
District III 1000 Rio Brazos	Rd., Aztec, NM 87410		uth St. Fran		STATE	⊠ FEE	
District IV	, 112100, 1111 07 110	Santa	ı Fe, NM 87	7505	6. State Oil & Ga	as Lease No.	
	s Dr., Santa Fe, NM						
87505	OT D ID DITTO	TOTAL AND DEPART			ļ		
(DO NOT LICE T		ICES AND REPORTS			7. Lease Name o	r Unit Agree	ment Name
		SALS TO DRILL OR TO D CATION FOR PERMIT" (F					
PROPOSALS.)	DERVOIR. COE THIEF	CATION TOKTERMIT (I	ORIM C-101)1 C	ok been	Pennzoil State		
1. Type of W	ell:OilWell 🛛	Gas Well Other			8. Well Number		
					001		
2. Name of C					9. OGRID Numb	per	
	gy Co. of Colorado				162683		
3. Address of					10. Pool name or		
PO Box 1409	07; Irving, TX 75014	I-0907			Lovington; Uppe	r Penn, NE	
4. Well Loca	ion						
Unit	Letter G : 1	980 feet from the	North	line and 198	feet from the	East	line
Secti			ange37			_	
Secti	JII 16 I					<u>Lea</u>	
988163	By Supplied St	11. Elevation (Show 3851' GR	wneiner DK,	, KKB, KI, GK, eic	.,	Transfer.	
Pit or Below-grad	e Tank Application 🔲 o					12 848	
Pit typeI	epth to Groundwater_	Distance from	nearest fresh wa	iter well	Distance from nearest	surface water_	<u>-</u>
Pit Liner Thickne	ss:	Below-Grade Tank: \	Volume	bbls; Co	nstruction Material		
	12 Check	Appropriate Box	to Indicate	Notura of Notic	a Danast as Oth	m Data	
	12. CHECK	. Appropriate box	io muicate i	ivature of ivolic	e, Report of Office	zi Data	
	NOTICE OF IN	NTENTION TO:		9115	SEQUENT RE	DODT OF	z.
PERFORM RI		PLUG AND ABAND	ом П	REMEDIAL WOR			CASING [
	· 			i	ILLING OPNS.	P AND A	
PULL OR ALT	ER CASING	MULTIPLE COMPL	. 🔲	CASING/CEMEN	IT JOB 🔲	1.611 No.	~ (~2)
OTHER:	* -		F-7	OTHER:		\D	100
	he proposed or com	oleted operations. (Cle	orly state all a		d size mantinant di	P AND A	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
13. Descri	g any proposed of comp	s). SEE RULE 1103.	arry State arr p	Commissions Atta	ia give periment dat	es, includativa	regumateu uate or
	g any proposed work pletion.	.). SEE ROLE 1105. 1	roi munipie (Completions: Atta	ch wendore diagram	or brobesed	ecompletion or
iccom	piction.				1	. 	\$ 151
07-13-06	Set RBP @ 8630'	w/2 ex cand			*	. '9	∵ ∆
07-14-06	DCI 10D1 (@ 0050						**
0, 1, 00	Set nacker in seve		and 5721' and	nrecoured up with	500 nei at each ston	to abook for	· anaima lante
		eral places b/tw 5332' a		pressured up with	500 psi at each stop		
07-15-06	Isolated bad casin	eral places b/tw 5332' and g from 5651' to 5721'.			_	ે જિલ્લ	18.7
07-15-06	Isolated bad casin Cemented hole in	eral places b/tw 5332' a g from 5651' to 5721', casing with 200 sx Cla			_	ે જિલ્લ	18.7
	Isolated bad casin Cemented hole in minutes. TOC est	eral places b/tw 5332' ag from 5651' to 5721'. casing with 200 sx Clat 5400'.			_	ે જિલ્લ	18.7
07-17-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce	eral places b/tw 5332' a g from 5651' to 5721'. casing with 200 sx Cla t 5400'. ement.	ass H + 2% Ca		_	ે જિલ્લ	18.7
07-17-06 07-18-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca	eral places b/tw 5332' a g from 5651' to 5721'. casing with 200 sx Cla t 5400'. ement. sing to 400 psi for 15 r	ass H + 2% Ca		_	ે જિલ્લ	18.7
07-17-06 07-18-06 07-19-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @	eral places b/tw 5332' ag from 5651' to 5721'. casing with 200 sx Clat 5400'. ement. sing to 400 psi for 15 r. 8630'.	ass H + 2% Ca		_	ે જિલ્લ	18.7
07-17-06 07-18-06 07-19-06 07-20-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1	eral places b/tw 5332' ag from 5651' to 5721'. casing with 200 sx Clat 5400'. ement. sing to 400 psi for 15 r 8630'. 1485'.	ass H + 2% Ca minutes.	aCl then 10 bbls U	ni-Flac S D167. Pre	essure tested	with 540 psi for 30
07-17-06 07-18-06 07-19-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2	eral places b/tw 5332' a g from 5651' to 5721'. casing with 200 sx Clat 5400'. ement. sing to 400 psi for 15 r 8630'. 1485'. 2-3/8" tbg & SN to 113	ass H + 2% Ca minutes. 371'. Acid wa	aCl then 10 bbls U	ni-Flac S D167. Pre	essure tested	with 540 psi for 30 Which seems to be see
07-17-06 07-18-06 07-19-06 07-20-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b	eral places b/tw 5332' a g from 5651' to 5721'. casing with 200 sx Cla t 5400'. ement. sing to 400 psi for 15 r 8630'. 1485'. 2-3/8" tbg & SN to 113 bbls treated water. Avg	. ass H + 2% Ca minutes. 371'. Acid wa g rate 3.3 BPN	aCl then 10 bbls U ashed perfs from 1 A @ 2300 psi. The	ni-Flac S D167. Pre	essure tested 2000 gal 15 from 11372	with 540 psi for 30 Which seems to be see
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE	eral places b/tw 5332' a g from 5651' to 5721'. casing with 200 sx Cla t 5400'. ement. sing to 400 psi for 15 r 8630'. 1485'. 2-3/8" tbg & SN to 113 bbls treated water. Avg FE HCL followed by f	ass H + 2% Ca minutes. 371'. Acid wa g rate 3.3 BPM lush with 44 t	aCl then 10 bbls U ashed perfs from 1 M @ 2300 psi. The bbls treated water.	ni-Flac S D167. Pre	essure tested 2000 gal 15 from 11372	with 540 psi for 30 Which seems to be see
07-17-06 07-18-06 07-19-06 07-20-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE	eral places b/tw 5332' a g from 5651' to 5721'. casing with 200 sx Cla t 5400'. ement. sing to 400 psi for 15 r 8630'. 1485'. 2-3/8" tbg & SN to 113 bbls treated water. Avg	ass H + 2% Ca minutes. 371'. Acid wa g rate 3.3 BPM lush with 44 t	aCl then 10 bbls U ashed perfs from 1 M @ 2300 psi. The bbls treated water.	ni-Flac S D167. Pre	essure tested 2000 gal 15 from 11372	with 540 psi for 30 Which seems to be see
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE	eral places b/tw 5332' a g from 5651' to 5721'. casing with 200 sx Cla t 5400'. ement. sing to 400 psi for 15 r 8630'. 1485'. 2-3/8" tbg & SN to 113 bbls treated water. Avg FE HCL followed by f	ass H + 2% Ca minutes. 371'. Acid wa g rate 3.3 BPM lush with 44 t	aCl then 10 bbls U ashed perfs from 1 M @ 2300 psi. The bbls treated water.	ni-Flac S D167. Pre	essure tested 2000 gal 15 from 11372	with 540 psi for 30 Which seems to be see
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump	g from 5651' to 5721'. casing with 200 sx Clate 5400'. ement. sing to 400 psi for 15 re 8630'. 1485'. 2-3/8" tbg & SN to 113 obls treated water. Avg FE HCL followed by find and spaced out tubing	ass H + 2% Caninutes. 371'. Acid was rate 3.3 BPM Sush with 44 to g. Put well bas	aCl then 10 bbls U ashed perfs from 1 A @ 2300 psi. The bbls treated water. ack on production.	ni-Flac S D167. Pre 1443' – 11453' with an acid washed perfs Avg rate 3 BPM @	2000 gal 15 from 11372 2300 psi.	with 540 psi for 30 When the second with 540 ps
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump	g from 5651' to 5721'. casing with 200 sx Clate 5400'. ement. sing to 400 psi for 15 re 8630'. 1485'. 2-3/8" tbg & SN to 113 bbls treated water. Avg FE HCL followed by find a packed out tubing above is true and com	ass H + 2% Caninutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bandle.	acl then 10 bbls U ashed perfs from 1 A@2300 psi. The bbls treated water. ack on production.	ni-Flac S D167. Pre	2000 gal 15 from 11372 2300 psi.	with 540 psi for 30 % NEFE followed ' – 11407' with
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump	g from 5651' to 5721'. casing with 200 sx Clate 5400'. ement. sing to 400 psi for 15 re 8630'. 1485'. 2-3/8" tbg & SN to 113 obls treated water. Avg FE HCL followed by find and spaced out tubing	ass H + 2% Caninutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bandle.	acl then 10 bbls U ashed perfs from 1 A @ 2300 psi. The bbls treated water. ack on production.	ni-Flac S D167. Pre	2000 gal 15 from 11372 2300 psi.	with 540 psi for 30 % NEFE followed ' – 11407' with
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06 07-25-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump	g from 5651' to 5721'. casing with 200 sx Clate 5400'. ement. sing to 400 psi for 15 re 8630'. 1485'. 2-3/8" tbg & SN to 113 bbls treated water. Avg FE HCL followed by find a packed out tubing above is true and com	ass H + 2% Caminutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bandle plete to the besidelines □, a ge	acl then 10 bbls U ashed perfs from 1 M@2300 psi. The bbls treated water. ack on production. est of my knowledgeneral permit or an	ni-Flac S D167. Pro	2000 gal 15 from 11372 2300 psi.	with 540 psi for 30 % NEFE followed ' – 11407' with any pit or below-grade
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump	g from 5651' to 5721'. casing with 200 sx Clate 5400'. ement. sing to 400 psi for 15 re 8630'. 1485'. 2-3/8" tbg & SN to 113 bbls treated water. Avg FE HCL followed by find a packed out tubing above is true and com	ass H + 2% Caninutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bandle.	acl then 10 bbls U ashed perfs from 1 A @ 2300 psi. The bbls treated water. ack on production.	ni-Flac S D167. Pro	2000 gal 15 from 11372 2300 psi.	with 540 psi for 30 % NEFE followed ' – 11407' with any pit or below-grade
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06 07-25-06 I hereby certify tank has been/will	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pum that the information be constructed or closed	g from 5651' to 5721', casing with 200 sx Clat 5400'. Ement. Sing to 400 psi for 15 r. 8630'. 1485'. 2-3/8" tbg & SN to 113 obls treated water. Avg FE HCL followed by f p and spaced out tubing above is true and comit according to NMOCD gu	ass H + 2% Caminutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bas plete to the besidelines □, a ge	acl then 10 bbls U ashed perfs from 1 M@ 2300 psi. The bbls treated water. ack on production. est of my knowledgeneral permit Grant or an	ni-Flac S D167. Presentation of the presentati	2000 gal 15 from 11372 2300 psi.	with 540 psi for 30 % NEFE followed ' – 11407' with any pit or below-grade l plan .
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06 1 hereby certify tank has been/will SIGNATURE Type or print na	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump that the information be constructed or closed	g from 5651' to 5721', casing with 200 sx Clat 5400'. Ement. Sing to 400 psi for 15 r. 8630'. 1485'. 2-3/8" tbg & SN to 113 obls treated water. Avg FE HCL followed by f p and spaced out tubing above is true and comit according to NMOCD gu	ass H + 2% Caminutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bas plete to the besidelines □, a ge	acl then 10 bbls U ashed perfs from 1 M@2300 psi. The bbls treated water. ack on production. est of my knowledgeneral permit or an	ni-Flac S D167. Presentation of the presentati	2000 gal 15 from 11372 2300 psi.	with 540 psi for 30 % NEFE followed ' – 11407' with any pit or below-grade
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06 07-25-06 I hereby certify tank has been/will	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump that the information be constructed or closed	g from 5651' to 5721', casing with 200 sx Clat 5400'. Ement. Sing to 400 psi for 15 r. 8630'. 1485'. 2-3/8" tbg & SN to 113 obls treated water. Avg FE HCL followed by f p and spaced out tubing above is true and comit according to NMOCD gu	ass H + 2% Caminutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bas plete to the besidelines □, a ge	acl then 10 bbls U ashed perfs from 1 M@ 2300 psi. The bbls treated water. ack on production. est of my knowledgeneral permit Grant or an	ni-Flac S D167. Presentation of the presentati	2000 gal 15 from 11372 2300 psi. er certify that a DCD-approved August 23, 2	with 540 psi for 30 % NEFE followed ' – 11407' with any pit or below-grade l plan □. 006 972-401-3111
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06 1 hereby certify tank has been/will SIGNATURE Type or print na For State Use	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump that the information be constructed or closed time Natalie Kru Dnly	g from 5651' to 5721', casing with 200 sx Clat 5400'. Ement. Sing to 400 psi for 15 r. 8630'. 1485'. 2-3/8" tbg & SN to 113 obls treated water. Avg FE HCL followed by f p and spaced out tubing above is true and comit according to NMOCD gu	ass H + 2% Caminutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bas plete to the besidelines □, a ge	acl then 10 bbls U ashed perfs from 1 M@ 2300 psi. The bbls treated water. ack on production. est of my knowledgeneral permit Grant or an	ni-Flac S D167. Presentation of the presentati	2000 gal 15 from 11372 2300 psi. er certify that a DCD-approved August 23, 2	with 540 psi for 30 % NEFE followed ' – 11407' with any pit or below-grade l plan □. 006 972-401-3111
07-17-06 07-18-06 07-19-06 07-20-06 07-21-06 1 hereby certify tank has been/will SIGNATURE Type or print not be a series of the	Isolated bad casin Cemented hole in minutes. TOC est Drilled through ce Pressure tested ca Released RBP @ Pushed CIBP to 1 RIH with 349 jts 2 by flush with 44 b 3000 gal 15% NE Installed rod pump that the information be constructed or closed time Natalie Kru Dnly	g from 5651' to 5721', casing with 200 sx Clat 5400'. Ement. Sing to 400 psi for 15 r. 8630'. 1485'. 2-3/8" tbg & SN to 113 obls treated water. Avg FE HCL followed by f p and spaced out tubing above is true and comit according to NMOCD gu	ass H + 2% Caminutes. 371'. Acid was rate 3.3 BPM lush with 44 to g. Put well bas plete to the besidelines □, a ge	acl then 10 bbls U ashed perfs from 1 M@ 2300 psi. The bbls treated water. ack on production. est of my knowledgeneral permit Grant or an	ni-Flac S D167. Presentation of the presentati	2000 gal 15 from 11372 2300 psi. er certify that a DCD-approved August 23, 2	with 540 psi for 30 % NEFE followed ' – 11407' with any pit or below-grade l plan □.