+Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C 103

DISTRICT I

## OIL CONSERVATION DIVISION

Revised 1-1-99

1625 N French Dr, Hobbs, NM S8240	O S. St. Francis Dr.	WELL API NO. 30 025 08606
DISTRICT II 1301 W. Grand Ave, Artesia, NM 88210  Santa Fe, New Mexico 87505		5. Indicate Type of Lease
DISTRICT III		STATE FEE 6. State Oil& Gas Lease No.
1000 Rio Brazos Rd., Aztec, NM 87410		B 11223-2
SUNDRY NOTICES AND REPORT (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR DIFFERENT RESERVOIR. USE "APPLICAT (FORM C-101) FOR SUCH PROP	TO DEEPEN OR PLUG BACK TON FOR PERMIT	7. Lease Name or Unit Agreement Name
1. Type of Well:  Oil Gas Well OTH		
2. Name of Operator  Melrose Operating Company		8. Well No.
3. Address of Operator		9. Pool name or Wildcat
c/o P.O. Box 953, Midland, TX 79702 (915 684-638l)		Jalmat, Tansill, Yates, Seven Rivers
4. Well Location  Unit Letter L 1980' Feet From The	South Line and _	660' Feet From The West Line
Section 13 Township 2	2S Range 35E	NMPM Lea County
//////////////////////////////////////	(Show whether DF, RKB. RT, GR,	etc.)
11. Check Appropriate Box to	Indicate Nature of No	otice, Report, or Other Data
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABAN	DON REMEDIAL WO	ORK ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE D	DRILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	CASING TEST	AND CEMENT JOB
OTHER:	OTHER	
12. Describe Proposed or Completed Operations (Clearly state all work) SEE RULE 1103.  Propose to plug and abandon Well #105 as follows:  Status of well:  11" hole: 8 5/8", 24# casing @ 284' cemented with 100 sx 7.7/8" hole: 5 1/2", 14# casing @ 2809' competed with 92	t, circulated to surface.	
7 7/8" hole: 5 1/2", 14# casing @ 3998' cemented with 92: Well perforated @ 3766-3906'.	sx calculates to surface.	1-0- 75-X
Well perforated @ 3766-3906'.  Plugging Proposal: IF DUMP BAILED  CIBP @ 3660' w/30' cement on top.  Current recommended surface water plug: SPOT  30 sx plug @ 234-334'. — TAG	35 IF SPOTTED	1800-1700 (TOP AF JALT PLUG
10 sx plug @ surface.	THE CO	Ommission must be notified 24
WOC, set dry hole marker.	F' ~ 3	S PRIOR TO THE BEGINNING OF BING OPERATIONS FOR THE C-103 APPROVED.
I hereby certify that the information prove 15 first and complete to the best of m		THE TRUE TO THE TENT OF THE TE
SIGNATURE MILETALE	Regulatory A	Agent 8-11-03
TYPE OR PRINT NAME Ann E. Ritchie		TELEPHONE NO. 915 684-6381
(this space for State Use)	OC FIELD REPRES	SENTATIVE II/STAFF MANAGER
APPROVED BY Lay W. Wink	TITLE	DATE AUG 15 200