

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-03404
5. Indicate Type of Lease
STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
1149418

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Finley Resources, Inc.

3. Address of Operator
1308 Lake Street, Ste. 200, Fort Worth, Texas 76102

4. Well Location

Unit Letter J: 2895' feet from the North line and 1650' feet from the East line
Section 3 Township 21S Range 35E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3606' KB

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Rotate through tight spot @ 1,731'. Tag up @ 3700'. Wash to 3744'. Spot 25sx cmt plug from 3744'-3514'. WOC. Tag TOC @ 3523'. Witnessed by NMOCD Rep Buddy Hill, Displace hole w/9.5# salt gel mud. Cut out slip bowl. 5 1/2 csg free to 690'. Back off 5 1/2" csg @ 558'. Recover 18jts (553") DIH to 1821'. Pump 30sx cmt plug from 1821'-1523'. WOC. Tag cmt @ 1712'. Witnessed by B. Hill. Pump additional 30sx cmt plug from 1712'—1414'. WOC. Tag TOC @ 1642'. Notified Mr. Gonzales with NMOCD. Ok'd to proceed. Pump 226sx cmt from 642' to surface, top off w/4sx. TOC 2' below ground level. Cut off 9 5/8" csg 4' below GL. Welded cap. Install 5 1/2" jt as DH marker per Mr. Gonzales. Remove wellhead, equipment, and clean location. Location inspected by Mr. Gonzales. P&A complete.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative NCD-approved plan ☐.

SIGNATURE James L. Nance TITLE: Western District Manager DATE 8/29/2006

Type or print name James L. Nance E-mail address: jim.nance@state.nm.gov Telephone No. (817) 231-8727

For State Use Only

APPROVED BY: Harry W. Wink TITLE _____ DATE SEP 06 2006

Conditions of Approval (if any):

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.