Submit 3 Copies To Appropriate District Office <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240	State of New Mexico Energy, Minerals and Natural Resources OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-103 May 27, 2004 YELL API NO.
District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505			30-025-36819 Indicate Type of Lease STATE FEE State Oil & Gas Lease No. VO-6588
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other			Lease Name or Unit Agreement Name Wynette AYS State Com Well Number 1
Name of Operator Yates Petroleum Corporation Address of Operator 105 S. 4 th Street, Artesia, NM 88210 4. Well Location			OGRID Number 025575 D. Pool name or Wildcat Saunders; Permo Up Penn, South
Unit Letter N : 660 feet from the South line and 1650 feet from the West line Section 32 Township 15S Range 33E NMPM Lea County			
	11. Elevation (Show whether DR 4206	R, RKB, RT, GR, etc.)	
Pit or Below-grade Tank Application or Closure			
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF IN PERFORM REMEDIAL WORK TEMPORARILY ABANDON DULL OR ALTER CASING OTHER:	<u>=</u>	REMEDIAL WORK COMMENCE DRILLII CASING/CEMENT JO	QUENT REPORT OF: ALTERING CASING DESCRIPTION OF & A DESCRIPTION OF A DESCRIPTION DESCRIPTION DE COMPONDA DE COMPO
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
1-31-06 Frac San Andres 5825-52' w/26000 gal 30# Lightning gel w/27000# 20/40 white sand and 15500# 20/40 Super LC sand. 7-10-06 Set 5-1/2" cement retainer @ 5783'. Pumped 150 sx "C" Neat cement to squeeze perfs to 5200#. ✓ 7-11-06 Drilled out cement and retainer. Fell out of cement @ 5870'. Circulated clean. 7-12-06 Perforated Strawn (6 JSPF) 12080-88' (48), 12096-104' (48), 12117-28' (66) and 12130-33' (18) for total of 180 .42" holes. 7-16-06 Acidized Strawn w/2000 gal 7-1/2% Morrow acid w/190 balls. 7-19-06 Set 5-1/2" CIBP @ 12060' and capped w/35' cement. Perforated Canyon 11552-69' (18), 11585-600' (16), 11650-52' (3) and 11662-70' (9) for total of 46 holes. 7-21-06 Acidized Canyon w/3000 gal 15% NEFE acid w/50 ball sealers. 7-26-06 Set RBP @ 11300'. 7-27-06 Perforated Canyon 11137-41' (11), 11144-54' (21), 11176-86' (21) and 11190-94' (11) for total of 64 holes. 7-28-06 Acidized 11137-94' w/1500 gal 7-1/2% Morrow type acid. 8-2-06 TOH w/RBP @ 11300'.			
2-7/8" tubing @ 11270'			
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.			
SIGNATURE Storm	TITLE _	Regulatory Compliance	Technician DATE 8-28-06
Type or print name Stormi Da For State Use Only		: stormid@ypcnm.com	
APPROVED BY: Mis C Conditions of Approval (if any):	Villiams TIBLE	STRICT SUPPRVISOR/	SEP 0 6 2006