

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-02314
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Seely Oil Company		6. State Oil & Gas Lease No. E-7990
3. Address of Operator 815 W 10th St., Ft. Worth, TX 76102		7. Lease Name or Unit Agreement Name: Central EK Queen Unit
4. Well Location Unit Letter P : 660 feet from the South line and 1980 feet from the West line Section 8 Township 18S Range 34E NMPM County Lea		8. Well No. 002
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 4070 DF		9. Pool name or Wildcat EK Yates-Seven Rivers-Queen

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/24/06 MIRU. Pick up WS. Tag plug @ 4326'. Circulate hole w/mud laden fluid. SDFN.

8/25/06 Spot 25 sx cement plug @ 4326' to 4085'. Spot 25 sx cement plug @ 3212' to 2971'. POH w/ tbg. Perf. 5 1/2 csg. @ 1750'. Set AD-1 packer @ 1449'. Sqz 50 sx cement plug and displace to 1650'. CWI w/ 1000 psi. WOC SDFN.

8/28/06 RIH w/ tbg. no tag. OCD approved spot 25 sx cement plug @ 765. Spot plug WOC 4 hrs. Tagged plug @ 1530'. Perf 5 1/2 csg. @ 425'. Established circulation. Circulated 150 sx cement down 5 1/2 csg and up 8 5/8 to surface. Cut off wellhead. Install dry hole marker. Clean loc. RD move off.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David L. Henderson TITLE Exec VP

Type or print name

David L. Henderson

Telephone No. 817-332-1377

(This space for State use)

APPROVED BY Gary W. Wink TITLE UC FIELD REPRESENTATIVE II/STAFF MANAGER

Conditions of approval, if any:

DATE SEP 15 2006

SEP 15 2006