Submit 3 Copies To Appropriate District Office	State of New Mexico			Form C-103	
District I	Energy, Minerals and Natural Resources			May 27, 2004	
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.		
<u>District II</u> 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		30-025-01429 5. Indicate Type of 1	T anna	
District III	1220 South St. Francis Dr.		STATE	FEE	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		6. State Oil & Gas I		
1220 S. St. Francis Dr., Santa Fe, NM 87505			B-2148		
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or U	Init Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A					
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			Shahara State Unit		
1. Type of Well: Oil Well Gas Well Other			8. Well Number		
2. Name of Operator			9. OGRID Number		
	AROC (Texas), Inc.			187940	
3. Address of Operator			10. Pool name or Wildcat		
110 Cypress Station Dr., #220 Houston, TX 77090			Maljamar Grayburg San Andres		
4. Well Location					
Unit Letter D :660feet from theNorth line and660feet from theWest line					
Section 16 Township 17S Range 33E NMPM Lea County					
11. Elevation (Show whether DR, RKB, RT, GR, etc.)					
4193' GL Pit or Below-grade Tank Application or Closure					
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material					
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data					
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:					
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ REMEDIAL WOR				LTERING CASING	
—			ILLING OPNS.□ P	AND A	
PULL OR ALTER CASING					
OTHER:	П	OTHER:		П	
	leted operations. (Clearly state all		d give pertinent dates,	including estimated date	
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion					
or recompletion.					
Perfs 4271'-4412'. 2-3/8" tbg to 4175'. Casing will not pass MIT. No tbg/csg communication. SITP 800#.					
 Sqz perfs down tbg w/20 sxs cement. MIRU PU. Release packer. Pull out of hole. Trip in hole open-ended. Spot 25 sxs plug from 4090'-4271'. 					
3. Circulate hole with mud. Pull up to 2800'. (Top of Yates 2750') Spot 25 sxs plug from 2620'-2800'. Tag. 4. Pull up to 1580'. (Top of salt 1530'). Spot 25 sxs plug 1350'- PERFY 5QZ. 50' 2077+1N TAGE 2/250					
Pull up to 347'. (8-5/8" at 297'). Spot 25 sxs from 167'-347'. To PERFT SQZ. 50' OUT +IN TAGE 167' 6. Cut casing 3' below ground level. Weld on plate. SPOT 105x @ SURF. OR 60' 3224.25 20					
6. Cut casing 3' belo	w ground level. Weld on plate.	2,01,107× 67	DURF, OR 60	32425262	
		•	The state of the s		
		ng papangan	TR.	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
	NSERVATION DIVISION ((5)	~ 10° 10° 10° 10° 10° 10° 10° 10° 10° 10°	
BE NOTIFIE	D 24 HOURS PRIOR TO	THE	E 6	S. C. S.	
	OF PLUGGING OPERATI		0	0 40 Ch	
I hereby certify that the information above is true and complete to the best of my knowledge and belief. Thereby certify that any pit of below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) afternative OCD-approved plan.					
SIGNATURE Sharitan D	avz / TITLE	Manager, Productio	n Administration D	ATE_9/19/06	
Type or print name E-mail address: <u>Juanita@sbenergy.com</u> Telephone No. SER-527-99306					
For State Use Only OC FIELD REPRESENTATIVE RESTAIN MANAGER					
APPROVED BY Laul	DUMB TITLE	and the second of the second s	- PANTO PANMACATA I	DATE	
Conditions of Approval (if any)					