

State of New Mexico
Energy, Minerals and Natural ResourcesOil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505Form C
Revised March 25, 1994

WELL API NO.

30-025-35178

5. Indicate Type of Lease

STATE ☒FEE ☐

6. Oil & Gas Lease No.

LG-1487 & L-723

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER _____

b. Type of Completion:

NEW ☐ WORK ☐ DEEPEN ☐ PLUG ☒ DIFF.
WELL OVER BACK RESVR. ☐ OTHER

2. Name of Operator

BTA Oil Producers 003002

3. Address of Operator

104 S. Pecos, Midland, TX 79701

7. Lease Name or Unit Agreement Name

Burgundy, 20005 JV-P

8. Well No.

1

9. Pool name or Wildcat

Grama Ridge; Bone Spring, Northeast (28435)

4. Well Location

Unit Letter E : 1548 Feet From The North Line and 660 Feet From The West LineSection 35 Township 21S Range 34E NMPM Lea County

10. Date Spudded

10/05/00 (orig)

03/23/06 (recomp)

11. Date T.D. Reached

12/07/00 (orig)

03/26/06 (recomp)

12. Date Compl. (Ready to Prod.)

03/15/01 (orig)

04/13/06 (recomp)

13. Elevations (DF& RKB, RT, GR, etc.)

3671' GL 3691' KB

15. Total Depth

16. Plug Back T.D.

17. If Multiple Compl. How Many

Zones? -----

18. Intervals

Drilled By

Rotary Tools

X (orig)

Cable Tools

S000H

19. Producing Interval(s), of this completion - Top, Bottom, Name

10,787 - 10,818'

20. Was Directional Survey Made

No

21. Type Electric and Other Logs Run

Micro CFLGR, Three Detector LD CN GR (orig) CBL (3/06)

22. Was Well Cored

No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	54.5	1297'	17-1/2"	1025 sx Circ	---
9-5/8"	40	5272'	12-1/4"	1540 sx Circ	---
7"	29	11400'	8-3/4"	1260 sx TOC 1700'	---

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN
5"	10971'	13343'	220	

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-7/8"	10,895'	---

26. Perforation record (interval, size, and number)

12713 - 12718' 4 JSPF (original) CIBP @ 12648', cap w/cmt
11429 - 11619' 2 JSPF (1st recomp) CIBP @ 11380', cap w/40' cmt, CIBP @
10950', cap w/40' cmt
10787 - 10818' 2 JSPF (2nd recom)

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
12713 - 12718'	A w/1250 gal F w/12800 gal + 7500# sd
11429 - 11619'	A w/6000 gal 15% NeFe & w/22000 gal 20% gelled acid
10787 - 10818'	A w/3500 gal 15% NeFe

28. PRODUCTION

Date First Production 03/14/01 (orig) 04/13/06 (recomp)		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping 2-1/2"x1-1/4"x32'			Well Status (Prod. or Shut-in) Producing		
Date of Test 04/24/06	Hours Tested 24	Choke Size ---	Prod'n For Test Period	Oil - Bbl 30	Gas - MCF 227	Water - Bbl. 44	Gas - Oil Ratio 7567
Flow Tubing Press. ---	Casing Pressure ---	Calculated 24- Hour Rate	Oil - Bbl. 30	Gas - MCF 227	Water - Bbl. 44	Oil Gravity - API - (Corr.) 44.6	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
SoldTest Witnessed By
Jim Shirley

30. List Attachments

Will submit new CBL as soon as it is received in our offices

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature

Pam Inskeep

Printed

Name Pam Inskeep

Title Regulatory Administrator Date 06/05/2006

2R Grama Ridge Wolfcamp West

Jm
GWA

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy <u>1734</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn <u>11670</u>	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt <u>3687</u>	T. Atoka <u>11954</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>4062</u>	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Delaware Sand <u>5542</u>	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs <u>8354</u>	T. Entrada _____	T. _____
T. Abo _____	T. Capitan Reef <u>4415</u>	T. Wingate _____	T. _____
T. Wolfcamp <u>11286</u>	T. Morrow Clastics <u>12528</u>	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....12713.....to.....12718..... No. 3, from.....10787.....to.....10818.....
 No. 2, from.....11429.....to.....11619..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	1734	1734	Anhydrite & Red Beds				
1734	3687	1953	Anhydrite & Salt				
3687	4415	728	Dolomite, Sand & Anhydrite				
4415	4956	541	Dolomite				
4956	5542	586	Limestone				
5542	8354	2812	Sand, Limestone, & Shale				
8354	11286	2932	Limestone, Sand & Shale				
11286	11670	384	Limestone & Shale				
11670	11954	284	Limestone & Chert				
11954	12528	574	Limestone & Shale				
12528	13353	825	Sand, Shale & Limestone				