## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 5-27-200

Revised 5-27-2004 FILE IN TRIPLICATE OIL CONSERVATION DIVISION WELL API NO. **DISTRICT I** 1220 South St. Francis Dr. 1625 N. French Dr., Hobbs, NM 88240 30-025-27138 Santa Fe, NM 87505 5. Indicate Type of Lease 1301 W. Grand Ave, Artesia, NM 88210 FEE X STATE **DISTRICT III** 6. State Oil & Gas Lease No. 1000 Rio Brazos Rd, Aztec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A North Hobbs (G/SA) Unit DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (Form C-101) for such proposals.) Section 19 1. Type of Well: 8. Well No. 142 Oil Well Gas Well 9. OGRID No. 2. Name of Operator 157984 Occidental Permian Ltd. 3. Address of Operator 10. Pool name or Wildcat Hobbs (G/SA) HCR 1 Box 90 Denver City, TX 79323 4. Well Location Unit Letter M Feet From The Feet From The 1200 South 1300 West Section **NMPM** Lea County Township 18-S 11. Elevation (Show whether DF, RKB, RT GR, etc.) 3659' GL Pit or Below-grade Tank Application or Closure Depth of Ground Water Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness Below-Grade Tank: Volume bbls; Construction Material Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 12. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. **PLUG & ABANDONMENT PULL OR ALTER CASING Multiple Completion** CASING TEST AND CEMENT JOB OTHER: OTHER: Squeeze/Perforate/Acid Treat 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 1. Kill well. RUPU. Pull tubing and injection equipment. 2. Clean out to PBTD @4317'. 3. Run in hole with RBP set @4160'. Plug back to 4130' with sand. 4. Set CR @4050'. Squeeze interval 4110' to ~4130'. 5. Drill out CR/cement to 4125' & test to 1000 PSI. 6. Perforate hole @2 JSPF at 4130'-4155'. 7. Acid treat well with 3000 gal 15% PAD acid. 8. Flow back well & circulate clean. 9. Run back in hole with injection equipment. 10. Test casing for NMOCD. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been will be constructed or closed according to NMOCD guidelines a general permit or an (attached) alternative OCD-approved nlan **SIGNATURE** 个ITLE Administrative Associate 10/04/2006 TYPE OR PRINT NAME /Jøhnson E-mail address: mendy johnson@oxy.com TELEPHONE NO. 806-592-6280 For State Use Only AGFIELD REPRESENTATIVE ILISTAFE MARATEGER APPROVED BY

CONDITIONS OF APPROVAL HANY: