

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-34917
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: CHATTER BOX 1823-19 STATE COM
8. Well Number 1
9. OGRID Number 230387
10. Pool name or Wildcat FOUR MILE DRAW; WOLF CAMP

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-103) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other	2. Name of Operator PARALLEL PETROLEUM CORPORATION
3. Address of Operator 1004 N. BIG SPRING STREET, SUITE 400, MIDLAND, TEXAS 79701	4. Well Location Unit Letter 1 : 300' feet from the NORTH line and 742' feet from the WEST line Section 19 Township 18S Range 23E NMPM County EDDY
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4066'	
Pit or Below-grade Tank Application ☐ or Closure ☐ Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: SURVEY ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08-12-06

RUN 5.5" CSG, 7.875" HOLE, 17# SET @ 8865', CMT W/

LEAD #1: 600 SX 50/50 CL C 11.6 PPG, 2.43 YIELD.

TAIL: 700 SX CL H + 2# CACO3, 15.6 PPG, 1.42 YIELD, 100 TURBOLIZERS & 20 STANDARD CENTRALIZERS

CMT CIRCULATED 50 SX TO PIT

WOC 8 HRS, TEST CSG TO 500 PSI FOR 30 MIN.

SCIENTIFIC GYRO SURVEY AND PATH FINDER MWD SURVEYS ATTACHED. NO OPEN HOLE LOGS TAKEN.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Kyle McCormick TITLE SR. PROD & REG TECH. DATE 09-25-2006

Type or print name Kyle McCormick E-mail address: kmccormick@plll.com Telephone No. 432-685-6563

For State Use Only

APPROVED BY District II Supervisor TITLE District II Supervisor DATE 9/29/06

Conditions of Approval, if any:

Page 1

Chatter Box 1823-19 State - GYRO.txt							
400.00	399.98	-2.47	1.03	179.58	-2.47	-1.23	0.54
500.00	499.97	-3.77	0.50	155.48	-3.77	-1.04	0.61
600.00	599.97	-4.21	0.24	102.97	-4.21	-0.66	0.40
700.00	699.97	-4.15	0.51	75.89	-4.15	-0.02	0.32
800.00	799.96	-4.06	0.70	91.84	-4.06	1.02	0.25
900.00	899.94	-3.63	1.63	71.39	-3.63	2.98	1.00
1000.00	999.89	-3.00	1.76	83.52	-3.00	5.85	0.38
1100.00	1099.86	-2.71	1.43	84.57	-2.71	8.62	0.33
1200.00	1199.84	-2.17	0.75	49.62	-2.17	10.36	0.92
1300.00	1299.82	-1.27	1.59	70.03	-1.27	12.16	0.92
1400.00	1399.77	0.03	1.91	60.41	0.03	14.92	0.43
1500.00	1499.72	1.59	1.79	61.72	1.59	17.74	0.13
1600.00	1599.68	3.03	1.46	56.47	3.03	20.18	0.36
1700.00	1699.65	4.27	1.27	61.45	4.27	22.21	0.22
1800.00	1799.63	5.28	1.00	56.67	5.28	23.92	0.29
1900.00	1899.61	6.19	1.04	61.24	6.19	25.44	0.09
2000.00	1999.60	6.99	0.83	60.24	6.99	26.87	0.21
2100.00	2099.59	7.63	0.81	66.05	7.63	28.14	0.09
2200.00	2199.58	8.29	0.70	53.09	8.29	29.28	0.20
2300.00	2299.57	9.03	0.63	46.52	9.03	30.16	0.10
2400.00	2399.57	9.68	0.58	57.26	9.68	30.99	0.12
2500.00	2499.56	10.24	0.46	44.34	10.24	31.69	0.17
2600.00	2599.56	10.72	0.47	62.54	10.72	32.34	0.15
2700.00	2699.56	11.05	0.50	71.95	11.05	33.12	0.09
2800.00	2799.55	11.27	0.48	77.96	11.27	33.94	0.06
2900.00	2899.55	11.52	0.36	58.98	11.52	34.62	0.18
3000.00	2999.55	11.76	0.18	61.40	11.76	35.03	0.18
3100.00	3099.55	11.85	0.25	84.47	11.85	35.38	0.11
3200.00	3199.55	11.84	0.30	97.58	11.84	35.86	0.08
3300.00	3299.54	11.74	0.49	97.82	11.74	36.54	0.19
3373.00	3372.54	11.76	0.34	75.69	11.76	37.06	0.30

The Horizontal Displacement (in Feet) at
Measured Depth 3373.00 is 38.88 in a Direction of 72.40 Degrees
=====

Pathfinder Energy Services

Survey Report

Calculated using the Minimum Curvature Method
Computed using PDS VER2.2.6
Vertical Section Plane: 0.00 deg.

Page 1

Job No: 101005711

Date: 8/11/2006

Time: 5:45 am

Wellpath ID: 10100571

Date Created: 7/28/2006

Last Revision: 8/11/2006

Survey Reference: WELLHEAD
Vertical Section Reference: WELLHEAD
Closure Reference: WELLHEAD
TVD Reference: WELLHEAD

Parallel Petroleum
Chatterbox 1823-19 St. #1
Patterson #498
New Mexico Eddy C.
101005711 WT - WT

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	T O T A L Rectangular Offsets (ft) (ft)		Closure Dist. Dir. (ft) (deg.)	DLS (dg/100ft)
3373.00	0.34	75.69	3372.54	0.00	11.76	11.76 N	37.06 E	38.88@ 72.39	0.00
3414.00	0.70	33.37	3413.54	41.00	12.00	12.00 N	37.32 E	39.20@ 72.17	1.23
3446.00	2.02	22.12	3445.53	32.00	12.68	12.68 N	37.64 E	39.72@ 71.37	4.19
3478.00	3.69	15.44	3477.49	32.00	14.20	14.20 N	38.12 E	40.68@ 69.57	5.31
3510.00	5.72	11.14	3509.38	32.00	16.76	16.76 N	38.70 E	42.18@ 66.59	6.43
3542.00	8.00	8.76	3541.15	32.00	20.52	20.52 N	39.35 E	44.38@ 62.46	7.18
3573.00	10.38	7.27	3571.75	31.00	25.43	25.43 N	40.03 E	47.43@ 57.58	7.72
3605.00	13.01	6.04	3603.08	32.00	31.87	31.87 N	40.78 E	51.75@ 51.99	8.26
3637.00	15.39	4.90	3634.10	32.00	39.68	39.68 N	41.52 E	57.43@ 46.30	7.49
3668.00	17.76	3.93	3663.81	31.00	48.50	48.50 N	42.19 E	64.25@ 41.02	7.70
3700.00	20.05	3.32	3694.08	32.00	58.85	58.85 N	42.85 E	72.79@ 36.06	7.18
3731.00	22.07	2.61	3723.01	31.00	69.97	69.97 N	43.42 E	82.35@ 31.82	6.57
3763.00	24.01	2.17	3752.46	32.00	82.48	82.48 N	43.94 E	93.46@ 28.05	6.09
3794.00	25.76	1.38	3780.58	31.00	95.52	95.52 N	44.34 E	105.31@ 24.90	5.75
3826.00	27.70	0.77	3809.16	32.00	109.91	109.91 N	44.61 E	118.62@ 22.09	6.12
3858.00	29.63	0.33	3837.23	32.00	125.26	125.26 N	44.75 E	133.01@ 19.66	6.07
3890.00	31.74	0.33	3864.75	32.00	141.59	141.59 N	44.85 E	148.52@ 17.58	6.59
3922.00	33.85	0.24	3891.65	32.00	158.92	158.92 N	44.93 E	165.15@ 15.79	6.60
3954.00	35.70	0.06	3917.93	32.00	177.17	177.17 N	44.98 E	182.79@ 14.25	5.79
3986.00	37.46	359.98	3943.63	32.00	196.24	196.24 N	44.99 E	201.33@ 12.91	5.50
4018.00	39.04	0.06	3968.76	32.00	216.05	216.05 N	45.00 E	220.65@ 11.76	4.94
4049.00	40.98	0.24	3992.50	31.00	235.98	235.98 N	45.05 E	240.24@ 10.81	6.27
4081.00	42.91	0.41	4016.30	32.00	257.37	257.37 N	45.17 E	261.30@ 9.95	6.04
4113.00	44.85	0.41	4039.36	32.00	279.55	279.55 N	45.33 E	283.20@ 9.21	6.06
4145.00	46.43	0.33	4061.74	32.00	302.42	302.42 N	45.48 E	305.82@ 8.55	4.94
4177.00	47.75	0.41	4083.52	32.00	325.86	325.86 N	45.63 E	329.04@ 7.97	4.13
4209.00	48.89	0.59	4104.80	32.00	349.76	349.76 N	45.84 E	352.75@ 7.47	3.59
4240.00	50.12	0.41	4124.93	31.00	373.33	373.33 N	46.04 E	376.16@ 7.03	3.99
4272.00	51.52	0.41	4145.15	32.00	398.14	398.14 N	46.22 E	400.81@ 6.62	4.38
4304.00	52.94	0.15	4164.75	32.00	423.43	423.43 N	46.34 E	425.96@ 6.25	4.48
4336.00	54.43	0.06	4183.70	32.00	449.21	449.21 N	46.39 E	451.60@ 5.90	4.66
4367.00	56.19	0.06	4201.34	31.00	474.70	474.70 N	46.42 E	476.97@ 5.58	5.68
4399.00	58.04	0.15	4218.71	32.00	501.57	501.57 N	46.47 E	503.72@ 5.29	5.79
4431.00	59.62	0.24	4235.28	32.00	528.95	528.95 N	46.56 E	531.00@ 5.03	4.94
4463.00	61.38	0.41	4251.03	32.00	556.80	556.80 N	46.72 E	558.76@ 4.80	5.52

Pathfinder Energy Services

Survey Report

Page 2

Date: 8/11/2006

Wellpath ID: 10100571

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	T O T A L Rectangular Offsets (ft)		Closure Dist. (ft)	Dir. (deg.)	DLS (dg/100ft)
4495.00	62.78	0.24	4266.02	32.00	585.08	585.08 N	46.88 E	586.95@	4.58	4.40
4526.00	64.54	0.41	4279.77	31.00	612.86	612.86 N	47.04 E	614.66@	4.39	5.70
4558.00	66.30	0.68	4293.08	32.00	641.95	641.95 N	47.31 E	643.70@	4.22	5.55
4590.00	67.88	0.41	4305.54	32.00	671.43	671.43 N	47.59 E	673.11@	4.05	5.00
4622.00	69.56	0.59	4317.15	32.00	701.24	701.24 N	47.85 E	702.87@	3.90	5.28
4654.00	71.31	0.68	4327.87	32.00	731.39	731.39 N	48.19 E	732.98@	3.77	5.48
4685.00	73.07	0.68	4337.35	31.00	760.90	760.90 N	48.54 E	762.45@	3.65	5.68
4717.00	74.74	0.68	4346.22	32.00	791.65	791.65 N	48.90 E	793.16@	3.53	5.22
4749.00	76.33	0.59	4354.21	32.00	822.63	822.63 N	49.25 E	824.10@	3.43	4.98
4781.00	78.17	0.59	4361.27	32.00	853.84	853.84 N	49.57 E	855.27@	3.32	5.75
4812.00	80.02	0.68	4367.14	31.00	884.27	884.27 N	49.90 E	885.68@	3.23	5.97
4844.00	82.04	0.68	4372.13	32.00	915.88	915.88 N	50.28 E	917.26@	3.14	6.31
4876.00	84.42	0.59	4375.90	32.00	947.65	947.65 N	50.63 E	949.00@	3.06	7.44
4908.00	86.09	0.41	4378.55	32.00	979.54	979.54 N	50.91 E	980.86@	2.98	5.25
4939.00	86.88	0.50	4380.45	31.00	1010.48	1010.48 N	51.16 E	1011.77@	2.90	2.56
4971.00	88.99	0.59	4381.60	32.00	1042.46	1042.46 N	51.46 E	1043.73@	2.83	6.60
5003.00	91.19	0.59	4381.55	32.00	1074.45	1074.45 N	51.79 E	1075.70@	2.76	6.88
5033.00	91.89	0.59	4380.74	30.00	1104.44	1104.44 N	52.10 E	1105.67@	2.70	2.33
5065.00	92.42	0.77	4379.54	32.00	1136.42	1136.42 N	52.48 E	1137.63@	2.64	1.75
5096.00	92.42	0.68	4378.23	31.00	1167.38	1167.38 N	52.87 E	1168.58@	2.59	0.29
5128.00	91.28	0.50	4377.20	32.00	1199.37	1199.37 N	53.20 E	1200.55@	2.54	3.61
5160.00	89.52	0.50	4376.98	32.00	1231.36	1231.36 N	53.48 E	1232.52@	2.49	5.50
5192.00	89.08	0.41	4377.37	32.00	1263.36	1263.36 N	53.73 E	1264.50@	2.44	1.40
5224.00	89.16	0.68	4377.86	32.00	1295.35	1295.35 N	54.04 E	1296.48@	2.39	0.88
5255.00	89.08	0.85	4378.33	31.00	1326.35	1326.35 N	54.45 E	1327.46@	2.35	0.61
5287.00	88.90	0.94	4378.90	32.00	1358.34	1358.34 N	54.95 E	1359.45@	2.32	0.63
5319.00	88.64	0.94	4379.58	32.00	1390.33	1390.33 N	55.48 E	1391.43@	2.28	0.81
5351.00	89.25	0.85	4380.17	32.00	1422.32	1422.32 N	55.97 E	1423.42@	2.25	1.93
5382.00	89.97	0.94	4380.39	31.00	1453.31	1453.31 N	56.46 E	1454.41@	2.22	2.34
5414.00	89.69	0.68	4380.48	32.00	1485.31	1485.31 N	56.91 E	1486.40@	2.19	1.19
5446.00	89.78	1.03	4380.63	32.00	1517.31	1517.31 N	57.39 E	1518.39@	2.17	1.13
5478.00	90.31	1.21	4380.60	32.00	1549.30	1549.30 N	58.01 E	1550.38@	2.14	1.75
5509.00	90.22	1.29	4380.46	31.00	1580.29	1580.29 N	58.69 E	1581.38@	2.13	0.39
5541.00	89.96	1.38	4380.41	32.00	1612.28	1612.28 N	59.44 E	1613.38@	2.11	0.86
5573.00	90.04	1.47	4380.41	32.00	1644.27	1644.27 N	60.23 E	1645.38@	2.10	0.38
5605.00	89.96	1.56	4380.41	32.00	1676.26	1676.26 N	61.08 E	1677.37@	2.09	0.38
5636.00	89.60	1.47	4380.53	31.00	1707.25	1707.25 N	61.90 E	1708.37@	2.08	1.20
5668.00	89.34	1.64	4380.82	32.00	1739.24	1739.24 N	62.77 E	1740.37@	2.07	0.97
5699.00	89.96	1.38	4381.01	31.00	1770.23	1770.23 N	63.58 E	1771.37@	2.06	2.17
5731.00	90.04	1.47	4381.01	32.00	1802.22	1802.22 N	64.38 E	1803.37@	2.05	0.38
5763.00	90.04	1.47	4380.99	32.00	1834.21	1834.21 N	65.20 E	1835.36@	2.04	0.00
5794.00	89.87	1.38	4381.02	31.00	1865.20	1865.20 N	65.97 E	1866.36@	2.03	0.62
5826.00	89.87	1.91	4381.09	32.00	1897.18	1897.18 N	66.89 E	1898.36@	2.02	1.66
5857.00	90.48	2.17	4380.99	31.00	1928.16	1928.16 N	67.99 E	1929.36@	2.02	2.14
5889.00	90.31	2.00	4380.77	32.00	1960.14	1960.14 N	69.16 E	1961.36@	2.02	0.75
5920.00	89.96	0.94	4380.70	31.00	1991.13	1991.13 N	69.95 E	1992.36@	2.01	3.60
5952.00	89.52	0.50	4380.84	32.00	2023.13	2023.13 N	70.35 E	2024.35@	1.99	1.94
6015.00	89.52	0.68	4381.37	63.00	2086.12	2086.12 N	71.00 E	2087.33@	1.95	0.29

Pathfinder Energy Services

Survey Report

Page 3

Date: 8/11/2006

Wellpath ID: 10100571

Measured Depth (ft)	Incl (deg.)	Drift Dir. (deg.)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	T O T A L Rectangular Offsets (ft)		Closure Dist. (ft)	Dir. (deg.)	DLS (dg/100ft)
6078.00	89.69	1.21	4381.81	63.00	2149.11	2149.11 N	72.04 E	2150.32@	1.92	0.88
6141.00	89.87	0.94	4382.05	63.00	2212.10	2212.10 N	73.22 E	2213.31@	1.90	0.52
6204.00	89.52	359.98	4382.38	63.00	2275.09	2275.09 N	73.73 E	2276.25@	1.86	1.62
6267.00	88.90	358.92	4383.25	63.00	2338.08	2338.08 N	73.12 E	2339.23@	1.79	1.95
6330.00	90.57	358.57	4383.54	63.00	2401.07	2401.07 N	71.75 E	2402.14@	1.71	2.71
6394.00	89.87	358.22	4383.30	64.00	2465.04	2465.04 N	69.95 E	2466.03@	1.63	1.22
6457.00	90.66	358.74	4383.01	63.00	2528.02	2528.02 N	68.28 E	2528.94@	1.55	1.50
6520.00	89.96	358.57	4382.67	63.00	2591.00	2591.00 N	66.80 E	2591.86@	1.48	1.14
6583.00	89.96	358.66	4382.71	63.00	2653.98	2653.98 N	65.28 E	2654.78@	1.41	0.14
6646.00	90.84	359.10	4382.27	63.00	2716.97	2716.97 N	64.05 E	2717.72@	1.35	1.56
6709.00	90.84	358.83	4381.35	63.00	2779.95	2779.95 N	62.91 E	2780.66@	1.30	0.43
6772.00	89.78	358.04	4381.01	63.00	2842.92	2842.92 N	61.19 E	2843.58@	1.23	2.10
6836.00	90.66	358.22	4380.76	64.00	2906.89	2906.89 N	59.10 E	2907.45@	1.16	1.40
6898.00	89.69	357.87	4380.57	62.00	2968.85	2968.85 N	56.99 E	2969.40@	1.10	1.66
6961.00	90.75	358.04	4380.33	63.00	3031.81	3031.81 N	54.74 E	3032.30@	1.03	1.70
7024.00	90.75	357.95	4379.50	63.00	3094.76	3094.76 N	52.53 E	3095.21@	0.97	0.14
7088.00	90.04	357.16	4379.06	64.00	3158.70	3158.70 N	49.80 E	3159.10@	0.90	1.66
7151.00	89.08	356.20	4379.55	63.00	3221.59	3221.59 N	46.16 E	3221.93@	0.82	2.15
7214.00	88.90	356.11	4380.66	63.00	3284.44	3284.44 N	41.93 E	3284.71@	0.73	0.32
7277.00	89.43	355.84	4381.57	63.00	3347.28	3347.28 N	37.51 E	3347.45@	0.64	0.94
7340.00	89.87	355.67	4381.96	63.00	3410.11	3410.11 N	32.85 E	3410.27@	0.55	0.75
7403.00	90.57	355.67	4381.72	63.00	3472.93	3472.93 N	28.09 E	3473.04@	0.46	1.11
7466.00	90.48	355.58	4381.14	63.00	3535.74	3535.74 N	23.29 E	3535.82@	0.38	0.20
7529.00	90.22	355.49	4380.76	63.00	3598.55	3598.55 N	18.38 E	3598.55@	0.29	0.44
7592.00	90.04	355.76	4380.61	63.00	3661.36	3661.36 N	13.57 E	3661.35@	0.21	0.52
7656.00	90.04	355.93	4380.57	64.00	3725.20	3725.20 N	8.94 E	3725.21@	0.14	0.27
7719.00	89.52	355.40	4380.81	63.00	3788.01	3788.01 N	4.18 E	3788.02@	0.06	1.18
7782.00	89.43	355.14	4381.39	63.00	3850.80	3850.80 N	1.02W	3850.80@359.98		0.44
7845.00	89.25	354.70	4382.11	63.00	3913.55	3913.55 N	6.60W	3913.55@359.90		0.75
7908.00	88.99	354.35	4383.08	63.00	3976.25	3976.25 N	12.61W	3976.27@359.82		0.69
7971.00	89.60	354.88	4383.86	63.00	4038.97	4038.97 N	18.52W	4039.01@359.74		1.28
8035.00	90.57	355.84	4383.76	64.00	4102.76	4102.76 N	23.70W	4102.82@359.67		2.13
8098.00	91.45	356.28	4382.65	63.00	4165.60	4165.60 N	28.02W	4165.65@359.61		1.56
8161.00	91.54	356.28	4381.01	63.00	4228.44	4228.44 N	32.11W	4228.56@359.56		0.14
8224.00	90.66	356.02	4379.80	63.00	4291.29	4291.29 N	36.34W	4291.44@359.51		1.46
8287.00	90.22	355.84	4379.31	63.00	4354.13	4354.13 N	40.81W	4354.32@359.46		0.75
8350.00	89.60	354.96	4379.41	63.00	4416.92	4416.92 N	45.86W	4417.16@359.41		1.71
8413.00	89.52	355.23	4379.90	63.00	4479.69	4479.69 N	51.25W	4479.98@359.34		0.45
8477.00	89.43	355.40	4380.48	64.00	4543.47	4543.47 N	56.48W	4543.82@359.29		0.30
8540.00	89.25	355.40	4381.21	63.00	4606.27	4606.27 N	61.53W	4606.68@359.23		0.29
8603.00	89.96	355.93	4381.64	63.00	4669.08	4669.08 N	66.29W	4669.55@359.19		1.41
8666.00	90.04	356.64	4381.64	63.00	4731.95	4731.95 N	70.37W	4732.47@359.15		1.13
8729.00	90.48	357.95	4381.36	63.00	4794.88	4794.88 N	73.35W	4795.44@359.12		2.19
8792.00	90.75	358.30	4380.68	63.00	4857.84	4857.84 N	75.41W	4858.43@359.11		0.70
8865.00	90.75	358.30	4379.72	73.00	4930.80	4930.80 N	77.57W	4931.41@359.10		0.00