

Submitt 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
May 27, 2004

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-00422
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. OG-5939
7. Lease Name or Unit Agreement Name Tipton Unit
8. Well Number 12
9. OGRID Number 013837
10. Pool name or Wildcat Maljamar Grbg SA
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4099' GR

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator Mack Energy Corporation	
3. Address of Operator P.O. Box 960 Artesia, NM 88211-0960	
4. Well Location Unit Letter <u>L</u> <u>1980</u> feet from the <u>South</u> line and <u>660</u> feet from the <u>West</u> line Section <u>31</u> Township <u>16S</u> Range <u>32E</u> NMPM County <u>Lea</u>	
5. Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input type="checkbox"/>	
Pit type <u>                    </u> Depth Groundwater <u>                    </u> Distance from nearest fresh water well <u>                    </u> Distance from nearest surface water <u>                    </u>	
Pit Liner Thickness: <u>                    </u> mil Below-Grade Tank: Volume <u>                    </u> bbls; Construction Material <u>                    </u>	


12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
OTHER: <u>                    </u> <input type="checkbox"/>		OTHER: <u>                    </u> <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hours prior to starting plugging operations.
2. Set CIBP at 3676' w/ 35' cement cap.
3. Circ hole with mud gel.
4. Set 100' plug from 1980-1880', 50' below and above bottom of salt.
5. Set 100' plug from 1050-950', 50' below and above top of salt.
6. Perf @ 330' squeeze 100sx 50' below and above 8 5/8 casing shoe. - WOC+TAG
7. Set 10 sx surface plug.
8. Install dry hole marker.

**THE OIL CONSERVATION DIVISION MUST  
BE NOTIFIED 24 HOURS PRIOR TO THE  
BEGINNING OF PLUGGING OPERATIONS.**



I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ a general permit ☐ or an (attached) alternative OCD-approved plan ☐


SIGNATURE Jerry W. Sherrell TITLE Production Clerk DATE 10/13/06  
Type or print name Jerry W. Sherrell E-mail address: jerrys@mackenergycorp.com Telephone No. (505)748-1288  
For State Use Only

APPROVED BY Jay W. Wink TITLE OCD FIELD REPRESENTATIVE II/STAFF MANAGER DATE OCT 13 2006  
Conditions of Approval (if any):

MACK ENERGY  
TIPTON #12  
Sec 31 T16S R32E 1980FSL 660FWL

- 1 Notify BLM 24 Hrs in advance of plugging
- 2 Set CIBP @ 3676' w/35'cmt cap
- 3 Set 100' cmt plug btm salt 1980-1880
- 4 Set 100' cmt plug TS 1050-950'
- 5 Perfs @ 330 Squeeze 100sks 50'above below shoe
- 6 Set suface plug and install Dry hole marker

BEFORE




8 5/8" 24# J-55 @ 330' c/w 250sks

Perfs 3776-3978'

4 1/2" 9.5# @ 4020' c/w 200sks

AFTER



60' Cmt Plug

8 5/8" 24# J-55 @ 330' c/w 250sks

Perfs @ 330 Squeeze 100sks 50'above below shoe

Set 100' cmt plug TS 1050-950'

Set 100' cmt plug btm salt 1980-1880

Set CIBP @ 3676' w/35'cmt cap  
Perfs 3776-3978'

4 1/2" 9.5# @ 4020' c/w 200sks