Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103	
District I Energy, 1625 N. French Dr., Hobbs, NM 88240	Minerals and Natural Resource	WEDDAPI NO.	May 27, 2004	
District II		20 11 27774		
District III 12	20 South St. Francis Dr.	5. Indicate Type		
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505	STATE		
1220 S. St. Francis Dr., Santa Fe, NM 87505		6. State Oil & G	as Lease No.	
SUNDRY NOTICES AND RE		7. Lease Name of	or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			_	
PROPOSALS.)		State 1		
1. Type of Well: Oil Well 🔲 Gas Well 🔀 Other 🔲		8. Well Number		
2. Name of Operator		002 9. OGRID Num	har	
Cimarex Energy Co. of Colorado			162683	
3. Address of Operator			10. Pool name or Wildcat	
PO Box 140907; Irving, TX 75014-0907		Antelope Ridg	Antelope Ridge; Morrow (Gas)	
4. Well Location			· · · · · · · · · · · · · · · · · · ·	
Unit Letter <u>B</u> : 660 feet from	the North line and 1	980 feet from the	East line	
Section 2 Township 24S			Lea .	
3424' GR	n (Show whether DR, RKB, RT, GR,	etc.)		
Pit or Below-grade Tank Application or Closure				
Pit type Depth to Groundwater Distan- Pit Liner Thickness: Below-Grade			surface water	
		Construction Material		
12. Check Appropriate	Box to Indicate Nature of No	otice, Report or Oth	er Data	
NOTICE OF INTENTION 1	ro: s	UBSEQUENT RE		
PERFORM REMEDIAL WORK D PLUG AND		-		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PAND A				
PULL OR ALTER CASING 🛛 MULTIPLE C		VENT JOB 🛛		
OTHER:				
13. Describe proposed or completed operation		s, and give pertinent dat	es, including estimated date of	
starting any proposed work). SEE RULE	1103. For Multiple Completions:	Attach wellbore diagram	1 of proposed completion or	
recompletion.				
05-06-06 Spudded 17-1/2" hole.				
1	sing to 393'. Cemented with 45	A sy Premium Plus +	2% CaCl (wt 14.8 wld	
1.68). Circulated 210 sx to sur	face. WOC 20 hours.		270 CaCl (wt 14.0, ylu	
05-08-06 Pressure tested casing to 500 p				
	ng to 5235'. Cemented with lead	d of 1200 sx Interfill (C + 0.25# Flocele (wt 11.9.	
yld 2.45) and tail of 200 sx Premium Plus + 1% CaCl2 (wt 14.8, yld 1.33). Circulated 225 sx to surface. WOC				
37.75 hours. Pressure tested ca	asing to 1000 psi for 30 minutes	•		
I hereby certify that the information above is true an	d complete to the best of my know	ledge and belief I furth	er certify that any pit or below good	
tank has been/will be constructed or closed according to NM	OCD guidelines [], a general permit [] o	r an (attached) alternative (CD-approved plan .	
SIGNATURE Nata Lin Kneger		Analyst 1	DATE October 18, 2006	
Type or print nameNatalie Krueger	amail address 1		1)1 000 404	
For State Use Only	email address: nkruege	r@cimarex.comTel	ephone No. 972-401-3111	
11. 110				
APPROVED BY: /////	am TITLE THE COM	THACOPACT MONT	DATE	
Conditions of Approval (if any):		and a second product a constraint from the	and the second	

Conditions	of Approval	(if any):