Office	State of New Me			** ** ***
District I	Energy, Minerals and Natur	ral Resources	WELL API NO.	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II			30-015-35164	
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION		5. Indicate Type of Lease	
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.		STATE FEE	
District IV	Santa Fe, NM 87505		6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM				
87505 SUNDRY NOTIO	CES AND REPORTS ON WELLS		7. Lease Name or Uni	t Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		Ohkay SWD		
	Gas Well Other SWD		8. Well Number 3	
2. Name of Operator		-	9. OGRID Number	
Yates Petroleum Corporation				
3. Address of Operator		10. Pool name or Wildcat		
105 S. 4th Street, Artesia, NM 882	10		Bell Canyon	
4. Well Location				
	990feet from theSouth		 _	
Section 6	Township 25S			ty Eddy
	11. Elevation (Show whether DR,	, RKB, RT, GR, etc	.)	
Pit or Below-grade Tank Application 🗌 or	3172'			
		votor well This	stance from nearest surface w	oton
				ater
Pit Liner Thickness: mil	Below-Grade Tank: Volume	bbls; C	Construction Material	
12. Check A	Appropriate Box to Indicate N	ature of Notice,	, Report or Other Dat	a
NOTICE OF IN	TENTION TO:	SUE	SEQUENT REPO	RT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WOR		ERING CASING
TEMPORARILY ABANDON	CHANGE PLANS ⊠			ND A
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMEN		
OTHER:		OTHER:	1	
13. Describe brobosed of comb	leted operations. (Clearly state all park) SEE RULE 1103 For Multiple			
of starting any proposed wor or recompletion.	in, obs ross from for many			
of starting any proposed won or recompletion. Yates Petroleum Corporation respendentered. If lost circulation is and cemented to surface. If lost c	pectfully requests permission to not encountered, the 12 1/4" hole circulation is encountered, then 9	e will be drilled to 9 5/8" casing will	4,450' and 7" production	on casing will be set
of starting any proposed won or recompletion. Yates Petroleum Corporation respenceuntered. If lost circulation is and cemented to surface. If lost circulation is and cemented to surface will be reduced to 8 3/4" and desize will be reduced to 8 3/4" and desize will be reduced to 8 3/4".	pectfully requests permission to not encountered, the 12 1/4" hole circulation is encountered, then strilled to 4,450' where 7" will be strilled to 4,450' where 7" will be strilled.	e will be drilled to 9 5/8" casing will set.	4,450' and 7" production	on casing will be set
of starting any proposed won or recompletion. Yates Petroleum Corporation respenceuntered. If lost circulation is and cemented to surface. If lost circulation is size will be reduced to 8 3/4" and displayed by the starting of the surface.	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then strilled to 4,450' where 7" will be strilled to 4.450' where 7" where 7" will be strilled to 4.450' where 7" where 7" will be strilled to 4.450' where 7" where 7" will be strilled to 4.450' where 7" whe	e will be drilled to 9 5/8" casing will set.	4,450' and 7" production	on casing will be set to surface then hole 17 18 19 20 27 3
of starting any proposed won or recompletion. Yates Petroleum Corporation respendentered. If lost circulation is and cemented to surface. If lost circulation is size will be reduced to 8 3/4" and displayed by the starting of the surface.	pectfully requests permission to not encountered, the 12 1/4" hole circulation is encountered, then strilled to 4,450' where 7" will be strilled to 4,450' where 7" will be strilled.	e will be drilled to 9 5/8" casing will set.	4,450' and 7" production	on casing will be set to surface then hole surface then hole 17 18 19 20 27 20 27 20 27 20 27 20 20 20 20 20 20 20 20 20 20 20 20 20
of starting any proposed won or recompletion. Yates Petroleum Corporation respendencementered. If lost circulation is and cemented to surface. If lost circulation is size will be reduced to 8 3/4" and displayed by the starting of the surface.	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then strilled to 4,450' where 7" will be strilled to 4.450' where 7" where 7" will be strilled to 4.450' where 7" where 7" will be strilled to 4.450' where 7" where 7" will be strilled to 4.450' where 7" whe	e will be drilled to 9 5/8" casing will set.	4,450' and 7" production	on casing will be set to surface then hole 17 18 19 20 27 3
of starting any proposed won or recompletion. Yates Petroleum Corporation respenceuntered. If lost circulation is and cemented to surface. If lost circulation is size will be reduced to 8 3/4" and desize will be reduced to 8 3/4" and desize will be reduced to 8 3/4".	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then strilled to 4,450' where 7" will be sometimes of the sountered of the sountere	e will be drilled to 9 5/8" casing will set.	4,450' and 7" production be set and cemented to	on casing will be set to surface then hole of 17 18 19 20 27 20 20 20 20 20 20 20 20 20 20 20 20 20
of starting any proposed wo or recompletion. Yates Petroleum Corporation respenceuntered. If lost circulation is and cemented to surface. If lost circulation is size will be reduced to 8 3/4" and desize will be reduced to 8 3/4" and	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then strilled to 4,450' where 7" will be strilled to 4,450' WITNESS L CASING STRINGS	e will be drilled to 9 5/8" casing will set.	4,450' and 7" production be set and cemented to the set and cemented to the set and belief. I further cere	on casing will be set to surface then hole of the surface of the surfac
of starting any proposed wo or recompletion. Yates Petroleum Corporation respenceuntered. If lost circulation is and cemented to surface. If lost circulation is size will be reduced to 8 3/4" and desize will be reduced to 8 3/4" and	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then strilled to 4,450' where 7" will be strilled to 4,450' WITNESS L CASING STRINGS	e will be drilled to 9 5/8" casing will set.	4,450' and 7" production be set and cemented to the set and cemented to the set and belief. I further cere	on casing will be set to surface then hole of the surface of the surfac
of starting any proposed wo or recompletion. Yates Petroleum Corporation respendented. If lost circulation is and cemented to surface. If lost circulation is size will be reduced to 8 ¾" and distributed in the start of the st	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then strilled to 4,450' where 7" will be stri	e will be drilled to 9 5/8" casing will set.	4,450' and 7" production be set and cemented to the set and cemented to the set and belief. I further certain and the set and the se	on casing will be set to surface then hole of the surface of the surfac
of starting any proposed won or recompletion. Yates Petroleum Corporation respendencemented. If lost circulation is and cemented to surface. If lost of size will be reduced to 8 3/4" and desize will be constructed or a start to the reduced to 8 3/4".	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then so drilled to 4,450' where 7" will be so described according to NMOCD guidelines. TITLE: Delen E-mail address: jmulle	e will be drilled to 9 5/8" casing will set. est of my knowled, a general permit Drilling Engineer A	4,450' and 7" production be set and cemented to the set and cemented to the set and belief. I further certain and the set and the se	on casing will be set to surface then hole of the surface of the surfac
of starting any proposed wo or recompletion. Yates Petroleum Corporation respendencemented. If lost circulation is and cemented to surface. If lost circulation is an experis	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then shalled to 4,450' where 7" will be shalled to 4,450' where	e will be drilled to 9 5/8" casing will set. est of my knowled, a general permit Drilling Engineer A	4,450' and 7" productive set and cemented to the set and cemented to the set and belief. I further certain alternative ssistantDATE_	on casing will be set to surface then hole of the surface of the surfac
of starting any proposed wo or recompletion. Yates Petroleum Corporation respendented. If lost circulation is and cemented to surface. If lost of size will be reduced to 8 ¾" and desize will be reduced to 8 ¾". Thereby certify that the information as trade tank has been/will be constructed or the start will be co	pectfully requests permission to not encountered, the 12 ½" hole circulation is encountered, then so drilled to 4,450' where 7" will be so described according to NMOCD guidelines. TITLE: Delen E-mail address: jmulle	e will be drilled to 9 5/8" casing will set. est of my knowled, a general permit Drilling Engineer A	4,450' and 7" productive set and cemented to the set and cemented to the set and belief. I further certain alternative ssistantDATE_	on casing will be set to surface then hole of the surface of the surfac

Operator to ma CBL from TD to surface