Submit 3 Copies To Appropriate District Office State of New Mexico	Form C-103 May 27, 2004
District I 1625 N. French Dr., Hobbs, NM 88240 District II Energy, Minerals and Natural Resources	WELL API NO. 30-025-08975
District II 1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III 1220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410	STATE FEE
District IV Santa Fe, Nivi 87303	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	025432
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	South Eunice Unit
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	8. Well Number 17
2. Name of Operator	9. OGRID Number
Breck Operating Corp.	002799
3. Address of Operator	10. Pool name or Wildcat
P.O. Box 911, Breckenridge, Texas 7624 4. Well Location	Eunice 7 Rivers Queen, South
Unit Letter L : 1980 feet from the South line and 660 feet from the West line	
Section 21 Township 22S Range 36E	NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc.,	•
3540' GR Pit or Below-grade Tank Application or Closure	
Pit type Steel Depth to Groundwater 300' Distance from nearest fresh water well >1000' Distance from nearest surface water >1000'	
	onstruction Material
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
1	
_	SEQUENT REPORT OF: K
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRI	
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN	
OTUED.	П
OTHER: OTHER: OTHER: OTHER:	d give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion	
or recompletion.	
9-07-06 MIRU (Notify NMOCD). RIH w/2-3/8" tbg to 3545'. Circulate 92 bbls B/W + 30	sx mud. Spot 25 sx Class "C" cement on RBP.
9-08-06 Spot 25 sx Class "C" cement at 1387'. Casing leak between 523'-554'. Call NMOCD, OK to pump cement from 625' to surface.	
Pumped 220 sx Class "C" cement from 625' to surface. 9-27-06 Cut wellhead 3' below surface. Install Dry Hole Marker.	
9-27-06 Cut wellifead 3 below surface. Histail Dry Hole Market.	9 1011121314Z
	12.3 10.0
approved as to plugging of the Well Bore.	
Liability under bond is retained until	
urface restoration is completed.	\& &
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-	
I hereby certify that the information above is true and complete to the best of my knowledg	e and belief. I further certify that any pit or below-
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit	
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit	or an (attached) alternative OCD-approved plan
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit	or an (attached) alternative OCD-approved plan
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit	or an (attached) alternative OCD-approved plan
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit	or an (attached) alternative OCD-approved plan
grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE TITLE District Engineer Type or print name DONALD R. CRAIG E-mail address: dcraig@breckop.com	or an (attached) alternative OCD-approved plan