

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

WELL API NO. 30-025-23457
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-2229
7. Lease Name or Unit Agreement Name Phillips "E" State
8. Well Number 12
9. OGRID Number 217817
10. Pool name or Wildcat Maljamar GB/SA

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> Water Injection	
2. Name of Operator ConocoPhillips Company ATTN: Celeste Dale	
3. Address of Operator 4001 Penbrook Street Odessa, Texas 79762	
4. Well Location Unit Letter <u>M</u> : <u>990</u> feet from the <u>South</u> line and <u>990</u> feet from the <u>West</u> line Section <u>10</u> Township <u>17-S</u> Range <u>33-E</u> NMPM County <u>Lea</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4,172' GL; 4,182' RKB	
Pit or Below-grade Tank Application <input type="checkbox"/> or Closure <input checked="" type="checkbox"/>	
Pit type <u>STEEL</u> Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water <u>N/A</u>	
Pit Liner Thickness: <u>STEEL</u> mil Below-Grade Tank: Volume <u>180</u> bbls; Construction Material <u>STEEL</u>	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPERATIONS ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHED WELLBORE DIAGRAM

10/26/2006 Notified NMOCD, Speedy Gonzales. MIRU Triple N rig #24 and plugging equipment. POOH w/ injection tubing/packer. Set CIBP @ 4,286'. Circulated hole w/ mud, pumped 25 sx C cmt 4,286 - 3,915'.
10/30/2006 Pumped 25 sx C cmt 2,889 - 2,519'. Perforated casing @ 1,855'. RIH w/ packer and squeezed 40 sx C cmt @ 1,855'. WOC & tagged cmt @ 1,665'. Perforated casing @ 412', Established rate and squeezed 50 sx C cmt @ 412'.
10/31/2006 Notified NMOCD. Tagged cmt @ 262'. Perforated casing @ 50', unable to pump into perforations. Circulated 15 sx C cmt 50' to surface. RDMO.

Cut off wellhead and anchors, installed dry hole marker. Backfilled cellar.

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE James F. Newman TITLE James F. Newman, P.E. (Triple N Services) DATE 11/06/06

Type or print name James F. Newman E-mail address: jim@triplenservices.com Telephone No. 432-687-1994
For State Use Only

APPROVED BY Larry W. Wink OC FIELD REPRESENTATIVE II/STAFF MANAGER
Conditions of Approval (if any):


NOV 14 2006

PLUGGED WELLBORE SKETCH **ConocoPhillips Company -- Mid-Continent BU/Odessa**

Date: November 6, 2006

RKB @ 4182'
 DF @ 4181'
 GL @ 4172'

Subarea : Buckeye
 Lease & Well No. : Phillips State E No. 12 W
 Legal Description : 990' FSL & 990' FWL, Sec. 10, T17S, R33E
 NMPM Survey
 County : Lea State : New Mexico
 Field : Maljamar (GB/SA)
 Date Spudded : April 1, 1970 Rig Released: April 15, 19707
 API Number : 30-025-23457 State Lse No. B-2229
 Status : plugged 10/31/06



15 sx C cmt 95' to surface
 (perforated at 50', unable to sqz)

12-1/4" Hole

8-5/8" 24# @ 362' cmt'd w/ 400 sx, surface
 Perf/sqz'd 50 sx C cmt 412 - 262' TAGGED

Perf/sqz'd 40 sx C cmt 1,855 - 1,665' TAGGED
 Top of Salt @ +/- 1,855'

TOC 4-1/2" csg @ 2,600'

Base of Salt @ ~2,800'
 25 sx C cmt 2,889 - 2,519'

7-7/8" Hole

CIBP w/25 sx C cmt 4,286 - 3,915'
 Possible collapsed csg @ 4,319 - 4,400'
Grayburg
 4378' - 4385' w/7 SPF - 48 holes
 4386' w/4 SPF - 4 holes
 4433' - 4438' w/8 SPF - 40 holes
 4439' - 4440' w/4 SPF - 8 holes
 4473' - 4478' w/8 SPF - 40 holes
 4479' - 4480' w/4 SPF - 8 holes

4-1/2" 11.6# N-80 @ 4,534' cmt'd w/ 275 sx, TOC 2,600'

PBTD: 4506'
 TD: 4538'

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate
	4/17/70	Perf 4378-4478 (select fire)					
4473-4478	4/18/70	12% HCl	500		2700	2300	2.0
4433-4438	4/18/70	12% HCl	500		2800	2250	1.5
4378-4478		Refined Oil (RO)	10,000	19,500	6350		17.9
	7/30/73	Convert to water injection					
4378-4478	5/5/90	20% NEFE HCl	2,000				
	6/24/96	Re-perforate 4378-4386, 32 holes, 4433-4440, 28 holes					
		4473-4480, 28 holes					
4378-4480	6/25/96	15% Fercheck	2,000		3800	2200	4.2
	2/5/97	Run casing check					
	4/12/05	Casing integrity test, OK set pkr @ 4240'					
	8/11/05	Casing integrity test, OK set pkr @ 4249'					



PLUGS SET 10/26/06 - 10/31/06

- 1) CIBP w/25 sx C cmt 4,286 - 3,915'
- 2) 25 sx C cmt 2,889 - 2,519'
- 3) Perforate/sqz'd 40 sx C cmt 1,855 - 1,665' TAGGED
- 4) Perforate/sqz'd 50 sx C cmt 412 - 262' TAGGED
- 5) 15 sx C cmt 95' to surface

Capacities

4 1/2" 11.6# csg:	11.468 ft/ft3	0.0872 ft3/ft
8 5/8" 24# csg:	2.797 ft/ft3	0.3575 ft3/ft
7 7/8" openhole:	2.957 ft/ft3	0.3382 ft3/ft
12 1/4" openhole:	1.222 ft/ft3	0.8185 ft3/ft

Formation Tops:

Rustler	1462'
Yates	2800'
Queen	3744'
Grayburg	4220'
San Andres	4490'