

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003 WELL API NO. 30-025-34625 5. Indicate Type of Lease STATE ☐ FEE ☒ State Oil & Gas Lease No.	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER b. Type of Completion: NEW ☐ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☒ OTHER				7. Lease Name or Unit Agreement Name VICEROY	
2. Name of Operator Capataz Operating, Inc.				8. Well No. 1	
3. Address of Operator P.O. Box 10549, Midland, TX 79702				9. Pool name or Wildcat House;BlinebryS, H Tubb, H Drinkard, H Abo	
4. Well Location Unit Letter E : 1980 Feet FromThe North Line and 330 Feet From The West Line Section 13 Township 20S Range 38E NMPM Lea County					
10. Date Spudded 06/01/1999		11. Date T.D. Reached 06/16/1999		12. Date Compl. (Ready to Prod.) 02/04/2003	
		13. Elevations (DF& RKB, RT, GR, etc.) 3578' GR		14. Elev. Casinghead	
15. Total Depth 7800'		16. Plug Back T.D. 7800'		17. If Multiple Compl. How Many Zones? 4	
18. Intervals Drilled By X				Rotary Tools Cable Tools	
19. Producing Interval(s), of this completion - Top, Bottom, Name Blinebry, Tubb, Drinkard, Abo				20. Was Directional Survey Made No	
21. Type Electric and Other Logs Run				22. Was Well Cored No	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE 8-5/8" 5-1/2"		WEIGHT LB./FT. 24# 17#		DEPTH SET 1587' 7800'	
				HOLE SIZE 12-1/4" 7-7/8"	
				CEMENTING RECORD 1000 sx, circ 1220 sx, TOC 2160' CBL	
24. LINER RECORD SIZE TOP BOTTOM SACKS CEMENT SCREEN 25. TUBING RECORD SIZE DEPTH SET PACKER SET 2-7/8" 6551' 6551'					
26. Perforation record (interval, size, and number) BINEBRY 5944 - 6104' 2 JSPF TUBB 6660 - 6788' 1 JSPF DRINKARD 7008 - 7039' 1 JSPF ABO 7330 - 7417' 1 JSPF				27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 6660 - 6788' Acidize 3000gals 15%NeFe, 6000gals 20%Ne 7008 - 7039' 1500gals15%NeFe,2500galsKCl+8820gals15% 7330 - 7417' Acidize 5000gals 20%NeFe&6500gals 28%Ne	
28. PRODUCTION Date First Production 02/04/2003 Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping Well Status (Prod. or Shut-in) Producing Date of Test 24 hrs Hours Tested Choke Size Prod'n For Test Period Oil - Bbl 3 Gas - MCF 164 Water - Bbl. 6 Gas - Oil Ratio 54667 Flow Tubing Press. Casing Pressure Calculated 24-Hour Rate Oil - Bbl. Gas - MCF Water - Bbl. Oil Gravity - API - (Corr.) 36.7					
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold				Test Witnessed By Capataz Operating	
30. List Attachments C-102s,C-103s,C-104s					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature		Printed Name H. Scott Davis		Title Agent Date 07/26/2006	
E-mail Address Capataz1@sbcglobal.net					

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates 2858 _____	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg 4109 _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres 4264 _____	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry 5994 _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb 6522 _____	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo 7083 _____	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Perm _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from _____ to _____ No. 3, from _____ to _____
 No. 2, from _____ to _____ No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.
 No. 2, from _____ to _____ feet.
 No. 3, from _____ to _____ feet.

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
3100	3120		Sandstone				
3120	3510		Anhydrite				
3510	3530		Sandstone				
4080	5360		Dolomite				
5360	5760		Limestone				
6020	7140		Dolomite				
7140	7310		Limestone				