

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505		Form C-105 Revised June 10, 2003	
		WELL API NO. 30-025-37934		5. Indicate Type of Lease STATE ☒ FEE ☐	
				State Oil & Gas Lease No. BO-0246	
WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____				7. Lease Name or Unit Agreement Name North Monument G/SA Unit	
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER					
2. Name of Operator Apache Corporation				8. Well No. 340	
3. Address of Operator 6120 S Yale Ave, Suite 1500 Tulsa, OK 74136-4224				9. Pool name or Wildcat Eunice Monument; Grayburg-San Andres	
4. Well Location Unit Letter O 165 Feet From The South Line and 2500 Feet From The East Line Section 20 Township 19S Range 37E NMPM Lea County					
10. Date Spudded 07/06/2006	11. Date T.D. Reached 07/11/2006	12. Date Compl. (Ready to Prod.) 08/01/2006	13. Elevations (DF& RKB, RT, GR, etc.) 3,645' GR	14. Rig / Cable Head 1615 Head	
15. Total Depth 4,206'	16. Plug Back T.D. 4,146'	17. If Multiple Compl. How Many Zones? N/A	18. Intervals Drilled By X	Rotary Tools	Cable Tools
19. Producing Interval(s), of this completion - Top, Bottom, Name Eunice Monument; Grayburg-San Andres 3876' - 3970'				20. Well Directional Survey Made NO	
21. Type Electric and Other Logs Run SD/DSN, DLL-MG				22. Was Well Cored? NO	
23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	
8-5/8"	24#	390'	11"	300 sx / circ	
5-1/2"	17#	4,206'	7-7/8"	850 sx / TOC 80' CBL	
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	PACKER SET
26. Perforation record (interval, size, and number) G/SA 3876-80', 3894-99', 3901-16', 3921-29', 3932-42', 3960-70' (2 JSPF)			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 3876-3970' 5K gals 15% HCl		
28. PRODUCTION					
Date First Production 08/01/2006		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping		Well Status (Prod. or Shut-in) Producing	
Date of Test 09/23/2006	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 6	Gas - MCF 24
				Water - Bbl. 74	Gas - Oil Ratio 4000
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.
					Oil Gravity - API - (Corr.) 32.4
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold					Test Witnessed By Apache
30. List Attachments Deviation Report, Logs, C-102, C-104					
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief					
Signature <i>Sophie Mackay</i>		Printed Name Sophie Mackay		Title Engineering Tech	
E-mail Address sophie.mackay@apachecorp.com		Date 11/14/2006			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2594'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2849'	T. Devonian	T. Menefee	T. Madison
T. Queen 3365'	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3673'	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4098'	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T. Rustler 1339'	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology